



100  
YEARS

A CENTURY OF INNOVATION

**Sail , Cover,  
Hardware  
& Accessories**





**BAINBRIDGE**  
**SAIL & COVER**

# Leading Brands – Leading Availability – Leading Service

- ◆ Over 8,000+ products for same day despatch
- ◆ Carriage free shipping on all orders placed on Mondays to UK mainland
- ◆ Next day option from £5.00
- ◆ All orders over £350 ship carriage free on any day
- ◆ Dedicated trade only ecommerce site
- ◆ 24/7 real time stock levels, online pricing, quick and simple ordering
- ◆ On site services - tailored to your exact requirements:
  - Cut Length Rolls – from our extensive cloth and cover inventory
  - Roll Slitting Service – for full rolls to your exact width
  - Batten Cut Sets – for all the most popular boat and dinghy types
  - Cut length Stainless Tube by the metre



**BAINBRIDGE**  
**SAIL & COVER**

**Dedicated Sail & Cover Team - direct line 01489 776010**

Bainbridge International Limited,  
Unit 8, Flanders Park, Flanders Road, Hedge End, Southampton, Hampshire SO30 2FZ, UK

**Office Hours: Weekdays 0830 – 1700hrs**

📞 **01489 776010**

📞 **01489 776015**

✉ **info@bainbridgeint.co.uk**

**www.bainbridgeint.com**



Sailcloth	Page
Bag Cloth	32
Diax Window	18
Hybrid Polyester	11
Laminates	12-17
Leechline	21-22
Luff Tape	20
Monofilm	18
Odyssey	30
PSA Fabric	24-25, 29
Seaming Tapes	26-28
Shockcord	23
Slit Tape	19
Sunbrella Furling	31
Woven Nylon	2-3
Woven Polyester	4-10

Hardware	Page
Aquabatten	33-36
Batten Fixings	46-47
Clamcleats	72-74
Class Insignia	78
Clewblocks/Boards	64
End Caps	39
English Grommets	77
H&B Dabond Thread	83-84
Hand Sewn thread	86
Headboards & Liners	61-63
Inox Rings	66
Jib Hanks	70-71
Pad Eyes	82
PTFE Thread	85
Pultruded Battens	37-38
Rivets	81
Sail Numbers & Letters	79
Sail Shackles	49
Sail slides	50-57
Sail Tack Hooks	69
Sailman Full Batten System	40-45
Sailman X Clewboards	60
Sailman X Headboards	58-59
SDA Batten Fittings	48
Sister Clips	80
Splicing Fids	82
Stainless Steel Rings	65, 68
Stimpson Grommets	76
Sunstop Thread	85
Thimbles & Ferrules	75
Webbing	67

Marine Covers & Awnings	Page
Bias Acrylic/Vinyl Binding	108-109
Boat Vent	138
Buckles	128-129
Cordura	101
D Rings	137
Dickson Seaguard Flex	97
Dickson Sunworker	105
Dot Fasteners	120-121
Firesist FR	96
H&B Dabond Anti-Wick Thread	110
Holdon Clips	130
Hooks & Eyes	127
Keder Tape	131
Lift The Dot & SNAD Fasteners	124
LOXX Fasteners	122-123
Nautimar & Nautiplus	98
Nylon/Jackstay Webbing	107
Odyssey & Pattern Material	92, 93
Permalock & Snapfast	125
Polyester Screen/Knit Mesh	104
Polypropylene Webbing	106
PTFE Thread	110
PVC Polyester & Nylon	101
PVC Window Material	99-100
Seamark	89
Self Piercing Grommets	117-118
Snap Hooks	119
Sola Vinyl	97
Solacryl	90-91
Stainless Tubing & Fittings	132-136
Sun Sox	137
Sunbrella	88
Sunbrella Plus	87
Sunbrella Supreme	89
Sunstop Anti-Wick Thread	111
Surlast	89
Top Gun	94, 96
Top Notch	95
Trampoline & Vinyl Mesh	102-103
Turnbutton Fasteners	126
Velcro	112-114
Webbing Bridges	130
YKK Zips	115-116

Tools	Page
Awls & Push Pins	141
Fabsil	154-155
Hand Sewing Needles	143
Hole Cutters & Die Sets	145-149
Hot Knives	140
Lubricants & Sealers	152
Measuring Tools	144
Palms	142
Plastimo Jib Reefing	163-166
Polish & Window Cleaner	156-157
Sail Repair Kits	151
Scissors	139
Seam Rollers	141
Spray Adhesive & Cleaner	153
Starbrite	158-162
Wire Cutters & Press	150

Rope	Page
3 Strand Nylon	176
3 Strand Polyester	177
Burgee Cord	179
Cruising Dock Line	178
Laser Line	173
Marstrand	173-174
Multifilament	177
Octoplait	178
Polylock	176
Sheetline	174
Shock Cord	180
Super 12	167
Super Braid	169
Super Lite	172
Super Speed	170
Super T Braid	168
Super TW Braid	168
Superyacht Dock Line	179
Vecklock	175
Vectran Braid	170
XD-Lite	175
YachtMaster	171

Clothing & Sailing Gear	Page
Bainbridge Sailcloth Bags	184-185
Bainbridge Sailcloth Jacket	181-183
Gerber Multi Tools	192-198
Overboard Waterproof Bags	186-189
Waterproof Device Cases	189-191

Please note: Colour representations for Sailcloth, Cover Material and other dye coloured items shown in this publication are the closest approximate match permissible by print process. Customers should also be aware that the colour of fabrics will alter appearance to the eye by the light and environment in which they show e.g. bright blue environments will change yellow colours to greener shades. In all cases with coloured product, customers should ensure at point of ordering to always match to batch for particular jobs.



P: 152

Boat Vent

P: 138



P: 153



P: 28, 153



P: 72-74



P: 130



P: 85, 111

Crown Arc

P: 150



P: 8-10



P: 3



P: 12-18



P: 11



P: 50



P: 87-89, 157



P: 156



P: 33-36



P: 120-121



P: 152, 156



Sailcloth

P: 13-32



P: 140



P: 122-123



P: 141



P: 30, 92-96

Hardware

P: 37-86



P: 154-155



P: 2

Marine  
Covers & Awning

P: 98-138



P: 96



P: 152

Tools

P: 139-150



P: 139



P: 156

Clothing

P: 181-185

Gransegel

P: 74



P: 144



P: 186-191

Bend Arc

P: 150



P: 83-84, 86, 110



P: 150, 163-166





P: 140



P: 158-162



P: 98



P: 76, 148



P: 100



P: 100



P: 40-45, 50-52



P: 137



P: 58-60



P: 87-89, 108



P: 48



P: 152



P: 89



P: 102



P: 125



P: 140



P: 90-91



P: 112-114



P: 85-110



P: 69-70, 80



P: 167-180



P: 143



P: 143



P: 139



P: 4-7



P: 131



P: 109



P: 115-116, 124

s  
p  
r  
i  
n  
g  
B



Cruising Spinnaker fabric developed to offer the optimum balance between durability, value and range

- ◆ Specially designed for cruise and club race application
- ◆ High strength 6.6 nylon yarn used throughout – creating a very strong cloth which performs even at high wind loads
- ◆ High density / low porosity weave construction gives class leading tear strengths reduces damage risk from rig contact
- ◆ Ideal weave and finish for snuffers and furling units – upper weights are stronger than equivalent polyester – ideal for handling local strain caused by furlers
- ◆ Finish and elongation figures are complimentary across the whole range, allowing for composite weights to be used – especially useful for furling sails

Delivering a Spinnaker fabric with consistent performance throughout the fabric weight range coupled with excellent tear strength and durability



Arctic White



Royal Blue



Red



Aqua Blue



Yellow



Green



Silver



Black



Pink

Series	Application	Construction Warp X Fill	Ripstop (mm)	Weight (gsm)	AWS	
MPEX70N	Robust 3/4oz with medium finish	40 x 40	6.5 x 6.5	1520	48	12
MPEX90N	High strength durable cloth ideal for the offshore cruiser	70 x 70	7 x 7	1520	70	16
MPEX250N	Strong and robust performance cloth ideal for use with snuffers and reaching when AWS is higher – Code Zero	140 x 140	7 x 7	1520	110	18
MPEX300N	Ideal for use with snuffers and reaching when AWS is higher for application on yachts 50 – 75ft	210 x 210	7 x 7	1520	130	20
MPEX350N	High performance cloth for bigger yachts and storm spinnaker applications	210 x 210	7 x 7	1520	150	22

Please note: Colour representations for Sailcloth, Cover Material and other dye coloured items shown in this publication are the closest approximate match permissible by print process. Customers should also be aware that the colour of fabrics will alter appearance to the eye by the light and environment in which they show e.g. bright blue environments will change yellow colours to greener shades. In all cases with coloured product, customers should ensure at point of ordering to always match to batch for particular jobs.

A premium range which combines unprecedented strength, performance and quality

- ◆ High Tenacity 6.6 yarns in a high density construction delivering light sails in higher wind ranges
- ◆ Double ripstop weave delivers exceptional burst and tear strength and reduces damage from rig contact and handling
- ◆ Fabric bias specifically engineered by weight to match optimum sail design
- ◆ High water repellency provides best physical performance and minimum sailing weight
- ◆ High density weave constructions deliver extremely low porosity which generates maximum power
- ◆ Elongation results make AIRX ideal for modern asymmetric sails using step-down construction
- ◆ AIRX excels in dealing with higher loads created by these designs
- ◆ Finish and elongation figures are complimentary across the whole range, ideal for strong lightweight composite race applications


New expanded colour and weight range coupled with race proven performance - AIRX the winners choice



Arctic White



Royal Blue



Red



Aqua Blue



Yellow



Green



Silver



Hot Yellow



Black



Violet



Pink



Tempest Grey

Series	Application	Width (mm)	Weight (gsm)	AWS
AIRX 400N	Lightweight Grand Prix VMG finish	1520	26	7
AIRX 500N	Idea for most $\frac{1}{2}$ oz applications	1520	30	8
AIRX 600N	Versatile for wide range of wind strengths	1520	37	10
AIRX 620NS	Silicone Coated AIRX 600N for dinghies and sportsboats	1520	37	10
AIRX 650N	Satisfies classes with a minimum 40gsm weight rule	1520	40	10
AIRX 700N	High Strength $\frac{3}{4}$ oz with a very stable and durable weave	1520	45	12
AIRX 800N	Increases scope of range above AIRX 700N	1520	53	14
AIRX 900N	Extreme strength and durability for ultimate offshore performance	1520	67	16

Please note: Colour representations for Sailcloth, Cover Material and other dye coloured items shown in this publication are the closest approximate match permissible by print process. Customers should also be aware that the colour of fabrics will alter appearance to the eye by the light and environment in which they show e.g. bright blue environments will change yellow colours to greener shades. In all cases with coloured product, customers should ensure at point of ordering to always match to batch for particular jobs.





This new cloth utilises the latest weaving and finish techniques – delivering consistent quality from start to finish. The unique construction design, coupled with exacting production control and yarn selection enables the cloth to be finished with the optimum level of finish – this means that **SPX** is suitable for a wide range of sail applications

**SPX** gives the sailmaker the option to select the type of handle they require in the cloth – with a choice of Hard, Firm or Medium finish. This menu selection allows for the cloth to be specifically tailored to the exact sail usage – enhancing the end users sailing experience

The **SPX** range has been specially selected to cover two main cloth types in the key weight ranges to ensure maximum appeal for sailmakers



Finish	Handle	Suitability	Equivalent bias rating
<b>H</b>	<b>Hard</b>	<b>One Design Racing</b>	<b>3-6</b>
<b>F</b>	<b>Firm</b>	<b>General use, Charter</b>	<b>6-9</b>
<b>M</b>	<b>Medium</b>	<b>Cruising</b>	<b>9-12</b>
<b>S</b>	<b>Soft</b>	<b>Ocean Cruising</b>	<b>12-15</b>



Balanced is produced to suit a large variety of sail applications and features high tenacity yarns for strength and durability

- ◆ Providing a wide set of construction styles the higher weights suit ALL bigger boat uses – including tall ships
- ◆ 4oz range offered in full colour palette – with Natural, Cream and Tan colour options available in a range of higher weights
- ◆ Near parity strength in warp and fill 'balances' the cloth and makes it suitable for low aspect sail designs
- ◆ Wide weight and colour range coupled with extensive application possibilities makes this cloth a competitive solution for sailmakers
- ◆ Exact finish required can be selected by the sailmaker – choice of Hard, Firm or Medium

	Count		Denier		dpi		Finished Weight		Part No.	Selected Finish - replaces 'X'
	w	f	w	f	w	f	g/m <sup>2</sup>	Sm Oz		
SPX 425	118	62	150	252	19724	17424	170	3.9	<b>FWP042500(X)</b>	H/F
SPX 525	106	47	252	300	29657	15648	223	5.2	<b>FWP052500(X)</b>	H/F
SPX 625	103	45	252	500	28804	24977	278	6.5	<b>FWP062500(X)</b>	H/F/M
SPX 725	118	48	252	500	33071	26833	325	7.6	<b>FWP072500(X)</b>	H/F/M
SPX 825	80	40	450	750	40000	33333	364	8.5	<b>FWP082500(X)</b>	H/F/M
SPX 925	80	38	450	846	40000	35720	415	9.7	<b>FWP092500(X)</b>	H/F/M
SPX 1025	58	35	750	1000	48314	38889	451	10.6	<b>FWP102500(X)</b>	H/F/M

Note: All data based on griage unless stated otherwise





# Strong Fill

# 55



Finish	Handle	Suitability	Equivalent bias rating
<b>H</b>	<b>Hard</b>	<b>One Design Racing</b>	<b>3-6</b>
<b>F</b>	<b>Firm</b>	<b>General use, Charter</b>	<b>6-9</b>
<b>M</b>	<b>Medium</b>	<b>Cruising</b>	<b>9-12</b>
<b>S</b>	<b>Soft</b>	<b>Ocean Cruising</b>	<b>12-15</b>

- ◆ Strong Fill produced as a high sley fabric – with high warp count matched with high fill denier
- ◆ This makes it ideal for high aspect sail designs
- ◆ Durability thanks to the inherent strength from construction design
- ◆ Multi stage process tailored to construction design allows for optimum finish – giving a cloth that is easier to handle and consistent quality
- ◆ Exact finish required can be selected by the sailmaker – choice of Firm or Medium

	Count w f		Denier w f		dpi w f		Finished Weight g/m <sup>2</sup> Sm Oz		Part No.	Selected Finish - replaces 'X'
SPX 755	97	35	252	850	27160	33056	329	7.6	<b>FWP075500(X)</b>	F/M
SPX 855	107	36	252	1008	29870	39827	353	8.3	<b>FWP085500(X)</b>	F/M
SPX 955	80	38	450	846	40000	35720	415	9.7	<b>FWP095500(X)</b>	F/M
SPX 1055	80	35	450	1000	40000	38885	455	10.7	<b>FWP105500(X)</b>	F/M
SPX 1155	80	33	450	1300	40000	47667	480	11.2	<b>FWP115500(X)</b>	F/M

Note: All data based on griegre unless stated otherwise





# Balanced

# 25



## Colours

SPX 425



Red  
**FWP042510M**



Pink  
**FWP042513M**



Yellow  
**FWP042530M**



Green  
**FWP042550M**



Dark Blue  
**FWP042561M**



Ice Blue  
**FWP042563M**



Black  
**FWP042599M**

SPX 525 - 1025



Classic Tan



Storm Orange



Black



Classic Cream

SPX 525 **FWP052521F**

SPX 625 **FWP062521F**

SPX 725 **FWP072521F**

SPX 825 **FWP082521F**

SPX 925 **FWP092521F**

SPX 1025

**FWP082520M**

**FWP102520M**

**FWP052599F**

**FWP062503F**

**FWP072503F**

**FWP082503F**

**FWP092503F**

## UV Coated Polyester

- ◆ 425 balanced construction
- ◆ High UV coating polyester
- ◆ Ideal UV cover fabric for roller furling genoas and in-mast furling mainsail
- ◆ Roll Width: 1370mm



White UV



Grey UV



Navy UV

SPX 425

**FWP042501MU**

**FWP042591MU**

**FWP042562MU**

Please note: Colour representations for Sailcloth, Cover Material and other dye coloured items shown in this publication are the closest approximate match permissible by print process. Customers should also be aware that the colour of fabrics will alter appearance to the eye by the light and environment in which they show e.g. bright blue environments will change yellow colours to greener shades.

In all cases with coloured product, customers should ensure at point of ordering to always match to batch for particular jobs.








## Sail Application Data Sheet

### Crosscut Sail Application

LOA ft	24-30	30-35	35-40	40-45	45-50	50-55
<b>Main</b>	625	755	855	955	1055	1155
<b>Genoa 1</b>	525	525	625	725	825	925
<b>Genoa 2</b>	625	725	825	925	1025	1155
<b>Genoa 3</b>	625	755	855	955	1055	1155
<b>Genoa 4</b>	755	855	955	1055	1155	1055
<b>High Aspect Jib</b>	625	755	855	955	1055	1155
<b>Furling Genoa</b>	625	725	825	925	1025	1155





Bainbridge **HSX** cloth is finished in our partnership production facility using the latest fill and digitally controlled finishing techniques. It harnesses countless years of experience, knowledge and expertise, combined with the very latest finish and UV inhibitors to provide a sailcloth which is tough and durable with a long service life.

**HSX** is a tightly packed premium woven cloth thanks to precision weaving techniques and exacting quality control. Offered in three different construction types:

- ◆ Balanced
- ◆ Strong Fill
- ◆ Strong Warp

Bainbridge's unique finishing process has been carefully reformulated to incorporate special UV inhibitors which effectively shield and protect **HSX** from harmful UV degradation, this finishing process has also been refined further to provide up to 4 different types of finish, allowing the sailmaker to select from Hard, Firm, Medium and Soft.



Finish	Handle	Suitability	Equivalent bias rating
<b>H</b>	<b>Hard</b>	<b>One Design Racing</b>	<b>3-6</b>
<b>F</b>	<b>Firm</b>	<b>General use, Charter</b>	<b>6-9</b>
<b>M</b>	<b>Medium</b>	<b>Cruising</b>	<b>9-12</b>
<b>S</b>	<b>Soft</b>	<b>Ocean Cruising</b>	<b>12-15</b>

**Balanced**

**22**



- ◆ Balanced denier construction which allows for a wide variety of sail applications
- ◆ Incredibly tough cloth thanks to near parity strength between warp and fill
- ◆ High warp and fill denier ensures exceptional fill modulus
- ◆ Provides for a wide set of construction styles, higher weights suit **ALL** bigger boat uses – including Tall Ships

	Count		Denier		dpi		Finished Weight		Part No.	Selected Finish - replaces 'X'
	w	f	w	f	w	f	g/m <sup>2</sup>	Sm Oz		
HSX 422	94	64	150	248	15695	17463	170	3.9	<b>FWP042200(X)</b>	H/F/M
HSX 522	97	46	252	300	27160	15333	223	5.2	<b>FWP052200(X)</b>	H/F/M
HSX 622	97	43	252	500	27160	23889	278	6.5	<b>FWP062200(X)</b>	H/F/M
HSX 722	109	41	300	600	36333	22796	325	7.6	<b>FWP072200(X)</b>	H/F/M/S
HSX 822	80	40	450	750	40000	33333	364	8.5	<b>FWP082200(X)</b>	H/F/M/S
HSX 922	80	38	450	850	40000	35889	415	9.7	<b>FWP092200(X)</b>	H/F/M/S
HSX 1022	58	35	750	1000	48314	38889	451	10.6	<b>FWP102200(X)</b>	H/F/M/S
HSX 1122	58	33	846	1000	54520	36667	483	11.3	<b>FWP112200(X)</b>	H/F/M/S
HSX 1222	47	33	999	1300	52170	47667	524	12.3	<b>FWP122200(X)</b>	H/F/M/S
HSX 1322	45	31	1296	1300	64800	44778	581	13.6	<b>FWP132200(X)</b>	H/F/M/S

Note: All data based on griage unless stated otherwise





A fully comprehensive range of superior weave sailcloth that delivers exceptional performance, durability and quality thanks to all super tenacity yarns and Bainbridge's unique finish.



Finish	Handle	Suitability	Equivalent bias rating
<b>H</b>	<b>Hard</b>	<b>One Design Racing</b>	<b>3-6</b>
<b>F</b>	<b>Firm</b>	<b>General use, Charter</b>	<b>6-9</b>
<b>M</b>	<b>Medium</b>	<b>Cruising</b>	<b>9-12</b>
<b>S</b>	<b>Soft</b>	<b>Ocean Cruising</b>	<b>12-15</b>

## Strong Fill



- Strong Fill produced as a high sley fabric – with high warp count matched with high fill denier
- This makes it ideal for high aspect sail designs
- Durability thanks to the inherent strength from construction design
- Multi stage process tailored to construction design allows for optimum finish – giving a cloth that is easier to handle and consistent quality
- Exact finish required can be selected by the sailmaker – choice of Firm or Medium

	Count w f		Denier w f		dpi w f		Finished Weight g/m <sup>2</sup> Sm Oz		Part No.	Selected Finish - replaces 'X'
HSX 756	89	38	297	850	29370	35889	329	7.6	<b>FWP075600(X)</b>	H/F/M/S
HSX 856	89	41	297	850	29370	38722	353	8.3	<b>FWP085600(X)</b>	H/F/M/S
HSX 956	80	38	450	846	40000	35720	415	9.7	<b>FWP095600(X)</b>	H/F/M/S
HSX 1056	80	35	450	1000	40000	38885	455	10.7	<b>FWP105600(X)</b>	H/F/M/S
HSX 1156	80	33	450	1300	40000	47667	480	11.2	<b>FWP115600(X)</b>	H/F/M/S

Note: All data based on griegle unless stated otherwise

## Strong Warp



- A warp orientated cloth with good warp modulus ideally suited for radial construction sail designs
- Matched styles allows for 'stepping down' in weight in radial construction
- Special construction featuring balanced denier produces a high warp dpi which ensures a good warp modulus
- Precision control of inline tension during the digital finishing process to minimise warp crimp

	Count w f		Denier w f		dpi w f		Finished Weight g/m <sup>2</sup> Sm Oz		Part No.	Selected Finish - replaces 'X'
HSX 615	105	45	280	556	29400	25000	253	5.97	<b>FWP061500(X)</b>	H/F/M
HSX 715	109	41	330	556	35970	22778	302	7.1	<b>FWP071500(X)</b>	H/F/M
HSX 815	109	36	330	944	35970	34000	342	8.05	<b>FWP081500(X)</b>	H/F/M
HSX 915	80	33	500	944	40000	31167	396	9.26	<b>FWP091500(X)</b>	H/F/M

Note: All data based on griegle unless stated otherwise







Crosscut Sail Application

LOA ft	24-30	30-35	35-40	40-45	45-50	50-55
Main	622	756	856	956	1056	1156
Genoa 1	522	522	622	722	822	922
Genoa 2	622	722	822	922	1022	1122
Genoa 3	622	756	856	956	1056	1156
Genoa 4	756	856	956	1056	1156	1056
High Aspect Jib	622	756	856	956	1056	1156
Furling Genoa	622	722	822	922	1022	1122



Radial Sail Application


LOA ft	Main	Genoa 1	Genoa 2	Genoa 3	Genoa 4	High Aspect Jib	Furling Genoa
25 - 30	615	615	-	615	615	715/615	615
30 - 35	715/615	715/615	515	715/615	715/615	815/715	715/615
35 - 40	815/715	815/715	615/515	815/715	815/715	915/815	815/715
40 - 45	915/815	915/815	715/615	915/815	915/815	1015/915	915/815
45 - 50	1015/915	1015/915	815/715	1015/915	1015/915	-	1015/915
50 - 55	-	-	915/815	-	-	-	-



New HSXv offers a premier hybrid polyester incorporating Vectran® yarns in warp and fill – the ultimate in woven polyester sailcloth

By utilising Vectran® in the construction HSXv is an incredibly strong and durable sailcloth – gram for gram Vectran® yarn is ten times stronger than aluminium

A balanced construction ideal for performance applications, with integrated Vectran® 5mm matrix providing enhanced bias strength, stability and long term durability



**This matrix makes a Vectran® cage within the cloth that is incredibly strong whilst retaining excellent flex and fold**

- ◆ UV protected – the unique Bainbridge finishing process with additional protection which shields the cloth and absorbs harmful UV rays
- ◆ Super tenacity, low shrink polyester yarns deliver a cloth of exceptional strength and finish
- ◆ Low to moderate resin finish ensures long term bias stability
- ◆ Potential weight saving over standard polyester/polyester weave cloth for similar applications makes for easier sail handling
- ◆ Balanced construction widens appeal of cloth for countless performance sail applications
- ◆ The ultimate in woven sailcloth

	Count		Denier		dpi		Finished Weight		Available Finish
	w	f	w	f	w	f	g/m <sup>2</sup>	Sm Oz	
HSXv 627	91	46	280	556	25603	25420	283	6.6	Hard & Firm
HSXv 827	75	41	525	600	39375	24384	360	8.4	Hard & Firm
HSXv 1027	77	33	525	944	40672	31171	408	9.6	Hard & Firm

HSXv




Premium Hybrid Sailcloth





Performance products bred from 1983 America's Cup through to Volvo Ocean Races and modern day IRC Race & Performance Cruise laminate designed and tested to deliver – DIA X the winners choice



- ◆ Selected bre construction and modulus to suit incremental performance gains and your yacht's sail design/specification
- ◆ Tri-axial construction of warp, fill and bias fibres significantly increases puncture resistance and virtually eliminates off axis tear
- ◆ Optional constructions in film-film and taffeta for ultimate performance and durability
- ◆ Medium-Soft Hand giving long-life performance
- ◆ Ultra high pressure lamination coupled with pre-tensioned scrim without crimp, ensures minimal weight on the race course or cruising sail inventory

## Range Overview

**One Design  
Polyester  
Pentex**

**High Modulus Twaron  
Carbon Fibre  
Cruise Laminate  
Double Taffeta**


Polyester, Pentex & Carbon





## SL 500P & 1000P



- ◆ The SL-P range is designed for lower load applications where minimal weight is vital
- ◆ Applications include drifters, luffs of light headsails and performance dinghies where class rules allow
- ◆ Balanced constructions: All styles use balanced scrims, making them ideal for radial and cross cut applications
- ◆ SL500P continues to be the ultimate choice for light weight Finn Class
- ◆ Film / Film style



Product Name	Colour	Laminate Style	Film: mil	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
SL 500	White	Film / Film	1.0	94	2.2	METRE	<b>F8365A00M</b>
SL 500	Black	Film / Film	1.0	94	2.2	METRE	<b>F8366A00M</b>
SL 500	White	Film / Film	1.5	111	2.6	METRE	<b>F8365B00M</b>
SL 1000	White	Film / Film	1.5	162	3.8	METRE	<b>F8065B00M</b>
SL 1000	White	Single Taffeta	1.5	230	5.36	METRE	<b>F8055B00M</b>

## Code Zero

- ◆ These specially designed **Technora** Code Zero laminates are both rugged and lightweight, these styles benefit from scrim technology utilised in our DIAX 2 range of laminates.
- ◆ The taffeta is lighter than conventionally used materials.
- ◆ Diax-Z1 is ideally suited for boats from 45-60ft and has been finished with anti-mildew treatment.
- ◆ Diax-Z0 is ideally suited for Dhow Sails.
- ◆ Single Taffeta style




Product Name	Colour	Laminate Style	Film: mil	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
Z-0	White	Single Taffeta	0.5	60	1.7	METRE	<b>F1715Z00M</b>
Z-1	Black	Single Taffeta	0.5	111	2.6	METRE	<b>F6006Z00M</b>
Z-2	Gold	Single Taffeta	0.75	137	3.2	METRE	<b>F6002W00M</b>
Z-3	Black	Single Taffeta	0.75	167	3.9	METRE	<b>F6003W00M</b>



## DIAX OD

- ◆ 100% Technora fibre in warp, fill and diax
- ◆ DiAx-One Design is fabric ideal for smaller sports boats and high performance dinghies
- ◆ 100% low stretch Technora construction
- ◆ Balanced construction making it ideal for cross cut or radial applications
- ◆ 45 degree Technora fibre gives stability on the bias
- ◆ Available in 1 or 1.5mil film style




Product Name	Colour	Laminate Style	Film: mil	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
OD 30	Black	Film / Film	1.0	127	2.2	METRE	<b>F7503A00M</b>
OD 30	Black	Film / Film	1.5	130	2.6	METRE	<b>F7503B00M</b>

## DIAX P

The DIAX-P range of Film-on-Film Polyester laminates is ideal for club racing, small keelboat and sportsboat applications.

- ◆ 0-90 load bearing scrim utilises best quality fibre. The manufacturing technique virtually eliminates warp crimp to further reduce stretch.
- ◆ The 45 degree Polyester DIAX grid forms a diagonal stabiliser to the 0-90 scrim, increasing panel stability for improved shape retention.
- ◆ DIAX reduces film loading, prolonging sail life.
- ◆ Film / Film style




Product Name	Colour	Laminate Style	Film: mil	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
60P	White	Film / Film	1.5	162	3.8	METRE	<b>F7565B00M</b>
120P	White	Film / Film	1.5	201	4.7	METRE	<b>F7682B00M</b>
180P	White	Film / Film	1.5	248	5.8	METRE	<b>F7783B00M</b>



## DIA X LSP

- ◆ All warp fibres are PENTEX, used in a zero crimp 0-90 scrim.
- ◆ More durable and softer Polyester is used in the fill to prolong competitive sail life.
- ◆ The soft scrim binder and Polyester fill serve to make a more durable product with softer hand.
- ◆ The Polyester DIA X reduces film loading, stabilises the bias and makes a 45 degree truss that reduces the shear effect within the laminate
- ◆ Lightweight, low stretch Pentex
- ◆ **90 / 130 /180 styles featuring increased warp count for 2016**

Pentex Warp Ribbons  
Polyester Diagonal Axis Ribbons  
Polyester Fill Ribbons  
Film/Film Sandwich




Product Name	Laminate Style	Film: mil	Warp x Fill (w x f)	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
60 LSP	Film / Film	1.5	6000 Pen x 2500 Polyester	167	3.9	METRE	<b>F7300B01M</b>
90 LSP	Film / Film	1.5	<b>10000</b> Pen x 2500 Polyester	184	4.3	METRE	<b>F7301B01M</b>
130 LSP	Film / Film	1.5	<b>14000</b> Pen x 2500 Polyester	231	5.4	METRE	<b>F7304B01M</b>
180 LSP	Film / Film	1.5	<b>20000</b> Pen x 2500 Polyester	265	6.2	METRE	<b>F7310B01M</b>

## DIA X OS HMT

- ◆ HMT Warp: Zero crimp HM Twaron fibres are used in the primary directions
- ◆ DIA X Scrim: Bias loads are controlled by the addition of a DIA X scrim. This also reduces loading on the film to increase sail life and locks the warp and fill fibres together to improve shape retention
- ◆ PP Taffeta backed versions available against special order, subject to minimum order quantities
- ◆ Film / Film style

High Modulus Twaron Warp & Fill Ribbons  
Film/Film Sandwich  
DIA X Diagonal Axis Ribbons




Product Name	Laminate Style	Film: mil	Warp x Fill (w x f)	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
45 HMT	Film / Film	1.5	2940 x 2940	149	3.5	METRE	<b>F7705B00M</b>
70 HMT	Film / Film	1.5	7260 x 2200	162	3.8	METRE	<b>F7707B00M</b>
100 HMT	Film / Film	1.5	10285 x 2200	193	4.5	METRE	<b>F7710B00M</b>
130 HMT	Film / Film	1.5	13685 x 3300	232	5.4	METRE	<b>F7713B00M</b>
180 HMT	Film / Film	1.5	19320 x 3300	252	5.9	METRE	<b>F7718B00M</b>
230 HMT	Film / Film	1.5	24180 x 3300	282	6.6	METRE	<b>F7723B00M</b>





## CL P


- ◆ 0-90 load bearing scrim utilises high quality Polyester fibre. Warp efficiency is further improved by a manufacturing technique that virtually eliminates warp crimp.
- ◆ Protected from chafe and UV.
- ◆ Mildew Resistant
- ◆ Softer cloth reduces fibre breakdown, extends life and makes sails easier to use and handle.
- ◆ Double Taffeta style
- ◆ Grey styles to special order



Product Name	Colour	Laminate Style	Film: mil	Warp x Fill (w x f)	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
CL 50P	White	Double Taffeta	1	6000 x 2500	253	5.9	METRE	<b>F6200A00M</b>
CL 65P	White	Double Taffeta	1.5	6000 x 2500	299	7	METRE	<b>F6390B00M</b>
CL 75P	White	Double Taffeta	2	12000 x 2000	334	7.8	METRE	<b>F6400C00M</b>
CL 90P	White	Double Taffeta	2	18000 x 2000	402	9.4	METRE	<b>F6450C00M</b>
CL 65P	Grey	Double Taffeta	1.5	6000 x 2500	299	7	METRE	<b>F6390B15M</b>
CL 75P	Grey	Double Taffeta	2	12000 x 2000	334	7.8	METRE	<b>F6400C15M</b>
CL 90P	Grey	Double Taffeta	2	18000 x 2000	402	9.4	METRE	<b>F6450C15M</b>

## CL DIAX P

- ◆ CL DIAX P is a premium range of Taffeta-on-Taffeta laminates that utilises Polyester warp fibre to reduce elongation.
- ◆ They are suitable for cruising applications up to 60ft and are an ideal mid range product, fitting between standard CL and Pentex products in performance
- ◆ The unique black polyester DIAX scrim increases bias strength



Product Name	Colour	Laminate Style	Film: mil	Warp x Fill (w x f)	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
CL DIAX 60P	White / Black Diax	Double Taffeta	1.5	6000 x 2500	334	7.8	METRE	<b>F6395B06M</b>
CL DIAX 120P	White / Black Diax	Double Taffeta	1.5	12000 x 2000	406	9.5	METRE	<b>F6405B06M</b>
CL DIAX 180P	White / Black Diax	Double Taffeta	1.5	18000x 2000	437	10.2	METRE	<b>F6455B06M</b>





## CL DIAX LSP

- ◆ All warp fibres are PENTEX
- ◆ Mildew Resistant
- ◆ Improved Lamination: Both layers of taffeta are laminated to film
- ◆ Double films reduce the pattern show through the scrim
- ◆ The DIAX scrim increases bias strength
- ◆ Double Taffeta style
- ◆ 90 / 130 / 180 styles featuring increased warp count for 2016


Polyester Diagonal  
Axis Ribbons

Polyester Fill Ribbons

Zero Crimp Pentex  
Warp Ribbons

Taffeta Film Base

Taffeta Top



Product Name	Laminate Style	Film: mil	Warp x Fill (w x f)	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
CL 60 LSP	Double Taffeta	1.5	6000 Pen x 2500 Polyester	334	7.8	METRE	<b>F6481B00M</b>
CL 90 LSP	Double Taffeta	1.5	10000 Pen x 2500 Polyester	385	9.0	METRE	<b>F6486B00M</b>
CL 130 LSP	Double Taffeta	1.5	14000 Pen x 2500 Polyester	420	9.8	METRE	<b>F6491B00M</b>
CL 180 LSP	Double Taffeta	1.5	20000 Pen x 2500 Polyester	437	9.5	METRE	<b>F6496B00M</b>

## CL DIAX CFG


- ◆ Tried and tested for performance and durability on sailcloth applications.
- ◆ Tough taffetas are bonded to both sides of the laminate to provide UV, abrasion and tear resistance.
- ◆ Constructed using two films that are encapsulated by the taffetas. Benefits include less moisture retention, increased bond strength and smoother appearance.
- ◆ Mildew resistant
- ◆ Double taffeta style

Polyester Taffetas

Technora Fill/ Warp Scrim

Carbon Fibre Warp Ribbons

Technora Diagonal Axis Ribbons



Product Name	Laminate Style	Film: mil	Warp x Fill (w x f)	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
CL 90 CFG	Double Taffeta	1.5	6000 x 1.5	313	7.3	METRE	<b>F9309B00M</b>
CL 130 CFG	Double Taffeta	1.5	12000 x 1.0	385	9.0	METRE	<b>F9313B00M</b>
CL 180 CFG	Double Taffeta	1.5	12000 x 1.5	400	9.5	METRE	<b>F9318B00M</b>
CL 240 CFG	Double Taffeta	2.0	12000 x 2.0	426	10.0	METRE	<b>F9324C00M</b>







## DIAX Window



- ◆ Black Polyester DIAX laminated with 4 mil optically clear film.
- ◆ Low stretch, high tear strength.
- ◆ Ideal for laminate and woven race sail windows.

Product Name	Laminate Style	Film: mil	Warp x Fill (w x f)	Weight (gsm)	Sailmaker Weight (sm oz)	Unit	No
Diax Window	Film / Film	4.0	-	170	4.0	METRE	<b>F6002X00M</b>

## Polyester Monofilm



- ◆ See-through polyester film for a light weight performance material for boardsails and telltale windows.

Thickness (mm)	Roll Length (m)	Roll Width (mm)	Unit	No
0.12	45.7	1370	METRE	<b>E078</b>
0.18	45.7	1370	METRE	<b>E088</b>
0.18	45.7	1524	METRE	<b>E088/60</b>
0.25	45.7	1370	METRE	<b>E080</b>


## Telltale Windows - Circle



- ◆ Telltale Windows are pre-cut from E206 Window Material.
- ◆ UV Stabilised Vinyl.
- ◆ Ideal for vision windows for all types of sails & classes.
- ◆ 10pcs in each pack.

Thickness (mm)	Diameter (mm)	Unit	No
0.7	225	PACK 10	<b>E210</b>

## Pattern Material



E062



K903

- ◆ Mylar pattern material.
- ◆ Thickness 350 & 175 microns.
- ◆ Stable pattern fabric

Colour	Roll Length (m)	Roll Width (mm)	Unit	No
Blue	25	1350	ROLL	<b>E062</b>
Opaque	50	1000	METRE	<b>K903</b>





## Sailcloth Tape



Polyester Tape



Polyester Coloured Tape



Nylon Coloured Tape



PTFE Tape


Material	Weight		Width						
	gsm	smoz	25mm	40mm	45mm	50mm	60mm	63mm	70mm
Polyester	170	4	<b>S40025</b>	<b>S40040</b>	<b>S40045</b>	<b>S40050</b>	<b>S40060</b>	<b>S40063</b>	<b>S40070</b>
Polyester	215	5	-	<b>S50040</b>	<b>S50045</b>	<b>S50050</b>	<b>S50060</b>	<b>S50063</b>	<b>S50070</b>
Polyester	255	6	-	<b>S60040</b>	<b>S60045</b>	<b>S60050</b>	<b>S60060</b>	<b>S60063</b>	<b>S60070</b>
Polyester	300	7	-	-	-	<b>S70050</b>	<b>S70060</b>	<b>S70063</b>	<b>S70070</b>
Polyester	343	8	-	-	-	<b>S80050</b>	<b>S80060</b>	<b>S80063</b>	<b>S80070</b>
PTFE	343	8	-	-	-	-	-	-	-
Polyester Colour	180	4	<b>T39025xx</b>	<b>T39040xx</b>	-	<b>T39050xx</b>	<b>T39060xx</b>	-	-
Nylon Colour	170	3.9	<b>T025xx</b>	<b>T040xx</b>	-	<b>T050xx</b>	<b>T060xx</b>	-	-

Polyester 170 full colour range available upon request

Material	Weight		Width							
	gsm	smoz	75mm	80mm	100mm	120mm	125mm	150mm	175mm	200mm
Polyester	170	4	<b>S40075</b>	<b>S40080</b>	<b>S40100</b>	-	-	-	-	-
Polyester	215	5	<b>S50075</b>	<b>S50080</b>	<b>S50100</b>	<b>S50120</b>	<b>S500125</b>	-	-	-
Polyester	255	6	<b>S60075</b>	<b>S60080</b>	<b>S60100</b>	<b>S60120</b>	<b>S60125</b>	<b>S60150</b>	<b>S60175</b>	-
Polyester	300	7	<b>S70075</b>	<b>S70080</b>	<b>S70100</b>	<b>S70120</b>	<b>S70125</b>	<b>S70150</b>	<b>S70175</b>	-
Polyester	343	8	<b>S80075</b>	<b>S80080</b>	<b>S80100</b>	<b>S80120</b>	<b>S80125</b>	<b>S80150</b>	<b>S80175</b>	<b>S80200</b>
PTFE	343	8	-	<b>S80080T</b>	<b>S80100T</b>	-	<b>S80125T</b>	-	-	-
Polyester Colour	180	4	<b>T39075xx</b>	<b>T39080xx</b>	-	-	-	-	-	-
Nylon Colour	170	3.9	<b>T075xx</b>	<b>T080xx</b>	-	-	-	-	-	-

Polyester 170 full colour range available upon request

Available Colour - xx	Colour
<b>BU</b>	Blue
<b>BK</b>	Black
<b>CR</b>	Classic Cream
<b>TN</b>	Tan
<b>GR</b>	Green
<b>RD</b>	Red



- ◆ Custom slitting available upon request
- ◆ Cold cuts available i.e Insignia cloth
- ◆ Hot cuts available i.e Polyester






## Headsail Luff Tape - Super Luff




- ◆ Coloured stitching for easy recognition and simplicity.
- ◆ High quality hard braid rope.
- ◆ Accurate stitching through genuine Bainbridge Sailcloth
- ◆ Consistent sizes for accuracy and optimum usage
- ◆ Packaged in a slim box for ease of handling and storage around the loft.

Single




Double



Colour	Description	Finished Size	Reel Length (m)	Unit	No
Red	Size 5 Single	5	100	METRE	<b>L401</b>
Green	Size 6 Single	6	100	METRE	<b>L402</b>
Blue	Size 7 Single	7	100	METRE	<b>L403</b>
Yellow	Size 4 Double	4	100	METRE	<b>L440</b>
Red	Size 5 Double	5	100	METRE	<b>L441</b>
Green	Size 6 Double	6	100	METRE	<b>L442</b>
Blue	Size 7 Double	7	100	METRE	<b>L443</b>

## Mainsail Bolt Rope Luff Tape



- ◆ Metric sized 3-strand pre-stretched polyester rope.
- ◆ Other sizes of bolt rope are also available.
- ◆ Single rope construction
- ◆ Average reel length 100m

Material	Rope Diameter	Tape Specification	Unit	No
Polyester	7	215 gsm x 80mm	METRE	<b>L150</b>
Polyester	9	215 gsm x 80mm	METRE	<b>L152</b>
Polypropylene	6	245 gsm x 100mm	METRE	<b>L141</b>
Polypropylene	6	245 gsm x 80mm	METRE	<b>L142</b>
Polypropylene	8	215 gsm x 80mm	METRE	<b>L144</b>

## Luff Foam



- ◆ Closed cell Foam used to reduce camber (draft) of roller furling sail when partially furled.
- ◆ Foam padding flattens sail when furled.
- ◆ Flatter sail reduces heeling and makes boat easier to steer.
- ◆ Easy to cut.
- ◆ Does not absorb water.
- ◆ Available on full rolls only

Roll Length (m)	Thickness (mm)	Width (mm)	Unit	No
25	5	1000	ROLL	<b>LR001025</b>



## Hard Braid Luffline Bolt Rope

- ◆ Material: Polyester
- ◆ Construction: Braid on braid
- ◆ Hard Braid luffline
- ◆ Hard section lufflines designed for maintaining their cross-sectional shape in luff tapes to facilitate smooth hoisting and lowering of the sail.
- ◆ Use for headsail luff tape and mainsail bolt rope
- ◆ Available only in white on full reels



Type	Diameter (mm)	Reel Length (m)	Unit	No
Polyester	4	200	METRE	E451
Polyester	5	200	METRE	E452
Polyester	6	200	METRE	E453
Polyester	7	200	METRE	E454
Polyester	8	200	METRE	E455

## 3-Strand Boltrope

- ◆ Use as mainsail bolt or bumper rope
- ◆ Available only on full reels.



Type	Diameter (mm)	Reel Length (m)	Unit	No
Polyester	6	200	METRE	E401
Polyester	8	200	METRE	E403
Polyester	12	200	METRE	E407

## Braided Leechline

- ◆ Economy line for leechline, drawcord and general applications.
- ◆ Only available on full reels.



Type	Diameter (mm)	Reel Length (m)	Unit	No
Polyester	2	100	REEL	E432
Polyester	3	100	REEL	E434
Polyester	4	100	REEL	E435

## Technora Aramid Leechline

- ◆ Very low stretch.
- ◆ Improved flex life compared to most aramid ropes.
- ◆ Polyester outer protects Technora core.
- ◆ Only available on full reels.



Type	Diameter (mm)	Reel Length (m)	Unit	No
Technora	1.7	500	METRE	E345
Technora	3	330	METRE	E347
Technora	6	270	METRE	E352





## GP90 Dyneema® Fibre



- ◆ GP90 Coated Dyneema® Fibre
- ◆ 100% Dyneema® Fibre construction with polyurethane coating.
- ◆ Very low stretch and no water absorption
- ◆ Only available on full reels

Type	Diameter (mm)	Reel Length (m)	Unit	No
GP90	3	200	METRE	<b>E361</b>
GP90	4	200	METRE	<b>E362</b>
GP90	6	200	METRE	<b>E364</b>

## Super Speed



- ◆ Cover: HT Polyester
- ◆ Core: 12 strand UHMwPE yarn
- ◆ Construction: Braid on braid
- ◆ Lightweight
- ◆ Low Creep
- ◆ UHMwPE internal core
- ◆ HT Polyester cover
- ◆ Only available on full reels.

Breaking Load (kg)	Diameter (mm)	Colour	Unit	No
280	2	White	REEL 100M	<b>SRSPB02W</b>
600	4	White	REEL 100M	<b>SRSPB04W</b>
1300	6	White	REEL 100M	<b>SRSPB06W</b>

## Titan Braid



- ◆ Cover: 12 strand UHMwPE yarn
- ◆ Core: HT Polyester
- ◆ Construction: Braid on braid
- ◆ Lightweight
- ◆ Low Creep
- ◆ UHMwPE external cover
- ◆ HT Polyester core
- ◆ The UHMwPE outer cover reduces friction for smooth operation when used as a leechline
- ◆ The HT polyester core maintains shape for grip in all leechline cleats
- ◆ Only available on full reels.

Breaking Load (kg)	Diameter (mm)	Colour	Unit	No
255	2	White	REEL 100M	<b>SRTB02W</b>
500	4	White	REEL 100M	<b>SRTB04W</b>
1100	6	White	REEL 100M	<b>SRTB06W</b>







## Shock Cord

- ◆ Cover: Polyester
- ◆ Core: Rubber
- ◆ Construction: Braid over parallel core
- ◆ Minimum 100% stretch
- ◆ Excellent recovery from stretch



Diameter (mm)	Colour	Unit	No
3	White / Black	REEL 100M	<b>SRSC03WBK</b>
5	White / Black	REEL 100M	<b>SRSC05WBK</b>

## Shockcord Fittings - Clamps

- ◆ Stainless steel clamps
- ◆ Use Pliers C449 to apply
- ◆ Available only in full packs of 100



For Cord Diameter (mm)	Size	Unit	No
3-5	X00	PACK 100	<b>B449</b>
6	X0	PACK 100	<b>B450</b>
8	X1	PACK 100	<b>B451</b>
10	X2	PACK 100	<b>B452</b>
12	X3	PACK 100	<b>B453</b>

## Shockcord Fittings - Hooks

- ◆ Place shockcord through bottom hole
- ◆ Squeeze shockcord clamp tightly



Colour	For Cord Diameter	Unit	Pack Quantity	No
Silver	6	EACH	10	<b>B461</b>
Silver	8	EACH	10	<b>B462</b>

- ◆ Made of stainless steel wire

## Hooks



Wire Diameter (mm)	Length (mm)	Unit	Pack Quantity	No
3.2	31	EACH	50	<b>B463</b>
4.8	44	EACH	50	<b>B464</b>





## High Tack PSA Polyester



- ◆ Manufactured in USA
- ◆ Aggressive glue, no grid on paper
- ◆ Cut lengths available
- ◆ J530WTUV: Titanium dioxide pigment coated fabric Uses: UV Patching and digital inkjet printing

Colour	Roll Length (m)	Roll Width (mm)	Unit	No
White	45.7	1370	METRE	<b>J530WT</b>
White UV	45.7	1370	METRE	<b>J530WTUV</b>

## PSA Kevlar



- ◆ Kevlar KW12 400D with self-adhesive backing.
- ◆ Ideal for lightweight corner patches and local reinforcement on laminate sails
- ◆ Spreader patches

Material	Weight (gsm)	Width (mm)	Unit	No
Kevlar	210	1370	METRE	<b>F7010Z00M</b>

## PSA Kevlar Tape



- ◆ Kevlar tape with self adhesive backing
- ◆ Ideal for lightweight corner patches and local reinforcement on laminate sails
- ◆ Onboard laminate sail repairs

Roll Length (m)	Tape Width (mm)	Unit	No
27 - 55	50	METRE	<b>J742</b>
27 - 55	75	METRE	<b>J743</b>
27 - 55	100	METRE	<b>J744</b>



## PSA Dyneema

- ◆ Dyneema 400D taffeta with self-adhesive backing
- ◆ Ideal for lightweight corner patches and local reinforcement on laminate sails.



Weight (gms)	Width (mm)	Unit	No
278	1370	METRE	<b>F7015Z00M</b>

## PSA Monofilm

- ◆ PSA polyester film with self adhesive backing material for boardsails repairs etc



Thickness (mm)	Roll Length (m)	Roll Width (mm)	Unit	No
0.12	50	50	ROLL	<b>J872</b>
0.18	50	1370	METRE	<b>J874</b>

## SPF-UV Film

- ◆ This clear UV resistant film with adhesive backing blocks virtually all damaging UV radiation.
- ◆ Keep minimum tension on SPF-UV to keep it flat but not distorted.
- ◆ Allow sufficient time for maximum bonding after applying SPF-UV.
- ◆ Film: 0.5mm
- ◆ Weight: 81g



Width (mm)	Unit	No
508	METRE	<b>J822</b>
762	METRE	<b>J832</b>

## Knitted Polyester (Snuffer Material)

- ◆ A lightweight knitted 100% polyester engineered specifically for exterior use, lustrous sheen and is ideal for high quality spinnaker snuffers, socks and flags.



Colour	Roll Width (mm)	Weight (gsm)	Unit	No
White	1530	130	METRE	<b>FHKP60WT</b>



## Fabric Based



- ◆ Designed for film / film laminate sails
- ◆ Fabric carrier
- ◆ Good initial tack
- ◆ High long term adhesion
- ◆ Non yellowing

Width (mm)	Roll Length (m)	Unit	No
12	45.7	ROLL	<b>J080</b>
25	45.7	ROLL	<b>J082</b>

## Tissue Based



- ◆ Economy grade seaming tape offering excellent value for money
- ◆ Good initial tack
- ◆ High long term adhesion
- ◆ Tissue Carrier
- ◆ Non Yellowing

Width (mm)	Roll Length (m)	Unit	No
6	50	ROLL	<b>J411</b>
9	50	ROLL	<b>J412</b>
12	50	ROLL	<b>J413</b>
15	50	ROLL	<b>J414</b>
19	50	ROLL	<b>J415</b>
25	50	ROLL	<b>J416</b>
30	50	ROLL	<b>J417</b>
40	50	ROLL	<b>J418</b>
14	50	ROLL	<b>J419</b>



## Acrylic Based

- ◆ High quality double sided tape for general sail seaming
- ◆ Good initial tack
- ◆ High long term adhesion
- ◆ Low stretch mylar carrier
- ◆ Non Yellowing



Width (mm)	Roll Length (m)	Unit	No
6	65	ROLL	<b>J451</b>
9	66	ROLL	<b>J452</b>
12	66	ROLL	<b>J453</b>
19	66	ROLL	<b>J455</b>

## High Adhesion

- ◆ High quality double sided tape for general sail seaming
- ◆ Good initial tack
- ◆ High long term adhesion
- ◆ Low stretch mylar carrier
- ◆ Non Yellowing



Width (mm)	Roll Length (m)	Unit	No
6	50	ROLL	<b>J310</b>
9	50	ROLL	<b>J311</b>
12	50	ROLL	<b>J312</b>
15	50	ROLL	<b>J313</b>
19	50	ROLL	<b>J314</b>
25	50	ROLL	<b>J315</b>







## Super Tack



- ◆ High quality double sided tape for general sail seaming.
- ◆ Good initial tack.
- ◆ High long term adhesion.
- ◆ Low stretch mylar carrier.
- ◆ Non Yellowing.

Width (mm)	Roll Length (m)	Unit	No
9	33	ROLL	<b>J472</b>

## Acrylic Transfer Tape



- ◆ High performance transfer tape, more elastic than conventional double sided tapes.
- ◆ Transfer tapes do not have a film or cloth carrier.
- ◆ Non Yellowing.
- ◆ Uses: Excellent for spinnakers and light sails where some stretch in the seam is desired.

Width (mm)	Roll Length (m)	Unit	No
9	55	ROLL	<b>J132</b>
12	55	ROLL	<b>J133</b>
20	55	ROLL	<b>J134</b>

## Super Seam Tape




- ◆ Super Seam Tape is better for the sailcloth, particularly on film/film laminates and nylons where stitching can tear through the cloth.
- ◆ Super Seam Taped seams often stretch less than conventional sewn seams.
- ◆ Super Seam Tape can reduce costs as the number of rows of stitching on horizontal seams of large sails can be reduced.
- ◆ Seams bonded with Super Seam Tape are light and smooth.

Width (mm)	Roll Length (m)	Unit	No
12	55	ROLL	<b>J180</b>
19	55	ROLL	<b>J181</b>
25	55	ROLL	<b>J182</b>

# Balanced > 25


- ◆ 425 balanced construction
- ◆ High UV coating polyester
- ◆ Ideal UV cover fabric for roller furling genoas and in-mast furling mainsail
- ◆ Roll Width: 1370mm

## UV Coated Polyester



- ◆ Standard Style
- ◆ Alignment grid on release paper
- ◆ Cut lengths available
- ◆ Uses: Sail Numbers and Patching
- ◆ Roll Length: 45.7m
- ◆ Roll Width: 1370mm
- ◆ J614WT: Suitable for print applications where applicable

## Polyester Insignia




## Odyssey



- ◆ ODYSSEY is an acrylic coated, high performance 100% woven polyester fabric (300 denier) with a clear back coat.
- ◆ Super high strength, durability and with great abrasion resistance & UV.
- ◆ Used in outdoor applications such as marine tops, trailer covers, gazebos, canopies, tarps, playground equipment covers & bags.
- ◆ Weight: 220gsm
- ◆ Roll Width: 1630mm
- ◆ Roll Length: 68.6m

## Odyssey PSA (Adhesive Backed)



- ◆ ODYSSEY PSA is a impregnated coated, 100% woven polyester swith Pressure Sensitive Adhesive suitable for many indoor or outdoor applications.
- ◆ Mildew and UV resistant.
- ◆ Uses: Boat cover repairs, reinforcement & roller furling covers.
- ◆ Weight: 271gsm
- ◆ Roll Width: 1520mm
- ◆ Roll Length: 45.7m



## Sunbrella Furling

Sunbrella® Furling is used to prevent UV radiation from attacking the headsail while a boat is moored. It is advisable to place a UV strip on the leech and foot. Once rolled up, the sail is completely protected from the harmful effects of the sun. Specifically designed for this application, Sunbrella Furling is a fabric which – thanks to its lightweight, flexibility and durability – does not interfere with the sail's performance.

- ◆ Composition: 100% Sunbrella® acrylic
- ◆ Finish: Special Marine Treatment
- ◆ Weight: 195gsm
- ◆ Width: 165cm
- ◆ Roll Length: 50m
- ◆ Available in 5 colours



Natural  
**SUNFU5020**



Dune  
**SUNFU5026**



Silver  
**SUNFU5035**



Captain Navy  
**SUNFU5057**



Marine Blue  
**SUNFU5031**

## Sunbrella Furling Adhesive

Sunbrella® Furling is used to prevent UV radiation from attacking the headsail while a boat is moored. It is advisable to place a UV strip on the leech and foot. Once rolled up, the sail is completely protected from the harmful effects of the sun. Specifically designed for this application, Sunbrella Furling is a fabric which – thanks to its lightweight, flexibility and durability – does not interfere with the sail's performance.

- ◆ 5020 adhesive backed acrylic
- ◆ Composition: 100% Sunbrella® acrylic
- ◆ Finish: Special Marine Treatment
- ◆ Weight: 250gsm
- ◆ Width: 150cm
- ◆ Roll Length



Natural  
**SUNFUA5020**



Dune  
**SUNFUA5026**



Silver  
**SUNFUA5035**



Captain Navy  
**SUNFUA5057**



Marine Blue  
**SUNFUA5031**





## Oxford Nylon Bag Cloth 6oz

Black  
**V006BK**



Bright Red  
**V006BR**



Royal Blue  
**V006BU**




- ◆ Coated Oxford 6oz nylon fabric for the manufacture of bags and dust covers and for a wide variety of other marine and industrial uses.
- ◆ Features - Durable Coating, Weather Resistant, Tight Weave & Urethane Coated.
- ◆ Uses - Sail Bags, Banners, Flags, Back Packs & Soft Sided Luggage
- ◆ Weight: 210gsm
- ◆ Roll Width: 1500mm
- ◆ Roll Length: 100m

Yellow  
**V006YE**



White  
**V006WT**



Red  
**V006RD**



Navy Blue  
**V006NB**



Silver Grey  
**V006GY**



Green  
**V006GR**



Dark Grey  
**V006DG**



## Oxford Nylon Bag Cloth 4oz

White  
**F5600D00W**



Yellow  
**F5600D35W**



Green  
**F5600D40W**



Royal Blue  
**F5600D79W**



- ◆ Coated Oxford 4oz nylon fabric for the manufacture of bags and dust covers and for a wide variety of other marine and industrial uses.
- ◆ Features - Durable Water Repellent, Weather Resistant, Urethane Coated.
- ◆ Uses - Sail Bags, Banners, Flags, Back Packs & Soft Sided Luggage
- ◆ Weight: 105gsm
- ◆ Roll Width: 1520mm
- ◆ Roll Length: 100m

## Cordura 1000

Silver  
**F5300D08W**



Yellow  
**F5300D35W**



Forest Green  
**F5300D46W**



Black  
**F5300D60W**



Royal Blue  
**F5300D79W**



White  
**F5300D00W**



- ◆ 1000 Denier super tough woven, high tenacity nylon with a 33gsm/1 ounce urethane coating for durability and water repellency.
- ◆ Excellent resistance to abrasion, fading, rot and mildew.
- ◆ Uses: Heavy duty sail bags, horse blankets, backpacks.
- ◆ Water repellent and quick drying.
- ◆ High Tensile Strength and Tear Resistance.
- ◆ Weight: 458gsm
- ◆ Roll Width: 1520mm
- ◆ Roll Length: 45.7m

## Engineered to beat all the competition

For decades leading sailors and yachtsmen have relied on aquabatten.

Thanks to the unique 'tapered by design' construction, aquabatten delivers finer tips with thicker ends - resulting in a maximum form and strength through the batten length.


- ◆ Unique layering process reduces the risk of inter-laminar bond failure
- ◆ No filaments cut in tapering process - unique laminate construction encapsulated in a multi layer outer casing
- ◆ Minimised batten failure - reduces replacement costs
- ◆ Construction reduces stress - maximum stress is dissipated along the batten

In line with market leading sail design software which utilises FEA (Flexible Element Analysis), these systems express batten specifications in terms of an EI number. Bainbridge has now engineered **aquabatten** to cover a balanced range of EI numbers, giving the widest possible range to maximise application of **aquabatten** products in modern sail designs.

By manufacturing the product in an advanced bi-directional scrim lay-up, aquabatten uses up to 56 laminations which are totally encapsulated; ensuring the inherent strength of the construction is not ground away – which is the case with most other tapered battens. This ensures greater structural integrity, strength and durability.

- ◆ Handles torque stress caused by twist, where uni-directional battens fail
- ◆ Increased durability and strength when sail is stored or covered
- ◆ Epoxy resin composition gives a stronger, hydrophobic batten which keeps the batten at design weight and eliminates loss of strength in the resin
- ◆ Battens carefully calculated to a specific EI number (stiffness) for easy product selection

Today, aquabatten has been developed to offer the most comprehensive range of widths, lengths and types – designed to suit the very latest sail designs and to continue to offer the very best performance.





## Definition of EI

EI is an expression of the 'Flexural Rigidity' of a bar – **flexural rigidity** is simply defined as the resistance offered by a structure while undergoing bending.

## Understanding of EI

E = the stiffness of the material (Youngs Modulus)

I = the stiffness of the shape (form) itself

Therefore EI is the combination of the material and the shape.


In combining the two together (**EI**) it delivers a '**common comparator**' which allows you to technically specify the correct batten for that particular part of the sail construction

The higher the **EI**, the 'stiffer' the batten will be.

By using **EI** a sail maker has the flexibility of reducing the width of a batten by increasing the thickness, this enables lighter battens to be specified in the sail design

- resulting in a lower weight sail delivering improved performance.

## PART NUMBER BREAKDOWN



## Tapered Side Profile



Tapered	Length of Max Thickness %	Thickness Outer (mm)	Thickness Tip (mm)	EI Numbers for Width yy - mm				
				10	15	20	25	30
L40200075xxxxGyy	40	2	0.75	0.2	0.3			
L40250075xxxxGyy	40	2.5	0.75	0.4	0.6	0.8		
L40300075xxxxGyy	40	3	0.75	0.7	1	1.3	1.7	
L40350075xxxxGyy	40	3.5	0.75	1	1.6	2	3	
L40400100xxxxGyy	40	4	1	1.5	2.3	3	4	5
L40500100xxxxGyy	40	5	1	3	5	6	8	9
L40600100xxxxGyy	40	6	1	5	8	10	13	16
L40700125xxxxGyy	40	7	1.25		12	17	21	25
L40800125xxxxGyy	40	8	1.25		19	25	31	37
L40900125xxxxGyy	40	9	1.25		26	35	44	53
L41000175xxxxGyy	40	10	1.75			48	60	73
L41050175xxxxGyy	40	10.5	1.75			56	70	84
L41100175xxxxGyy	40	11	1.75			64	80	96
L41150200xxxxGyy	40	11.5	2				92	110
L41200200xxxxGyy	40	12	2				104	125
L41300200xxxxGyy	40	13	2					160
L41400200xxxxGyy	40	14	2					200

## Uniform Side Profile



Uniform	Length of Max Thickness %	Thickness Outer (mm)	Thickness Tip (mm)	EI Numbers for Width yy - mm				
				10	15	20	25	30
L00200200xxxxGyy	100	2	2	0.2	0.3			
L00250250xxxxGyy	100	2.5	2.5	0.4	0.6	0.8		
L00300300xxxxGyy	100	3	3	0.7	1	1.3	1.7	
L00350350xxxxGyy	100	3.5	3.5	1	1.6	2	3	
L00400400xxxxGyy	100	4	4	1.5	2.3	3	4	5
L00500500xxxxGyy	100	5	5	3	5	6	8	9
L00600600xxxxGyy	100	6	6	5	8	10	13	16
L00700700xxxxGyy	100	7	7		12	17	21	25
L00800800xxxxGyy	100	8	8		19	25	31	37
L00900900xxxxGyy	100	9	9		26	35	44	53
L01001000xxxxGyy	100	10	10			48	60	73
L01051050xxxxGyy	100	10.5	10.5			56	70	84
L01101100xxxxGyy	100	11	11			64	80	96
L01151150xxxxGyy	100	11.5	11.5				92	110
L01201200xxxxGyy	100	12	12				104	125
L01301300xxxxGyy	100	13	13					160
L01401400xxxxGyy	100	14	14					200

All sizes are in millimetres. EI calculated and tested by the 3 point method. EI calculated at stiffest part.



Main

LOA Feet	Roach Profile	Batten Top	Batten Upper Middle	Batten Lower Middle	Batten Lower
12.5	IMS/IRC	L00300300xxxxG10	L40200075xxxxG10	L40200075xxxxG10	L40250075xxxxG10
15	IMS/IRC	L00300300xxxxG10	L40250075xxxxG10	L40300075xxxxG10	L40300075xxxxG10
20	IMS/IRC	L00300300xxxxG10	L40350075xxxxG10	L40400100xxxxG10	L40400100xxxxG10
25	IMS/IRC	L00350350xxxxG15	L40400100xxxxG15	L40500100xxxxG15	L40500100xxxxG15
30	IMS/IRC	L00400400xxxxG15	L40600100xxxxG15	L40600100xxxxG15	L40700125xxxxG15
35	IMS/IRC	L00600600xxxxG15	L40700125xxxxG15	L40800125xxxxG15	L40800125xxxxG15
40	IMS/IRC	L00600600xxxxG20	L40700125xxxxG20	L40800125xxxxG20	L40900125xxxxG20
45	IMS/IRC	L00700700xxxxG20	L40900125xxxxG20	L41000175xxxxG20	L41050175xxxxG20
50	IMS/IRC	L00800800xxxxG25	L40900125xxxxG25	L41050175xxxxG25	L41100175xxxxG25
55	IMS/IRC	L00800800xxxxG30	L41000175xxxxG30	L41100175xxxxG30	L41150200xxxxG30
60	IMS/IRC	L00900900xxxxG30	L41100175xxxxG30	L41300200xxxxG30	L41400200xxxxG30


Jib

LOA Feet	Roach Profile	Batten Top	Batten Upper Middle	Batten Lower Middle	Batten Lower
12.5	Straight	L00200200xxxxG10	L40200075xxxxG10	L40200075xxxxG10	L40200075xxxxG10
15	Straight	L00200200xxxxG10	L40200075xxxxG10	L40200075xxxxG10	L40200075xxxxG10
20	Straight	L00200200xxxxG10	L40200075xxxxG10	L40250075xxxxG10	L40300075xxxxG10
25	Straight	L00200200xxxxG10	L40300075xxxxG10	L40350075xxxxG10	L40400100xxxxG10
30	Straight	L00250250xxxxG10	L40400100xxxxG10	L40500100xxxxG10	L40500100xxxxG10
35	Straight	L00300300xxxxG15	L40400100xxxxG15	L40500100xxxxG15	L40600100xxxxG15
40	Straight	L00350350xxxxG15	L40500100xxxxG15	L40600100xxxxG15	L40700125xxxxG15
45	Straight	L00400400xxxxG15	L40600100xxxxG15	L40700125xxxxG15	L40800125xxxxG15
50	Straight	L00400400xxxxG20	L40600100xxxxG20	L40700125xxxxG20	L40900125xxxxG20
55	Straight	L00500500xxxxG20	L40700125xxxxG20	L40800125xxxxG20	L41000175xxxxG20
60	Straight	L00600600xxxxG20	L40800125xxxxG20	L40900125xxxxG20	L41100175xxxxG20



## Pultruded Round Battens

- ◆ Outstanding stiffness to weight combined with low cost make round section pultrusions an excellent choice for full batten applications
- ◆ Considerably better stiffness/weight ratio than flat battens
- ◆ Longer lengths are available against special order



Diameter(mm)	Length (m)	EI	Weight (gpm)	Unit	No
6	6	3.3	52	METRE	<b>06R</b>
6	30	3.3	52	REEL 30M	<b>06R30</b>
8	6	11.2	88	METRE	<b>08R</b>
8	30	10.6	88	REEL 30M	<b>08R30</b>
10	6	25.8	144	METRE	<b>10R</b>
10	30	25.8	144	REEL 30M	<b>10R30</b>
12	6	53.6	211	METRE	<b>12R</b>
14	6	99.2	286	METRE	<b>14R</b>
16	6	169	364	METRE	<b>16R</b>
20	6	413	560	METRE	<b>20R</b>

## Pultruded Vinylester Batten

- ◆ High quality Vinylester construction
- ◆ Progressive range of stiffness
- ◆ Ideal for full length battens Bridgedeck catamarans, bluewater cruiser for example
- ◆ Only available in full lengths



20CV062



20CV080



20CV107



20CV125

Width (mm)	Length (m)	EI	Weight (gpm)	Unit	No
20	12	12.3	212	METRE	<b>20CV062</b>
20	12	26.5	273	METRE	<b>20CV080</b>
20	12	63.3	376	METRE	<b>20CV107</b>
20	12	101	441	METRE	<b>20CV125</b>





## Pultruded Sailman Batten



U30063




U30076



U30102



U30114



U30127

Width (mm)	Length (m)	EI	Weight (gms)	Unit	No
30	12	23.3	293	METRE	<b>U30063</b>
30	12	40.4	382	METRE	<b>U30076</b>
30	12	101.6	530	METRE	<b>U30102</b>
30	12	136.8	618	METRE	<b>U30114</b>
30	12	199.3	704	METRE	<b>U30127</b>

## Pultruded Batten



15CT



15CTM



15CTST



16HCP




25NTM




30CT024



30CT031R



30CT044



30CT044R



30CT052



40CT



40CTST

- ◆ These low cost, quality pultrusions are tough and durable.
- ◆ 30CT styles offer logical increases in stiffness and compliment the Sailman battens range.
- ◆ Allows consistent use of batten pocket & luff box
- ◆ 16HCP is used by most of the new skiff type dinghy classes.
- ◆ Only available in full lengths except 30CT031R and 30CT044R which are sold as 30m reels.

Dimensions (mm)	Length (m)	EI	Weight (gpm)	Unit	No
15 X 3.0	6	1.2	60	METRE	<b>15CT</b>
15 x 2.7	6	0.86	54	METRE	<b>15CTM</b>
15 x 4.0	6	1.7	84	METRE	<b>15CTST</b>
16 x 6.0	6	9.4	108	METRE	<b>16HCP</b>
25 x 8.0	7.62	29	186	METRE	<b>25NTM</b>
30 x 2.4	6	1.1	145	METRE	<b>30CT024</b>
30 x 3.1	6	2.3	188	METRE	<b>30CT031</b>
30 x 3.1	30	2.3	188	REEL 030M	<b>30CT031R</b>
30 x 4.4	6	7.1	266	METRE	<b>30CT044</b>
30 x 4.4	30	7.1	266	REEL 030M	<b>30CT044R</b>
30 x 5.2	6	12.7	315	METRE	<b>30CT052</b>
30 x 5.2	30	12.7	315	REEL 030M	<b>30CT052R</b>
38 x 3.0	6	2.8	192	METRE	<b>40CT</b>
38 x 5.0	6	12.9	292	METRE	<b>40CTST</b>



## Batten End Caps

- ◆ Spreads load at end of sail pocket.
- ◆ Use these endcaps for untapered batten styles
- ◆ Manufactured from nylon.



Type	Colour	Use With Batten	Width (mm)	Unit	Pack Quantity	No
Aquabatten 10mm	Black	L402000750300G10-L406001251400G10	-	EACH	10	<b>10DECI</b>
Aquabatten 10mm	Black	L402000750300G10-L406001251400G10	-	EACH	10	<b>10DECO</b>
Aquabatten 10mm	Black	L402000750300G10-L406001251400G10	-	EACH	1	<b>10DXSTECI</b>
Aquabatten 15mm	Red	Aquabatten 15mm	19	EACH	10	<b>15EC002</b>
Aquabatten 15mm	Red	Aquabatten 15mm	19	EACH	10	<b>15EC006</b>
Aquabatten 20mm	Red	Aquabatten 20mm	23	EACH	1	<b>20EC002</b>
Aquabatten 20mm	Red	Aquabatten 20mm	23	EACH	1	<b>20EC006</b>
Aquabatten 20mm	Red	Aquabatten 20mm	23	EACH	1	<b>20EC010</b>
Aquabatten 30mm / 30CT0xx	Black	AQ 30mm/30CT0xx Batten	30	EACH	10	<b>30CEC</b>
Aquabatten 30mm / 30CT0xx	Blue	30CT0xx Batten	30	EACH	10	<b>30CTEC</b>
Aquabatten 40mm/40CT/40CTST	Black	AQ 40mm/40CT/40CTST	40	EACH	10	<b>40CEC</b>
Round Battens	Black	06R	20	EACH	10	<b>06REC</b>
Round Battens	Black	08R	20	EACH	10	<b>08REC</b>
Round Battens	Black	10R	32.5	EACH	10	<b>10REC</b>
Round Battens	Black	12R	32.5	EACH	10	<b>12REC</b>
Round Battens	Black	14R	50	EACH	10	<b>14REC</b>
Round Battens	Black	16R	50	EACH	10	<b>16REC</b>
Round Battens	Black	20R	50	EACH	10	<b>20REC</b>
15mm Dinghy	Black	L402000750300G15-L406001251400G15	18	EACH	10	<b>15DNECI</b>
15mm Dinghy	Black	L402000750300G15-L406001251400G15	18	EACH	10	<b>15DNECO</b>
15mm Dinghy	Black	L402000750300G15-L406001251400G15	38	PAIR	10	<b>15DWEC</b>
15mm Dinghy	Black	15CT	20	EACH	10	<b>15CTECI</b>
15mm Dinghy	Black	15CT	20	EACH	10	<b>15CTECO</b>
15mm	Black	15CTST   16HCP	20	EACH	10	<b>15DXSTECI</b>
15mm	White	15CTST   16HCP	20	EACH	10	<b>15DXSTECIWT</b>
Untapered Batten	Black	16HCP	28	EACH	10	<b>A150</b>
Untapered Batten	White	25NTM	28	EACH	10	<b>25CTJM</b>
Untapered Batten	Black	25NTR, 25NTS	28	EACH	10	<b>24CTEC</b>






## Full Batten Systems

**sailman**  3000




- ◆ Precision moulded plastic slides
- ◆ Solid hinge system with 'lay-flat' rotation
- ◆ Flat battens with integral tension adjuster



**sailman**  3500




- ◆ Ideal for composite spars
- ◆ Used with wing masts
- ◆ Suits gates that are proud of sail track




**sailman**  4000



- ◆ Low friction sliders with stainless reinforced I-beam
- ◆ Cast stainless hinge with 'lay-flat' rotation
- ◆ Battens 30mm x 12.7mm or 16mm round



- ◆ Low friction sliders with stainless reinforced I-beam
- ◆ Cast stainless hinge with 'lay-flat' rotation
- ◆ Tough, durable construction
- ◆ Battens 30mm x 10.2mm or 12mm round








## Sailman 3000


Sailman 3000 is a compact integrated full batten system for boats up to 35ft. The system comprises seven profiles of slide and a durable slide linkage that is compatible with Series 25 and Series 35 batten boxes.



## Sailman 3500


The Sailman 3500 system has been specifically designed to fit a full batten sail on three of the most difficult types of spars:

- ◆ Alloy spars with sail feeding gates that are proud of the aft face of the mast.
- ◆ Composite spars.
- ◆ Alloy and composite wing masts.



## Sailman 4000


Sailman 4000 is a premium trackless full batten system for boats up to 43ft. The system comprises seven profiles of slides that feature a durable hinge system and stainless steel reinforced slugs. All slides are compatible with Series 35 and Series 55 batten boxes.






## Sailman 3000


A107  
Low friction slide  
15.2mm width




A108  
Low friction slide  
19mm width




A109  
Low friction slide  
22.2mm width




A114  
Low friction slide  
15.2mm Selden 'E'  
Series  
15.2mm wide




A116  
Low friction slide  
7.4mm diameter



A117  
Low friction slide  
8.4mm diameter



A118  
Low friction slide  
11.4mm diameter



Slides should be a snug fit and bear on aft face of mast.



1 Batten Slide



2 M10 Slide Linkage U00642



3 Long reach screw-on shackle A035BK



1 Batten Slides:

- Seven profiles to fit most modern spars.
- Precision moulded from glass fibre reinforced plastic with a PTFE impregnation.
- Integral compression pad transfers load directly on to aft face of spar.
- Slides can also be used as intermediates using A035BK long reach shackle.
- All slides measure 45mm or 1 <sup>3</sup>/<sub>4</sub> inches in length.


2 M10 Slide Linkage U00642:

- Pressure formed 316 stainless steel double toggle transfers compression directly and evenly onto slide.
- M10 thread allows connection to Series 25, Series 35 and most other brands of batten box.
- Hinge system allows 'lay-flat' rotation of battens when sail is stowed or reefed.
- Clevis pin with heavy duty split ring provides simple sail removal.

3 Long Reach Screw-On Shackle A035BK:

- Specifically designed for connecting our regular 7 Allslip slides to full batten sails, including those equipped with Sailman 3000, 3500 and 4000 systems.

Series 25 Luff Box  
U01540



Series 35 Luff Box  
U01531 / U01530



Series 35 Heavy Duty  
Luff Box  
Adjustable U01535



Description	Width (mm)	Waist (mm)	Length (mm)	Connection	Weight (g)	Battens	Part No.
Low Friction Slide 16mm Flat	15.2	7.5	45	U00642/A035BK/Webbing	13	-	<b>A107</b>
Low Friction Slide 19mm Flat	19	9	45	U00642/A035BK/Webbing	14	-	<b>A108</b>
Low Friction Slide 22mm Flat	22.2	11	45	U00642/A035BK/Webbing	16	-	<b>A109</b>
Low Friction Slide 16mm Selden 'E' Series	15.2	4.4	45	U00642/A035BK/Webbing	14	-	<b>A114</b>
Low Friction Slide 8mm Diameter	7.4	4	45	U00642/A035BK/Webbing	12	-	<b>A116</b>
Low Friction Slide 9mm Diameter	8.4	4	45	U00642/A035BK/Webbing	13	-	<b>A117</b>
Low Friction Slide 12.5mm Diameter	11.4	4	45	U00642/A035BK/Webbing	15	-	<b>A118</b>
Slide Linkage M10	-	-	-	M10 Thread	50	-	<b>U00642</b>
Selden Sail Groove Insert	30	-	155	-	-	-	<b>U99980</b>
Series 35 Standard Luff Box	62	-	120	M10 Thread	209	A, B, C, D, E, J, K, L	<b>U01530</b>
Series 35 Luff Box With Batten Tension Adjuster	62	-	120	M10 Thread	234	A, B, C, D, E, J, K, L	<b>U01531</b>
Series 35 Luff Box With Batten Tension Adjuster	62	-	120	M12 Thread	234	A, B, C, D, E, J, K, L	<b>U01532</b>
Series 35 HD Luff Box With Batten Tension Adjuster	62	-	120	M10 Thread	267	All Battens	<b>U01535</b>
Series 35 HD Luff Box With Batten Tension Adjuster	62	-	120	M12 Thread	267	All Battens	<b>U01536</b>
Series 25 Standard Luff Box With Batten Tension Adjuster	50	-	104	M10 Thread	122	A, B, C, D	<b>U01540</b>

## Sailman 3500

U00341S M10 Arm  
U00361 Intermediate



15.5mm width  
7.3mm waist

U00343S M10 Arm  
U00363 Intermediate



17.9mm width  
8.7mm waist

U00345S M10 Arm  
U00365 Intermediate



21.5mm width  
10.3mm waist

U00357S M10 Arm  
U00377 Intermediate




9.0mm width  
3.4mm waist

**1** Intermediate Slide



**1** M10 Batten Slide



**1** Batten Slides:

- ◆ Sailman 3500 slides are designed to run inside the mast groove and unlike Sailman 3000 and 4000 slides, do not bear on the aft face of the mast. This allows them to run past feeding gates and to slide in very narrow grooves on composite wing masts.
- ◆ To prevent wear on composite spars the slides have no exposed metal parts.
- ◆ The smallest slug version has a waist of just 3.4mm, allowing it to fit the narrowest of grooves.
- ◆ Glass reinforced and PTFE impregnated construction.
- ◆ Fully articulating solid stainless steel joint allows 'lay-flat' rotation of battens when sail is stowed or reefed.
- ◆ M10 thread allows connection to Series 25, Series 35, Series 55 and most other brands of batten box.

Series 25 Luff Box  
U01540



Series 35 Luff Box  
U01531 / U01530




Series 35 Heavy Duty  
Luff Box  
Adjustable U01535




30CT024

30CT031



30CT044

30CT052



U30063

U30076



U30102

U30114



U30127



06R



08R



10R



11RD/12R



14R



16R


Description	Width (mm)	Waist (mm)	Length (mm)	Connection	Weight (g)	Battens	Part No.
Intermediate/Head Slide 15.5mm	15.5	7.3	55	Webbing	30	-	<b>U00361</b>
Intermediate/Head Slide 18mm	17.9	8.7	55	Webbing	31	-	<b>U00363</b>
Intermediate/Head Slide 22mm	21.5	10.3	55	Webbing	34	-	<b>U00365</b>
Intermediate/Head Slide 9mm Diameter	9	3.4	55	Webbing	30	-	<b>U00377</b>
Batten Slide 15.5mm Series 35 Luff Box	15.5	7.3	55	M10 Thread	81	-	<b>U00341S</b>
Batten Slide 18mm Series 35 Luff Box	17.9	8.7	55	M10 Thread	81	-	<b>U00343S</b>
Batten Slide 22mm Series 35 Luff Box	21.5	10.3	55	M10 Thread	84	-	<b>U00345S</b>
Batten Slide 9mm Diameter Series 35 Luff Box	9	3.4	-	M10 Thread	80	-	<b>U00357S</b>
Series 35 Standard Luff Box	62	-	120	M10 Thread	209	A, B, C, D, E, J, K, L	<b>U01530</b>
Series 35 Luff Box With Batten Tension Adjuster	62	-	120	M10 Thread	234	A, B, C, D, E, J, K, L	<b>U01531</b>
Series 35 Luff Box With Batten Tension Adjuster	62	-	120	M12 Thread	234	A, B, C, D, E, J, K, L	<b>U01532</b>
Series 35 HD Luff Box With Batten Tension Adjuster	62	-	120	M10 Thread	267	All Battens	<b>U01535</b>
Series 35 HD Luff Box With Batten Tension Adjuster	62	-	120	M12 Thread	267	All Battens	<b>U01536</b>
Series 25 Standard Luff Box With Batten Tension Adjuster	50	-	104	M10 Thread	122	A, B, C, D	<b>U01540</b>





## Sailman 4000

U00462 Intermediate  
U00442S M10  
U00462H 16.3mm headslide



U00468 Intermediate  
U00448S M10  
U00468H 24mm headslide




U00464 Intermediate  
U00444S M10  
U00464H 18.8mm headslide



U00472 Intermediate  
U00452S M10  
U00472H 10mm headslide




U00466 Intermediate  
U00446S M10  
U00466H 23mm headslide



U00474 Intermediate  
U00454S M10  
U00474H 11mm headslide



U00463 Intermediate  
U00443S M10  
U00463H 19.8mm headslide



Slides should be a snug fit and bear on aft face of mast.



### 1 M10 Batten Slide



### 2 Intermediate Slide






Series 35 Luff Box  
U01531 / U01530



Series 35 Heavy Duty Luff Box  
Adjustable U01535



Series 55 Luff Box  
U01520Y



U30127

08R

10R

11RD/12R

14R

16R

### 1 Batten Slides:

- Seven profiles to fit most modern spars.
- Precision moulded from glass fibre reinforced plastic with PTFE impregnation.
- Durable stainless steel hinge system and connecting arm.
- Low friction compression pads transfer load directly onto aft face of spar.

### 2 Intermediate Slide:

- Moulded cotton reels for web on attachment in intermediate positions
- Can also be webbed to standard headboards as light duty headslides

The Sailman 4000 car is 52mm overall in length with a 40mm slug which is reinforced with a full width stainless steel I-beam insert giving it the strength to deal with the application.

Description	Width (mm)	Waist (mm)	Length (mm)	Connection	Weight (g)	Battens	Part No.
Intermediate/Head Slide 16mm Flat	16.3	8.5	52	Webbing	61	-	<b>U00462</b>
Intermediate/Head Slide Selden 'C'	19.8	9.4	52	Webbing	68	-	<b>U00463</b>
Intermediate/Head Slide 19mm Flat	18.8	4.7	52	Webbing	65	-	<b>U00464</b>
Intermediate/Head Slide 23mm Flat	23	12	52	Webbing	68	-	<b>U00466</b>
Intermediate/Head Slide 24mm Flat	24	12	52	Webbing	68	-	<b>U00468</b>
Intermediate/Head Slide 10mm Slug	10	3.6	52	Webbing	64	-	<b>U00472</b>
Intermediate/Head Slide 11mm Slug	11	3.7	52	Webbing	63	-	<b>U00474</b>
Spare Cotton Reel for Intermediate Slides	-	-	-	Webbing	-	-	<b>U00322</b>
Batten Slide 16mm Flat	16.3	8.5	52	M10 Thread	112	-	<b>U00442S</b>
Batten Slide Selden 'C'	19.8	9.4	52	M10 Thread	118	-	<b>U00443S</b>
Batten Slide 19mm Flat	18.8	4.7	52	M10 Thread	112	-	<b>U00444S</b>
Batten Slide 23mm Flat	23	12	52	M10 Thread	118	-	<b>U00446S</b>
Batten Slide 24mm Flat	24	12	52	M10 Thread	117	-	<b>U00448S</b>
Batten Slide 10mm Slug	10	3.6	52	M10 Thread	113	-	<b>U00452S</b>
Batten Slide 11mm Slug	11	3.7	52	M10 Thread	112	-	<b>U00454S</b>

### U01540

#### Series 25 Luff Box:

- ◆ Tough injection moulded fibre reinforced construction.
- ◆ Integrated tension adjustment system with friction lock.
- ◆ Accommodates battens up to 30mm x 5.2mm including 30CT052.
- ◆ Top plate design allows simple batten fitting and removal.
- ◆ Moulded M10 thread.



### U01530 / U01531 / U01532

#### Series 35 Luff Box:

- ◆ Tough injection moulded fibre reinforced construction.
- ◆ Concealed M10 nut for extra strength compared to threaded plastic designs.
- ◆ Optional batten tension adjustment with metal drive dog.
- ◆ U01530 is non adjustable.
- ◆ Snap in guides to suit round or flat battens supplied with every box.
- ◆ U01532 - M12 link connector



### U01535 / U01536

#### Series 35 HD Luff Box - Adjustable:

- ◆ Tough injection moulded fibre reinforced construction.
- ◆ Concealed M10 nut for extra strength compared to threaded plastic designs.
- ◆ Batten tension adjustment for Sailman battens with metal drive dog.
- ◆ Snap in guides to suit round or flat battens supplied with every
- ◆ U01536 - M12 link connector box.



### U01520Y

#### Series 55 Luff Box - Adjustable:

- ◆ Tough injection moulded fibre reinforced construction.
- ◆ Concealed M10 nut for extra strength compared to threaded plastic designs.
- ◆ Tension adjustment for Sailman battens with metal drive dog.
- ◆ Additional cover plates included for both flat battens and rod battens.
- ◆ Tension adjustment options:
  - ◆ - Adjustable or non adjustable for battens 30CT024, 30CT031, 30CT044, 30CT052, U30063, U30076, U30102
  - ◆ - Non adjustable only for battens 06R, 08R, 10R, 12R





## Batten Pocket Protectors

- ◆ All batten protectors have smoothly radiused nose to give low friction contact with the mast.
- ◆ Prices include screws, nuts and or rivets as appropriate



Attachment Type	Max Cavity Depth (mm)	Max Batten Width (mm)	Unit	Pack Quantity	No
Screw	14	15	EACH	10	<b>A001</b>
Rivets	15	15	EACH	10	<b>A000</b>
Screw	20	30	EACH	10	<b>A302</b>
Screw	25	30	EACH	10	<b>A002</b>
Rivet	25	30	EACH	10	<b>A004</b>
Nut & Bolt	25	40	PAIR	10	<b>A006</b>
Screw	30	60	EACH	10	<b>A005</b>

## Batten Pocket - Elastic



- ◆ Manufactured from woven elastic which does not narrow under stretch
- ◆ Polyester covering
- ◆ Only available in full rolls.

Width (mm)	Unit	Reel Length (m)	No
19	METRE	25	<b>E551</b>
25	METRE	25	<b>E552</b>
38	METRE	25	<b>E553</b>

## Batten Tensioners & End Fittings



- ◆ Suitable for use with full batten mainsails on catamarans / Skiffs up to 6m/20ft.
- ◆ Attach into size 00 grommets on each side of the batten pocket

Max Batten Width (mm)	Unit	Pack Quantity	No
8	EACH	10	<b>A082</b>







## Batten Box - Flat Battens

- ◆ Manufactured in reinforced nylon, with type 316 stainless steel bolts
- ◆ Can be used as a leech fitting or luffbox with Allslip slides.
- ◆ A300 attaches the slide with webbing.
- ◆ Sold complete: 2 halves with screws and nuts.



Max Cavity Depth (mm)	Max Batten Width (mm)	Unit	No
40	30 x 6.5	EACH	<b>A300BK</b>
40	30 x 6.5	EACH	<b>A300WT</b>
47	45 x 7	EACH	<b>A303BK</b>
47	46 x 7	EACH	<b>A303WT</b>

## Batten Box - Attachment Shackle

- ◆ Manufactured from type 316 stainless steel fittings.
- ◆ Custom designed for use with A303BK or A303WT.



Length (mm)	Width (mm)	Unit	No
42	12	EACH	<b>B303</b>

## Batten Box - Round Battens

- ◆ Manufactured in reinforced nylon, with type 316 stainless steel fastenings.
- ◆ Can also be used as a leech fitting.
- ◆ compression screws manufactured in type 316 stainless steel.
- ◆ A305 dimensions: 97mm x 44mm.
- ◆ A306 dimensions: 130mm x 55mm.



Max Batten Width (mm)	Use With Batten	Unit	No
12	06R-12R	EACH	<b>A305BK</b>
12	06R-12R	EACH	<b>A305WT</b>
20	16R-20R	EACH	<b>A306BK</b>

## Batten Box - Compression Screws

- ◆ Replacement compression screws manufactured in type 316 stainless steel.




Fits	Unit	No
A305BK/A305WT	EACH	<b>A305SS</b>
A306BK	EACH	<b>A306SS</b>






## SDA Batten Fittings - Leech



- ◆ These fittings manufactured by SDA,
- ◆ Suitable for fully battened mainsails on boats up to 40ft.
- ◆ Types are offered for either flat section or round section battens
- ◆ All are compatible with a wide range of track slides including sailman 3500,4000 & 4000HD systems.

Fitting Dimensions (mm)	Connection	Unit	No
80 x 38	M10 Thread	EACH	<b>A4081</b>
80 x 50	M10 Thread	EACH	<b>A4121</b>
80x 50	M10 Thread	EACH	<b>A4161</b>
120 x 50	M10 Thread	EACH	<b>A4201</b>

## SDA Batten Fittings - Luff



Fitting Dimensions (mm)	Connection	Unit	No
65 x 50	M10 Thread	EACH	<b>A4122</b>
80 X 38	M10 Thread	EACH	<b>A4082</b>
80 x 50	M10 Thread	EACH	<b>A4162</b>
100 x 50	M10 Thread	EACH	<b>A4202</b>
100 x 70	M10 Thread	EACH	<b>A453</b>

## SDA Batten Fittings - Compression Screws



- ◆ Alloy Screw

Unit	No
EACH	<b>A4121S</b>
EACH	<b>A4161S</b>
EACH	<b>A4201S</b>



## Nylon Sail Shackles - Plastic Snap In

- ◆ Bainbridge International's nylon shackles are designed for ease of use, high strength and ability to absorb shock loads.
- ◆ The unique snap design is often preferred as they are easier to fit



Length (mm)	Width (mm)	Unit	Pack Quantity	No
39	10	EACH	10	<b>A022</b>
45	11	EACH	10	<b>A021</b>

## Nylon Sail Shackles - Anti Jamming

- ◆ The unique design helps prevent slides jamming
- ◆ Injection moulded from tough nylon to absorb sudden impact loads.
- ◆ Unique design of shackle reduces elongation under load and offers higher strength.



Length (mm)	Width (mm)	Unit	Pack Quantity	No
39	10	EACH	10	<b>A023</b>
45	11	EACH	10	<b>A024</b>
47	11	EACH	10	<b>A028</b>
61	11	EACH	1	<b>A035BK</b>

## Nylon Sail Shackles - Screw On

- ◆ Bainbridge International's plastic shackles are designed for ease of use, high strength and ability to absorb shock loads.
- ◆ The screw design is strongest and permits easy detachment and re-attachment.



Length (mm)	Width (mm)	Unit	Pack Quantity	No
45	10	EACH	10	<b>A027</b>
47	11	EACH	10	<b>A026</b>

## Stainless Sail Shackles- Screw On

- ◆ Rolled edges to reduce chafe.
- ◆ Manufactured in type 316 stainless





Length (mm)	Width (mm)	Unit	Pack Quantity	No
16	10	EACH	10	<b>B129</b>
20	10	EACH	10	<b>B130</b>
24	10	EACH	10	<b>B131</b>
34	15	EACH	10	<b>B110</b>





## Sail Slides - Flat



Material	Cross Section	Description	Flange Width (mm)	Web Depth (mm)	Flange Depth (mm)	Waist (mm)	Length (mm)
Nylon 66	Flat		15.5	none	3	6.5	30
Nylon 66	Flat		18	none	2.7	9	33
Nylon 66	Flat	Metal Mast System 6	20	none	3.4	10	6
Nylon 66	Flat		22	none	3.5	11	35
Nylon 66	Flat	HA	22	none	3.5	8.25	39
Nylon 66	Flat	Metal Mast System 6	24	none	3	11	
N66/GRP	Flat	Compression	15.5	3.8	none	7.3	55
N66/GRP	Flat	Intermediate	15.5	3.8	none	7.3	55
N66/GRP	Flat	Allslip	15.8	-	3	4	45
N66/GRP	Flat	Compression	16.5	4.1	3.5	8.5	55
N66/GRP	Flat	Intermediate	16.5	4.1	3.5	8.5	55
N66/GRP	Flat	Compression	18	4.8	none	8.6	55
N66/GRP	Flat	Intermediate	18	4.8	none	8.6	55
N66/GRP	Flat	Compression	18.8	7.7	4.5	tba	52
N66/GRP	Flat	Intermediate	18.8	7.7	4.5	tba	52
N66/GRP	Flat	Allslip	19	-	2.8	9	45
N66/GRP	Flat	Compression	19.9	3.6	5.2	9.4	52
N66/GRP	Flat	Intermediate	19.9	3.6	5.2	9.4	52
N66/GRP	Flat	Compression	20.8	4.9	3.6	9.8	55
N66/GRP	Flat	Intermediate	20.8	4.9	3.6	9.8	55
N66/GRP	Flat	Compression	21	4.9	none	10	55
N66/GRP	Flat	Allslip	22.2	-	3.5	11	45
N66/GRP	Flat	Compression	23	-	4.5	12	52
N66/GRP	Flat	Intermediate	23	-	4.5	12	52
S/S	Flat	Proctor Mast	21	none	4	10	50
S/S	Flat	Proctor Mast	24.5	none	4.2	11	50
S/S	Flat	Proctor Mast	30.5	none	6	16	50



## Sail Slides - Flat



PTFE Coated Stainless  
B307 - B309



Bronze  
B006/B008A





Nylon Encapsulated Stainless  
B008 - B010

Mast Section	Part No
<b>Z-Spars:</b> Z301 - Trysail Track	<b>A007</b>
-	<b>A008</b>
-	<b>A006M</b>
<b>Sparcraft:</b> NG60, NG70, NG80, NG86, F580, F740, F1060, F1395, S1630, S2100, F2390, F3360, F4600	<b>A009</b>
<b>Z-Spars:</b> Z901, Z1001, Z1400 - Trysail Track	
<b>John Mast:</b> 220E, 262E, 290E	
<b>Sparcraft:</b> NG60, NG70, NG80, NG86, F580, F740, F1060, F1395, S1630, S2100, F2390, F3360, F4600	<b>A0091</b>
<b>Z-Spars:</b> Z901, Z1001, Z1400	
<b>John Mast:</b> 220E, 262E, 290E	
-	<b>A008M</b>
-	<b>U00341S</b>
-	<b>U00361</b>
<b>Z-Spars:</b> Z301	<b>A107</b>
<b>Sparcraft:</b> NG51, NG46, NG37, NG31, NG28	<b>U00442S</b>
<b>Z-Spars:</b> Z300, Z300e Z301, Z400E, Z404, Z500e, Z501	
<b>Sparcraft:</b> NG51, NG46, NG37, NG31, NG28	<b>U00462</b>
<b>Z-Spars:</b> Z300, Z300e Z301, Z400E, Z404, Z500e, Z501	
-	<b>U00343S</b>
-	<b>U00363</b>
<b>Sparcraft:</b> F460, F305, F230, F135, F385	<b>U00444S</b>
<b>Selden:</b> E-SECTION	
<b>Sparcraft:</b> F460, F305, F230, F135, F385	<b>U00464</b>
<b>Selden:</b> E-SECTION	
-	<b>A108</b>
<b>Selden:</b> C156, C175, C193, C211, C227, C245, C246, C285, C246, C285, C304	<b>U00443S</b>
<b>Selden:</b> C156, C175, C193, C211, C227, C245, C246, C285, C246, C285, C304	<b>U00463</b>
-	<b>U00345S</b>
-	<b>U00365</b>
-	<b>U00345S</b>
-	<b>A109</b>
<b>Sparcraft:</b> NG86, NG80, NG70, NG60, NG105, F1395, F1060, F580, F740	<b>U00446S</b>
<b>Z-Spar:</b> Z600E, Z700E, Z800E, Z900E, Z1100	
<b>Sparcraft:</b> NG86, NG80, NG70, NG60, NG105, F1395, F1060, F580, F740	<b>U00466</b>
-	<b>B008</b>
-	<b>B009</b>
-	<b>B010</b>






## Sail Slides - Flat



Material	Cross Section	Description	Flange Width (mm)	Flange Depth (mm)	Waist (mm)	Length (mm)
S/S coated	Flat		16	2.8	7	38
S/S coated	Flat		19.5	2.8	7	39
S/S coated	Flat		22	2.8	7	38
Bronze	Flat	Metal Mast System 6	20	4	10	6
Bronze	Flat	Metal Mast System 8	24	4	11	8

## Sail Slides - Semi Circular

Semi Circular Section Slide



Material	Material 2	Cross Section	Description 2	Flange Width (mm)	Flange Depth (mm)	Waist (mm)	Length (mm)
Nylon 66		Semi-circular	Selden	11	4.5	3	25
Nylon 66		Semi-circular	Selden	14	5.1	4	30
Nylon 66		Semi-circular	Selden	15	6	4	40
Nylon 66		Semi-circular	Selden C	19.5	6	8.5	30
Nylon 66		Semi-circular	Selden C	20	5.8	8.5	40
N66/GRP		Semi-circular	Compression	11	5.2	3.7	52
N66/GRP		Semi-circular	Intermediate	11	5.2	3.7	52
N66/GRP	PTFE	Semi-circular	Allslip	15.5	7.5	4.4	45
S/S	PTFE coated	Semi-circular	Selden	13		3	37



## Sail Slides - Flat



PTFE Coated Stainless  
B307 - B309



Bronze  
B006/B008A



Nylon Encapsulated Stainless  
B008 - B010

Mast Section	Part No
Z-Spars: Z301	<b>B307</b>
-	<b>B308</b>
Sparcraft: NG60, NG70, NG80, NG86, F580, F740, F1060, F1395, S1630, S2100, F2390, F3360, F4600	<b>B309</b>
Z-Spars: Z901, Z1001, Z1400	
John Mast: 220E, 262E, 290E	
-	<b>B006</b>
-	<b>B008A</b>

## Sail Slides - Semi Circular



A011 - A012



PTFE Coated Stainless  
B044


Mast Section	Part No
Sparcraft: F35, F50, F67, F78, F101, S137, S180, S260, S330, IMS80, IMS256	<b>A013</b>
Z-Spars: Z145, Z170, Z190, Z230, Z265	
John Mast: 150E, 116E, 125E	
-	<b>A014</b>
-	<b>A015</b>
Selden: C156, C175, C193, C211, C227, C245, C246, C285, C246, C285, C304	<b>A011</b>
Selden: C156, C175, C193, C211, C227, C245, C246, C285, C246, C285, C304	<b>A012</b>
Z-Spars: Z531, Z230, Z265, Z204, Z480, Z120, Z160, Z360, Z145	<b>U00454S</b>
Z-Spars: Z531, Z230, Z265, Z204, Z480, Z120, Z160, Z360, Z145	<b>U00474</b>
-	<b>A114</b>
-	<b>B044</b>





## Sail Slides - Circular

### Circular Section Slide



Allslip  
U00357S/U00377



A016 - A019

Material	Material 2	Cross Section	Description 2	Flange Width (mm)	Flange Depth (mm)	Waist (mm)	Length (mm)
Nylon 66	-	Circular	Slug	7.5	na	3	27
Nylon 66	S/S Bail	Circular	Slug	6.9	na	2.5	27
Nylon 66	-	Circular	Slug	9	na	3	27
Nylon 66	S/S Bail	Circular	Slug	8	na	2.5	27
Nylon 66	-	Circular	Slug	12	na	3	27
Nylon 66	S/S Bail	Circular	Slug	10	na	3.4	30
Nylon 66	-	Circular	Slug	14	na	3	25
Nylon 66	S/S Bail	Circular	Slug	11	na	3.4	30
Nylon 66	S/S Bail	Circular	Slug	8	na	3	50
Nylon 66	S/S Bail	Circular	Slug	8	na	1.7	50
Nylon 66	S/S Bail	Circular	Slug	9	na	3	51
Nylon 66	S/S Bail	Circular	Slug	12	na	4	73
N66/GRP	PTFE	Circular	Allslip	7.5	na	4	45
N66/GRP	PTFE	Circular	Allslip	8.5	na	4	45
N66/GRP	PTFE	Circular	Allslip	11.5	na	4	45
Nylon 66	Webbing	Circular	Kiwi	5.6	na	na	33
Nylon 66	Webbing	Circular	Kiwi	8	na	na	33
Nylon 66	Webbing	Circular	Kiwi	10	na	na	33
S/S	PTFE coated	Circular	Slug	7.5	na	3.5	37
S/S	PTFE coated	Circular	Slug	8.6	na	3.5	37
S/S	PTFE coated	Circular	Slug	10.5	na	3.5	37
N66/GRP	-	Circular	Compression	9	none	3.4	55
N66/GRP	-	Circular	Intermediate	9	none	3.4	55







## Sail Slides - Circular



Nylon 66 with S/S Bail  
A016S - A019S



PTFE Coated Stainless  
B035-B037




Kiwi  
A310/A313/A315

Mast Section	Part No
Z-Spars: Z145, Z170, Z190, Z230	A016
-	A016S
-	A017
-	A017S
-	A018
-	A018S
-	A019
-	A019S
-	A031
-	A031C
-	A032
-	A033
-	A116
-	A117
-	A118
-	A310
-	A313
-	A315
-	B035
-	B036
-	B037
-	U00357S
-	U00377





## Sail Slides - External




Stainless Steel  
B014SS - B016SS

Material	Material 2	Cross Section	Description 2	Flange Width (mm)	Flange Depth (mm)	Waist (mm)	Length (mm)
S/S	-	Flat	Track	15	na	na	
S/S	-	Flat	Track	22	na	na	
S/S	-	Flat	Track	25	na	na	
Bronze	-	Flat	Track	22	na	na	

## Sail Slides - Clew



PTFE Coated Stainless Steel  
B011 - B013



Cast Aluminium - B101




Cast Aluminium - B102

Material	Material 2	Cross Section	Description 2	Flange Width (mm)	Flange Depth (mm)	Waist (mm)	Length (mm)
Nylon 66	S/S Bail	Circular	Slug	8	na	3	50
Nylon 66	S/S Bail	Circular	Slug	8	na	1.7	50
Nylon 66	S/S Bail	Circular	Slug	9	na	3	51
Nylon 66	S/S Bail	Circular	Slug	12	na	4	73
S/S	PTFE coated	Circular	Slug	7.5	na	3	74
S/S	PTFE coated	Circular	Slug	9	na	3	75
S/S	PTFE coated	Circular	Slug	12.2	na	3	75
Aluminium Cast	-	Circular	Slug	11	na	2.6	38
Aluminium Cast	-	Circular	Slug	11	na	4	72
Aluminium Cast	-	Semi-circular	Selden Outhaul	12	10.5	4	78





## Sail Slides - External



Bronze  
Q110

Mast Section	Part No
-	<b>B014SS</b>
-	<b>B015SS</b>
-	<b>B016SS</b>
-	<b>Q110</b>

## Sail Slides - Clew



Cast Aluminium - B103



Nylon 66 S/S Bail  
A031 - A033




Boom Section	Part No
-	<b>A031</b>
-	<b>A031C</b>
<b>Z-Spars:</b> Z160, Z204	<b>A032</b>
-	<b>A033</b>
-	<b>B011</b>
<b>Z-Spars:</b> Z360, Z480, Z690A, Z690B	<b>B012</b>
-	<b>B013</b>
-	<b>B101</b>
-	<b>B102</b>
-	<b>B103</b>



# Headboards


## Small



- ◆ Smart Design gives a strong headboard which is incredibly easy to fit
- ◆ Heavy radius fillet on all edges - sail damage is substantially reduced
- ◆ Marine grade alloy - 5083 BS EN 573 3.2009 - highly resistant to seawater.
- ◆ The liners (D039S/D039N) complete the assembly making these fast, simple and easy to fit
- ◆ Quick fitting thanks to pilot holes for temporary pins - no slipping, forcing or reworking
- ◆ No rivets required
- ◆ Hole layout allows for headboard to be used in 3 planes of orientation

Luff (m)	LOA (ft)	Width (mm)	Length (mm)	Thickness (mm)	Weight (g)	Unit	Pack Quantity	No
12	30	100	123	2	32	EACH	2	<b>HBA912GY</b>
12	35	100	123	3	45	EACH	2	<b>HBA913GY</b>


## Small Medium



- ◆ Aluminium with hard anodised finish
- ◆ Colour: Anthracite Grey
- ◆ 5083 marine grade alloy

Luff (m)	LOA (ft)	Width (mm)	Length (mm)	Thickness (mm)	Weight (g)	Unit	Pack Quantity	No
14	35	116	142	2	41	EACH	2	<b>HBA922GY</b>
16	40	116	142	3	61	EACH	2	<b>HBA923GY</b>

## Medium




- ◆ Aluminium with hard anodised finish
- ◆ Colour: Anthracite Grey
- ◆ 5083 marine grade alloy

Luff (m)	LOA (ft)	Width (mm)	Length (mm)	Thickness (mm)	Weight (g)	Unit	Pack Quantity	No
14	42.5	135	165	2	54	EACH	2	<b>HBA932GY</b>
17	50	135	165	3	82	EACH	2	<b>HBA933GY</b>

A new technical design to accommodate the higher loading conditions of modern yachts and sails. The use of stainless steel liners allows faster assembly, with small pilot holes to position accurately during installation. Webbing can be applied for extra security and load holding through the liners. Can be used in three orientations with option to drill a hole for a slide bridge, allowing for any required sail offset.

- ◆ Aluminium with hard anodised finish
- ◆ Colour: Anthracite Grey
- ◆ 5083 marine grade alloy
- ◆ Recommended liner: D039S


## Medium Large



Luff (m)	LOA (ft)	Width (mm)	Length (mm)	Thickness (mm)	Weight (g)	Unit	Pack Quantity	No
20	50	155	189	3	114	EACH	2	<b>HBA943GY</b>
23	56	155	189	4	152	EACH	2	<b>HBA944GY</b>

- ◆ Aluminium with hard anodised finish
- ◆ Colour: Anthracite Grey
- ◆ 5083 marine grade alloy
- ◆ Recommended liner: D039S


## Large



Luff (m)	LOA (ft)	Width (mm)	Length (mm)	Thickness (mm)	Weight (g)	Unit	Pack Quantity	No
18	45	181	222	3	150	EACH	2	<b>HBA953GY</b>
21	54	181	222	4	200	EACH	2	<b>HBA954GY</b>

- ◆ Aluminium with hard anodised finish
- ◆ Colour: Anthracite Grey
- ◆ 5083 marine grade alloy
- ◆ Recommended liner: D039S

## Extra Large




Luff (m)	LOA (ft)	Width (mm)	Length (mm)	Thickness (mm)	Weight (g)	Unit	Pack Quantity	No
22	55	221	271	3	225	EACH	2	<b>HBA963GY</b>
25	62.5	221	271	4	300	EACH	2	<b>HBA964GY</b>

# Clewboards



Medium 3mm - CBA833GY

## Small



These new Clewboards are strong and easy to fit and are suitable for a large range of yachts.


With the increasing popularity of self-tacking jibs they are able to cope with the increased loads created by modern yachts.

Made in Marine grade Aluminium with a hard anodised finish, the use of stainless steel liners allows faster installation.

Boards are available in various thicknesses to cover the high loading conditions of these sails.

Luff (m)	LOA (ft)	Width (mm)	Length (mm)	Thickness (mm)	Weight (g)	Unit	Pack Quantity	No
15	37	42	201	3	60	EACH	2	<b>CBA813GY</b>


## Medium



- ◆ New 'Strong Arc' Shape - stronger and allows integrated fit and appearance to the sail
- ◆ Filleted external edges - on both face and back of plate
- ◆ Marine grade alloy - 5083 BS EN 573 3.2009 - highly resistant to seawater
- ◆ Designed to fit standard D039S/D039N liners
- ◆ The liners complete the assembly making these fast, simple and easy to fit
- ◆ No rivets required
- ◆ For larger sails clewboards can be layered

Luff (m)	LOA (ft)	Width (mm)	Length (mm)	Thickness (mm)	Weight (g)	Unit	Pack Quantity	No
18	45	71	306	3	140	EACH	2	<b>CBA833GY</b>
23	56	71	306	4	186	EACH	2	<b>CBA834GY</b>

## Large




- ◆ Aluminium with hard anodised finish
- ◆ Colour: Anthracite Grey
- ◆ 5083 marine grade alloy

Luff (m)	LOA (ft)	Width (mm)	Length (mm)	Thickness (mm)	Weight (g)	Unit	Pack Quantity	No
21	52	79	396	3	247	EACH	2	<b>CBA853GY</b>
25	62.5	79	396	4	330	EACH	2	<b>CBA854GY</b>



## Headboard Liners

- ◆ D039S stainless liner use with all Sailman X headboards & Clewboards



Use with Closing Tool	Diameter (mm)	Unit	Pack Quantity	No
C323	22	EACH	10	<b>D039S</b>

## Dinghy Headboards - Nylon

- ◆ Plastic headboards meet all major dinghy classes rules and are made from rigid nylon.
- ◆ Suitable for wide range of One Design classes.
- ◆ Manufactured from a rigid grade of nylon to give maximum leech support.
- ◆ Use D037N liner and D331 rivets.



Colour	Width (mm)	Length (mm)	Unit	Pack Quantity	No
White	75	100	EACH	10	<b>A043</b>
White	150	150	EACH	10	<b>A045</b>
White	145	145	EACH	10	<b>A048</b>

## Dinghy Headboards - Aluminium

- ◆ Suitable for wide range of One Design classes.
- ◆ Manufactured from a rigid grade of nylon to give maximum leech support.
- ◆ Use D037N liner and D331 rivets.



Colour	Width (mm)	Length (mm)	Thickness (mm)	Unit	Pack Quantity	No
Blue	105	115	1.6	EACH	10	<b>B907N</b>

## Yacht Headboards - Nylon

- ◆ Moulded from ultra rigid glass reinforced nylon.
- ◆ Smoothly rounded edges and webbing slot
- ◆ Smoothly rounded liner hole permits liner to sit flat.
- ◆ These headboards use D038N liner and D335 - D339 rivets.



Colour	Width (mm)	Length (mm)	Unit	Pack Quantity	No
White	115	140	EACH	10	<b>A052</b>







## Legacy Headboards - Aluminium



- ◆ Dual halyard position
- ◆ Manufactured from marine grade aluminium
- ◆ Use D039S/D039N liners and D335 - D339 rivets.
- ◆ Webbing slot for slide attachment
- ◆ Available in Gold, Silver & Blue anodized aluminium

Width (mm)	Length (mm)	Thickness (mm)	Unit	Pack Quantity	No
102	130	1.6	EACH	1	<b>B909SR</b>
115	146	1.6	EACH	1	<b>B910SR</b>
115	146	3.2	EACH	1	<b>B911SR</b>
133	165	3.2	EACH	1	<b>B912SR</b>
153	195	3.2	EACH	1	<b>B913SR</b>

## Legacy Headboards - Aluminium



- ◆ Dual halyard position
- ◆ Manufactured from marine grade aluminium
- ◆ Use D039S/D039N liners and D335 - D339 rivets. Webbing slot for slide attachment

Width (mm)	Length (mm)	Thickness (mm)	Unit	Pack Quantity	No
89	123	1.6	EACH	1	<b>B908</b>
102	130	1.6	EACH	1	<b>B909</b>
115	146	1.6	EACH	1	<b>B910</b>
115	146	3.2	EACH	1	<b>B911</b>
133	165	3.2	EACH	1	<b>B912</b>
153	195	3.2	EACH	1	<b>B913</b>
133	165	1.6	EACH	1	<b>B914</b>
178	227	3.2	EACH	1	<b>B915</b>



## Legacy Headboards - Aluminium



B908N / B909N



B910N / B911N



B912N / B913N



Width (mm)	Length (mm)	Thickness (mm)	Unit	Pack Quantity	No
89	123	1.6	EACH	1	<b>B908N</b>
102	130	1.6	EACH	1	<b>B909N</b>
115	146	1.6	EACH	1	<b>B910N</b>
115	146	3.2	EACH	1	<b>B911N</b>
133	165	3.2	EACH	1	<b>B912N</b>
153	195	3.2	EACH	1	<b>B913N</b>
133	165	1.6	EACH	1	<b>B914N</b>

## Headboard & Sailman X Liners

- ◆ D037N, D038N, D039N Manufactured from brass with nickel plated finish
- ◆ D039S manufactured from type 316 stainless steel



D037N / D038N / D039N



D039S

Use with Closing Tool	Diameter (mm)	Unit	Pack Quantity	No
C321	16	EACH	10	<b>D037N</b>
C322	19	EACH	10	<b>D038N</b>
C323	22	EACH	10	<b>D039N</b>
C323	22	EACH	10	<b>D039S</b>





## Outhaul Clew Blocks

B0901 / B0902 / B0903



B091 / B092 / B093 / B097



- ◆ A range of mainsail outhaul blocks available to suit boat sizes up to 25 metres.
- ◆ Ideal for inmast furling mainsails
- ◆ Manufactured in silver anodised, marine grade aluminium, Kemetal sheaves and carbon fibre rollers
- ◆ Plastic bushes protect webbing from abrasion on B092/3/7

Boat Size (ft)	Rope Size (mm)	Sheave (mm)	SWL (kg)	Unit	Pack Quantity	No
23-32	14	51	453	EACH	1	<b>B0901</b>
23-29	16	76	1360	EACH	1	<b>B0902</b>
32-52	16	95	1587	EACH	1	<b>B0903</b>
23-32	8	42	625	EACH	1	<b>B091</b>
23-39	10	50	750	EACH	1	<b>B092</b>
32-52	12	70	1750	EACH	1	<b>B093</b>
46-59	14	100	1750	EACH	1	<b>B097</b>

## Outhaul Clew Blocks



- ◆ Designed for offshore applications
- ◆ Block can easily be removed from sail and disassembled for servicing.
- ◆ Applications for 75ft
- ◆ Turned Ertalyte sheave takes rope up to 14mm
- ◆ High load bearing system
- ◆ Large radius bar for 25mm webbing

Boat Size (ft)	Rope Size (mm)	Sheave (mm)	SWL (kg)	Unit	Pack Quantity	No
75	14	70	3000	EACH	1	<b>B089</b>

## Legacy Clewboards

B845



B847



- ◆ Made of marine grade Aluminium and manufactured using a unique system that ensures an extra smooth finish.
- ◆ Available in a range of sizes & colours.
- ◆ Use with D332-D337/D339 rivets.

Width (mm)	Length (mm)	Thickness (mm)	Unit	Pack Quantity	No
29	140	1.6	EACH	1	<b>B845</b>
38	203	1.6	EACH	1	<b>B847</b>



## Round Rings Stainless Steel

- ◆ High grade 316 stainless steel
- ◆ TIG welded.
- ◆ Small diameter rings with the same size bar diameter will deform at a higher load although both will have similar tensile strength.



Bar Diameter (mm)	Inside Diameter (mm)	Weight (g)	SWL (kg)	Unit	Pack Quantity	No
3	25	5	100	EACH	10	<b>B204</b>
4.8	25	14	300	EACH	10	<b>B214</b>
4.8	32	16	150	EACH	10	<b>B118</b>
6.3	25	21	800	EACH	10	<b>B227</b>
6.3	32	28	600	EACH	10	<b>B117</b>
6.3	38	35	400	EACH	10	<b>B119</b>
6.3	51	42	350	EACH	10	<b>B120</b>
7.9	32	49	1000	EACH	1	<b>B228</b>
7.9	38	57	750	EACH	10	<b>B219</b>
7.9	44	64	900	EACH	10	<b>B121</b>
7.9	51	71	550	EACH	1	<b>B220</b>
9.3	38	85	1300	EACH	1	<b>B229</b>
9.3	51	106	1000	EACH	1	<b>B221</b>
9.3	64	127	750	EACH	1	<b>B223</b>
11.1	51	149	2300	EACH	1	<b>B225</b>

## Clew Pieces & Sail Rings - Stainless Steel

- ◆ Lighter and stronger than conventional equivalent welded rings.
- ◆ Cast construction eliminates weld weak point
- ◆ Made from 17-4 stainless steel, higher SWL than type 316.
- ◆ Elliptical cross-section and strengthening bar increase stiffness.
- ◆ Easy to web to sail.
- ◆ Can accommodate multiple sheets during sail or sheet point changes.



Bar Diameter (mm)	Weight (g)	SWL (kg)	Unit	Pack Quantity	No
9.3 x 6.4	73	2000	EACH	1	<b>B248</b>
10.5 x 7.2	126	3000	EACH	1	<b>B250</b>





## Inox Pressed Rings



- ◆ Manufactured from type 316 stainless steel, and injection moulded nylon
- ◆ Liners and pins are zinc passivated to reduce risk of staining
- ◆ Liners are seamless for maximum strength
- ◆ Range of colours to permit the use of house colours and sail identification



### Available Colour - xx

Available Colour - xx	Colour
<b>N</b>	Blue
<b>B</b>	Black
<b>R</b>	Red

Type	Set Hole Diameter (mm)							
	10	12	15	20	25	30	35	40
Inox Pressed Rings	<b>D208x</b>	<b>D207x</b>	<b>D209x</b>	<b>D210x</b>	<b>D211x</b>	<b>D212x</b>	<b>D213x</b>	<b>D214x</b>

## Inox Outhaul Attachments



- ◆ Type 316 stainless steel strap provides ultra-high strength attachment to Inox rings
- ◆ Minimum offset permits ring to be very low in the sail
- ◆ Low friction injection moulded slide with encapsulated bail
- ◆ 'C' products feature reduced bail thickness of 2mm for use in modern dinghy booms with very narrow groove opening

To be Used With	Slug Diameter (mm)	Unit	Pack Quantity	No
D207	7.9	EACH	10	<b>B2075</b>
D207	7.9	EACH	10	<b>B2075C</b>
D207	9.3	EACH	10	<b>B2076</b>
D207	9.3	EACH	10	<b>B2076C</b>
D209	7.9	EACH	10	<b>B2095</b>
D209	7.9	EACH	10	<b>B2095C</b>
D209	9.3	EACH	10	<b>B2096</b>
D210	9.3	EACH	10	<b>B2106</b>
D210	12	EACH	10	<b>B2108</b>
D211	9.3	EACH	10	<b>B2116</b>

## Technora Webbing

- ◆ 100% technora webbing
- ◆ Low elongation to high load ratio



Colour	Width (mm)	Breaking Load (kg)	Reel Length (m)	Unit	No
Black	20	1500	25	REEL	<b>E132</b>
Black	25	2100	25	REEL	<b>E134</b>





## Polyester Webbing

- ◆ Polyester Webbing available in various weights & widths
- ◆ Suitable for medium / high load application
- ◆ Sold in full reels only
- ◆ Other colours available on special request



Style	Width (mm)	Colour	Breaking Load (kg)	Reel Length (m)	Unit	No
Tubular	25	White	1700	46	METRE	<b>E124</b>
Standard	12	White	300	50	METRE	<b>E110</b>
Standard	19	White	500	50	METRE	<b>E111</b>
Standard	25	White	600	50	METRE	<b>E112</b>
Standard	30	White	850	50	METRE	<b>E117</b>
Heavy	12	White	400	25	METRE	<b>E109</b>
Heavy	20	White	500	25	METRE	<b>E127</b>
Heavy	25	White	750	25	METRE	<b>E113</b>
Heavy	30	White	850	25	METRE	<b>E114</b>
Heavy	40	White	1000	25	METRE	<b>E115</b>
Heavy	50	White	1200	25	METRE	<b>E116</b>
Heavy	63	White	1400	25	METRE	<b>E108</b>
Extra Heavy	25	White	1500	25	METRE	<b>E118</b>
Extra Heavy	30	White	1800	25	METRE	<b>E119</b>
Extra Heavy	40	White	2400	25	METRE	<b>E120</b>
Extra Heavy	51	White	3100	25	METRE	<b>E121</b>
Super Heavy	45	White	2800	25	METRE	<b>E129</b>

## Kevlar Webbing


- ◆ Polyester cover protects Kevlar from UV degradation and reduces flexing and chafe
- ◆ Available only on full reels



Colour	Width (mm)	Breaking Load (kg)	Reel Length (m)	Unit	No
White	25	1900	25	METRE	<b>E131</b>
White	35	2600	25	METRE	<b>E133</b>

## Dyneema Webbing

- ◆ Bainbridge Dyneema webbing
- ◆ Lighter than Kevlar and does not absorb water
- ◆ Excellent UV resistance and flex characteristics
- ◆ Dyneema is a very strong and low stretch fibre
- ◆ Available only on full reels



E135SPBK



E135SP / E139SP

Colour	Width (mm)	Breaking Load (kg)	Reel Length (m)	Unit	No
Natural	25	4000	25	METRE	<b>E135SP</b>
Natural	45	3100	25	METRE	<b>E139SP</b>
Black	25	4000	25	METRE	<b>E135SPBK</b>





## Maxi Rings Stainless Steel



- ◆ Bainbridge Maxi Rings are manufactured from Type 316 stainless steel, which is cleaned and passivated after welding to reduce the risk of staining
- ◆ TIG welded maximises strength
- ◆ Reinforcing bar reduces potential distortion under high load

Bar Diameter (mm)	Inside Width (mm)	Weight (g)	SWL (kg)	Unit	No
9.3	38	106	2600	EACH	<b>B229B</b>
11.1	51	191	4000	EACH	<b>B225B</b>
12.7	64	298	4500	EACH	<b>B226BB</b>
15.8	76	568	10000	EACH	<b>B218B</b>

## Maxi Rings with Bar Stainless Steel



- ◆ Type 316 stainless steel
- ◆ TIG welded,
- ◆ Reinforcing bar reduces potential distortion under high load
- ◆ Additional bar can be used to attach head carriage

Bar Diameter (mm)	Inside Width (mm)	Weight (g)	SWL (kg)	Unit	No
9.3	38	106	2600	EACH	<b>B229BB</b>
11.1	51	191	4000	EACH	<b>B225BB</b>
12.7	64	298	4500	EACH	<b>B226BB</b>
15.8	76	568	10000	EACH	<b>B218BB</b>

## Clew Pieces Stainless Steel



- ◆ Bainbridge Clew pieces are manufactured from Type 316 stainless steel, which is cleaned and passivated after welding to reduce the risk of staining
- ◆ TIG welded maximises strength
- ◆ Distinctive pattern incorporates high strength with slots to secure webbing and prevents ring from rotating

Bar Diameter (mm)	Inside Width (mm)	Weight (g)	SWL (kg)	Unit	No
7.9	51	99	850	EACH	<b>B123</b>
9.3	64	156	1000	EACH	<b>B124</b>
11.1	76	276	2800	EACH	<b>B125</b>
12.7	96	446	3800	EACH	<b>B126</b>



## Stainless Steel Tack Hooks

- Working loads shown are according to manufacturer's data and is dependent on application



B531/B532



B518/B519/B520



B528/B529

Length (mm)	SWL (kg)	Unit	Pack Quantity	No
50	200	EACH	1	<b>B518</b>
75	480	EACH	1	<b>B519</b>
100	1120	EACH	1	<b>B520</b>
75	880	EACH	1	<b>B528</b>
100	1680	EACH	1	<b>B529</b>
60	360	EACH	1	<b>B531</b>
80	880	EACH	1	<b>B532</b>

## Tylaska

### Tylaska Snap Shackles - Large Bail


- Allows fast and positive sheet attachment to sail.
- Use as tack fitting on code headsails
- Single handed operation
- Working loads shown are according to manufacturer's data and is dependent on application



Length (mm)	SWL (kg)	Breaking Load (kg)	Weight (g)	Unit	Pack Quantity	No
84	1136	2273	74	EACH	1	<b>TYT5L</b>
92	1818	3636	116	EACH	1	<b>TYT8L</b>
114	2727	5455	205	EACH	1	<b>TYT12L</b>
141	4545	9091	406	EACH	1	<b>TYT20L</b>

### Tylaska Tack Shackle

- Use 25mm webbing to attach to sail.
- Operation is one handed even under maximum 1800kg load
- Single handed operation
- Working loads shown are according to manufacturer's data and is dependent on application



SWL (kg)	Length (mm)	Unit	Pack Quantity	No
1800	73	EACH	1	<b>B710</b>



## Swedish Brass Piston Hanks - Forged Bronze



- ◆ Swedish brass jib hanks are renowned world-wide for quality, reliability and ease of fitting.
- ◆ Forged from marine quality brass and fitted with a stainless steel spring.
- ◆ B516 has a jaw opening of 25mm and internal dimensions of 25mm x 29mm. It is designed for use over forestay systems for storm jibs, not for large genoas.

Style	Size Type	Length (mm)	Unit	Pack Quantity	No
Knock On	0	44	EACH	10	<b>B510</b>
Knock On	1	52	EACH	10	<b>B511</b>
Knock On	2	65	EACH	10	<b>B512</b>
Knock On	3	74	EACH	10	<b>B513</b>
Knock On	4	82	EACH	10	<b>B514</b>
Knock On	5	95	EACH	10	<b>B515</b>
Knock On	6	107	EACH	10	<b>B516</b>

## Bronze Jib Hanks



- ◆ Wichard Jib hanks are easy to install- single handed operation
- ◆ Efficient use - no jamming of the system.

Style	Maximum Forestay (mm)	Length (mm)	Unit	Pack Quantity	No
Bronze	7.5	50	EACH	1	<b>B701</b>
Bronze	9	55	EACH	1	<b>B702</b>
Bronze	11	65	EACH	1	<b>B703</b>

## Stainless Jib Hanks



- ◆ Wichard Jib hanks are easy to install- single handed operation
- ◆ Efficient use - no jamming of the system.

Style	Maximum Forestay (mm)	Length (mm)	Unit	Pack Quantity	No
Stainless Steel	7.5	50	EACH	1	<b>B506</b>
Stainless Steel	9	55	EACH	1	<b>B504</b>
Stainless Steel	11	65	EACH	1	<b>B507</b>
Stainless Steel	13	80	EACH	1	<b>B505</b>
Stainless Steel	17	90	EACH	1	<b>B508</b>





## Swedish Brass Piston Hanks

- ◆ These traditional style jib snaps are sewn onto the foresail.



Style	Size Type	Length (mm)	Unit	Pack Quantity	No
Sew On	0	50	EACH	10	<b>B411</b>
Sew On	4	95	EACH	10	<b>B414</b>

## Plastic Jib Hanks

- ◆ Twist-On Hanks are ideal for dinghies, dayboats and sportsboats up to 25ft.
- ◆ Piston Hanks ideal for sportsboats and daysailers such as J24 and 1720.
- ◆ A090 suitable for 10mm webbing



A039



A038



A090



A188A

Forestay Diameter (mm)	Length (mm)	Unit	Pack Quantity	No
3.5	30	EACH	10	<b>A038</b>
5.0	30	EACH	10	<b>A039</b>
6.4	50	EACH	10	<b>A188A</b>
-	-	PACK 100	1	<b>A090</b>

## Hank Protectors

- ◆ Cut from clear vinyl.
- ◆ Available only in full packs of 100.



To be Used With	Unit	No
B506/B510/B511/B701	PACK 100	<b>A511</b>
B504/B507/B512/B702/B703	PACK 100	<b>A512</b>
B505/B513	PACK 100	<b>A513</b>
B508/B514/B515	PACK 100	<b>A514</b>



## Alloy Clamcleats - Starboard

The clamcleat principle is simple. A ridged 'V' groove holds rope firmly, yet is devoid of any moving parts to break or seize. It allows the immediate release of the rope by a short downward pull. Always tension the rope before it enters the cleat to avoid damage to the cleat.

A060



B057



B057AN



Item	Leechline Size (mm)	Unit	Pack Quantity	No
Cleat Only	3 - 6	EACH	10	<b>A060</b>
Cleat Only	3 - 6	EACH	10	<b>A068</b>
Cleat/Backplate/Rivets	3 - 6	EACH	10	<b>B057</b>
Cleat Only	3 - 6	EACH	10	<b>B057A</b>
Cleat/Backplate/Rivets	3 - 6	EACH	10	<b>B057AN</b>

## Alloy Clamcleats - Port

B067



B067A



B067AN



B301



B301A



B301AN



Item	Leechline Size (mm)	Unit	Pack Quantity	No
Cleat/Backplate/Rivets	3 - 6	EACH	10	<b>B067</b>
Cleat Only	3 - 6	EACH	10	<b>B067A</b>
Cleat Only	3 - 6	EACH	10	<b>B067AN</b>
Cleat/Backplate/Rivets	3 - 6	EACH	10	<b>B301</b>
Cleat Only	3 - 6	EACH	10	<b>B301A</b>
Cleat Only	3 - 6	EACH	10	<b>B301AN</b>

## Nylon Clamcleats - Starboard

- ◆ The tooth design allows a quick, positive lock that is easy to release
- ◆ It's low profile it is an ideal cleat for adjusting leech lines.

A067ABK



A067



A067A



Item	Leechline Size (mm)	Unit	Pack Quantity	No
Cleat/Backplate/Rivets	2 - 5	EACH	10	<b>A067</b>
Cleat Only	2 - 5	EACH	10	<b>A067A</b>
Cleat Only	2 - 5	EACH	10	<b>A067ABK</b>

## Nylon Clamcleats - Port

A057



A057A



A057ABK



Item	Leechline Size (mm)	Unit	Pack Quantity	No
Cleat/Backplate/Rivets	2 - 5	EACH	10	<b>A057</b>
Cleat Only	2 - 5	EACH	10	<b>A057A</b>
Cleat Only	2 - 5	EACH	10	<b>A057ABK</b>

## Nylon Clamcleats - Sail Edge

- ◆ Fits on the edge of a sail.
- ◆ Low profile nylon casing with a strong aluminium cleat

A061 A061A



A066 A066A



Item	Leechline Size (mm)	Unit	Pack Quantity	No
Cleat and Rivets	2 - 4	EACH	10	<b>A061</b>
Cleat Only	2 - 4	EACH	10	<b>A061A</b>
Cleat and Rivets	2 - 4	EACH	10	<b>A066</b>
Cleat Only	2 - 4	EACH	10	<b>A066A</b>

## Nylon Clamcleats



- ◆ The clamcleat principle is simple. A ridged 'V' groove holds rope firmly, yet is devoid of any moving parts to break or seize.
- ◆ It allows the immediate release of the rope by a short downward pull.
- ◆ Always tension the rope before it enters the cleat to avoid damage to the cleat.

Item	Leechline Size (mm)	Unit	Pack Quantity	No
Cleat/Backplate/Rivets	Up to 3	EACH	10	<b>A056</b>
Backplate	-	EACH	10	<b>A057BP</b>
Cover for A057/A057A	-	EACH	10	<b>A058</b>
Cleat Only	1.5 - 3	EACH	10	<b>A062</b>
Cleat Only	2 - 6	EACH	10	<b>A063A</b>
Backplate for A063A	-	EACH	10	<b>A063BP</b>

## Gransegel Cleats

Gransegel



- ◆ Gransegel sail edge leechline cleats
- ◆ Compact and lightweight fitting

Leechline Size (mm)	Length (mm)	Unit	Pack Quantity	No
1.5 - 2	29	EACH	10	<b>A054</b>
1.5 - 4	44	EACH	10	<b>A055</b>
2 - 4	58	EACH	10	<b>A059</b>



## Stainless Steel Thimbles

- ◆ Bainbridge International's sailmaker solid thimbles are manufactured from heavy gauge type 316 stainless steel
- ◆ Chemically cleaned and electropolished



Split



Solid

Wire Diameter (mm)	Type	Internal Diameter (mm)	Unit	Pack Quantity	No
3	Split	10	EACH	10	<b>B133</b>
4	Split	12	EACH	10	<b>B134</b>
5	Split	14	EACH	10	<b>B135</b>
6	Split	16	EACH	10	<b>B136</b>
7	Split	20	EACH	5	<b>B137</b>
8	Split	22	EACH	5	<b>B138</b>
10	Split	25	EACH	5	<b>B140</b>
3	Solid	12	EACH	10	<b>B153</b>
4	Solid	15	EACH	10	<b>B154</b>
5	Solid	18	EACH	10	<b>B155</b>
6	Solid	20	EACH	10	<b>B156</b>
8	Solid	24	EACH	10	<b>B158</b>

## Copper & Zinc Sleeves

- ◆ Plain copper and zinc sleeves.
- ◆ Manufactured to metric sizes.
- ◆ Closing tools available against special order



Wire Size (mm)	Material	Unit	No
2	Copper	PACK 100	<b>B540</b>
2.5	Copper	PACK 100	<b>B541</b>
3	Copper	PACK 100	<b>B542</b>
3.5	Copper	PACK 100	<b>B543</b>
4	Copper	PACK 100	<b>B544</b>
5	Copper	PACK 100	<b>B546</b>
6	Copper	PACK 100	<b>B547</b>
8	Copper	PACK 50	<b>B549</b>
2	Zinc	PACK 100	<b>B542N</b>
2.5	Zinc	PACK 100	<b>B543N</b>
3	Zinc	PACK 100	<b>B544N</b>
4	Zinc	PACK 100	<b>B545N</b>
3	Zinc	PACK 100	<b>B546N</b>







## Stimpson Grommets - Nickel



- ◆ The higher strength of these spur-toothed grommets derives from their thicker metal gauge, and flange closing.
- ◆ Available in full packs of 144.

Size	Set Hole Diameter (mm)	Unit	No
0	6.4	PACK 144	<b>D003NS</b>
1	9.5	PACK 144	<b>D004NS</b>
2	10.3	PACK 144	<b>D005NS</b>
3	11.1	PACK 144	<b>D006NS</b>
4	14.2	PACK 144	<b>D007NS</b>
5	15	PACK 144	<b>D008NS</b>
6	17.4	PACK 144	<b>D009NS</b>
8	26	PACK 144	<b>D011NS</b>

## Stimpson Grommets - Brass



- ◆ The higher strength of these spur-toothed grommets derives from their thicker metal gauge, and flange closing.
- ◆ Available in full packs of 144.

Size	Set Hole Diameter (mm)	Unit	No
0	6.4	PACK 144	<b>D003BS</b>
1	9.5	PACK 144	<b>D004BS</b>
2	10.3	PACK 144	<b>D005BS</b>
3	11.1	PACK 144	<b>D006BS</b>
4	14.2	PACK 144	<b>D007BS</b>
5	15.0	PACK 144	<b>D008BS</b>
6	17.4	PACK 144	<b>D009BS</b>
8	26	PACK 144	<b>D011NS</b>



## English Grommets - Nickel

- ◆ Low cost, roll-rim, spur-toothed grommets suitable for a wide range of applications in sailmaking and cover work
- ◆ Sizes 000 - 4 available in 200 (NX) or 1000 (N)
- ◆ Sizes 5 & 6 available in 100 (NX) or 1000 (N)



Size	Set Hole Diameter (mm)	Unit	No
000	4.8	PACK 200 or 1000	<b>D001(x)</b>
00	7.9	PACK 200 or 1000	<b>D002(x)</b>
0	9.5	PACK 200 or 1000	<b>D003(x)</b>
1	11.1	PACK 200 or 1000	<b>D004(x)</b>
2	12.7	PACK 200 or 1000	<b>D005(x)</b>
3	14.3	PACK 200 or 1000	<b>D006(x)</b>
4	14.7	PACK 200 or 1000	<b>D007(x)</b>
5	17.5	PACK 100 or 1000	<b>D008(x)</b>
6	22.2	PACK 100 or 1000	<b>D009(x)</b>

## English Grommets - Brass

- ◆ Low cost, roll-rim, spur-toothed grommets suitable for a wide range of applications in sailmaking and cover work.
- ◆ Available only in full packs.



Size	Set Hole Diameter (mm)	Unit	No
00	6.4	PACK 1000	<b>D002B</b>
0	8.4	PACK 1000	<b>D003B</b>
1	9.5	PACK 1000	<b>D004B</b>
2	11.9	PACK 1000	<b>D005B</b>
3	12.7	PACK 1000	<b>D006B</b>
4	14.7	PACK 1000	<b>D007B</b>
5	17	PACK 1000	<b>D008B</b>
8	26	PACK 50	<b>D011B</b>





## Circle & Tell Tale Patches

- ◆ Self Adhesive Insignia circles for reinforcement, protection, or repair.



Colour	Size (mm)					
	25	50	100	150	200	225
Black	<b>SD002BK</b>	<b>SL002BK</b>	<b>SL003BK</b>	<b>SL004BK</b>	<b>SL006BK</b>	-
Blue	<b>SD002BU</b>	<b>SL002BU</b>	<b>SL003BU</b>	<b>SL004BU</b>	-	-
Green	<b>SD002GR</b>	<b>SL002GR</b>	-	-	-	-
Red	<b>SD002RD</b>	<b>SL002RD</b>	-	-	-	-
White	<b>SD002WT</b>	<b>SL002WT</b>	<b>SL003WT</b>	<b>SL004WT</b>	<b>SL006WT</b>	<b>SL009WT</b>

## Class Insignia

- ◆ Pre-cut class insignia
- ◆ Precision die cut from self-adhesive polyester fabric.
- ◆ Supplied in pairs only.

Class	Colour					
	Black	Blue	Blue & Red	Green	Grey	Red
470	-	<b>INS017BU</b>	-	-	-	<b>INS017RD</b>
Albacore	-	<b>INS001BU</b>	-	-	-	-
Albin	-	-	-	-	-	<b>INS003RD</b>
Europe	-	-	<b>INS007BR</b>	-	-	-
Finn	-	<b>INS009BU</b>	-	-	-	<b>INS009RD</b>
Flying Fifteen	<b>INS019BK</b>	<b>INS019BU</b>	-	-	-	-
GP 14	<b>INS023BK</b>	<b>INS023BU</b>	-	-	-	-
H-Boat	-	-	<b>INS027B/R</b>	-	-	-
J22	-	<b>INS028BU</b>	-	-	-	-
J24	-	<b>INS029BU</b>	-	-	-	-
Kestrel	<b>INS031BK</b>	<b>INS031BU</b>	-	-	-	-
Merlin Rocket	<b>INS033BK</b>	-	-	-	-	-
Miracle	-	-	-	-	-	<b>INS037RD</b>
Mirror	<b>INS039BK</b>	-	-	-	-	-
Moody	<b>INS041BK</b>	<b>INS041BU</b>	-	-	-	-
OK	<b>INS045BK</b>	<b>INS045BU</b>	-	-	<b>INS045GY</b>	<b>INS045RD</b>
Optimist	<b>INS047BK</b>	<b>INS047BU</b>	-	-	<b>INS047GR</b>	<b>INS047RD</b>
Osprey	<b>INS049BK</b>	-	-	-	-	<b>INS049RD</b>
Pirate	-	-	-	-	-	<b>INS051RD</b>
Scorpion	<b>INS055BK</b>	<b>INS055BU</b>	-	-	-	<b>INS055RD</b>
Snipe	-	<b>INS059BU</b>	-	-	-	<b>INS059RD</b>
Solo	<b>INS061BK</b>	<b>INS061BU</b>	-	<b>INS061GR</b>	-	-
Topper	<b>INS067BK</b>	<b>INS067BU</b>	-	-	-	-
Wayfarer	-	-	-	-	-	<b>INS071RD</b>
Westerly	<b>INS073BK</b>	<b>INS073BU</b>	-	-	-	-
Yngling	-	<b>INS075BU</b>	-	-	-	-





## Plain Style Sail Numbers

- Numbers are cut from self adhesive insignia fabric
- Compatible with all types of Polyester & Laminate sailcloth.
- SN230 = Optimist class compliant effective May 2016

Order Example: **SN300BU2** — No = 2

Colour  
= Blue

0123

Available Colour - xx	Colour
<b>BU</b>	Blue
<b>BK</b>	Black
<b>RD</b>	Red

Digit	Actual Size (mm)							
	101	150	227	236	250	307	394	457
0	<b>SN100xx0</b>	<b>SN150xx0</b>	<b>SN225xx0</b>	<b>SN230xx0</b>	<b>SN250xx0</b>	<b>SN300xx0</b>	<b>SN380xx0</b>	<b>SN457xx0</b>
1	<b>SN100xx1</b>	<b>SN150xx1</b>	<b>SN225xx1</b>	<b>SN230xx1</b>	<b>SN250xx1</b>	<b>SN300xx1</b>	<b>SN380xx1</b>	<b>SN457xx1</b>
2	<b>SN100xx2</b>	<b>SN150xx2</b>	<b>SN225xx2</b>	<b>SN230xx2</b>	<b>SN250xx2</b>	<b>SN300xx2</b>	<b>SN380xx2</b>	<b>SN457xx2</b>
3	<b>SN100xx3</b>	<b>SN150xx3</b>	<b>SN225xx3</b>	<b>SN230xx3</b>	<b>SN250xx3</b>	<b>SN300xx3</b>	<b>SN380xx3</b>	<b>SN457xx3</b>
4	<b>SN100xx4</b>	<b>SN150xx4</b>	<b>SN225xx4</b>	<b>SN230xx4</b>	<b>SN250xx4</b>	<b>SN300xx4</b>	<b>SN380xx4</b>	<b>SN457xx4</b>
5	<b>SN100xx5</b>	<b>SN150xx5</b>	<b>SN225xx5</b>	<b>SN230xx5</b>	<b>SN250xx5</b>	<b>SN300xx5</b>	<b>SN380xx5</b>	<b>SN457xx5</b>
6/9	<b>SN100xx6/9</b>	<b>SN150xx6/9</b>	<b>SN225xx6/9</b>	<b>SN230xx6/9</b>	<b>SN250xx6/9</b>	<b>SN300xx6/9</b>	<b>SN380xx6/9</b>	<b>SN457xx6/9</b>
7	<b>SN100xx7</b>	<b>SN150xx7</b>	<b>SN225xx7</b>	<b>SN230xx7</b>	<b>SN250xx7</b>	<b>SN300xx7</b>	<b>SN380xx7</b>	<b>SN457xx7</b>
8	<b>SN100xx8</b>	<b>SN150xx8</b>	<b>SN225xx8</b>	<b>SN230xx8</b>	<b>SN250xx8</b>	<b>SN300xx8</b>	<b>SN380xx8</b>	<b>SN457xx8</b>

## Plain Style Sail Letters

- Numbers are cut from self adhesive insignia fabric
- Compatible with all types of Polyester & Laminate sailcloth.
- SL230 = Optimist class compliant effective May 2016

Order Example: **SL300RDB** — Letter = B

Colour  
= Red

ABC

Available Colour xxx	Colour
<b>BU</b>	Blue
<b>BK</b>	Black
<b>RD</b>	Red
<b>GY</b>	Grey

Letter	Actual Size (mm)						
	101	227	235	250	305	394	458
A - Z	<b>SL001xxx</b>	<b>SL225xxx</b>	<b>SL230xxx</b>	<b>SL250xxx</b>	<b>SL300xxx</b>	<b>SL380xxx</b>	<b>SL450xxx</b>





## INGLEFIELD CLIPS - NYLON



- ◆ These nylon hooks are ideal for securing covers etc.
- ◆ shock cord can be made to loop around items such as sails on a boom and sail covers.

Colour	Cord Size (mm)	Unit	Pack Quantity	No
Black	8	PAIR	1	<b>A550BK</b>

## SISTER CLIPS - STAINLESS STEEL



- ◆ Allows fast and positive sheet attachment to sail.
- ◆ Use on one- design or light air spinnakers.

Length (mm)	Weight (g)	Unit	Pack Quantity	No
38	11	EACH	1	<b>B605</b>

## WICHARD HALYARD SHACKLE - CAPTIVE PIN



- ◆ Standard type.
- ◆ Working loads shown are according to manufacturer's data and is dependent on application

Safe Working Load (kg)	Length (mm)	Unit	Pack Quantity	No
400	37	EACH	1	<b>B536</b>





## Rivets

- ◆ Semi-Tubular rivets available in both Aluminium and Brass



Diameter (mm)	Length (mm)	Unit	No
3.2	9.5	PACK 1000	<b>D332</b>
3.2	12.7	PACK 1000	<b>D333</b>
3.9	9.5	PACK 1000	<b>D331</b>
3.9	12.7	PACK 1000	<b>D334</b>
4.2	12.5	PACK 1000	<b>D336</b>
4.8	9.5	PACK 1000	<b>D335</b>
4.8	12.7	PACK 1000	<b>D337</b>
4.8	15.9	PACK 1000	<b>D339</b>

## Speedy Rivets

- ◆ Use with B401 hooks
- ◆ Tap the two parts together with a hammer until they connect firmly
- ◆ Available only in full packs of 100



Finish	Unit	No
Nickel Plated	PACK 100	<b>D050N</b>





## Pad Eyes - Folding



- ◆ Folding stainless steel pad eyes
- ◆ Fully polished finish
- ◆ 316 polished stainless steel

Style	Unit	No
Folding	EACH	<b>Q054744</b>
Folding	EACH	<b>Q054745</b>

## Pad Eyes



- ◆ Stainless steel pad eyes
- ◆ Fully polished finish
- ◆ 316 polished stainless steel

Unit	No
EACH	<b>Q054744P</b>
EACH	<b>Q054745P</b>

## Splicing Fids



- ◆ 5 piece stainless steel splicing kit
- ◆ Used by professionals

Unit	No
EACH	<b>RSE5097SPL</b>





## Heminway & Bartlett Dabond NANO Thread

- ◆ Dabond 2000 thread is available in other colours against special order
- ◆ Some colours available on 225g (8oz) spools
- ◆ Normally put up on 450g (1lb) spools, average box size 10 spools - 10lbs
- ◆ Heminway & Bartlett Dabond 2000 thread sets industry standards
- ◆ High strength and controlled stretch
- ◆ Resistance to abrasion and salt water
- ◆ Stability in sunlight and resistance to mildew
- ◆ Bonding and resistance to needle heat
- ◆ Continuous thread: no knots/breaks in thread



Dabond Size	Nearest Metric Size	Colour	Unit	No
V30	NM80	White	LB	ET030WT
V46	NM60	Black	LB	ET046BK
V46	NM60	Blue	LB	ET046BU
V46	NM60	White	LB	ET046WT
V69	NM36	Black	LB	ET069BK
V69	NM36	Blue	LB	ET069BU
V69	NM36	Grey	LB	ET069GY
V69	NM36	Red	LB	ET069RD
V69	NM36	Tan	LB	ET069TN
V69	NM36	White	LB	ET069WT
V92	NM25	Black	LB	ET092BK
V92	NM25	Blue	LB	ET092BU
V92	NM25	Grey	LB	ET092GY8
V92	NM25	Tan	LB	ET092TN8
V92	NM25	White	LB	ET092WT
V138	NM20	Black	LB	ET138BK
V138	NM20	Blue	LB	ET138BU
V138	NM20	Grey	LB	ET138GY
V138	NM20	Red	LB	ET138RD
V138	NM20	Tan	LB	ET138TN
V138	NM20	White	LB	ET138WT
V207	NM13	Black	LB	ET207BK
V207	NM13	White	LB	ET207WT
V346	NM8	V346	LB	ET346WT

## Thread Data Chart

Dabond Part No.	Needle Size Imperial/Metric		Average Yield m/yd per lb		Average Tensile kg lb	
V30	11-14	75-90	12,951	14,170	2.13	4.7
V46	12-15	80-95	7,467	8,170	3.36	7.4
V69	15-18	95-110	5,110	5,590	4.95	10.9
V92	17-20	105-125	3,866	4,230	6.58	14.5
V138	19-21	120-130	2,523	2,760	10.26	22.6
V207	21-23	130-160	1,682	1,840	14.71	32.4
V346	-	23-26	1,005	1,100	26.38	58.1



## Heminway & Bartlett Dabond NANO Anti-Wick Thread



- ◆ Anti-Wick combines superior sewability with a permanent additive that blocks water migration through seams and meets MIL SPEC V-T- 285 Type II
- ◆ Dabond 2000 thread is available in other colours against special order.
- ◆ Normally put up on 450g (1lb) spools, average box size 10 spools - 10lbs

Dabond Size	Nearest Metric Size	Colour	Unit	No
V69	NM36	Black	LB	<b>EA069BK</b>
V69	NM36	Pacific Blue	LB	<b>EA069PB</b>
V69	NM36	White	LB	<b>EA069WT</b>
V92	NM25	Black	LB	<b>EA092BK</b>
V92	NM25	Blue	LB	<b>EA092BU</b>
V92	NM25	Silver Grey	LB	<b>EA092GY</b>
V92	NM25	Pacific Blue	LB	<b>EA092PB</b>
V92	NM25	White	LB	<b>EA092WT</b>
V138	NM20	Black	LB	<b>EA138BK</b>
V138	NM20	White	LB	<b>EA138WT</b>

## Heminway & Bartlett Dabond Pre-Wound Bobbins



- ◆ Heminway and Bartlett Pre-Wound bobbins are wound on a thin core and therefore can have up to 30% more thread per bobbin than can be wound on by a sewing machine.
- ◆ Saves time and effort with fewer bobbin changes and longer continuous seams.

Dabond Type	Colour	Bobbin Type	Unit	No
V46	White	F	PACK 144	<b>EB046FWT</b>
V46	White	G	PACK 144	<b>EB046GWT</b>
V46	White	L	PACK 144	<b>EB046LWT</b>
V69	White	D	PACK 144	<b>EB069DWT</b>
V69	White	F	PACK 144	<b>EB069FWT</b>
V69	White	G	PACK 144	<b>EB069GWT</b>
V69	Tan	L	PACK 144	<b>EB069LTN</b>
V69	White	L	PACK 144	<b>EB069LWT</b>
V92	White	D	PACK 144	<b>EB092DWT</b>
V92	White	F	PACK 144	<b>EB092FWT</b>
V92	Black	G	PACK 144	<b>EB092GBK</b>
V92	White	G	PACK 144	<b>EB092GWT</b>
V92	White	L	PACK 144	<b>EB092LWT</b>
V138	White	39	PACK 144	<b>EB13839WT</b>
V138	White	G	PACK 144	<b>EB138GWT</b>



## SolarFix Thread

- ◆ SolarFix® Made of 100% PTFE (Poly Tetra Fluoro Ethylene) fibre.
- ◆ SolarFix® is an excellent thread choice for all marine and outdoor applications
- ◆ Extremely resistant to harmful UV rays and atmospheric degradation
- ◆ SolarFix thread will not lose any significant strength due to UV
- ◆ Limited warranty



Colour	Equivalent dtex	Equivalent Tex	Unit	Spool Length (m)	No
Clear	1500	92	SP00L	3400	<b>EF1500CH1T</b>
Black	1500	92	SP00L	3400	<b>EF1500DH1T</b>
White	1500	92	SP00L	3400	<b>EF1500WH1T</b>
Clear	2640	138	SP00L	1920	<b>EF2640CH1T</b>
Black	2640	138	SP00L	1920	<b>EF2640DH1T</b>
White	2640	138	SP00L	1920	<b>EF2640WH1T</b>

## SunStop Antiwick Polyester Thread

- ◆ SunStop Thread, A high performance twisted multifilament polyester sewing thread with advanced UV protection and anti-wick finish. Specially designed for outdoor applications where seam strength retention and fade prevention during UV exposure are required
- ◆ Top 16 Sunbrella Colours.
- ◆ Anti-Wicking
- ◆ 225g (8oz) spools

Type	Thread Size	
	<b>92 - NM25</b>	<b>138 - NM20</b>
Polyester Thread	<b>EY092xxx8</b>	<b>EY138xxx8</b>



Available Colour - xxx	Colour
<b>BEG</b>	Beige
<b>BK</b>	Black
<b>BRN</b>	Brown
<b>BG</b>	Burgundy
<b>GY</b>	Cadet Grey
<b>CNV</b>	Captain Navy
<b>FGR</b>	Forest Green
<b>JRD</b>	Jockey Red
<b>LN</b>	Linen
<b>LRD</b>	Logo Red
<b>NV</b>	Navy
<b>PB</b>	Pacific Blue
<b>SR</b>	Silver
<b>TS</b>	Toast
<b>BR</b>	True Brown
<b>WT</b>	White





## Hand Sewing Thread

- ◆ Hand Sewing Thread & Sailmaker Wax.
- ◆ Supplied on spools only
- ◆ White waxed thread ideal for repair kits



EW351 / EW352



EW352BK



EW346 / EW462 / EW499



ET353



EW500

Colour	Spool Length (m)	Spool Weight (g)	Width	Unit	Pack Quantity	No
White	457	-	1.6	SP00L	1	<b>EW351</b>
White	457	-	3.2	SP00L	1	<b>EW352</b>
Black	457	-	3.2	SP00L	1	<b>EW352BK</b>
White	346	450	-	LB	1	<b>EW346</b>
White	462	450	-	LB	1	<b>EW462</b>
White	499	450	-	LB	1	<b>EW499</b>
White	-	30	-	SP00L	1	<b>ET353</b>
White	6	-	-	BOX 12	1	<b>EW500</b>

## Sailmakers Wax



C040



C041

- ◆ White waxed thread ideal for repair kits
- ◆ C040 Natural bees wax
- ◆ C041 Composition bees wax

Weight (g)	Unit	Pack Quantity	No
85	EACH	1	<b>C040</b>
454	EACH	1	<b>C041</b>

## Leather



- ◆ Sailmakers soft chrome leather
- ◆ 1.6 - 2.0mm average thickness
- ◆ Used in corner reinforcement and final finishing
- ◆ E161 - Only available in full hides
- ◆ Smooth on one side, suede on the other

Size (mm)	Unit	No
305 x 610	EACH	<b>E160</b>
Variable	EACH	<b>E161</b>



## Sunbrella Plus

- ◆ The classic marine fabric combined with a special acrylic coating on one side
- ◆ Sunbrella® Plus is the premier solution for protecting boats and their crews in extreme conditions
- ◆ Sunbrella Marine fabrics are the superior choice for Boat Covers, Biminis, Protective & Rear Closures
- ◆ Sunbrella® Plus has three times greater water resistance than standard Sunbrella, and enhanced resistance to mildew, thanks to its anti-fungal treatment, formulated specifically for use in a marine environment
- ◆ Composition: 100% Sunbrella® acrylic
- ◆ Finish: Resin based anti-fungi coating, water and UV resistant
- ◆ Weight: 320gsm
- ◆ Width: 1520mm
- ◆ Roll Length: 50m
- ◆ 5 year limited warranty
- ◆ Available in 32 colours

Natural  
**SUNTT5020**



Dune  
**SUNTT5026**



Oyster  
**SUNTT5030**



Marine Blue  
**SUNTT5031**



Jet Black  
**SUNTT5032**



Burgundy  
**SUNTT5034**



Silver  
**SUNTT5035**



Forest Green  
**SUNTT5040**



Hemp Beige  
**SUNTT5048**



Charcoal Grey  
**SUNTT5049**



Captain Navy  
**SUNTT5057**



Dark Navy  
**SUNTT5058**



Graphite  
**SUNTT5082**



Toast  
**SUNTT5528**



Cadet Grey  
**SUNTT5530**



Taupe  
**SUNTT5548**



Dark Smoke  
**SUNTT5085**



Fianelle  
**SUNTT5087**



Charcoal Pique  
**SUNTT5088**



Beige Chine  
**SUNTT5089**



Dark Green  
**SUNTP016**



Flax  
**SUNTP017**



Apricot  
**SUNTP018**



Amethyst  
**SUNTP019**



Heather Beige  
**SUNTP012**



Prussian Blue  
**SUNTP013**



Crimson Red  
**SUNTP015**



Hazel Brown  
**SUNTP020**



Midnight Blue  
**SUNTP021**



Blue Jeans  
**SUNTP022**



Arctic Blue  
**SUNTP023**



Atlantic Blue  
**SUNTP024**



Ebony  
**SUNTP025**



## Sunbrella

Natural  
**SUNB5020**



Dune  
**SUNB5026**



Oyster  
**SUNB5030**



Marine Blue  
**SUNB5031**



Jet Black  
**SUNB5032**



Burgundy  
**SUNB5034**



Silver  
**SUNB5035**



Hemp Beige  
**SUNB5048**



Charcoal Grey  
**SUNB5049**



Captain Navy  
**SUNB5057**



Dark Navy  
**SUNB5058**



Graphite  
**SUNB5082**



Toast  
**SUNB5528**



Cadet Grey  
**SUNB5530**



Taupe  
**SUNB5548**



Heather Beige  
**SUNB5572**



Prussian Blue  
**SUNBP013**



Crimson Red  
**SUNBP015**



Dark Green  
**SUNBP016**



Flax  
**SUNBP017**




Amethyst  
**SUNBP019**



Arctic Blue  
**SUNBP023**

- ◆ Sunbrella® is recommended for making sail, winch, steering wheel, stackpacks and Bimini covers
- ◆ Sunbrella Marine is highly breathable and certified rot-proof
- ◆ Manufactured using solution-dyed acrylic fibre, Sunbrella® is treated with a fluorocarbon finish that boosts the fabrics resistance to stains, greasy substances and water

- ◆ Composition: 100% Sunbrella® acrylic
- ◆ Finish: Special Marine Treatment
- ◆ Weight: 300gsm
- ◆ Width: 1520mm
- ◆ 10 year limited warranty
- ◆ Available in 21 colours



## Sunbrella Supreme

Sunbrella Supreme is a luxurious, waterproof exterior marine fabric featuring Sunbrella canvas on the exterior face and a special Sunbrella flocking on the reverse side.

The unique bonding process creates a waterproof Sunbrella canvas with a beautifully soft headliner underneath.

Available in five colour options, Sunbrella Supreme is ideal for any marine application where a waterproof canvas is necessary and the luxurious style the flocking creates is desired.


Sunbrella Supreme will surely bring your next project to a higher level

- ◆ Weight: 440gsm
- ◆ Width: 1520mm
- ◆ Roll Length: 50m



## Surlast

- ◆ Surlast from Dickson is a 100% solution dyed polyester with a PU coating on one side Recommended for winter covers, bimini tops and console covers
- ◆ Finish: PU Coating on one side
- ◆ Weight: 240gsm
- ◆ Width: 1520mm
- ◆ Roll Length: 90m
- ◆ 3 year limited warranty
- ◆ Available in 4 colours



## Seamark

- ◆ Seamark PVC coated Sunbrella acrylic
- ◆ Colour matched PVC backing with Sunbrella top coat
- ◆ Roll Length: 45.7m
- ◆ Roll Width: 1520mm





## Solacryl Coated Acrylic



- ◆ Perfect for use in biminis, tonneaus, spray hoods, flybridge and mooring covers
- ◆ Optimal waterproofing - giving a water column in excess of 1000mm
- ◆ Solacryl is coated on one side with hi tech resin impregnation
- ◆ Resin finish is matt and clear - no white or milky appearance to canvas
- ◆ Antimicrobial treatment prevents mico-organisms adhering to the fabric
- ◆ Offers superior waterproof qualities with breathability
- ◆ Acrylic yarns give excellent UV protection
- ◆ Weight: 355gsm
- ◆ Width: 1520mm
- ◆ Roll Length: 60m




## Solacryl Uncoated Acrylic

- ◆ Perfect for use in dodgers, stack packs, sail covers, awnings and upholstery
- ◆ Solacryl Unique Infinity Process creates a softer fabric resulting in a smooth finish ideal for complex curves as seen in sprayhoods and cockpit enclosures etc
- ◆ Rot proof, oil and grease resistant
- ◆ Weather resistant - rain or shine
- ◆ Easy Clean
- ◆ Colour fastness 7-8 rating
- ◆ Weight: 320gsm
- ◆ Width: 1520mm



## Odyssey

White  
**F0800A00Y**



Red  
**F0800A10Y**



Birch  
**F0800A14Y**



Caribbean Blue  
**F0800A18Y**



Lakeside Blue  
**F0800A20Y**



Teal  
**F0800A44Y**



Forest Green  
**F0800A46Y**



Black  
**F0800A60Y**



Brown  
**F0800A62Y**



Taupe  
**F0800A65Y**



Sand  
**F0800A66Y**



Burgundy  
**F0800A75Y**



Turquoise  
**F0800A85Y**



Silver Grey  
**F0800A88Y**



Harbour Blue  
**F0800A90Y**



Charcoal Grey  
**F0800A97Y**




Royal Blue  
**F0800A79Y**

- ◆ ODYSSEY is an acrylic coated, high performance 300dpi woven polyester fabric with a clear back coat
- ◆ Strong, durable. with a high UV and abrasion resistance
- ◆ ODYSSEY can be used in outdoor applications such as marine tops, trailer covers, gazebos, canopies, tarpaulins, playground equipment covers & bags
- ◆ Weight: 220gsm
- ◆ Roll Width: 1630mm
- ◆ Roll Length: 68.6m

## Odyssey Softouch

White  
**F0805A00Y**



Caribbean Blue  
**F0805A18Y**



Harbour Blue  
**F0805A90Y**




Black  
**F0805A60Y**

- ◆ ODYSSEY SOFTOUCH is a 100% solution dyed woven polyester with a light weight, non-woven, soft fuzzy polyester backing
- ◆ Strong, durable. with a high UV and abrasion resistance
- ◆ Uses: Boat, trailer covers, carbon spinnaker poles and wheels
- ◆ The softtouch finish helps reduce scratching, excellent on polished or varnished surfaces
- ◆ Weight: 405gsm
- ◆ Roll Width: 1520mm
- ◆ Roll Length: 45.7m


## Odyssey PSA (Adhesive Backed)

- ◆ ODYSSEY PSA is an acrylic coated, 100% woven polyester with Pressure Sensitive Adhesive suitable for many indoor or outdoor applications
- ◆ Mildew and UV resistant
- ◆ Uses: Boat cover repairs, reinforcement & roller furling covers
- ◆ Weight: 271gsm
- ◆ Roll Width: 1520mm
- ◆ Roll Length: 45.7m



## Odyssey FR

- ◆ ODYSSEY FR is an fire retardant acrylic coated, high performance 300dpi woven polyester fabric with a clear back coat
- ◆ Super high strength, durability and with great abrasion resistance & UV
- ◆ Meets CPAI-84 & NFPA-701
- ◆ Weight: 240gsm
- ◆ Roll Width: 1630mm
- ◆ Roll Length: 68.6m




## Pattern Material

- ◆ Economical, flexible and stable pattern material.
- ◆ The ideal material to make on site patterns for awnings and any type of cover.
- ◆ Can also be used to make sail bags and accessories.
- ◆ Roll Width: 1830mm
- ◆ Roll Length: 200m



## Top Gun

White  
**F0300A00Y**



Sunset Red  
**F0300A10Y**



Indian Birch  
**F0300A14Y**



Caribbean Blue  
**F0300A18Y**



Navy Blue  
**F0300A22Y**



Teal  
**F0300A44Y**



Forest Green  
**F0300A46Y**



Onyx Black  
**F0300A60Y**



Taupe  
**F0300A65Y**



Sand  
**F0300A66Y**



Hemp Beige  
**F0300A67Y**



Chocolate Brown  
**F0300A68Y**



Buckskin Tan  
**F0300A74Y**



Burgundy  
**F0300A75Y**



Royal Blue  
**F0300A79Y**



Turquoise  
**F0300A85Y**



Aquamarine  
**F0300A89Y**



Harbour Blue  
**F0300A90Y**



Seagull Grey  
**F0300A97Y**



Charcoal Grey  
**F0300A98Y**

- ◆ TOP GUN is an acrylic-coated 100% 600dpi woven polyester fabric utilising a proprietary process to coat both sides, top and bottom, thus allowing the fabric to be reversible
- ◆ It is characterised by excellent strength, durability, tear & abrasion resistance
- ◆ Dimensional stability, UV and mildew resistance
- ◆ TOP GUN can be used in marine tops, trailer covers, gazebos, canopies, tarpaulins, playground equipment covers, BBQ grill covers, patio furniture
- ◆ Weight: 373gsm
- ◆ Roll Width: 1570mm
- ◆ Roll Length: 45.7m

## Top Gun 9



Seagull Grey  
**F0550A97Y**

- ◆ TOP GUN 9 formerly known as Mustang is an acrylic coated 100% 450dpi woven polyester fabric with a proprietary coating on both sides, top and bottom, allowing the fabric to be completely reversible
- ◆ It is characterised by excellent strength & durability, tear and abrasion resistance, dimensional stability
- ◆ Top Gun 9 can be used for many outdoor applications such as marine tops, dinghy covers, trailer covers, awnings, gazebos, canopies, tarpaulins & patio furniture covers
- ◆ Weight: 305gsm
- ◆ Roll Width: 1570mm
- ◆ Roll Length: 45.7m



## Top Notch

- ◆ Solution dyed 840dpi polyester - colourfast & UV resistant
- ◆ Dimensionally stable and exceptional tear strength
- ◆ Durable and abrasion resistant finish
- ◆ Fluorocarbon finish for excellent water repellance
- ◆ 5 year limited warranty
- ◆ Excellent dimension stability and UV resistance
- ◆ Ideal for marine tops, dinghy covers, trailer covers, awnings, gazebos, canopies, patio furniture and anywhere that a reversible and breathable fabric is needed
- ◆ Weight: 373gsm
- ◆ Roll Width: 1520mm
- ◆ Roll Length: 45.7m




## Top Notch 9

- ◆ TOP NOTCH 9 formerly known as Top Notch Elite is a 100% solution dyed polyester fabric with Fluorocarbon finish
- ◆ It is more breathable than other solution dyed fabrics while still being more water resistant
- ◆ TOP NOTCH 9 can be used in many applications like marine tops, dinghy covers, trailer covers, awnings, gazebos, canopies
- ◆ Colourfast & UV resistant
- ◆ Excellent tear & tensile strength
- ◆ Breathable & water repellent
- ◆ 5 year limited warranty
- ◆ Weight: 305gsm
- ◆ Roll Width: 1520mm
- ◆ Roll Length: 45.7m



## Top Gun FR

White  
**F0350A00Y**



Ivory  
**F0350A13Y**



Hunter Green  
**F0350A47Y**



Royal Blue  
**F0350A79Y**



Burgundy  
**F0350A75Y**



Black  
**F0350A60Y**



Silver Grey  
**F0350A97Y**



- ◆ TOP GUN FR formerly known as Holiday is an acrylic coated 100% 600dpi woven polyester flame retardant fabric
- ◆ TOP GUN FR can be used for many outdoor applications such as tents, commercial and industrial awnings, canopies and many other useful applications
- ◆ Super high strength with great abrasion resistance
- ◆ UV and Mildew resistant
- ◆ Water repellent, permeable to water vapour but will not trap excess moisture
- ◆ Meets USA CA State Fire Marshall NFPA 701 & CPAI-84
- ◆ Weight: 407gsm
- ◆ Roll Width: 1570mm
- ◆ Roll Length: 45.7m

## Firesist 3 FR

Regatta  
**FS82000**



Forest Green Tweed  
**FS82002**



Forest Green  
**FS82003**



Regatta Tweed  
**FS82005**



Sand  
**FS82006**



Black  
**FS82008**



- ◆ FIRESIST from Glen Raven is a fire retardant awning fabric that replaces Sunbrella Firesist and Firesist HUV line of fabrics
- ◆ Firesist awning fabric combines state of the art fire retardant performance
- ◆ Excellent UV resistance
- ◆ Deep rich colours and robust durability
- ◆ Workability improvements make cutting, sewing and welding easier than ever
- ◆ Weight: 297gsm
- ◆ Roll Width: 1520mm
- ◆ Roll Length 45.7m

Admiral Navy  
**FS82010**



Toasty Beige  
**FS82012**



Sunburst Yellow  
**FS82013**



Ivory  
**FS82015**



Burgundy  
**FS82016**



Crimson Red  
**FS82017**






## Dickson Seaguard Flex

- ◆ Seaguard Flex from Dickson is a high tenacity polyester cover fabric 280 dtex coated on both sides
- ◆ Recommended for winter covers, winch covers and protected fitted covers
- ◆ Composition: High Tenacity Polyester 280 dtex coated on both sides
- ◆ Weight: 300gsm
- ◆ Standard roll: 1500mm x 60m
- ◆ Wide roll: 3000mm x 30m (Suffix 'W')
- ◆ 5 year limited warranty



- ◆ PVC fabric for use in smaller yachts & dinghy covers
- ◆ Produced especially for the marine market
- ◆ Ideal for 100% external waterproof covers

## Sola Vinyl



Colour	Weight (gsm)	Roll Width (mm)	Roll Length (m)	Unit	No
Grey	350	1500	50	METRE	<b>FH350GY</b>
Royal Blue	350	1500	50	METRE	<b>FH350RB</b>
White	350	1500	50	METRE	<b>FH350WT</b>
Navy Blue	550	1500	50	METRE	<b>FH550NV</b>







## Nautimar

Snow White  
**F86500100**



Ivory  
**F86500102**



Navy  
**F86500210**



Black  
**F86500450**

- ◆ NAUTIMAR Fabric is made out of high tenacity polyester, woven, PVC coated and embossed on one side
- ◆ A lightweight product, easy to store & 100% waterproof
- ◆ The ideal solution for cockpit covers, protective covers and biminis
- ◆ 300gsm
- ◆ Standard roll: 2200mm x 60m



## Nautiplus

Snow White  
**F87500100**



Ivory  
**F87500101**



- ◆ NAUTIPLUS Fabric is designed for all marine exterior covers, spray hoods, bimini tops, cockpit covers and winter covers
- ◆ High tenacity polyester fabric
- ◆ Base fabric is **double coated** with high quality PVC to resist fading in all marine conditions
- ◆ Nautiplus is 100% waterproof
- ◆ 300gsm
- ◆ Standard roll: 2200mm x 60m





## PVC Window Material

- ◆ High Grade Clear PVC Window material used in marquees, sprayhoods, biminis and cockpit covers
- ◆ Available only on full rolls
- ◆ UV Stabilised Vinyl
- ◆ E205 & E206 are FR rated to BS5438
- ◆ Super clear PVC



Description	Roll Length (m)	Roll Width (mm)	Unit	No
10 Thou	50	1370	ROLL	<b>E204</b>
20 Thou	40	1370	ROLL	<b>E206</b>
30 Thou	30	1370	ROLL	<b>E205</b>

## 1000 hour UV Roll-A-Glass

- ◆ 1000 hour UV Roll-A-Glass is a high grade FR302 Fire Resistant window material used in marquees sprayhoods, biminis and cockpit covers
- ◆ Available only on full rolls
- ◆ Passes the 1000 hour UV weatherometer test
- ◆ Sparkling Clarity



Description	Roll Length (m)	Roll Width (mm)	Unit	No
20 Thou	27	1370	ROLL	<b>K631</b>

## CLEAR-VU High Optical Window

- ◆ Clear-VU window is a top quality extruded vinyl product that offers optical clarity Close to a polished press sheet vinyl, while still retaining the benefits of rolled glass convenience
- ◆ Available only on full rolls
- ◆ UV Stabilised Vinyl
- ◆ K432 has a soft hand similar to rolled window vinyl
- ◆ K434 has a firm hand similar to a pressed polished sheet



Description	Roll Length (m)	Roll Width (mm)	Unit	No
30 Thou	17.8	1370	ROLL	<b>K432</b>
40 Thou	14	1370	ROLL	<b>K434</b>

## Roll-A-Glass Window

- ◆ High Grade Clear PVC Window material used in marquees sprayhoods, biminis and cockpit covers
- ◆ Available only on full rolls
- ◆ UV Stabilised Vinyl
- ◆ Can use RF to heat seal seams against water penetration
- ◆ K232 - Clear with paper interleaving for protection



Thickness (mm)	Roll Length (m)	Roll Width (mm)	Unit	No
0.50	18	1370	ROLL	<b>K232</b>





## Regalite Polished Sheet Window



- ◆ REGALITE Pressed Polished window sheets from O'Sullivan manufactured from thermoplastic clear vinyl material
- ◆ Highly polished finish that results in a soft, flexible, press polished sheet
- ◆ This clear vinyl material is perfect for marine windows, awnings, cabin enclosures and automotive applications
- ◆ UV Stabilised Vinyl

Thickness (mm)	Sheet Length (mm)	Sheet Width (mm)	Unit	No
0.5	1727	737	SHEET	<b>K221</b>

## Strataglass Vinyl Window

**STRATAGLASS**



- ◆ STRATAGLASS Scratch Resistant glass is the leading brand in quality clear vinyl
- ◆ Excellent UV durability
- ◆ Tested to 12 years accelerated UV
- ◆ Easy roll-up, the same as regular vinyl
- ◆ Available only in full drums
- ◆ Uses: Boat curtains, Automotive Windows, Tents & Awning applications
- ◆ DSM - Dark smoke tint
- ◆ SM - Smoke tint
- ◆ LSM - Light smoke tint

Thickness (mm)	Sheet Length (mm)	Sheet Width (mm)	Unit	No
0.76	2820	1370	SHEET	<b>K305/2</b>
0.76	2820	1370	SHEET	<b>K305/5</b>
1.02	2820	1370	SHEET	<b>K310/2</b>
1.02	2820	1370	SHEET	<b>K310/2SM</b>
1.02	2820	1370	SHEET	<b>K310/5</b>
1.02	2820	1370	SHEET	<b>K310/5DSM</b>
1.02	2820	1370	SHEET	<b>K310/5SM</b>
1.5	2820	1370	SHEET	<b>K315/2</b>
1.5	2820	1370	SHEET	<b>K315/2LSM</b>



## Cordura 1000

- ◆ 1000 Denier super tough woven, high tenacity nylon with a 33gsm urethane coating for durability and water repellency
- ◆ Excellent resistance to abrasion, fading, rot and mildew
- ◆ Uses: Heavy Duty Bags, horse blankets, backpacks
- ◆ Water repellent and quick drying
- ◆ High Tensile Strength and Tear Resistance
- ◆ Weight: 458gsm
- ◆ Roll Length: 46m
- ◆ Roll Width: 1520mm

Silver  
**F5300D08W**



Yellow  
**F5300D35W**



Forest Green  
**F5300D46W**



Black  
**F5300D60W**



Royal Blue  
**F5300D79W**



White  
**F5300D00W**



## Polyester PVC

- ◆ 600 Denier tightly woven polyester with PVC coating on one side
- ◆ Uses: Super yacht deck bags, sport bags, soft-sided luggage, garment bags
- ◆ Super durable with high abrasion resistance
- ◆ Textured yarn for soft hand
- ◆ High Tear and tensile strength
- ◆ Excellent cold crack characteristics
- ◆ Waterproof
- ◆ Weight: 407gsm
- ◆ Roll Length: 46m
- ◆ Roll Width: 1470mm

Burgundy  
**FH600BG**



Charcoal Grey  
**FH600CG**



Green  
**FH600GR**



Teal  
**FH600TL**



Silver  
**FH600SR**



Red  
**FH600RD**



Royal Blue  
**FH600RB**



Navy Blue  
**FH600NV**

## Nylon PVC

- ◆ 70 Denier woven nylon with PVC coating on one side
- ◆ Uses: Banners, Indoor covers, Sport Bags, soft-sided luggage
- ◆ Accepts pressure sensitive graphics
- ◆ Can be silk screen printed
- ◆ Textured yarn for soft hand
- ◆ Fire retardant, meets California fire code 117, section E
- ◆ Weight: 373gsm
- ◆ Roll Length: 101m
- ◆ Roll Width: 1520mm

Black  
**FH070BK**



Green  
**FH070GRN**



Light Grey  
**FH070GY**



Orange  
**FH070OR**



Royal Blue  
**FH070RB**



Red  
**FH070RD**



White  
**FH070WT**



Yellow  
**FH070YE**





## Bainflata 210 Vinyl

Bright Green  
**FH210BGR**



Black  
**FH210BK**



Green  
**FH210GR**



Grey  
**FH210CNW**



Light Blue  
**FH210LBU**



Navy  
**FH210NV**



White  
**FH210WT**



Yellow  
**FH210YE**



Red  
**FH210RD**



Royal Blue  
**FH210RB**



Orange  
**FH210OR**

- ◆ 210 denier plain weave nylon with pigmented PVC coating on both sides
- ◆ Uses: Cold air inflatable advertising structures, ink jet printing, canopies & banners
- ◆ Weight: 255gsm
- ◆ Width: 1530mm
- ◆ Roll Length: 91.4m
- ◆ Tensile Strength: 166 x 117 lbs - 1" strip
- ◆ Tongue Tear: 20 x 20lbs
- ◆ Low Temperature: -40 Degree F
- ◆ UV Fade: 200hrs

## Textilene Vinyl Mesh



Almond  
**FH354AL**



Black  
**FH354BK**



Green  
**FH354GR**



Yellow  
**FH354YE**



White  
**FH354WT**



Red  
**FH354RD**



Royal Blue  
**FH354RB**



Navy Blue  
**FH354NV**



Dove Grey  
**FH354GY**

- ◆ TEXTILENE PVC vinyl encapsulated polyester FR mesh material
- ◆ 45% to 65% shade factor
- ◆ Very strong with excellent tear and abrasion resistance
- ◆ Uses: Screens, Sun Awnings, Cushion bottoms & Banners
- ◆ Fire retardant, meets CA 117, Section E
- ◆ Weight: 350gsm
- ◆ Roll Width: 1370mm

## Sunsure Vinyl Mesh



Black  
**FH359BK**



Forest Green  
**FH359GR**



Dove Grey  
**FH359GY**



Navy Blue  
**FH359NV**



Porcelain  
**FH359PN**



Royal Blue  
**FH359RB**



Sunset  
**FH359SCST**



White  
**FH359WT**



Yellow  
**FH359YE**

- ◆ SUNSURE PVC vinyl encapsulated polyester FR mesh material
- ◆ 95% shade factor
- ◆ Very strong with excellent tear and abrasion resistance
- ◆ Uses: Wind & Sun Screens, Sun Awnings, Banners & Signs
- ◆ Fire retardant
- ◆ Weight: 550gsm
- ◆ Roll Width: 1370mm



## Heavy Duty Trampoline Mesh

- ◆ Diamond mesh made netting
- ◆ Uses include: bridgedeck catamarans
- ◆ Ideal safety equipment with children on board
- ◆ Weight: 848gsm
- ◆ Roll Width: 1800mm

Black



White



Colour	Flame Retardent	Roll Width (mm)	Weight (gsm)	Unit	No
Black	Yes	1800	848	METRE	<b>FH590BK</b>
White	Yes	1800	848	METRE	<b>FH590WT</b>

## Extra Heavy Duty Trampoline Mesh

- ◆ Extremely strong polyester mesh
- ◆ UV and mildew inhibitors
- ◆ Suited to outdoor tensile structures where strength, durability and resistance to the elements are required
- ◆ Designed for industrial applications and as trampolines on bridgedeck catamarans
- ◆ Weight: 1017gsm
- ◆ Roll Width: 1800mm



Colour	Flame Retardent	Roll Width (mm)	Weight (gsm)	Unit	No
White	Yes	1800	1017	METRE	<b>FH592WT</b>

## Trampoline Mesh

- ◆ Diamond mesh made netting
- ◆ Uses include: Beach cats and spinnaker launch tubes
- ◆ Ideal safety equipment with children on board
- ◆ Weight: 271gsm



Colour	Flame Retardent	Roll Width (mm)	Weight (gsm)	Unit	Pack Quantity	No
Black	No	1880	271	METRE	91 44	<b>FH374BK</b>
Black	No	3937	271	METRE	91 44	<b>FH374BK4</b>







## Polyester Screen Mesh

**FH160FO**



**FH160BU**



**FH160BK**



- ◆ Sleeveknit vinyl mesh
- ◆ Uses: Windscreens, banners, outdoor furniture and shades
- ◆ FH162WTFR - Fire retardant, meets CA 117 section E



**FH372CG**



**FH162WTFR**



**FH160WT**



**FH160RD**

Colour	Flame Retardant	Roll Width (mm)	Weight (gsm)	Unit	No
Black	No	1524	220	METRE	<b>FH160BK</b>
Bermuda Blue	No	1524	220	METRE	<b>FH160BU</b>
Flo Orange	No	1524	220	METRE	<b>FH160FO</b>
Red	No	1524	220	METRE	<b>FH160RD</b>
White	No	1524	220	METRE	<b>FH160WT</b>
White	Yes	1575	271	METRE	<b>FH162WTFR</b>

## Mosquito Netting



Colour	Flame Retardant	Roll Width (mm)	Weight (gsm)	Unit	No
Slate Grey	No	1828	31	METRE	<b>FH172GY</b>

## Polyester Knit Mesh

**FH062WT**



**FH160BK**



Colour	Flame Retardant	Roll Width (mm)	Weight (gsm)	Unit	No
Black	No	1575	108	METRE	<b>FH062BK</b>
White	No	1575	108	METRE	<b>FH062WT</b>

## Heavy Polyester Knit Mesh



Colour	Flame Retardant	Roll Width (mm)	Weight (gsm)	Unit	No
White	No	1600	339	METRE	<b>FH063WT</b>



## Dickson Sunworker

- ◆ 100% high tenacity polyester composition
- ◆ Recommended for external windshield and window covers
- ◆ Fire resistance to M1 - NF 92503, B1 - DIN 4102, C1 - UNI 9176, Classe 1 - UNE-EN 13773 : 2003, Bs2d0 - Euroclass EN 13501-1
- ◆ Finish: Solution dyed plastisol coating
- ◆ Weight: 320gsm
- ◆ Standard roll: 1500mm x 60m
- ◆ Wide roll: 3000mm x 30m (Suffix 'W')
- ◆ 5 year limited warranty
- ◆ Available in 10 colours



## Dickson Sunworker Cristal

- ◆ Finish: Solution dyed plastisol coating + translucent PVC coating
- ◆ 100% high tenacity polyester composition
- ◆ Recommended for external windshield and window covers
- ◆ Fire resistance to M1 - NF 92503, B1 - DIN 4102, C1 - UNI 9176, Classe 1 - UNE-EN 13773 : 2003, Bs2d0 - Euroclass EN 13501-1
- ◆ Weight: 440gsm
- ◆ Width: 296cm
- ◆ Roll Length: 25m
- ◆ 5 Year limited warranty
- ◆ Available in 7 colours







## Coloured Polypropylene Webbing




- ◆ Polypropylene Webbing available in various widths & colours
- ◆ Suitable for low load application
- ◆ Sold in full reels only
- ◆ Other colours available on request
- ◆ Uses: Sail ties

Colour	Width (mm)	Reel Length (m)	SWL (kg)	Unit	No
Black	19	50	225	METRE	<b>E225BK</b>
Blue	19	50	225	METRE	<b>E225BU</b>
Grey	19	50	225	METRE	<b>E225GY</b>
Navy	19	50	225	METRE	<b>E225NB</b>
White	19	50	225	METRE	<b>E225WT</b>
Yellow	19	50	225	METRE	<b>E225YE</b>
Black	25	50	275	METRE	<b>E226BK</b>
Blue	25	50	275	METRE	<b>E226BU</b>
Grey	25	50	275	METRE	<b>E226GY</b>
Navy	25	50	275	METRE	<b>E226NB</b>
Red	25	50	275	METRE	<b>E226RD</b>
White	25	50	275	METRE	<b>E226WT</b>
Black	40	50	425	METRE	<b>E227BK</b>
Black	38	50	425	METRE	<b>E227BK38</b>
Blue	40	50	425	METRE	<b>E227BU</b>
Green	40	50	425	METRE	<b>E227GR</b>
Grey	40	50	425	METRE	<b>E227GY</b>
Navy	40	50	425	METRE	<b>E227NB</b>
Red	40	50	425	METRE	<b>E227RD</b>
White	40	50	425	METRE	<b>E227WT</b>
Yellow	40	50	425	METRE	<b>E227YE</b>
Black	50	50	525	METRE	<b>E228BK</b>
Navy	50	50	525	METRE	<b>E228NB</b>
Red	50	50	525	METRE	<b>E228RD</b>
White	50	50	525	METRE	<b>E228WT</b>



## Nylon Webbing


- ◆ Nylon Webbing available in various widths & colours
- ◆ Suitable for medium / high load application
- ◆ Sold in full reels only



Style	Width (mm)	Colour	SWL (kg)	Reel Length (m)	Unit	No
Standard	12	White	317	46	METRE	<b>E110N</b>
Standard	12	Black	317	46	METRE	<b>E110NBK</b>
Standard	25	Black	700	91	METRE	<b>E125</b>
Super Heavy	12	White	700	183	METRE	<b>E122</b>
Super Heavy	19	White	1450	183	METRE	<b>E123</b>
Super Heavy	25	Black	680	91	METRE	<b>E112NBK</b>

## Jackstay & Seatbelt Webbing


- ◆ Rugged polyester webbing, five panel construction, recommended for hiking straps, bag handles, nose piece for kites, reinforcement, tie down, trampolines, etc
- ◆ Excellent UV resistance



Style	Width (mm)	Colour	SWL (kg)	Reel Length (m)	Unit	No
Seatbelt	38	Black	1135	137	METRE	<b>E115BK</b>
Seatbelt	50	Black	1135	91	METRE	<b>E121BK</b>
Jackstay	25	White	3000	50	METRE	<b>E150</b>

## Herringbone Webbing

- ◆ 50mm polypropylene herringbone webbing



Style	Width (mm)	Colour	SWL (kg)	Reel Length (m)	Unit	No
Herringbone	50	White	453	91.4	METRE	<b>E130</b>




## Sunbrella Double Fold Bias Acrylic Binding



- ◆ Sunbrella double fold BIAS acrylic binding, double edge is turned and glued Binding for sail covers, tents, canopies, sprayhoods, dodgers and biminis
- ◆ Available only on full rolls of 91 4m
- ◆ Finish width of E098 is 20mm
- ◆ Finish width of E097 is 25mm

## Sunbrella Centre Fold Acrylic Binding



- ◆ Woven with Sunbrella acrylic yarns
- ◆ Matching or contrasting binding can be used to trim boat covers, cushions, canopies, sprayhoods, dodgers and biminis etc
- ◆ Sold in full reels only

Colour	Width (mm)	Roll Length (m)	Unit	No
Black	19	91	REEL	<b>E090BK</b>
Pacific Blue	19	91	REEL	<b>E090BU</b>
White	19	91	REEL	<b>E090WT</b>
Burgundy	22	183	REEL	<b>E095BG</b>
Beige	22	183	REEL	<b>E095BI</b>
Black	22	183	REEL	<b>E095BK</b>
Pacific Blue	22	183	REEL	<b>E095BU</b>
Forest Green	22	183	REEL	<b>E095FGR</b>
Grey	22	183	REEL	<b>E095GY</b>
Navy	22	183	REEL	<b>E095NV</b>
Persian Green	22	183	REEL	<b>E095PG</b>
Jockey Red	22	183	REEL	<b>E095RD</b>
White	22	183	REEL	<b>E095WT</b>




## Vinyl Bias Binding

- ◆ Stamoid vinyl has outstanding UV resistance
- ◆ Dirt repellent & washable
- ◆ Waterproof & treated against mildew
- ◆ Matching binding is used with Stamoid to trim or bind cushions, canopies, dodgers and biminis etc
- ◆ Sold in full reels only

White - **E075WT**  
**E085WT**  
**E086WT**

Black - **E085BK**  
**E086BK**



White - **E085WT**

Cream - **E085CR**

Navy - **E085NV**

Sand - **E085SD**

Snow White - **E085SW**

Style	Colour	Width (mm)	Roll Length (m)	Unit	No
Standard	White	19	91.4	REEL	<b>E075WT</b>
Double	Black	19	91.4	REEL	<b>E085BK</b>
Double	Cream	19	91.4	REEL	<b>E085CR</b>
Double	Ivory	19	91.4	REEL	<b>E085II</b>
Double	Navy	19	91.4	REEL	<b>E085NV</b>
Double	Royal Blue	19	91.4	REEL	<b>E085RB</b>
Double	Sand	19	91.4	REEL	<b>E085SD</b>
Double	Snow White	19	91.4	REEL	<b>E085SW</b>
Double	White	19	91.4	REEL	<b>E085WT</b>
Double	Black	25	91.4	REEL	<b>E086BK</b>
Double	White	25	91.4	REEL	<b>E086WT</b>



## Heminway & Bartlett Dabond NANO Anti-Wick Thread



- ◆ Dabond 2000 thread is available in other colours against special order.
- ◆ Nominal 450g (1lb) spools.
- ◆ Anti-Wick combines superior sewability with a permanent additive that blocks water migration through seams and meets MIL SPEC V-T- 285 Type II

Dabond Size	Colour	Nearest Metric Size	Unit	No
V69	Black	NM36	LB	<b>EA069BK</b>
V69	Pacific Blue	NM36	LB	<b>EA069PB</b>
V69	White	NM36	LB	<b>EA069WT</b>
V92	Black	NM25	LB	<b>EA092BK</b>
V92	Blue	NM25	LB	<b>EA092BU</b>
V92	Silver Grey	NM25	LB	<b>EA092GY</b>
V92	Pacific Blue	NM25	LB	<b>EA092PB</b>
V92	White	NM25	LB	<b>EA092WT</b>
V138	Black	NM20	LB	<b>EA138BK</b>
V138	White	NM20	LB	<b>EA138WT</b>

## SolarFix Thread



- ◆ SolarFix® Made of 100% PTFE( Poly Tetra Flouro Ethylene) fibre.
- ◆ SolarFix® is an excellent thread choice for all marine and outdoor applications
- ◆ Extremely resistant to harmful UV rays and atmospheric degradation
- ◆ SolarFix thread will not lose any significant strength due to UV
- ◆ Limited lifetime warranty

Colour	Equivalent dtex	Equivalent Tex	Unit	Spool Length (m)	No
Clear	1500	92	SP00L	3400	<b>EF1500CH1T</b>
Black	1500	92	SP00L	3400	<b>EF1500DH1T</b>
White	1500	92	SP00L	3400	<b>EF1500WH1T</b>
Clear	2640	138	SP00L	1920	<b>EF2640CH1T</b>
Black	2640	138	SP00L	1920	<b>EF2640DH1T</b>
White	2640	138	SP00L	1920	<b>EF2640WH1T</b>

## SunStop Anti-Wick Polyester Thread

- ◆ SunStop Thread, A high performance twisted multifilament polyester sewing thread with advanced UV protection and anti-wick finish. Specially designed for outdoor applications where seam strength retention and fade prevention during UV exposure are required.
- ◆ Anti-Wicking
- ◆ 225g (8oz) spools
- ◆ Excellent UV resistance
- ◆ Fade resistant
- ◆ Top 16 Sunbrella Colours.

Type	Thread Size	
	92 - NM25	138 - NM20
Polyester Thread	EY092xxx8	EY138xxx8



Available Colour - xxx	Colour
BEG	Beige
BK	Black
BRN	Brown
BG	Burgundy
GY	Cadet Grey
CNV	Captain Navy
FGR	Forest Green
JRD	Jockey Red
LN	Linen
LRD	Logo Red
NV	Navy
PB	Pacific Blue
SR	Silver
TS	Toast
BR	True Brown
WT	White

## Thread Data Chart

Dabond Part No.	Needle Size Imperial/Metric		Average Yield m/yd per lb		Average Tensile kg lb	
V30	11-14	75-90	12,951	14,170	2.13	4.7
V46	12-15	80-95	7,467	8,170	3.36	7.4
V69	15-18	95-110	5,110	5,590	4.95	10.9
V92	17-20	105-125	3,866	4,230	6.58	14.5
V138	19-21	120-130	2,523	2,760	10.26	22.6
V207	21-23	130-160	1,682	1,840	14.71	32.4
V346	-	23-26	1,005	1,100	26.38	58.1



## Velcro - Sew On - 20mm



- ◆ VELCRO original sew on fastening available in sets, and separate Hook & Loop
- ◆ Available in Navy Blue, White, Black & Royal Blue
- ◆ Durable hook fastening gives maximum life cycle
- ◆ Available only on 25mtr reels
- ◆ Various widths in 20mm, 25mm, 30mm & 50mm

Colour	Size (mm)	Reel Length (m)	Type	Unit	No
White	20	25	Hook & Loop	METRE	<b>E510</b>
White	20	25	Hook Only	METRE	<b>E510H</b>
White	20	25	Loop Only	METRE	<b>E510L</b>
Black	20	25	Hook & Loop	METRE	<b>E511</b>
Black	20	25	Hook Only	METRE	<b>E511H</b>
Black	20	25	Loop Only	METRE	<b>E511L</b>
Navy Blue	20	25	Hook & Loop	METRE	<b>E513</b>
Navy Blue	20	25	Hook Only	METRE	<b>E513H</b>
Navy Blue	20	25	Loop Only	METRE	<b>E513L</b>



## Velcro - Sew On - 25mm



Colour	Size (mm)	Reel Length (m)	Type	Unit	No
White	25	25	Hook & Loop	METRE	<b>E515</b>
White	25	25	Hook Only	METRE	<b>E515H</b>
White	25	25	Loop Only	METRE	<b>E515L</b>
Black	25	25	Hook & Loop	METRE	<b>E517</b>
Black	25	25	Hook Only	METRE	<b>E517H</b>
Black	25	25	Loop Only	METRE	<b>E517L</b>
Navy Blue	25	25	Hook & Loop	METRE	<b>E518</b>
Navy Blue	25	25	Hook Only	METRE	<b>E518H</b>
Navy Blue	25	25	Loop Only	METRE	<b>E518L</b>





## Velcro - Sew On - 30mm

- ◆ VELCRO original sew on fastening available in sets, and separate Hook & Loop
- ◆ Available in Navy Blue, White, Black & Royal Blue
- ◆ Durable hook fastening gives maximum life cycle
- ◆ Available only on 25mtr reels
- ◆ Various widths in 20mm, 25mm, 30mm & 50mm



Colour	Size (mm)	Reel Length (m)	Type	Unit	No
White	30	25	Hook & Loop	METRE	<b>E520</b>
White	30	25	Hook Only	METRE	<b>E520H</b>
White	30	25	Loop Only	METRE	<b>E520L</b>
Black	30	25	Hook & Loop	METRE	<b>E521</b>
Black	30	25	Hook Only	METRE	<b>E521H</b>
Black	30	25	Loop Only	METRE	<b>E521L</b>
Navy Blue	30	25	Hook & Loop	METRE	<b>E523</b>
Navy Blue	30	25	Hook Only	METRE	<b>E523H</b>
Navy Blue	30	25	Loop Only	METRE	<b>E523L</b>



## Velcro - Sew On - 50mm



Colour	Size (mm)	Reel Length (m)	Type	Unit	No
White	50	25	Hook & Loop	METRE	<b>E530</b>
White	50	25	Hook Only	METRE	<b>E530H</b>
White	50	25	Loop Only	METRE	<b>E530L</b>
Black	50	25	Hook & Loop	METRE	<b>E531</b>
Black	50	25	Hook Only	METRE	<b>E531H</b>
Black	50	25	Loop Only	METRE	<b>E531L</b>
Navy Blue	50	25	Hook & Loop	METRE	<b>E533</b>
Navy Blue	50	25	Hook Only	METRE	<b>E533H</b>
Navy Blue	50	25	Loop Only	METRE	<b>E533L</b>

## Velcro - Sew On - 100mm

Colour	Size (mm)	Reel Length (m)	Type	Unit	No
White	100	25	Hook & Loop	METRE	<b>E534</b>
White	100	25	Hook Only	METRE	<b>E534H</b>
White	100	25	Loop Only	METRE	<b>E534L</b>





## Velcro - Adhesive Backed - 25mm



- ◆ Width 25mm
- ◆ Supplied in full rolls only
- ◆ Easily stored & give you the flexibility to cut the length you need
- ◆ Velcro PS-14 - General Adhesive
- ◆ Rubber based adhesive, offering great tack
- ◆ Can be used in temperature ranges from -15C to 60C
- ◆ Available in Navy Blue, Black & White

Colour	Size (mm)	Reel Length (m)	Type	Unit	No
White	25	25	Hook & Loop	METRE	<b>E540</b>
White	25	25	Hook Only	METRE	<b>E540H</b>
White	25	25	Loop Only	METRE	<b>E540L</b>
Black	25	25	Hook & Loop	METRE	<b>E541</b>
Black	25	25	Hook Only	METRE	<b>E541H</b>
Black	25	25	Loop Only	METRE	<b>E541L</b>
Navy Blue	25	25	Hook & Loop	METRE	<b>E542</b>
Navy Blue	25	25	Hook Only	METRE	<b>E542H</b>
Navy Blue	25	25	Loop Only	METRE	<b>E542L</b>

## Velcro - Adhesive Backed - 30mm

Colour	Size (mm)	Reel Length (m)	Type	Unit	No
White	30	25	Hook & Loop	METRE	<b>E543</b>
White	30	25	Hook Only	METRE	<b>E543H</b>
White	30	25	Loop Only	METRE	<b>E543L</b>
Black	30	25	Hook & Loop	METRE	<b>E544</b>
Black	30	25	Hook Only	METRE	<b>E544H</b>
Black	30	25	Loop Only	METRE	<b>E544L</b>

## Velcro - Adhesive Backed - 50mm

Colour	Size (mm)	Reel Length (m)	Type	Unit	No
White	50	25	Hook & Loop	METRE	<b>E545</b>
White	50	25	Hook Only	METRE	<b>E545H</b>
White	50	25	Loop Only	METRE	<b>E545L</b>
Black	50	25	Hook & Loop	METRE	<b>E546</b>
Black	50	25	Hook Only	METRE	<b>E546H</b>
Black	50	25	Loop Only	METRE	<b>E546L</b>
Navy Blue	50	25	Hook & Loop	METRE	<b>E547</b>
Navy Blue	50	25	Hook Only	METRE	<b>E547H</b>
Navy Blue	50	25	Loop Only	METRE	<b>E547L</b>

## YKK Zipper & Sliders - Coil Reel

- ◆ No 5 coil only available in white
- ◆ No 10 coil Zips stocked in white & black

Size	Colour	Length (m)	Unit	No
#5C	White	200	METRE	<b>E588</b>
#10C	White	100	METRE	<b>E591</b>
#10C	Black	100	METRE	<b>E591BK</b>

## YKK Zipper & Sliders - Vislon Reel

- ◆ No 5 vislon only available in white
- ◆ No 10 Vislon Zips stocked in white, navy blue, black & beige unless stated otherwise

Size	Colour	Length (m)	Unit	No
#5	White	200	EACH	<b>E580</b>
#10	White	100	EACH	<b>E584</b>
#10	Beige	100	EACH	<b>E584BE</b>
#10	Black	100	EACH	<b>E584BK</b>
#10	Navy	100	EACH	<b>E584NB</b>

## #10 YKK Open Ended Vislon Zips

- ◆ YKK Zippers & Sliders offered by Bainbridge International have been engineered especially for the marine industry and other outdoor applications
- ◆ All materials used have been selected to resist damage from UV & Corrosion
- ◆ Various sizes available in Vislon & Coil Style
- ◆ No 10 Vislon Zips stocked in White, Navy Blue, Black & Beige unless stated otherwise

Available Colour - xx	Colour
<b>BK</b>	Black
<b>NV</b>	Navy
<b>WT</b>	White
<b>BE</b>	Beige



Length (mm / ft)	Unit	No
610	EACH	<b>E560xx</b>
762	EACH	<b>E571xx</b>
910	EACH	<b>E561xx</b>
1060	EACH	<b>E562xx</b>
1070	EACH	<b>E562xx</b>
1220	EACH	<b>E605xx</b>
1370	EACH	<b>E564xx</b>
1520	EACH	<b>E565xx</b>
1680	EACH	<b>E566xx</b>
1830	EACH	<b>E608xx</b>
1980	EACH	<b>E568xx</b>
2130	EACH	<b>E570xx</b>
2440	EACH	<b>E572xx</b>
2740	EACH	<b>E574xx</b>
3050	EACH	<b>E576xx</b>
3660	EACH	<b>E577xx</b>
4570	EACH	<b>E578WT</b>
5950	EACH	<b>E579WT</b>
6710	EACH	<b>E600WT</b>
8250	EACH	<b>E609WT</b>
10000	EACH	<b>E569WT</b>



## YKK Zipper & Sliders - Vislon Sliders



- ◆ YKK Zippers & Sliders offered by Bainbridge International have been engineered especially for the marine industry and other outdoor applications
- ◆ All materials used have been selected to resist damage from UV & Corrosion
- ◆ Various sizes available in Vislon & Coil Style
- ◆ No 10 vislon zip sliders stocked in white, navy blue, black & beige

Style	Colour	Sliders	Unit	Pack Quantity	No
#10C	Beige	Single Metal	EACH	10	<b>E585BE</b>
#10C	White	Single Metal	EACH	10	<b>E592</b>
#10C	White	Double Metal	EACH	10	<b>E593</b>
#10C	Nickel	Double Metal	EACH	10	<b>E594</b>
#10V	White	Single Metal	EACH	10	<b>E585</b>
#10V	Black	Single Metal	EACH	10	<b>E585BK</b>
#10V	Navy	Single Metal	EACH	10	<b>E585NB</b>
#10V	White	Single Plastic	EACH	10	<b>E587</b>
#10V	White	Double Metal	EACH	10	<b>E586</b>
#10V	Beige	Double Metal	EACH	10	<b>E586BE</b>
#10V	Black	Double Metal	EACH	10	<b>E586BK</b>
#10V	Navy	Double Metal	EACH	10	<b>E586NB</b>
#5C	White	Single Metal	EACH	10	<b>E589</b>
#5V	White	Single Metal	EACH	10	<b>E581</b>
#5V	White	Single Plastic	EACH	10	<b>E583</b>

## YKK Zipper & Sliders - Zip Stops

Colour	Unit	Pack Quantity	No
White	PACK 100	1	<b>E584BS</b>
Silver	PACK 200	1	<b>E584SSTS</b>
White	PACK 200	1	<b>E584TS</b>
Black	PACK 100	1	<b>E585TSBK</b>
White	PACK 100	1	<b>E585TSWT</b>

## YKK - Zippy Cool



- ◆ Remove harmful dirt, sand, and salt deposits Great for marine zippers!
- ◆ Zippy Cool will effectively clean and lubricate all types of metal, coil, and plastic zippers
- ◆ **Kit Contains:**
- ◆ 2oz Zippy Cool fluid
- ◆ 0.5oz Zippy Cool Stick

Unit	Pack Quantity	No
KIT	1	<b>M030</b>
EACH	1	<b>M031</b>
EACH	1	<b>M032</b>





## Plain Rim Grommets - Nickel

◆ Available only in full packs of 144



Size	Inside Diameter (mm)	Unit	No
1	8	PACK 144	<b>D604N</b>
3	10	PACK 144	<b>D605N</b>
3	11	PACK 144	<b>D606N</b>

## Plain Rim Grommets - Brass

◆ Available only in full packs of 144



Size	Inside Diameter (mm)	Unit	No
00	4	PACK 144	<b>D602B</b>
0	6	PACK 144	<b>D603B</b>
2	10	PACK 100	<b>D605B</b>

## Hipkiss Self Piercing Grommets - Nickel

◆ Hipkiss self-piercing grommets eliminate the need for hole punches, since the grommet cuts its own hole when being set



Size	Set Hole Diameter (mm)	Unit	No
000	5.1	PACK 1000	<b>D001NH</b>
00	6.4	PACK 1000	<b>D002NH</b>
0	8.4	PACK 1000	<b>D003NH</b>
1	9.5	PACK 1000	<b>D004NH</b>

## Hipkiss Self Piercing Brass Grommets

◆ Hipkiss self-piercing grommets eliminate the need for hole punches, since the grommet cuts its own hole when being set



Size	Set Hole Diameter (mm)	Unit	No
000	5.1	PACK 1000	<b>D001BH</b>





## Self Piercing Grommets - Brass



- ◆ Bainbridge self-piercing grommets eliminates the need for hole punches, since the grommet cuts its own hole when being set

Size	Inside Diameter (mm)	Unit	No
1	8	PACK 100	<b>D101B</b>
2	10	PACK 100	<b>D102B</b>

## Self Piercing Grommets - Stainless Steel



- ◆ Bainbridge Manufactured stainless steel grommets are sharper and stronger than nickel or brass grommet
- ◆ Self-piercing grommets and washers are sold in full boxes only

Size	Inside Diameter (mm)	Unit	No
2	10	PACK 100	<b>D112SS</b>

## Brass Rings

- ◆ Manufactured from solid brass



Thickness (mm)	Inside Width (mm)	Unit	Pack Quantity	No
3	12	EACH	10	<b>Q143</b>
4	15	EACH	10	<b>Q144</b>
5	19	EACH	10	<b>Q145</b>
5	22	EACH	10	<b>Q146</b>
5	25	EACH	10	<b>Q147</b>
5	28	EACH	10	<b>Q148</b>
6	31	EACH	10	<b>Q149</b>





## Brass Snap Hooks

- ◆ Brass snap hooks are all purpose hooks,
- ◆ Used in many applications where loads are relatively low
- ◆ B611N - Made from brass nickel



Inside Eye Diameter (mm)	Length (mm)	Unit	Pack Quantity	No
10	53	EACH	10	<b>B610</b>
15	72	EACH	10	<b>B611</b>
15	72	EACH	10	<b>B611N</b>

## Stainless Steel Snap Hooks

- ◆ Stainless steel offers the same efficient and easy to use shape, but has much greater safe working loads



Inside Eye Diameter (mm)	Length (mm)	Unit	Pack Quantity	No
10	53	EACH	10	<b>B610S</b>
20	81	EACH	10	<b>B612S</b>
25	50	EACH	10	<b>B617S</b>

## Bronze Snap Hooks

- ◆ Bronze snap hooks are an all purpose hook used in many applications where loads are relatively low
- ◆ Swivel prevents halyard from twisting

B611SW


B612



B615

B632

B637



Inside Eye Diameter (mm)	Length (mm)	Unit	Pack Quantity	No
10	64	EACH	10	<b>B632</b>
10	75	EACH	10	<b>B615</b>
15	81	EACH	10	<b>B611SW</b>
20	81	EACH	10	<b>B612</b>
25	75	EACH	10	<b>B637</b>





## Button Snap Fasteners



G140



G154



G149SS

- ◆ When superior snap action and holding strength is needed, DOT button snaps are the fastener to use
- ◆ Self-piercing so no pre-punching is required,
- ◆ Snap fastener's heavy duty construction assures a firm grip that will remain secure through years of use



G140BK



G140BKM



G140BU



G140NV



G140SS



G140WT



G141



G141SS



G142



G143



G145



G145SS



G146



G147

Description	Finish	Unit	No
5mm Barrel	Nickel Plated Brass	PACK 100	<b>G140</b>
Military Black Cap 5mm	Nickel Plated Brass	PACK 100	<b>G140BK</b>
Military Cap Black	Nickel Plated Brass	PACK 100	<b>G140BKM</b>
Pacific Blue 5mm	Nickel Plated Brass	PACK 100	<b>G140BU</b>
Navy Blue 5mm	Nickel Plated Brass	PACK 100	<b>G140NV</b>
4.8mm Barrel	Stainless Steel	PACK 100	<b>G140SS</b>
Beige 5mm	Nickel Plated Brass	PACK 100	<b>G140TST</b>
White 5mm	Nickel Plated Brass	PACK 100	<b>G140WT</b>
6.5mm Barrel	Nickel Plated Brass	PACK 100	<b>G141</b>
6.5mm Barrel	Stainless Steel	PACK 100	<b>G141SS</b>
Regular Action Sockets	Nickel Plated Brass	PACK 100	<b>G142</b>
Regular Action Sockets Military Black	Nickel Plated Brass	PACK 100	<b>G142BKM</b>
Regular Action Sockets	Stainless Steel	PACK 100	<b>G142SS</b>
Stud for Eyelet	Nickel Plated Brass	PACK 100	<b>G143</b>
Stud for Eyelet Military Black	Nickel Plated Brass	PACK 100	<b>G143BKM</b>
Stud for Eyelet	Stainless Steel	PACK 100	<b>G143SS</b>
Deep Stud	Nickel Plated Brass	PACK 100	<b>G144</b>
6.5mm Barrel	Nickel Plated Brass	PACK 100	<b>G145</b>
6.5mm Barrel Military Black	Nickel Plated Brass	PACK 100	<b>G145BKM</b>
6.5mm Barrel	Stainless Steel	PACK 100	<b>G145SS</b>
8mm Barrel	Nickel Plated Brass	PACK 100	<b>G146</b>
10mm Barrel	Nickel Plated Brass	PACK 100	<b>G147</b>
Stud Reversible	Nickel Plated Brass	PACK 100	<b>G148</b>







## Button Snap Fasteners

- ◆ Bainbridge's DOT fasteners low profile secure fittings for numerous applications
- ◆ As used by professional cover and sailmakers



G153



G182



G155



G156



G157



G158



G171FW



G151



G171



G152



G175

Description	Finish	Unit	No
Easy Action Sockets	Stainless Steel	PACK 100	<b>G149SS</b>
10mm Self Tapping Screw	Nickel Plated Brass	PACK 100	<b>G151</b>
10mm Self Tapping Screw	Stainless Steel	PACK 100	<b>G151SS</b>
8mm Self Tapping Screw	Nickel Plated Brass	PACK 100	<b>G152</b>
Over Size Stud	Stainless Steel	PACK 100	<b>G1520S</b>
9.5mm Snap Studs	Stainless Steel	PACK 100	<b>G153</b>
15.9mm Machine Screw	Stainless Steel	PACK 100	<b>G154</b>
Stiff Action Sockets	Nickel Plated Brass	PACK 100	<b>G155</b>
3/4 Windshield Clip	Nickel Plated Brass	PACK 100	<b>G156</b>
7/8 Windshield Clip	Nickel Plated Brass	PACK 100	<b>G157</b>
Windshield Stud Clip	Nickel Plated Brass	PACK 100	<b>G158</b>
Button Cap	Nickel Plated Brass	PACK 100	<b>G170</b>
12mm Self Tapping Screw	Nickel / SS 316	PACK 100	<b>G171</b>
Washer for Eyelet Button or Studs	Nickel Plated Brass	PACK 100	<b>G171FW</b>
Rivet Stud 3.2mm	Nickel Plated Brass	PACK 100	<b>G174</b>
20mm Self Tapping Screw	Nickel / SS 316	PACK 100	<b>G175</b>
Screw Stud	Nickel Plated Brass	PACK 100	<b>G176</b>
Flangless Stud	Nickel Plated Brass	PACK 100	<b>G182</b>



## LOXX Fasteners

- ◆ Simple one-handed operation
- ◆ 3-year limited warranty
- ◆ High strength resists tensile forces over 1000N
- ◆ Rounded surfaces, helps to reduce chafe and tearing



Smooth Head



Small Head



Big Head



XL



Smooth Head with Ring



Big Head Hybrid



Stainless Steel



Brass



Gold



Copper



Nickel



Black



Style	Finish	Unit	Pack Quantity	No
Smooth Head	Brass/Antique Copper	EACH	1	<b>L00511569000</b>
Smooth Head	Brass/Antique	EACH	1	<b>L00511525000</b>
Smooth Head	Brass/Black Chrome Plated	EACH	1	<b>L00511579098</b>
Smooth Head	Brass/Chrome Plated	EACH	1	<b>L00511511000</b>
Smooth Head	Brass/Nickel Plated	EACH	1	<b>L00511505000</b>
Small Head	Black Chrome Plated	EACH	1	<b>L00513479098</b>
Small Head	Brass/Antique Brass Plated	EACH	1	<b>L00513425000</b>
Small Head	Brass/Chrome Plated	EACH	1	<b>L00513411000</b>
Small Head	Brass/Chrome Plated	EACH	1	<b>L00513469000</b>
Small Head	Brass/Nickel Plated	EACH	1	<b>L00513405000</b>
Small Head	Chrome Plated	EACH	1	<b>L00518011000</b>
Big Head	Stainless Steel	EACH	1	<b>L00886502098</b>
Big Head	Antique Brass	EACH	1	<b>L00514025000</b>
Big Head	Antique Brass	EACH	1	<b>L00514125000</b>
Big Head	Antique Copper	EACH	1	<b>L00514069000</b>
Big Head	Antique Copper	EACH	1	<b>L00514169000</b>
Big Head	Brass/Black Chrome Plated	EACH	1	<b>L00514079098</b>
Big Head	Chrome Plated	EACH	1	<b>L00514011000</b>
Big Head	Chrome Plated	EACH	1	<b>L00514111000</b>
Big Head	Chrome Plated	EACH	1	<b>L00514179098</b>
Big Head	Nickel Plated	EACH	1	<b>L00514005000</b>
Big Head	Nickel Plated	EACH	1	<b>L00514105000</b>
Big Head Hybrid	Nickel Plated	EACH	1	<b>L00889102098</b>
XL	Black Chrome Plated	EACH	1	<b>L00514279098</b>
XL	Chrome Plated	EACH	1	<b>L00514211000</b>
XL	Nickel Plated	EACH	1	<b>L00514205000</b>
Smooth Head and Ring	Black Chrome Plated	EACH	1	<b>L00565879098</b>
Smooth Head and Ring	Nickel Plated	EACH	1	<b>L00565805000</b>

## LOXX Fasteners

- ◆ Easy to use, especially tear-proof, leak-proof and rust-proof
- ◆ resists tensile forces over 1000 N, rounded surfaces
- ◆ Wide range of designs and finishes, including individual laser engraving, painting or printing
- ◆ Made in Germany



Self Tapping Metal Screw - Gold



Machine Screw



Self Tapping Metal Screw - Black



Fabric Base



Windshield Clip - 21mm



Windshield Clip - 24mm

Style	Size (mm)	Finish	Unit	Pack Quantity	No
Self Tapping Metal Screw	10	Stainless Steel	EACH	1	<b>L00593105098</b>
Self Tapping Metal Screw	12	Brass/Nickel Plated	EACH	1	<b>L00438605098</b>
Self Tapping Metal Screw	12	Brass/Chrome Plated	EACH	1	<b>L00438611000</b>
Self Tapping Metal Screw	12	Brass/Black Chrome Plated	EACH	1	<b>L00438679098</b>
Self Tapping Metal Screw	12	Stainless Steel	EACH	1	<b>L00885900000</b>
Self Tapping Metal Screw	16	Brass/Steel	EACH	1	<b>L00159005098</b>
Self Tapping Metal Screw	16	Brass/Steel	EACH	1	<b>L00159011000</b>
Self Tapping Metal Screw	16	Nickel Plated	EACH	1	<b>L00719005098</b>
Self Tapping Metal Screw	16	Chrome Plated	EACH	1	<b>L00719011000</b>
Self Tapping Metal Screw	16	Chrome Plated	EACH	1	<b>L00719079098</b>
Self Tapping Metal Screw	22	Nickel Plated	EACH	1	<b>L00800305098</b>
Self Tapping Metal Screw	22	Chrome Plated	EACH	1	<b>L00800311000</b>
Self Tapping Metal Screw	22	Black Chrome Plated	EACH	1	<b>L00800379098</b>
Machine Screw	6	Brass/Nickel Plated	EACH	1	<b>L00220405098</b>
Machine Screw	6	Brass/Chrome Plated	EACH	1	<b>L00220411000</b>
Machine Screw	8	Brass/Nickel Plated	EACH	1	<b>L00223405098</b>
Machine Screw	10	Brass/Nickel	EACH	1	<b>L00220205098</b>
Machine Screw	10	Brass/Chrome Plated	EACH	1	<b>L00220211000</b>
Machine Screw	10	Brass/Black Chrome Plated	EACH	1	<b>L00220279098</b>
Machine Screw	10	Brass/Nickel Plated	EACH	1	<b>L00220305098</b>
Machine Screw	10	Brass/Chrome Plated	EACH	1	<b>L00220311000</b>
Machine Screw	10	Stainless Steel	EACH	1	<b>L00220802098</b>
Machine Screw	12	Stainless Steel	EACH	1	<b>L00222802098</b>
Machine Screw	14	Brass/Nickel Plated	EACH	1	<b>L00222205098</b>
Machine Screw	16	Brass/Nickel Plated	EACH	1	<b>L00222005098</b>
Machine Screw	16	Stainless Steel	EACH	1	<b>L00222402098</b>
Machine Screw	20	Stainless Steel	EACH	1	<b>L00222502098</b>
Machine Screw	25	Stainless Steel	EACH	1	<b>L00222602098</b>
Windshield Clip	21	Stainless Steel	EACH	1	<b>L00223000000</b>
Windshield Clip	24	Stainless Steel	EACH	1	<b>L00223100000</b>
Piping Dowel	-	Plastic Black	EACH	1	<b>L00223300000</b>
Fabric Base	-	Nickel	EACH	1	<b>L09512105000</b>



## Lift The Dot Fasteners



G115S



G116S



G113



G110



G116S



G119



G120



G130



G119FW

- ◆ Traditional fastenings for boat, marine covers and canvas work
- ◆ Wide range of fixings to suit virtually any application a cover maker requires
- ◆ Combines secure fastening with ease of use

Finish	Unit	No
Nickel Plated Brass	PACK 100	<b>G110</b>
Nickel Plated Brass	PACK 100	<b>G113</b>
Nickel Plated Brass	PACK 100	<b>G118</b>
Nickel Plated Brass	PACK 100	<b>G119</b>
Nickel Plated Brass	PACK 100	<b>G119FW</b>
Nickel Plated Brass	PACK 100	<b>G120</b>
Nickel Plated Brass	PACK 100	<b>G130</b>
Stainless Screw	PACK 100	<b>G115S</b>
Stainless Screw	PACK 100	<b>G116S</b>

## Fasteners SNAD



- ◆ Unlike traditional metal trims, SNAD® is a plastic adhesive snap component
- ◆ This product will not snag clothing or deteriorate from exposure to sunlight, sand, or dirt
- ◆ Plus, walking on SNAD® is pain free due to its unique dome shape
- ◆ Installation is simple, clean the surface where the snap is to be applied, peel off the protective paper backing, position and firmly hold the snap in place and release
- ◆ No tools, no waiting, no splits, no holes!

Colour	Size (mm)	Type	Unit	No
Clear	25	Stud - Flexible	EACH	<b>G196CL</b>
White	25	Stud - Dome	EACH	<b>G194WT</b>
White	25	Stud - Flexible	EACH	<b>G192WT</b>
Black	25	Stud - Dome	EACH	<b>G194BK</b>
Black	25	Stud - Flexible	EACH	<b>G192BK</b>
Clear	40	Stud - Flexible	EACH	<b>G195CL</b>
White	40	Stud - Dome	EACH	<b>G190WT</b>
White	40	Socket - Dome	EACH	<b>G191WT</b>
Black	40	Stud - Dome	EACH	<b>G190BK</b>
Black	40	Socket - Dome	EACH	<b>G191BK</b>



## Permalock Fasteners

- ◆ All manufactured from Dupont non-corrosive, UV stabilised "Zytel"
- ◆ Can be sewn or attached in place with flathead screws or rivets
- ◆ Recommend 2 x G145 / G147 eyelets as alternative to use standard rivets



G161BK



G160BK



G160ABK



G161WT



G160WT



G160AWT

Colour	Unit	No
Black	EACH	<b>G161BK</b>
Black	EACH	<b>G160BK</b>
Black	EACH	<b>G160BK</b>
White	EACH	<b>G161WT</b>
White	EACH	<b>G160WT</b>
White	EACH	<b>G160AWT</b>



- ◆ Snapfast directional locking fasteners are non corrosive and ideal for outdoor applications, marine or domestic
- ◆ Nylon stud is mounted with a screw or attach to fabric with a standard eyelet/rivet
- ◆ Stainless Steel pronged cap self-pierces most fabrics



G061



G062BK



G062WT



G063WT



G063BK

Unit	No
PACK 10	<b>G061</b>
PACK 10	<b>G061LP</b>
PACK 10	<b>G062BK</b>
PACK 10	<b>G062WT</b>
PACK 10	<b>G063BK</b>
PACK 10	<b>G063WT</b>





## Common Sense Turnbutton Fasteners



G100



G106



G105

- ◆ Traditional fastenings for boat and marine covers and canvas work,
- ◆ Combines secure fastening with ease of use
- ◆ Common Sense fasteners are positive locking fasteners that will not open accidentally
- ◆ Each fastener is assembled with a spring mechanism that holds the fastener under tension in the desired position until turned and released by hand



G104



G103A



G101FW



G101

Finish	Unit	No
Nickel Plated Brass	PACK 100	<b>G100</b>
Nickel Plated Brass	PACK 100	<b>G101</b>
Nickel Plated Brass	PACK 100	<b>G101FW</b>
Nickel Plated Brass	PACK 100	<b>G102A</b>
Nickel Plated Brass	PACK 100	<b>G102B</b>
Nickel Plated Brass	PACK 100	<b>G103</b>
Nickel Plated Brass	PACK 100	<b>G104</b>
Nickel Plated Brass	PACK 100	<b>G104A</b>
Nickel Plated Brass	PACK 100	<b>G104BP</b>
Nickel Plated Brass	PACK 100	<b>G105</b>
Nickel Plated Brass	PACK 100	<b>G105A</b>
Nickel Plated Brass	PACK 100	<b>G105FW</b>
Nickel Plated Brass	PACK 100	<b>G105MW</b>
Nickel Plated Brass	PACK 100	<b>G106</b>
Nickel Plated Brass	PACK 100	<b>G108</b>
Nickel Plated Brass	PACK 100	<b>G108BP</b>

## Stayput Fasteners



G852



G854

- ◆ Horizontal single stud with two screw base works with No 1 and No 2 spur grommets
- ◆ Stayput fasteners are manufactured from UV stabilised nylon with nickel plated brass tabs and pivot
- ◆ Screw mounted to deck or cloth to cloth

Unit	Pack Quantity	No
EACH	100	<b>G852</b>
EACH	100	<b>G854</b>





## Awning Hooks & Eyes

- ◆ Injection moulded nylon sew through plastic hooks & eyes
- ◆ Can be used alone, or together with lacing & shockcord
- ◆ Allows quick and easy attachment on dodgers to guard rails, sailcover, marques, tents and awning structures



A068BK



A068WT



A069BK



A069WT



A071



A170



A172



B401S



G200S



G203S



G204N

Colour	Finish	Style	Unit	Pack Quantity	No
Black	Nylon	Sew On	EACH	100	<b>A068BK</b>
White	Nylon	Sew On	EACH	100	<b>A068WT</b>
Black	Nylon	Sew On	EACH	100	<b>A069BK</b>
White	Nylon	Sew On	EACH	100	<b>A069WT</b>
White	Nylon	Rivet On	EACH	100	<b>A071</b>
Dark Grey	Nylon	Sew On	EACH	1	<b>A170</b>
Dark Grey	Nylon	Sew On	EACH	1	<b>A172</b>
Stainless	Stainless Steel	Screw On	EACH	100	<b>B401S</b>
Stainless	Stainless Steel	Screw On	EACH	10	<b>G200S</b>
Stainless	Stainless Steel	Screw On	EACH	1	<b>G203S</b>
Nickel Plated	Nickel Plated Brass	Screw On	EACH	1	<b>G204N</b>

## Lacing Buttons

- ◆ Injection moulded nylon
- ◆ Up to 5mm cord
- ◆ Knob diameter 18mm



G045WT



G055BK



G055WT



G045BK

Colour	Finish	Style	Unit	Pack Quantity	No
Black	Nylon	Screw On	PACK 100	1	<b>G045BK</b>
White	Nylon	Screw On	PACK 100	1	<b>G045WT</b>
Black	Nylon	Screw On	PACK 50	1	<b>G055BK</b>
White	Nylon	Screw On	PACK 50	1	<b>G055WT</b>







## Ladderlock Buckles

- ◆ A selection of buckles and fittings suitable for use with webbing & cover making applications



Heavy Duty

Webbing (mm)	Material	Unit	Pack Quantity	No
15	Black Nylon	EACH	10	<b>A074</b>
19	Black Nylon	EACH	10	<b>A075</b>
25	Black Nylon	EACH	10	<b>A076</b>
25	Heavy Duty Nylon	EACH	10	<b>A076HD</b>
40	Black Nylon	EACH	10	<b>A073</b>
50	Heavy Duty Nylon	EACH	10	<b>A077HD</b>

## Snap Buckles



- ◆ A selection of buckles and fittings suitable for use with webbing & cover making applications

Webbing (mm)	Material	Unit	Pack Quantity	No
15	Black Nylon	EACH	10	<b>A087</b>
19	Black Nylon	EACH	10	<b>A088</b>
25	Black Nylon	EACH	10	<b>A089</b>
25	White Nylon	EACH	10	<b>A089WT</b>
38	Black Nylon	EACH	10	<b>A086</b>
38	Black Plastic	EACH	50	<b>A142BK</b>
50	Black Nylon	EACH	10	<b>A085</b>

## Centre Release Buckles



A084



A090



A159BK

- ◆ Easy-to-use push button release buckle
- ◆ Uses include One Design jib hanks

Webbing (mm)	Material	Unit	No
10	Acetal	PACK 100	<b>A084</b>
10	Black Nylon	PACK 100	<b>A090</b>
19	Acetal	PACK 100	<b>A159BK</b>





## Webbing Fittings - Cam Buckles

- ♦ A selection of buckles and fittings suitable for using with webbing & cover making applications



B087

A078WT A079WT

A079BK A072BK

Webbing (mm)	Material	Unit	Pack Quantity	No
19	White Nylon	EACH	10	<b>A078WT</b>
25	Black Nylon	EACH	10	<b>A079BK</b>
25	White Nylon	EACH	10	<b>A079WT</b>
25	Stainless Steel	EACH	1	<b>B087</b>
50	Black Nylon	EACH	10	<b>A072BK</b>

## Static & Sliding Buckles



G222S

G221 / G222 / G223

G221S

A122BK / A125BK / A142BK

G211S

G210S

Webbing (mm)	Material	Unit	Pack Quantity	No
25	Stainless Steel	EACH	10	<b>G210S</b>
25	Stainless Steel	EACH	10	<b>G211S</b>
25	Black Plastic	EACH	10	<b>A122BK</b>
25	Stainless Steel/ Nylon	EACH	10	<b>G221</b>
25	Stainless Steel	EACH	1	<b>G221S</b>
38	Black Plastic	EACH	50	<b>A142BK</b>
40	Black Nylon	EACH	10	<b>A096BK</b>
40	White Nylon	EACH	10	<b>A096WT</b>
40	Stainless Steel/Nylon	EACH	10	<b>G223</b>
50	Black Nylon	EACH	10	<b>A097BK</b>
50	White Nylon	EACH	10	<b>A097WT</b>
50	Black Plastic	EACH	50	<b>A125BK</b>
50	Stainless Steel/ Nylon	EACH	10	<b>G222</b>
50	Stainless Steel	EACH	10	<b>G222S</b>





## Webbing Bridges



G205S



G209S



A125BK



A124WT

Webbing (mm)	Material	Unit	Pack Quantity	No
25	Stainless Steel	EACH	10	<b>G205S</b>
25	Stainless Steel	EACH	10	<b>G209S</b>
25 - 30	Black Nylon	EACH	10	<b>A095BK</b>
25 - 30	White Nylon	EACH	10	<b>A095WT</b>

## Holdon Clips



- ◆ Holdon© MIDI Tarp Clip - Heavy duty instant reusable clip-on eyelet The patented and reusable Holdon© MIDI instant clip-on eyelet and tarp clip is ideal for securing all types of textiles, fabrics, substrates, polythene and other sheet products, hemmed or non-hemmed up to 5 mm thickness
- ◆ It is ideal for customizing shelters, emergency repairs to covers, shade sails and cloths, backdrops adding new fixing points/ guy lines and securing tarpaulins
- ◆ Available in Midi (Tested to 100kg) & Mini style (Tested to 45kg)
- ◆ Stronger than traditional eyelets
- ◆ For flexible material up to 1.5mm use Mini (45kg)
- ◆ For flexible material up to 5mm use Midi (100kg)
- ◆ No tools needed
- ◆ Reusable/relocatable



A160WT



A161WT

Colour	Style	Unit	Pack Quantity	No
White	Midi	EACH	10	<b>A160WT</b>
White	Mini	EACH	1	<b>A161WT</b>

## Triangles Stainless Steel



B127



B127B

- ◆ Bainbridge Triangles are manufactured from Type 316 stainless steel,
- ◆ Cleaned and passivated after welding to reduce the risk of staining
- ◆ TIG welded to maximise strength

Safe Working Load (kg)	Weight (g)	Bar Diameter (mm)	Inside Width (mm)	Unit	Pack Quantity	No
500	49	6.3	51	EACH	1	<b>B127</b>
1000	57	6.3	51	EACH	1	<b>B127B</b>





## Keder Sprayhood Tapes

- ◆ Keder is a durable & reinforced woven polyester tape which easily slides into vinyl or plastic mouldings & tracks for marine, automotive and awning industries
- ◆ Ideal for sides of tents, awnings, lorry curtains and marine covers
- ◆ Full rolls only



L575T



L585 / L575



L585BK / L575BK

Colour	Diameter (mm)	Style	Roll Length (m)	Unit	No
White	7 5	Standard	100	METRE	<b>L575</b>
Black	7 5	Standard	100	METRE	<b>L575BK</b>
White	7 5	Repair	100	METRE	<b>L575T</b>
White	8 5	Standard	100	METRE	<b>L585</b>
Black	8 5	Standard	100	METRE	<b>L585BK</b>

## Polyester Awning Tape

- ◆ Monofilm core polyester sail tape
- ◆ Ideal for sprayhoods, caravan awnings and marine covers
- ◆ Use with G512 Flex-A-Rail awning track & G520-8 Aluminium Track
- ◆ Full rolls only



Colour	Diameter (mm)	Roll Length (m)	Unit	No
White	7	100	METRE	<b>LS001</b>
White	6	100	METRE	<b>LS002</b>

- ◆ P-Section design ensures maximum efficiency
- ◆ Durable extruded foam rubber composition
- ◆ Hi-tack adhesive with release paper on rear
- ◆ This product is ideal weather strip for sealing: enclosures, dodgers, covers etc
- ◆ A must for bow corners & radar arches anywhere a water problem may occur

## Xtreme Seal



L710BK



L705BKA



L710WT

Colour	Diameter (mm)	Roll Length (m)	Unit	No
Black	34	75	METRE	<b>L705BKA</b>
Black	44	15	METRE	<b>L710BK</b>
White	44	15	METRE	<b>L710WT</b>





## Stainless Steel Tubing



- ◆ Mirror polished Type 316 stainless steel tubes used for high quality canvas & framework Great for machining, welding and fabricating
- ◆ Sold in 6m lengths only (Special shipping & collection only)
- ◆ Cutting service available based on purchasing full lengths only, cutting charge applied

Inside Diameter (mm)	Outside Diameter (mm)	Wall Thickness (mm)	Unit	Pack Quantity	No
19.8	22.2	1.2	METRE	6	<b>TUB001</b>
22.4	25.4	1.5	METRE	6	<b>TUB002</b>
23.0	25.4	1.2	METRE	6	<b>TUB003</b>

## End Plugs



G611S / G621S



G631SHD / G641SHD



G621BK

- ◆ Type 316 stainless steel mirror polished finish, canopy eye end fittings for use on stainless steel tubing.
- ◆ Designed specifically for the marine cover, auto & awning industries
- ◆ Available in either type 316 stainless steel or non corrosive nylon
- ◆ Ideal for sprayhoods, biminis, cockpits & sun deck awnings



G675 / G676 / G679



G674



G620SS



G671S



G678S

Finish	Fitting Type	Tube Size (mm)	Unit	No
Stainless Steel 316	Tube	19	EACH	<b>G611S</b>
Stainless Steel 316	Tube	22	EACH	<b>G621S</b>
Stainless Steel 316	Tube	25	EACH	<b>G631SHD</b>
Stainless Steel 316	Tube	31	EACH	<b>G641SHD</b>
Nylon	Tube	22	EACH	<b>G621BK</b>
Stainless Steel 316 / Nylon	Tube	19	EACH	<b>G675</b>
Stainless Steel 316 / Nylon	Tube	19	EACH	<b>G676</b>
Stainless Steel 316 / Nylon	Tube	22	EACH	<b>G679</b>
Stainless Steel	Tube	-	EACH	<b>G674</b>
Stainless Steel	Tube	-	PACK 10	<b>G620SS</b>
Stainless Steel 316	Tube	22	EACH	<b>G671S</b>
Stainless Steel 316	Tube	22	EACH	<b>G678S</b>
Stainless Steel 316	Tube	25	EACH	<b>G681S</b>



## Jaw Slides

- ◆ Type 316 stainless steel mirror polished finish, jaw slides fittings for use on stainless steel tubing.
- ◆ Designed specifically for the marine cover, auto & awning industries
- ◆ Available in either type 316 stainless steel or non corrosive nylon
- ◆ Ideal for sprayhoods, biminis, cockpits & sun deck awnings
- ◆ G8\*\*S separates for ease of mounting
- ◆ G65\*WT tension by hand



G610S / G620S



G630SHD / G640SHD



G620BK



G650WT / G651WT / G652WT / G653WT



G820S / G830S / G840S



G655

Finish	Fitting Type	Tube Size (mm)	Unit	No
Stainless Steel 316	Tube	19	EACH	<b>G610S</b>
Stainless Steel 316	Tube	19	EACH	<b>G655</b>
Stainless Steel 316	Tube	22	EACH	<b>G672S</b>
Stainless Steel 316	Tube	22	EACH	<b>G620S</b>
Stainless Steel 316	Tube	22	EACH	<b>G820S</b>
Nylon	Tube	22	EACH	<b>G620BK</b>
Stainless Steel 316	Tube	25	EACH	<b>G682S</b>
Stainless Steel 316	Tube	25	EACH	<b>G630SHD</b>
Stainless Steel 316	Tube	25	EACH	<b>G635S</b>
Stainless Steel 316	Tube	25	EACH	<b>G830S</b>
Stainless Steel 316	Tube - Double	25	EACH	<b>G697S</b>
Stainless Steel 316	Tube	31	EACH	<b>G640SHD</b>
Stainless Steel 316	Tube	31	EACH	<b>G840S</b>
Stainless Steel 316	Tube	31	EACH	<b>G840SSP</b>
Stainless Steel 316 / Nylon	Tube	19	EACH	<b>G650WT</b>
Stainless Steel 316 / Nylon	Tube	19	EACH	<b>G651WT</b>
Stainless Steel 316 / Nylon	Tube	22	EACH	<b>G652WT</b>
Stainless Steel 316 / Nylon	Tube	25	EACH	<b>G653WT</b>

## QR Tube Hinges

- ◆ Type 316 stainless steel mirror polished finish, hinge fittings for use on stainless steel tubing.
- ◆ Designed specifically for the marine cover, auto & awning industries
- ◆ Features a quick release pin
- ◆ Ideal for sprayhoods, biminis, cockpits & sun deck awnings



G744S / G747S

Finish	Fitting Type	Tube Size (mm)	Unit	No
Stainless Steel 316	Tube	22	EACH	<b>G747S</b>
Stainless Steel 316	Tube	25	EACH	<b>G744S</b>





## Deck Mounts

- ◆ Produced from either type 316 stainless steel with a mirror polished finish or nylon so that they will not corrode
- ◆ Canopy Deck Mount fittings for use on stainless steel tubing have been designed specifically for the marine cover, auto & awning industries
- ◆ High strength black nylon fittings Excellent resistance to UV works with either stainless steel or aluminium tubing
- ◆ Ideal for sprayhoods, biminis, cockpits & sun deck awnings
- ◆ Concave base allows for rail or tube mounting
- ◆ Lanyard is used to attach quick release pin to the deck mount to prevent accidental loss
- ◆ Side mount accepts all eye ends
- ◆ For quick release use G625PIN
- ◆ For drop nose use G627PIN

Finish	Base	Style	Unit	No
Stainless Steel 316	Flat	Screw	EACH	<b>G604S</b>
Stainless Steel 316	Flat	Screw	EACH	<b>G622S</b>
Stainless Steel 316	Flat	Pin	EACH	<b>G625S</b>
Stainless Steel 316	Flat	Pin	EACH	<b>G675S</b>
Stainless Steel 316	Flat	Pin	EACH	<b>G677S</b>
Stainless Steel 316	Flat	Quick Release	EACH	<b>G605S</b>
Stainless Steel 316	Flat	Quick Release	EACH	<b>G625SQP</b>
Stainless Steel 316	Flat	Hinge	EACH	<b>G692S</b>
Stainless Steel 316	Angled	Screw	EACH	<b>G623S</b>
Stainless Steel 316	Angled	Quick Release	EACH	<b>G628SQP</b>
Stainless Steel 316	Hinged	Screw	EACH	<b>G607S</b>
Stainless Steel 316	Hinged	Screw	EACH	<b>G615S</b>
Stainless Steel 316	Hinged	Pin	EACH	<b>G615SQP</b>
Stainless Steel 316	Concave	Screw	EACH	<b>G626S</b>
Stainless Steel 316	Concave	Pin	EACH	<b>G674S</b>
Stainless Steel 316	Side	-	EACH	<b>G624S</b>
Stainless Steel 316	Side	-	EACH	<b>G629S</b>
Stainless Steel 316 / Nylon	Flat	Screw	EACH	<b>G603</b>
Stainless Steel 316 / Nylon	Flat	Hinge	EACH	<b>G646S</b>
Nylon	Flat	Screw	EACH	<b>G622BK</b>
Stainless Steel 316	Accessory	-	EACH	<b>G623SS</b>
Stainless Steel 316	Accessory	-	EACH	<b>G625LAN</b>
Stainless Steel 316	Accessory	-	EACH	<b>G625PIN</b>
Stainless Steel 316	Accessory	-	EACH	<b>G627PIN</b>





## Deck Mounts



G604S



G622S



G625S



G675S



G605S



G625SQP



G692S



G623S



G628SQP



G607S



G615S



G615SQP



G626S



G624S



G629S



G603



G622BK



G623SS



G625LAN



G625PIN



G627PIN





## Gemlock Snap Button



- ◆ All stainless steel designed for tubing 19mm to 32mm inside diameter

Finish	Fitting Type	Tube Size (mm)	Unit	Pack Quantity	No
Stainless Steel 316	Tube		EACH	1	<b>G758</b>

## Track & Track Mounts



G670



G590



G590C

- ◆ Quick release adjustment manufactured from 316 stainless steel ultra low profile design with positive locking mechanism
- ◆ Easily operated by hand
- ◆ Ideal for mounting biminis on centre cockpits canopy deck mount fittings for use on stainless steel tubing have been designed specifically for the marine cover, auto & awning industries
- ◆ Produced from either type 316 stainless steel with a mirror polished finish or nylon so that they will not corrode
- ◆ Ideal for sprayhoods, biminis, cockpits & sun deck awnings

Finish	Fitting Type	Unit	Pack Quantity	No
Stainless Steel 316		PAIR	1	<b>G670</b>
Nylon / SS 316	Deck	EACH	1	<b>G590</b>
Nylon / SS 316	Deck	EACH	1	<b>G590C</b>

## Sunblocker Clips

- ◆ Sunblocker is a self insulated protective clip which eliminates contact between your metal tubular top frame and the clear plastic window
- ◆ Two or three Sunblocker clips on metal frame tubing can give maximum protection against destruction of clear plastic windows, by reducing singeing, scorching and heat cracking
- ◆ Marine Grey in colour



G738



G639



G638


Tube Size (mm)	Finish	Fitting Type	Unit	Pack Quantity	No
22	Nylon	Accessories	EACH	1	<b>G738</b>
25	Nylon	Accessories	EACH	1	<b>G638</b>
25	Nylon	Accessories	EACH	1	<b>G639</b>





## Sun Sox

- ◆ SUN SOX offer a simple inexpensive window protector
- ◆ Non-woven spun polyester cover - soft finish with velcro strip closure
- ◆ SUN SOX simply wraps around tubing up to 37mm & secures to itself 1800mm lengths can be cut to match tube size & come in five attractive colours



Colour	Length (mm)	Unit	Pack Quantity	No
Burgundy	1800	PACK	1	<b>LS401BG</b>
Black	1800	PACK	1	<b>LS401BK</b>
Blue	1800	PACK	1	<b>LS401BU</b>
Grey	1800	PACK	1	<b>LS401GY</b>
Beige	1800	PACK	1	<b>LS401TN</b>

- ◆ Manufactured from Type 316 stainless steel,
- ◆ Chemically and passivated after welding to reduce the risk of staining
- ◆ TIG welded maximises strength

## D Rings Stainless Steel



Bar Diameter (mm)	Inside Width (mm)	SWL (kg)	Weight (g)	Unit	Pack Quantity	No
5.0	25	300	14	EACH	10	<b>B169</b>
4.8	25	300	14	EACH	10	<b>B170</b>
4.8	31	150	18	EACH	10	<b>B171</b>
4.8	38	300	21	EACH	10	<b>B172</b>
4.8	51	150	23	EACH	10	<b>B173</b>
6.3	51	500	42	EACH	10	<b>B174</b>

## Carabiner Hook

- ◆ Carabiner snaps ("Fireman hook") with spring loaded jaw, in economy steel for use on banners, key rings, buckets, etc
- ◆ Warning: Carabiner Snap Hooks should not be used for high load applications such as emergency safety equipment
- ◆ **Not** recommended for marine applications



Dimensions (mm)	Unit	Pack Quantity	No
60 x 6	EACH	1	<b>B651</b>



# Boat Vent

## Boat Vents



G048BK



G050BK



G050BU



G050GY



G050IV



G050WT

- ◆ UV resistant material
- ◆ No screws or awls needed
- ◆ Fits 3/4" or 7/8" tubing
- ◆ Boat Vents and Awning Poles used to help boat cover ventilation
- ◆ Overhanging top to allow in less moisture Boat Vent 3 has additional teeth for a better grip - G048BK

Colour	Finish	Unit	No
Black	Nylon	EACH	<b>G048BK</b>
Black	Nylon	EACH	<b>G049BK</b>
Black	Nylon	EACH	<b>G050BK</b>
Blue	Nylon	EACH	<b>G050BU</b>
Grey	Nylon	EACH	<b>G050GY</b>
Ivory	Nylon	EACH	<b>G050IV</b>
White	Nylon	EACH	<b>G050WT</b>

## Awning Poles



G371

G308 / G309

- ◆ Adjustable anodised aluminium poles
- ◆ Range from 0.98 - 3.6m
- ◆ G371 features cam lock and supports high loads

Colour	Finish	Length (m)	Unit	No
Silver	Aluminium	1.2 to 2.4	EACH	<b>G308</b>
Silver	Aluminium	1.18 to 3.6	EACH	<b>G309</b>
Silver	Aluminium	0.98 to 1.7	EACH	<b>G371</b>

## Pole Bases



G049BK



G051BK



- ◆ Easy to install
- ◆ Suitable for all types of fabric
- ◆ Base designed to disperse the pole weight to prevent damage to the carpet/vinyl floors

Colour	Finish	Unit	No
Black	Nylon	EACH	<b>G049BK</b>
Black	Nylon	EACH	<b>G051BK</b>



## Scissors, Thread Snips, Rippers & Cutters

◆ Scissors, Seam Rippers and Cutters used for a variety of jobs in sailmaking & covermaking applications.



C552-10



C551-7



C550-12



C550-10



C912



C909



C552-12



C907



C908



C906



C905



C561



C554



C553

Hand	Type	Length (mm)	Unit	No
Right	Wiss 27	178	EACH	<b>C551-7</b>
Right	Wiss 28	203	EACH	<b>C551-8</b>
Right	Wiss 29	229	EACH	<b>C551-9</b>
Right	Wiss 20	254	EACH	<b>C552-10</b>
Right	Wiss 22	305	EACH	<b>C552-12</b>
Right	Teflon Coated Shears	260	EACH	<b>C912</b>
Right	Wiss 20	254	EACH	<b>C555-10</b>
Right	Wiss 22	305	EACH	<b>C555-12</b>
Right	Knife Edge Shears	254	EACH	<b>C550-10</b>
Right	Knife Edge Shears	305	EACH	<b>C550-12</b>
Right	Fiskar	215	EACH	<b>C907</b>
Left	Wiss 20	254	EACH	<b>C552L-10</b>
Left	Fiskar	215	EACH	<b>C908</b>
Left & Right	Fiskar	215	EACH	<b>C909</b>
Left & Right	Wiss Snips	-	EACH	<b>C553</b>
Left & Right	Wiss Snips	-	EACH	<b>C554</b>
Left & Right	Thread Snips	-	EACH	<b>C910</b>
Left & Right	Seam Rippers	80	EACH	<b>C905</b>
Left & Right	Seam Rippers	120	EACH	<b>C906</b>
-	Sharpener	-	EACH	<b>C561</b>



## Hot Knives

- ◆ Designed to cut and seal synthetics, woven, knit fabrics, rope, cord and webbing
- ◆ Quick heating with built in spot lights
- ◆ Combine with optional blades for a variety of uses
- ◆ Engel hot knife blades sold separately
- ◆ C852 is a standard blade
- ◆ C853 is ideal for applique work, to cut and seal synthetics

# HSGM

C850



C852



C853



- ◆ Designed to cut and seal synthetics, woven, knit fabrics, rope, cord and webbing
- ◆ Seals edges with minimum smoke and no singed edges
- ◆ Effortless cutting - no mess, no fuss
- ◆ Spring loaded safety trigger on/off switch
- ◆ Quick heating
- ◆ C857B is a standard blade

C857



C857B



### CAUTION

Hot knives are designed for intermittent operation and should not be used for more than 10 minutes at one time without a pause.

These lightweight, easy to hold tools have a heating element which slides inside the selected tip attachment allowing a very efficient use of heat. Tips may be interchanged for cutting, sealing or circle cuts.

- ◆ Easy to hold tools with hot knife blade included.
- ◆ Heats quickly up to working temperature.
- ◆ Heat element of tool fits inside tip for greater efficiency.

C880



C840



C860



C834



Brand	Voltage	Watts	Unit	No
Engel	220	60	EACH	<b>C850</b>
Engel	-	-	EACH	<b>C852</b>
Engel	-	-	EACH	<b>C853</b>
Bainbridge	230	60	EACH	<b>C857</b>
Bainbridge	-	-	EACH	<b>C857B</b>
Bainbridge	230	60	EACH	<b>C857D</b>
Bainbridge	110	18	EACH	<b>C860</b>
Bainbridge	110	60	EACH	<b>C861</b>
Bainbridge	-	-	EACH	<b>C862</b>
Bainbridge	-	-	EACH	<b>C865</b>
Bainbridge	Gas	-	EACH	<b>C880</b>
Bainbridge	-	-	EACH	<b>C882</b>
Portasol	Gas	-	EACH	<b>C834</b>
Ungar	110	18	EACH	<b>C840</b>



- ◆ The Wrist-Saver roller's patent pending design allows for proper positioning of your arm, wrist and hand into a neutral, relaxed working position.
- ◆ The design allows you to use the power of your whole arm and conserve energy
- ◆ Keeps your wrist in a more comfortable position and your arm moves in a natural motion

## Seam Rollers

EVERHARD



C523



Silicone Roller - EVRMR05200



Smooth Roller - EVRMR02143

Width (mm)	Weight (g)	Unit	No
51	811	EACH	<b>EVMR02143</b>
45	340	EACH	<b>EVMR05200</b>
31	-	EACH	<b>C523</b>

## Pushpins & Awls

- ◆ Awls & Pushpins to help keep cloth in position when measuring & marking.
- ◆ C900 - 130mm & C901 - 100mm

C903



C903FP



C903BK



C900 / C901



Colour	Unit	Pack Quantity	No
Yellow	EACH	10	<b>C900</b>
Yellow	EACH	10	<b>C901</b>
Silver	PACK 100	1	<b>C903</b>
Black	PACK 100	1	<b>C903BK</b>
Hot Pink	PACK 100	1	<b>C903FP</b>

- ◆ Spring loaded fabric clamps

## Cloth Clamps



Jaw Opening (mm)	Length (mm)	Unit	No
25	102	EACH	<b>C515</b>
51	152	EACH	<b>C516</b>
76	229.9	EACH	<b>C517</b>

## Cutting Pad

- ◆ Dimensions: 250 x 250 x 13
- ◆ Made from reinforced vinyl



Colour	Unit	No
Black	EACH	<b>C501</b>





## Sailmakers Palms

C026



C024



C027



C036



C032



C028



C030



C023



C025



C033



C037



C034



C029



- ◆ Excellent quality sailmakers palm.
- ◆ Handcrafted in England
- ◆ These seaming and roping palms are made for long lasting wear and comfort.
- ◆ Moulded rawhide palm protection.
- ◆ C028 as used by professionals

Hand	Style	Type	Unit	No
Right	2	Seaming	EACH	<b>C023</b>
Right	3	Seaming	EACH	<b>C024</b>
Right	2 <sup>1/2</sup>	Seaming	EACH	<b>C026</b>
Right	11	Seaming	EACH	<b>C028</b>
Right	12	Roping	EACH	<b>C030</b>
Right	15	Seaming	EACH	<b>C032</b>
Right	16	Roping	EACH	<b>C034</b>
Right	9	Seaming	EACH	<b>C036</b>
Left	3	Seaming	EACH	<b>C025</b>
Left	2 <sup>1/2</sup>	Seaming	EACH	<b>C027</b>
Left	11	Seaming	EACH	<b>C029</b>
Left	15	Seaming	EACH	<b>C033</b>
Left	9	Seaming	EACH	<b>C037</b>

## Dip it Whip It



- ◆ Prevents unraveling.
- ◆ Forms a permanent, flexible coating.
- ◆ Available in multiple colors to match or color code rope.
- ◆ 118g

Colour	Unit	No
White	EACH	<b>SB84904</b>
Red	EACH	<b>SB84905</b>
Green	EACH	<b>SB84906</b>
Clear	EACH	<b>SB84907</b>
Black	EACH	<b>SB84908</b>



## Sailmakers Needles

- ◆ All needles are hand-made and hand polished for ease of use
- ◆ Tube pack contains assorted size needles



C007



C021 / C022



C005 - C019

Diameter (mm)	Length (mm)	Size	Unit	Pack Quantity	No
3.25	89	10	PACK 25	1	<b>C010</b>
2.64	81	12	PACK 25	1	<b>C012</b>
2.34	79	13	PACK 25	1	<b>C013</b>
2.03	76	14	PACK 25	1	<b>C014</b>
1.88	72	15	PACK 25	1	<b>C015</b>
1.63	69	16	PACK 25	1	<b>C016</b>
1.42	65	17	PACK 25	1	<b>C017</b>
1.22	62	18	PACK 25	1	<b>C018</b>
1.02	49	19	PACK 25	1	<b>C019</b>
Assorted	Assorted	13-19	PACK 5	1	<b>C005</b>
Assorted	Assorted	14-18	TUBE 10	1	<b>C021</b>
Assorted	Assorted	14-18	TUBE 20	1	<b>C022</b>
Assorted	Assorted	-	PACK 7	1	<b>C007</b>

## Speedy Stitcher

- ◆ The Speedy Stitcher can be used to sew most heavy materials. It is a hand operated sewing machine which is suitable for use with most fabrics and leather
- ◆ A handy tool to have on board for sail repairs.

C917C8



C917ST8



C916



C910US



Used With	Unit	No
-	EACH	<b>C910US</b>
C910US	PACK 3	<b>C9105</b>
C910US	PACK 3	<b>C9106</b>
C910US	PACK 3	<b>C9108</b>
-	EACH	<b>C916</b>
C916	EACH	<b>C917C8</b>
C916	EACH	<b>C917ST8</b>





## Measuring Tapes & Ruler

◆ Measuring tools for both covermaking & sailmaking.

C713



C706



C705



C710



Length (m)	Type	Colour	Unit	No
30	Steel Tape	Black	EACH	<b>C705</b>
3	Fibreglass	Orange / Yellow	EACH	<b>C706</b>
30	Fibreglass Tape	Orange / Yellow	EACH	<b>C713</b>
1	Aluminium	Silver	EACH	<b>C710</b>

## Lofting Battens

- ◆ Fibreglass Lofting battens available in 12 x 9 or 25 x 8 in various lengths.
- ◆ Ideal for splining sail edges



Cross section C914/5



Cross section C920/2/4

Length (m)	Sections (mm)	Unit	No
5	12 x 9	EACH	<b>C914</b>
10	12 x 9	EACH	<b>C915</b>
12.2	25 x 8	EACH	<b>C920</b>
18.3	25 x 8	EACH	<b>C922</b>
30.5	25 x 8	EACH	<b>C924</b>

## Chalk & Pencils

◆ Marking tools for both covermaking & sailmaking.

C933



C933S



ZMARKERWT



ZPENCILBU



ZPENCILW2



Type	Colour	Unit	Pack Quantity	No
Chalk	White	BOX 12	1	<b>C933</b>
Shapener	Yellow	EACH	1	<b>C933S</b>
China Marker	White	EACH	12	<b>ZMARKERWT</b>
Washable Pencil	Blue	EACH	12	<b>ZPENCILBU</b>
Washable Pencil	White	EACH	12	<b>ZPENCILW2</b>





## Mallets

- ◆ Traditional sailmaking tool used with punches, hole cutters, grommet dies and wherever a cushioned hit is desired, now offered in a heavy weight and larger face style.
- ◆ C233 - Maul Master is available in two sizes and offers a dramatic improvement over the old mallet or hammer style
- ◆ Special shock absorbing, no slip rubber grip
- ◆ Special nylon compound striking surface
- ◆ Machined from aircraft aluminium



Length (mm)	Weight (kg)	Unit	No
-	1.2	EACH	<b>C530</b>
-	1.4/5	EACH	<b>C531</b>
229	1.4	EACH	<b>C233</b>
254	2	EACH	<b>C234</b>

## Hole Cutters

- ◆ Hole punches used for all grommets & inox ring system.



Size (mm)	Unit	No
3.2	EACH	<b>C101</b>
4	EACH	<b>C102</b>
4.8	EACH	<b>C103</b>
6.3	EACH	<b>C104</b>
7.9	EACH	<b>C105</b>
9.5	EACH	<b>C106</b>
11.1	EACH	<b>C107</b>
12.7	EACH	<b>C108</b>
14.3	EACH	<b>C109</b>
15.9	EACH	<b>C110</b>
17.5	EACH	<b>C111</b>
19	EACH	<b>C112</b>
20	EACH	<b>C113</b>
22	EACH	<b>C114</b>
25.4	EACH	<b>C116</b>
28.6	EACH	<b>C117</b>
34.9	EACH	<b>C119</b>
38.1	EACH	<b>C120</b>
44.5	EACH	<b>C122</b>

## Revolving Hole Punch

- ◆ Revolving hand punch for canvas and cover work
- ◆ C350 - Heavy duty hole punch



Size (mm)	Unit	No
230	EACH	<b>C125</b>
-	EACH	<b>C350</b>





## Lift The Dot Cutter

- ◆ C953BK - a temporary cutting punch for G130 fasteners



C952



C953BK



C953

Used With	Unit	No
-	EACH	<b>C952</b>
G130	EACH	<b>C953BK</b>
G130	EACH	<b>C953</b>

## Permalock Cutter



Colour	Unit	No
Stainless	EACH	<b>C140</b>

## Turnbutton Cutters



C950



C951

Finish	Cutting Punch	Unit	No
Nickel Plated Brass	-	EACH	<b>C950</b>
Nickel Plated Brass	-	EACH	<b>C951</b>

## Tylaska Snap Setter

**Tylaska**



- ◆ A new die solves the problem of setting two fasteners at once, by having two precisely spaced cavities allowing two buttons or eyelets to be installed at the same time.
- ◆ One side is for 2 x G140 buttons & the other for 2 x G145 eyelet

Finish	Unit	No
Chrome	EACH	<b>C959</b>





## Closing Tools for Button Snap Fasteners



Finish	Unit	No
Steel	EACH	<b>C954</b>
Steel	EACH	<b>C955</b>
Steel	EACH	<b>C956</b>
Alloy Cast	EACH	<b>C360</b>
Alloy Cast	EACH	<b>C361</b>
Rubber	EACH	<b>C361BKW</b>
Alloy Cast	EACH	<b>C361CAP</b>
Rubber	EACH	<b>C361GYW</b>
Alloy Cast	EACH	<b>C361SOCKET</b>
Alloy Cast	EACH	<b>C370</b>
Alloy Cast	EACH	<b>C371</b>

## Staplers & Staples

- ◆ C758 - For stapling around bolt ropes or rolled up material
- ◆ C759 - Lightweight stapler, ideal for spinnakers & One Design sails
- ◆ D732 - 1/4 Staples
- ◆ D733 - 3/8 Staples
- ◆ 1 Box = 5000 Staples



Unit	No
EACH	<b>C758</b>
EACH	<b>C759</b>
BOX	<b>D733</b>
BOX	<b>D732</b>

## Rivet Tools - Closing Tools

- ◆ For best results: hit closing tools with a rawhide mallet or Maul Master against a steel or aluminium plate.
- ◆ Do not use steel head hammer or mallet.



Use With	Unit	No
D331 - D334	EACH	<b>C324</b>
D331-D334	EACH	<b>C325</b>
D335-D339	EACH	<b>C326</b>





## Stimpson Grommets - Closing Tools



- ◆ Stimpson Grommets should not be used with English Grommet tools.
- ◆ Stimpson tools are machined steel case hardened dies
- ◆ For best results use the correct Stimpson die set

Size	Unit	No
0	EACH	<b>C303C</b>
0	EACH	<b>C303S</b>
1	EACH	<b>C304C</b>
1	EACH	<b>C304S</b>
2	EACH	<b>C305C</b>
2	EACH	<b>C305S</b>
3	EACH	<b>C306C</b>
3	EACH	<b>C306S</b>
4	EACH	<b>C307C</b>
4	EACH	<b>C307S</b>
5	EACH	<b>C308S</b>
6	EACH	<b>C309S</b>

## English Grommets - Closing Tools

- ◆ Tools for English Grommets should not be used with Stimpson Grommets.



Set Hole Diameter (mm)	Size	Unit	No
4.8	000	EACH	<b>C301</b>
6.4	00	EACH	<b>C302</b>
8.4	0	EACH	<b>C303</b>
9.5	1	EACH	<b>C304</b>
11.9	2	EACH	<b>C305</b>
12.7	3	EACH	<b>C306</b>
14.7	4	EACH	<b>C307</b>
17	5	EACH	<b>C308</b>
	6	EACH	<b>C309</b>







## Headboard Liners - Closing Tools

- ◆ Two piece closing tool for setting with hydraulic press.
- ◆ Add the handle to set liners by hand with a mallet for D037N
- ◆ All 3 items are supplied with handle



Use with Liners	Unit	No
D037N	EACH	<b>C321</b>
D038	EACH	<b>C322</b>
D039N & D039S	EACH	<b>C323</b>

## Inox Pressed Rings - Closing Tools

- ◆ These tools are suitable for most presses. All except C408 can be used with Enerpac-Nautilus pull down presses by removing the centre post.



Use Tool For	Unit	No
D207	EACH	<b>C407</b>
D208	EACH	<b>C408</b>
D209	EACH	<b>C409</b>
D210	EACH	<b>C410</b>
D211	EACH	<b>C411</b>
D212	EACH	<b>C412</b>
D213	EACH	<b>C413</b>
D214	EACH	<b>C414</b>

## Nicropress Tool

- ◆ The finest and most accurate hand closing tool for Nicropress Sleeves.



Type	Length (cm)	Size	Unit	No
63V XPM	51	1/8, 5/32, 3/16	EACH	<b>C960N</b>
64CgMP	51	1/16, 3/32, 1/8, 5/32	EACH	<b>C962N</b>





## Pliers



- ◆ C352 - Zipper stop pliers
- ◆ C449 - Shockcord clamp closing pliers for all sizes

	Unit	No
	EACH	<b>C449</b>
	EACH	<b>C352</b>


## Wire Cutters

- ◆ Not suitable for cutting chain



Max Cutting Size (mm)	Unit	No
5	EACH	<b>C970</b>
6-8	EACH	<b>P63579</b>
10-12	EACH	<b>P63580</b>

## Presses & Tube Bending



- ◆ Bend Arc tube bender and dies
- ◆ Ring master hand & hydraulic power press, suitable for inox rings, headboard liners and all Sailman X boards

Description	Tube & Radius (inch)		Unit	No
Bend Arc Tube Bender	7/8	6	EACH	<b>C994</b>
Bend Arc Tube Bender	7/8	8	EACH	<b>C996B</b>
Bend Arc Die Only	7/8	6	EACH	<b>C996/6</b>
Bend Arc Die Only	7/8	8	EACH	<b>C996/8</b>
Bend Arc Die Only	7/8	10	EACH	<b>C996/10</b>
Bend Arc Die Only	7/8	12	EACH	<b>C996/12</b>
Bend Arc Tube Bender	1	8 & 10	EACH	<b>C997</b>
Bend Arc Die Only	1	6	EACH	<b>C997/6</b>
Bend Arc Die Only	1	8	EACH	<b>C997/8</b>
Bend Arc Die Only	1	12	EACH	<b>C997/12</b>
Bend Arc Clamp Only	7/8	-	EACH	<b>C996CLAMP</b>
Bend Arc Roller Only	7/8	-	EACH	<b>C996ROLLER</b>
Bend Arc Clamp Only	1	-	EACH	<b>C997CLAMP</b>
Bend Arc Roller Only	1	-	EACH	<b>C997ROLLER</b>
Crown Arc Tube Bender	3/4, 7/8, 1	-	EACH	<b>C998</b>
Ringmaster Hand Pumped Press	-	-	EACH	<b>C995</b>
Super Ringmaster Power Press	-	-	EACH	<b>C996</b>



## Gerber Multi Tool

- ◆ Needlenose pliers, fine edge blade, serrated edge blade, saw, phillips driver, small flat driver, medium driver, lanyard ring, bottle opener, can opener, scissors, Vcut wire cutters and ballistic nylon sheath.



Unit	No
EACH	GE01471

- ◆ Includes sailmakers palm, wax, tube of 10 needles and thread.

## Repair Kit



Type	Unit	No
Left Hand	EACH	C038L
Right Hand	EACH	C039

## On Board Repair Kit

- ◆ Sturdy zip holdall containing the following:
- ◆ 1x sailmakers palm
- ◆ 1x tube mixed sail needles
- ◆ 5m of 12mm lightweight webbing
- ◆ 5m of 25mm heavyweight webbing
- ◆ 10m of 100mm slit sailcloth
- ◆ 25m of white self-adhesive repair tape
- ◆ 1x roll double-sided tape
- ◆ 1x bench knife
- ◆ 2x awls
- ◆ 1 pair Fiskars stainless steel scissors
- ◆ 2x 30mm stainless steel rings
- ◆ Thread and whipping twine
- ◆ 2x pencils
- ◆ 20x pushpins



Unit	Pack Quantity	No
EACH	1	C980

## Shoreline Repair Kit

- ◆ Sturdy zip holdall containing the following:
- ◆ 1x sailmakers palm
- ◆ 1x tube mixed sail needles
- ◆ 2m of 12mm lightweight webbing
- ◆ 2m of 25mm heavyweight webbing
- ◆ 2m of 100mm slit sailcloth
- ◆ 5m of white self-adhesive repair tape
- ◆ 1x awl
- ◆ Spool waxed thread and spool waxed whipping twine



Unit	Pack Quantity	No
EACH	1	C981





## Dry Lubricants & Machine Oil

◆ High performance dry lubricant & machine oil

M401 / M402



M321 / M322



M301 / M305



M005



C063



C061



Type	Volume (ml)	Unit	No
Thread Lubricants	-	EACH	<b>C061</b>
Sewing Machine Oil	120	EACH	<b>C063</b>
Teflon Spray	312	EACH	<b>M005</b>
Thread Lubricants	950	EACH	<b>M301</b>
Thread Lubricants	950	EACH	<b>M305</b>
Sewing Machine Oil	950	EACH	<b>M321</b>
Sewing Machine Oil	3360	EACH	<b>M322</b>
Mclube Sailkote Spray	177	EACH	<b>M401</b>
Mclube Sailkote Spray	473	EACH	<b>M402</b>

## 303 UV Protectants

- ◆ 303 is excellent for preventative maintenance, with UV screen that reduces fading and degradation due to ozone, acid rain and weather
- ◆ 303 High Tech Fabric is advanced fluropolymers fabric treatment specifically developed for exterior applications.

M010



M012



M013



M020



Type	Size (ml)	Unit	No
UV Protectant	236	EACH	<b>M010</b>
UV Protectant	3800	EACH	<b>M012</b>
Fabric Guard	473	EACH	<b>M013</b>
Fabric Guard	3780	EACH	<b>M016</b>
Fabric Cleaner	946	EACH	<b>M020</b>

## Seam Sealers

- ◆ Weather resistant plastic coating to protect seams from abrasion
- ◆ Use on all types of outdoor fabrics: Tents / Backpacks / Awnings / Boat Tops & Sails

M216

M151 / M150



Size (ml)	Unit	No
3800	EACH	<b>M150</b>
18500	EACH	<b>M151</b>
118	EACH	<b>M216</b>





## 3M Spray Adhesive

- ◆ An extremely versatile spray adhesive that permits either a temporary or permanent bond with a new "low mist" formula.



Size (ml)	Unit	Pack Quantity	No
710	EACH	12	<b>J959</b>
500	EACH	12	<b>J959A</b>

## HH-66 Vinyl Cement

- ◆ HH-66 Vinyl Cement is a superior quality, fast drying adhesive. It is used extensively for bonding vinyl coated and vinyl laminated fabrics to themselves or to various materials.
- ◆ HH-66 is also used to bond urethanes, vinyl foams and films, rigid plastics, synthetic fabrics, wood, leather and metals.
- ◆ HH-66 dries quickly with a very strong, yet flexible bond.
- ◆ Application is by brush, roller, or squeeze bottle.



Size (ml)	Unit	No
236	EACH	<b>J969</b>
472	EACH	<b>J970</b>
945	EACH	<b>J971</b>



## Sail & Canvas Cleaner

- ◆ Biodegradable.
- ◆ Cleans and brightens whites and colours.
- ◆ Concentrated formula.
- ◆ Safe and easy to use.
- ◆ Removes dirt, grease and mildew stains from sails, canvas and fabrics
- ◆ Great for boat covers, bimini tops and sails.
- ◆ Does not weaken fabric or thread.
- ◆ Also cleans nylon or dacron sails.
- ◆ Brightens whites and colors



Volume (ml)	Unit	No
475	EACH	<b>SB82016</b>





## Fabsil Universal Cleaner



- ◆ Water-based and biodegradable
- ◆ Powerful deep cleaning, ideal preparation for re-proofing

Volume (ml)	Unit	No
300	EACH	<b>GRFAB01</b>

## Fabsil Gold



- ◆ Replicates the original water-repellent finish applied to outdoor products
- ◆ Versatile - works on any outdoor fabric
- ◆ Easy to use - can be painted or sprayed on

Volume (ml)	Unit	No
1000	EACH	<b>GRFAB13</b>
200	EACH	<b>GRFAB16</b>

## Fabsil UV Liquid



- ◆ Replicates the original water-repellent finish applied to outdoor products.
- ◆ Enhanced UV stability formula
- ◆ Versatile - works on any outdoor fabric.
- ◆ Easy to use - can be painted or sprayed on.

Volume (ml)	Unit	No
1000	EACH	<b>GRFAB05</b>
2500	EACH	<b>GRFAB06</b>
5000	EACH	<b>GRFAB07</b>

## Fabsil Beeswax Proofer



- ◆ Ideal for full-grain leather boots
- ◆ Produced using natural beeswax
- ◆ Protects against water, oil, and stains

Weight (g)	Unit	No
80	EACH	<b>GRFAB26</b>



## Fabsil Universal Protector

- ◆ The high performance silicone-based waterproofing has been trusted by professionals and outdoor enthusiasts for years
- ◆ By using it you can restore the waterproofing of any outdoor fabrics including boat covers.
- ◆ Spray-on application, saving time and energy



Volume (ml)	Unit	No
400	EACH	GRFAB03
600	EACH	GRFAB04

## Fabsil Wax Cotton Proofer

- ◆ Effectively restores the appearance of your waxed cotton clothing
- ◆ Refreshes and replenishes your clothing's water-repellent finish
- ◆ Spray-on application, saving time and energy



Volume (ml)	Unit	No
200	EACH	GRFAB35

## Fabsil Footwear Protection

- ◆ Removes dirt, oil, and stains
- ◆ Suitable for leather, suede, nubuck and synthetic footwear
- ◆ Contains a conditioning oil to help prolong the life of leather shoes
- ◆ Provides the ideal base for waterproofing treatments
- ◆ High-performance, silicone-based waterproofing
- ◆ Spray-on application, saving time and energy

GRFAB23



GRFAB24



GRFAB25



Volume (ml)	Unit	No
200	EACH	GRFAB23
200	EACH	GRFAB24
200	EACH	GRFAB25





## Window Polish & Cleaner



M171 / M181



M172



M173



- ◆ Window polish and cleaners made by Novus and IMAR
- ◆ Gently cleans all plastics without scratching
- ◆ Leaves a lustrous shine that resists fogging, repels dust and eliminates static
- ◆ Resists finger marking
- ◆ Contains no abrasives or harsh chemicals
- ◆ Leaves a smooth, clean and greaseless shine

M2214



M2224



Volume (ml)	Type	Unit	No
60	Window Polish	EACH	<b>M171</b>
60	Window Polish	EACH	<b>M172</b>
60	Window Polish	EACH	<b>M173</b>
236	Window Polish	EACH	<b>M181</b>
118	Strataglass Cleaner	EACH	<b>M2214</b>
118	Strataglass Polish	EACH	<b>M2224</b>

## Y10 Gelcoat Stain Remover



- ◆ Y-10 rapidly "absorbs" yellow/brown waterline and transom stains on white or light-coloured fibreglass boats
- ◆ Will not damage gelcoat
- ◆ Also effective against rust stains and may be used on painted boats

Weight (g)	Unit	Pack Quantity	No
340	PACK 6	1	<b>Q003035</b>

## Mould & Mildew Remover



- ◆ Removes mould, mildew, tough dirt and stains
- ◆ Use on fabric, vinyl, plastic, fibreglass and wood
- ◆ Colour safe
- ◆ Gentle to skin, no harmful vapours
- ◆ Just add water to the biodegradable non toxic, non chlorine powder
- ◆ 1 x 340g makes 11 litres of solution

Weight (g)	Unit	No
340	EACH	<b>M212</b>





## Dickson TEX'AKTIV Clean

- ◆ Recommended for all sunbrella fabrics
- ◆ Dickson TEX'AKTIV CLEAN removes stains and eliminates bad odours on marine fabrics.
- ◆ Deep-acting powerful stain-remover
- ◆ Works well on deck chairs, cushions and all marine covers such as biminis & sprayhoods



Volume (ml)	Unit	No
1000	EACH	<b>SUNTEX003</b>
5000	EACH	<b>SUNTEX004</b>

## Dickson TEX'AKTIV Guard

- ◆ Recommended for all sunbrella fabrics
- ◆ Dickson TEX'AKTIV GUARD protects fabric from dirt and stains Acts as a fabric water-proofer and is perfect for use on marine, outdoor furniture and solar protection fabrics
- ◆ It prevents grease and water from penetrating into the fabric. Its colourless beading effect preserves and restores your outdoor fabric's original beauty



Volume (ml)	Unit	No
1000	EACH	<b>SUNTEX001</b>
5000	EACH	<b>SUNTEX002</b>



## YKK - Zippy Cool

- ◆ Remove harmful dirt, sand, and salt deposits great for marine zippers
- ◆ Zippy Cool will effectively clean and lubricate all types of metal, coil, and plastic zippers
- ◆ **Kit Contains:**
- ◆ 2oz Zippy Cool fluid
- ◆ 0.5oz Zippy Cool Stick

M031

M032



Unit	No
KIT	<b>M030</b>
EACH	<b>M031</b>
EACH	<b>M032</b>





## Boat Cleaner

SB83222

SB83200



- ◆ Spray on, rinse off to clean vinyl, fibreglass, plastic, metal or painted surfaces
- ◆ Ideal for cleaning spills, fish blood, grease spots, footprints and more

Volume (ml)	Unit	No
3790	EACH	<b>SB83200</b>
650	EACH	<b>SB83222</b>

## Boat Cover Cleaner



- ◆ Keeps your covers looking beautiful all year long
- ◆ Removes dirt and stains from boat covers, tarpaulins, biminis etc

Volume (ml)	Unit	No
650	EACH	<b>SB92122</b>

## Boat Cover Waterproofing

SB81922

SB81900



- ◆ For boat covers, bimini tops, sail covers, clothing and tents.
- ◆ Does not change the color or feel of the fabric
- ◆ Waterproofing is safe for all marine fabrics, including Sunbrella acrylic

Volume (ml)	Unit	No
3790	EACH	<b>SB81900</b>
650	EACH	<b>SB81922</b>



## Black Streak Remover

- ◆ Quickly removes black streaks caused by water run off
- ◆ Safe for use on fibreglass, metal and painted surfaces
- ◆ Will not remove wax or polish
- ◆ Spray directly onto black streaks and wipe off; no hard scrubbing needed
- ◆ Hundreds of uses; will instantly remove stains and marks on boats, cars, caravans and around the house

SB71622



SB71600



SB71664



Volume (ml)	Unit	No
650	EACH	<b>SB71622</b>
1890	EACH	<b>SB71664</b>
3790	EACH	<b>SB71600</b>

## Bird Stain Remover

- ◆ Quickly dissolves messy spider and bird droppings
- ◆ Non-toxic, all-natural formula
- ◆ Contains no bleach; safe for use around children and pets.
- ◆ Will not remove polish or wax
- ◆ Safe for all marine surfaces and fabrics



Volume (ml)	Unit	No
650	EACH	<b>SB95122</b>

## Bug Off

- ◆ Quickly removes insects and road film from glass, paint, plastic and metal
- ◆ No hard rubbing or scrubbing required
- ◆ Does not remove waxes or polishes
- ◆ Convenient spray-on, wipe off application



Volume (ml)	Unit	No
650	EACH	<b>SB92722</b>



## Mildew Stain Remover

SB85616



SB85600



- ◆ Removes mildew stains on contact without heavy scrubbing
- ◆ Special buffered formula will not harm vinyl upholstery or thread
- ◆ Safe for use on fibreglass, painted surfaces, rubber, plastic and vinyl headliners, bolsters and upholstery
- ◆ Does not weaken fabric or thread

Volume (ml)	Unit	No
600	EACH	<b>SB85616</b>
3790	EACH	<b>SB85600</b>

## Plastic Scratch Remover



- ◆ Restores hazy or yellowed clear plastic enclosures
- ◆ Removes fine scratches from acrylic, polycarbonate and most other types of plastic surfaces
- ◆ Cleans off stains, salt deposits and surface discolouration
- ◆ Use as the first step in the restoration of deteriorated plastic

Volume (ml)	Unit	No
475	EACH	<b>SB82016</b>

## Plastic Polish Restorer



- ◆ Restores shine and clarity to acrylic, polycarbonate and most other types of plastic surfaces
- ◆ Adds UV protection to all clear plastic surfaces
- ◆ Use as the second step in the restoration of deteriorated plastic

Volume (ml)	Unit	No
236	EACH	<b>SB87308</b>



## Rain View

- ◆ Improves wet weather visibility through windshield and windows
- ◆ Use on glass
- ◆ Works with or without windshield wipers
- ◆ Makes surface so slick that rain and wet weather deposits literally slide off
- ◆ High-Tech Formula



Volume (ml)	Unit	No
237	EACH	SB88708

## Sea-Safe Waterproofing

- ◆ Unique formula is lake and reservoir safe; can be applied while boat is in or near the water
- ◆ Ideal for use on foul weather gear, tents, tarps and other outdoor gear
- ◆ Unique biodegradable bottle helps reduce landfill overcrowding
- ◆ Protects new fabrics, adds years to service life
- ◆ Will not affect colours or the feel of fabric



Volume (ml)	Unit	No
650	EACH	SB89755

## Slime & Grime Stain Remover

- ◆ Removes mould stains and mildew stains, rust, tarnish and other tough stains quickly
- ◆ Works on boat bottoms, shower stalls, floor tiles, fibreglass, wood, aluminium, cement, non-skid decks and metal surfaces
- ◆ Concentrated powder formula



Weight (g)	Unit	No
500	EACH	SB94816

## Snap & Zipper Lubricant

- ◆ Apply to boat snaps, metal and plastic zippers to protect against corrosion, reduce wear and friction, prevent binding and repel salt spray deposits
- ◆ Non-toxic, non-staining
- ◆ Will not wash off



Weight (g)	Unit	No
56	EACH	SB89102





## Spider Away



- ◆ Keeps messy spiders away from your boat
- ◆ Safe for use around pets and children
- ◆ Ideal for use on docks, boathouses, homes, garages, etc.

Volume (ml)	Unit	No
650	EACH	<b>SB95022</b>

## View Guard



- ◆ Repels water to enhance wet weather visibility
- ◆ Repels water, spray, salt & dirt

Volume (ml)	Unit	No
650	EACH	<b>SB95222</b>

## Vinyl Brite

SB80316

SB80308



- ◆ Protects and moisturises vinyl, rubber and plastic surfaces
- ◆ Keeps new vinyl looking good, adds shine to old vinyl
- ◆ Spray on, wipe up excess, ideal for car interiors & tyres

Volume (ml)	Unit	No
237	EACH	<b>SB80308</b>
473	EACH	<b>SB80316</b>

## Vinyl Shampoo



- ◆ Quickly removes dirt, stains and grease
- ◆ Gets out deeply embedded grime
- ◆ Excellent for all interior and exterior vinyl
- ◆ Restores original bright, fresh colour
- ◆ Contains no harsh chemicals
- ◆ Cleans all vinyl surfaces

Volume (ml)	Unit	No
500	EACH	<b>SB80216</b>






## Jib Reefing

The Plastimo jib reefing range stems from 50 years of expertise in high-pressure injection and composite materials engineering for 4 to 11-metre boats, our headsail reefing meets the needs of all yachtsmen, whether experienced sailors or beginners. Very easy to use and virtually maintenance free, the Plastimo jib reefing is a reliable crew member which contributes to your sailing performance.

## Selecting your Plastimo jib reefing

The S-series jib reefing features a single groove spar (S for "single"). Its patented assembly system allows for very easy installation with no need to un-step the existing forestay.

The T-series jib reefing features a twin groove spar (T for "twin"). It allows the use of the jib reefing on a hollow forestay when racing, or the setting of twin head sails, to avoid hoisting the spinnaker.



## Chainplates or Turnbuckle

Most sailing boats are equipped with chainplates to fasten the forestay to the stem fitting. Chainplates come with several holes which facilitates the adjustment of the standing rigging. The use of chainplates also allows to position the tack point as low as possible.

The turnbuckle version allows for more accurate rigging adjustments. However, the tack point will have to be positioned slightly higher depending on the turnbuckle size.


## Which jib reefing size for my boat?

Plastimo proposes 3 models to fit all sailboats from 4 to 11 metres. While the boat length is important, you must also consider the forestay diameter and the headsail size. For example, in the case of a 6-metre boat, the 406 model will offer the best compromise. However, if the headsail size is much larger than the maximum sail area recommended, selecting a 609 model is a better option.



## 406 Jib Reefing

- ◆ Lightweight and sturdy, the 406 jib reefing features all the benefits of a large headsail reefing system : 2 Delrin® twin ball bearing races in both drum and halyard swivel.
- ◆ All components are manufactured from polyamide.



Version	Forestay Diameter (mm)	Max Headsail Size (m <sup>2</sup> )	Luffrope Diameter (mm)	Drum Sheet Capacity (m)	Part No
406-S Chainplates	4-7	12	6.5	7	<b>P25722</b>
406-S Turnbuckle	4-7	12	6.5	7	<b>P25723</b>
406-T Chainplates	4-7	12	5	7	<b>P25200</b>
406-T Turnbuckle	4-7	12	5	7	<b>P25286</b>

Specifications shown are from manufacturers data

## 609 Jib Reefing

The 609 drum cheeks swivel through 360°, ensuring safe manoeuvres through a smooth and regular feeding of the reefing line. These cheeks protect the reefing drum efficiently and the round unobtrusive design, combined with recessed screws, allow the free running of the ropes. Reefing drum features highly resistant stainless steel and Delrin® ball bearings. Halyard swivel features Teflon® and Delrin® ball bearings which enhances the overall performance and increases the mechanical resistance. Chainplates width is adjustable.



Version	Forestay Diameter (mm)	Max Headsail Size (m <sup>2</sup> )	Luffrope Diameter (mm)	Drum Sheet Capacity (m)	Part No
609-S Chainplates	4-7	25	6.5	13	<b>P58202</b>
609-S Turnbuckle	4-7	25	6.5	13	<b>P58203</b>
609-T Chainplates	4-7	25	5	13	<b>P58207</b>
609-T Turnbuckle	4-7	25	5	13	<b>P58208</b>

Specifications shown are from manufacturers data


## 811 Jib Reefing

The 811 drum cheeks swivel through 360°, ensuring safe manoeuvres through a regular feeding of the reefing line. The drum core is manufactured from highly resistant aluminium combining performance and lightweight features. Drum and halyard swivel are equipped with Torlon® and Delrin® ball bearings for increased performance and mechanical resistance. 811 model comes as standard with adjustable chain plates



Version	Forestay Diameter (mm)	Max Headsail Size (m²)	Luffrope Diameter (mm)	Drum Sheet Capacity (m)	Part No
811-S	4-7	35	5	17.5	<b>P58204</b>
811-T	4-7	35	5	17.5	<b>P58209</b>

Specifications shown are from manufacturers data



## Additional Packages

	Description	406-S	406-T	609-S	609-T	811-S	811-T	Part No
Spar Package	1.5m includes: 1x alloy spar, 1x plastic spar, 1 quick-coupling sleeve with screws	✓	-	✓	-	✓	-	<b>P26901</b>
	2.15m includes: 1x alloy spar, 1x quick-coupling sleeve with screws	-	✓	-	✓	-	✓	<b>P26902</b>
Blocks and Sheets Package	Includes: 12.50m pre-stretched sheet, 3 blocks for 25m stanchion	✓	✓	-	-	-	-	<b>P17069</b>
	Includes: 20m pre-stretched sheet, 4 blocks for 25mm stanchion	-	-	✓	✓	✓	✓	<b>P17071</b>

## Accessories



P25884



P25720




P26140 / 25677

Description	406-S	406-T	609-S	609-T	811-S	811-T	Part No
Rope Pre-Feeder	-	✓	-	✓	-	✓	<b>P25884</b>
Halyard Diverter Wheel	✓	✓	✓	✓	✓	✓	<b>P25720</b>
Stainless Steel Halyard Feeder	✓	✓	-	-	-	-	<b>P26140</b>
	-	-	✓	✓	✓	✓	<b>P25677</b>

## Replacement Parts

	406-S	406-T	609-S	609-T	811-S	811-T
A	<b>P25752</b>	<b>P25184</b>	<b>P25752</b>	<b>P25184</b>	<b>P25752</b>	<b>P25184</b>
B+C	<b>P26901</b>	<b>P26902</b>	<b>P26901</b>	<b>P26902</b>	<b>P26901</b>	<b>P26902</b>
C (x7)	<b>P55979</b>	<b>P55980</b>	<b>P55979</b>	<b>P55980</b>	<b>P55979</b>	<b>P55980</b>
L + N + J	<b>P55977</b>	<b>P55978</b>	<b>P55977</b>	<b>P55978</b>	<b>P55977</b>	<b>P55978</b>
I	<b>P17067</b>	<b>P17067</b>	<b>P58248</b>	<b>P58248</b>	<b>P58248</b>	<b>P58248</b>
D	<b>P10001</b>	<b>P10001</b>	-	-	<b>P58249</b>	<b>P58249</b>
E	-	-	<b>P58245</b>	<b>P58245</b>	-	-
G + H + K	<b>P55975</b>	<b>P55976</b>	<b>P55975</b>	<b>P55976</b>	<b>P55975</b>	<b>P55976</b>
F (5 holes)	<b>P26325</b>	<b>P26325</b>	<b>P21291</b>	<b>P21291</b>	<b>P22850</b>	<b>P22850</b>
F (11 holes)	-	-	<b>P21295</b>	<b>P21295</b>	-	-
M (x1)	<b>P26179</b>	-	<b>P26179</b>	-	<b>P26179</b>	-



## Super 12

- ◆ Heat-treated 12 strand single braid UHMwPE rope with polyurethane coating
- ◆ This rope is designed for high load applications where ultra-low stretch is required
- ◆ Floats and is Hydrophobic
- ◆ Low Creep
- ◆ Easy to splice
- ◆ Highly resistant to UV and most chemicals
- ◆ Internal and external abrasion resistance
- ◆ Applications: Strops, purchase systems, runner tails and control lines



Available Colour - xx	Colour
<b>B</b>	Blue
<b>R</b>	Red
<b>G</b>	Grey
<b>Y</b>	Yellow
<b>FY</b>	Flo Yellow

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
2	880	Blue, Green, Red, Yellow	REEL 100M	<b>SRSUP1202x</b>
3.5	1700	Blue, Flo Yellow, Grey, Red, Yellow	REEL 100M	<b>SRSUP12035xx</b>
3	1300	Blue, Flo Yellow, Grey, Red, Yellow	REEL 100M	<b>SRSUP1203xx</b>
4	2220	Blue, Grey, Red, Yellow	REEL 100M	<b>SRSUP1204x</b>
5	3100	Blue, Grey, Red	REEL 100M	<b>SRSUP1205x</b>
6	3900	Blue, Grey, Red	REEL 100M	<b>SRSUP1206x</b>
7	5300	Blue, Grey, Red	REEL 100M	<b>SRSUP1207x</b>
8	6660	Blue, Grey, Red	REEL 100M	<b>SRSUP1208x</b>
9	8400	Blue, Grey, Red	REEL 100M	<b>SRSUP1209x</b>
10	9700	Blue, Grey, Red	REEL 100M	<b>SRSUP1210x</b>
11	11,500	Grey	REEL 100M	<b>SRSUP1211G</b>
12	12.6	Black, Grey	REEL 100M	<b>SRSUP1212xx</b>
14	17,600	Grey	REEL 100M	<b>SRSUP1214G</b>
16	21,300	Grey	REEL 100M	<b>SRSUP1216G</b>
18	30,000	Grey	REEL 100M	<b>SRSUP1218G</b>
20	40,000	Grey	REEL 100M	<b>SRSUP1220G</b>
22	-	Grey	REEL 100M	<b>SRSUP1222G</b>
24	-	Grey	REEL 100M	<b>SRSUP1224G</b>





## Super T Braid



- ◆ Cover: Technora / HT Polyester
- ◆ Core: Super 12, 12 strand UHMwPE yarn
- ◆ Construction: Braid on braid
- ◆ Durable on the winch and in blocks
- ◆ 500°C decomposition temperature of Technora®
- ◆ Applications: Halyards, reefing lines, control lines, sheets and traveller lines

Available Colour - xxxx	Colour
<b>GRBK</b>	Grey/Charcoal
<b>GRG</b>	Green/Charcoal
<b>GRR</b>	Red/Charcoal
<b>Y</b>	Yellow/Charcoal
<b>BC</b>	Blue/Charcoal
<b>GRG</b>	Green/Gold
<b>BG</b>	Blue/Gold

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
6	1770	Grey/Black, Grey/Green, Grey/Red, Grey/Yellow	REEL 100M	<b>SRSTPB06xxxx</b>
8	3990	Grey/Black, Grey/Green, Grey/Red, Grey/Yellow	REEL 100M	<b>SRSTPB08xxxx</b>
10	6660	Grey/Black, Grey/Green, Grey/Red, Grey/Yellow	REEL 100M	<b>SRSTPB10xxxx</b>
12	9760	Grey/Black, Grey/Green, Grey/Red, Grey/Yellow	REEL 100M	<b>SRSTPB12xxxx</b>
14	12,600	Grey/Black, Grey/Green, Grey/Red, Grey/Yellow	REEL 100M	<b>SRSTPB14xxxx</b>
16	17,640	Grey/Black, Grey/Green, Grey/Red, Grey/Yellow	REEL 100M	<b>SRSTPB16xxxx</b>
18	21,380	Grey/Black, Grey/Green, Grey/Red, Grey/Yellow	REEL 100M	<b>SRSTPB18xxxx</b>

## Super TW Braid



- ◆ Cover: Technora & HT Polyester
- ◆ Core: Super 12, 12 strand single braid UHMwPE
- ◆ Construction: Braid on braid
- ◆ Very high abrasion qualities
- ◆ 500°C decomposition temperature of Technora®
- ◆ Applications: Halyards, reefing lines, control lines, sheets and traveller lines

Available Colour - xx	Colour
<b>G</b>	Green
<b>R</b>	Red
<b>Y</b>	Yellow

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
2	-	Green, Red, Yellow	REEL 100M	<b>SRSTW02xx</b>
3	-	Green, Red, Yellow	REEL 100M	<b>SRSTW03xx</b>
4	-	Green, Red, Yellow	REEL 100M	<b>SRSTW04xx</b>
5	-	Green, Red, Yellow	REEL 100M	<b>SRSTW05xx</b>
6	1770	Green, Red, Yellow	REEL 100M	<b>SRSTW06xx</b>
8	3990	Green, Red, Yellow	REEL 100M	<b>SRSTW08xx</b>
10	6660	Green, Red, Yellow	REEL 100M	<b>SRSTW10xx</b>
12	9760	Green, Red, Yellow	REEL 100M	<b>SRSTW12xx</b>
14	12,600	Green, Red, Yellow	REEL 100M	<b>SRSTW14xx</b>
16	17,640	Green, Red, Yellow	REEL 100M	<b>SRSTW16xx</b>
18	21,380	Green, Red, Yellow	REEL 100M	<b>SRSTW18xx</b>

# Super Braid

- ◆ Cover: HT Polyester
- ◆ Core: Super 12, 12 strand UHMwPE yarn
- ◆ Construction: Braid on braid
- ◆ Applications: Strops, halyards, sheets, purchase systems, runner tails



## Solid Colours

Available Colour - xx	Colour
<b>GR</b>	Grey
<b>BK</b>	Black
<b>W</b>	White
<b>B</b>	Beige
<b>N</b>	Navy

## Mottled Colours

Available Colour - xx	Colour
<b>B</b>	Blue
<b>G</b>	Green
<b>R</b>	Red
<b>Y</b>	Yellow
<b>BK</b>	Black

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
2	-	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSUPB02xx</b>
3	-	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSUPB03xx</b>
4	-	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSUPB04xx</b>
5	-	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB05xx</b>
6	1,770	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB06xx</b>
7	3,100	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB07xx</b>
8	3,990	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB08xx</b>
9	5,320	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB09xx</b>
10	6,660	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB10xx</b>
12	9,760	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB12xx</b>
14	12,600	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB14xx</b>
16	17,640	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB16xx</b>
18	21,380	Blue, Black, Green, Red, Grey Cover, Yellow	REEL 100M	<b>SRSUPB18xx</b>
20	25,340	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB20xx</b>
22	30,090	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB22xx</b>
24	35,640	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRSUPB24xx</b>

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
4	-	Black, Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB04xx</b>
5	-	Black, Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB05xx</b>
6	1770	Black, Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB06xx</b>
7	3100	Black, Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB07xx</b>
8	3,990	Black, Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB08xx</b>
9	5,320	Black, Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB09xx</b>
10	6,660	Black, Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB10xx</b>
12	9760	Black, Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB12xx</b>
14	12,600	Black, Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB14xx</b>
16	17,640	Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB16xx</b>
18	21,380	Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB18xx</b>
20	25,340	Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB20xx</b>
22	30,090	Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB22xx</b>
24	35,640	Beige, Grey, Navy, White	REEL 100M	<b>SRSUPSB24xx</b>



## Super Speed



- ◆ Cover: HT Polyester
- ◆ Core: 12 strand UHMwPE yarn
- ◆ Construction: Braid on braid
- ◆ Lightweight
- ◆ Low Creep
- ◆ UV resistance core
- ◆ HT Polyester sheath prevents block and jammer slippage
- ◆ Good for cruising yachts
- ◆ Applications: Halyards, reefing lines, control lines, sheets and travellers lines

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
2	-	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSPB02xx</b>
3	-	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSPB03xx</b>
4	600	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSPB04xx</b>
6	1,300	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSPB06xx</b>
8	3,000	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSPB08xx</b>
10	5,300	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSPB10xx</b>
12	7,000	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRSPB12xx</b>

## Vectran Braid



- ◆ Cover: 100% HT Polyester
- ◆ Core: 12 strand single braid Vectran
- ◆ Construction: Braid on braid
- ◆ Durable on the winch and in blocks
- ◆ HT Polyester sheath prevents block and jammer slippage
- ◆ Applications: Halyards, checkstays, runner tails, kickers/Vangs/Vangs and strops

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
2	-	White	REEL 100M	<b>SRVB02W</b>
3	-	White	REEL 100M	<b>SRVB03W</b>
4	-	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRVB04xx</b>
5	-	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRVB05xx</b>
6	-	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRVB06xx</b>
8	3650	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRVB08xx</b>
10	5840	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRVB10xx</b>
12	7500	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRVB12xx</b>
14	10,100	Blue, Black, Green, Red, Yellow	REEL 100M	<b>SRVB14xx</b>
16	11,950	Blue, Black, Green, Red, White, Yellow	REEL 100M	<b>SRVB16xx</b>

## YachtMaster

- ◆ Cover: HT Polyester
- ◆ Core: HT Polyester braid
- ◆ Construction: Braid on braid
- ◆ High tenacity and high abrasion resistance
- ◆ High UV resistance
- ◆ Applications: Halyards, reefing lines, control lines, sheets and travellers lines



### Solid Colours

Available Colour - xx	Colour
<b>BE</b>	Beige
<b>BK</b>	Black
<b>G</b>	Green
<b>P</b>	Purple
<b>PK</b>	Pink
<b>R</b>	Red
<b>W</b>	White
<b>Y</b>	Yellow

### White with Fleck

Available Colour - xx	Colour
<b>B</b>	White/Blue
<b>BK</b>	White/Black
<b>G</b>	White/Green
<b>R</b>	White/Red
<b>Y</b>	White/Yellow

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
6	-	White/Blue, White/Black, White/Green, White/Red, White/Yellow	REEL 100M	<b>SRRB06xx</b>
6	-	Beige, Black, Green, Purple, Pink, Red, White, Yellow	REEL 100M	<b>SRRBS06xx</b>
8	1,700	White/Blue, White/Black, White/Green, White/Red, White/Yellow	REEL 100M	<b>SRRB08xx</b>
8	1,700	Blue, Beige, Black, Green, Navy, Red, White, Yellow	REEL 100M	<b>SRRBS08xx</b>
10	2,350	White/Blue, White/Black, White/Green, White/Red, White/Yellow	REEL 100M	<b>SRRB10xx</b>
10	2,350	Blue, Beige, Black, Green, Navy, Red, White, Yellow	REEL 100M	<b>SRRBS10xx</b>
12	3,250	White/Blue, White/Green, White/Red, White/Yellow	REEL 100M	<b>SRRB12xx</b>
12	3,250	Blue, Beige, Black, Green, Navy, Red, White, Yellow	REEL 100M	<b>SRRBS12xx</b>
14	4,200	White/Blue, White/Black, White/Green, White/Red, White/Yellow	REEL 100M	<b>SRRB14xx</b>
14	4,200	Blue, Beige, Black, Green, Navy, Red, White, Yellow	REEL 100M	<b>SRRBS14xx</b>
16	5,600	White/Blue, White/Green, White/Red, White/Yellow	REEL 100M	<b>SRRB16xx</b>
16	5,600	Blue, Beige, Black, Green, Red, White, Yellow	REEL 100M	<b>SRRBS16xx</b>
18	7,800	White/Blue, White/Green, White/Red, White/Yellow	REEL 100M	<b>SRRB18xx</b>
18	7,800	Blue, Beige, Black, Green, Red, White, Yellow	REEL 100M	<b>SRRBS18xx</b>
20	-	White/Blue, White/Green, White/Red, White/Yellow	REEL 100M	<b>SRRB20xx</b>
20	-	Blue, Beige, Black, Green, Red, White, Yellow	REEL 100M	<b>SRRBS20xx</b>
22	-	Blue, Beige, Black, Green, Red, White, Yellow	REEL 100M	<b>SRRBS22xx</b>
24	-	White/Blue, White/Green, White/Red, White/Yellow	REEL 100M	<b>SRRB24xx</b>
24	-	Blue, Beige, Black, Green, Red, White, Yellow	REEL 100M	<b>SRRBS24xx</b>



# Super Lite



- ◆ Cover: HT Polyester
- ◆ Core: HT Polyester / UHMwPE parallel yarns
- ◆ Construction: Braid on braid
- ◆ Lightweight
- ◆ Applications: Halyards, sheets, control lines, outhaul, downhauls, and kickers/Vangs

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
2	-	Blue / Yellow	REEL 100M	<b>SRDL02BY</b>
2	-	Blue / Yellow / Green	REEL 100M	<b>SRDL02BYG</b>
2	-	Orange / Purple / Green	REEL 100M	<b>SRDL020PG</b>
2	-	Purple / Green / Orange	REEL 100M	<b>SRDL02PGO</b>
2	-	White / Purple / Orange	REEL 100M	<b>SRDL02WPO</b>
2	-	Yellow / Blue	REEL 100M	<b>SRDL02YB</b>
3	175	Blue / Yellow	REEL 100M	<b>SRDL03BY</b>
3	175	Blue / Yellow / Green	REEL 100M	<b>SRDL03BYG</b>
3	175	Orange / Purple / Green	REEL 100M	<b>SRDL030PG</b>
3	175	Purple / Green / Orange	REEL 100M	<b>SRDL03PGO</b>
3	175	White / Purple / Yellow	REEL 100M	<b>SRDL03WPY</b>
3	175	Yellow / Blue	REEL 100M	<b>SRDL03YB</b>
4	300	Blue / Yellow	REEL 100M	<b>SRDL04BY</b>
4	300	Blue / Yellow / Green	REEL 100M	<b>SRDL04BYG</b>
4	300	Orange / Purple / Green	REEL 100M	<b>SRDL040PG</b>
4	300	Purple / Green / Orange	REEL 100M	<b>SRDL04PGO</b>
4	300	White / Purple / Yellow	REEL 100M	<b>SRDL04WPY</b>
4	300	Yellow / Blue	REEL 100M	<b>SRDL04YB</b>
5	450	Blue / Yellow	REEL 100M	<b>SRDL05BY</b>
5	450	Blue / Yellow / Green	REEL 100M	<b>SRDL05BYG</b>
5	450	Orange / Purple / Green	REEL 100M	<b>SRDL050PG</b>
5	450	Purple / Green / Orange	REEL 100M	<b>SRDL05PGO</b>
5	450	White / Purple / Yellow	REEL 100M	<b>SRDL05WPY</b>
5	450	Yellow / Blue	REEL 100M	<b>SRDL05YB</b>
6	500	Blue / Yellow	REEL 100M	<b>SRDL06BY</b>
6	500	Blue / Yellow / Green	REEL 100M	<b>SRDL06BYG</b>
6	500	Orange / Purple / Green	REEL 100M	<b>SRDL060PG</b>
6	500	Purple / Green / Orange	REEL 100M	<b>SRDL06PGO</b>
6	500	White / Purple / Yellow	REEL 100M	<b>SRDL06WPY</b>
6	500	Yellow / Blue	REEL 100M	<b>SRDL06YB</b>

## Laser Line

- ◆ Cover: 16 plait Multi-filament polypropylene
- ◆ Core: HT Polyester
- ◆ Construction: Braid on braid
- ◆ Limited water absorption
- ◆ Applications: Control lines and general applications where stretch is not critical



Available Colour - xx	Colour
<b>B</b>	Blue
<b>BK</b>	Black
<b>L</b>	Lime
<b>P</b>	Purple
<b>R</b>	Red
<b>W</b>	White
<b>Y</b>	Yellow

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
2	120	Blue, Red, White, Yellow	REEL 100M	<b>SRLL02B</b>
3	250	Blue, Red, White, Yellow	REEL 100M	<b>SRLL03B</b>
4	375	Blue, Purple, Red, White, Yellow	REEL 100M	<b>SRLL04B</b>
5	490	Blue, Black, Lime, Purple, Red, White, Yellow	REEL 100M	<b>SRLL05B</b>
6	585	Blue, Lime, Purple, Red, Yellow	REEL 100M	<b>SRLL06B</b>

## Marstrand

- ◆ Cover: Multi-filament polypropylene
- ◆ Core: Multi-filament polypropylene
- ◆ Construction: 8 plait 16 plait
- ◆ Hydrophobic
- ◆ UV resistant
- ◆ Applications: Sheets and rescue lines



Available Colour - xx	Colour
<b>BK</b>	Black
<b>W</b>	White

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
5	2,100	Black, White	REEL 100M	<b>SRMAR08P05xx</b>
6	3,360	Black, White	REEL 100M	<b>SRMAR08P06xx</b>
7	-	Black, White	REEL 100M	<b>SRMAR08P07xx</b>
8	7,680	Black, White	REEL 100M	<b>SRMAR08P08xx</b>
9	-	Black, White	REEL 100M	<b>SRMAR08P09xx</b>
10	-	Black, White	REEL 100M	<b>SRMAR08P10xx</b>



## Sheetline (ZS75)



- ◆ Cover: HT Polyester + spun HT Polyester
- ◆ Core: 12 strand UHMwPE
- ◆ Construction: braid on braid
- ◆ Hard wearing HT Polyester cover
- ◆ Applications: Laser mainsheet

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
6	720	Black	REEL 100M	<b>SRZS7506BK</b>
6	720	Blue	REEL 100M	<b>SRZS7506BL</b>
6	720	Red	REEL 100M	<b>SRZS7506R</b>

## Sheetline (ZS75 Lite)



- ◆ Cover: Multifilament + spun HT Polyester
- ◆ Core: 12 strand UHMwPE
- ◆ Construction: braid on braid
- ◆ Non-absorbent
- ◆ Floats
- ◆ Applications: Extreme lightweight mainsheet

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
5.5	720	Yellow	REEL 100M	<b>SRZS75L55Y</b>





## XD-Lite

- ◆ Cover: HT Polyester
- ◆ Core: 12 strand UHMwPE
- ◆ Construction: braid on braid
- ◆ Non-rotating
- ◆ Non-locking
- ◆ Applications: Lengthy mainsheet



Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
6.5	860	Blue / Yellow	REEL 100M	<b>SRXDL65BY</b>

## Vecklock

- ◆ Cover: HT 8 plait HT Polyester
- ◆ Core: Vectran
- ◆ Construction: braid on braid
- ◆ Low creep
- ◆ Abrasion resistant
- ◆ Applications: Control lines, sheets, halyards and rope that is under constant tension



Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
4	350	Blue / Black / Yellow	REEL 100M	<b>SRVL04BBY</b>
4	350	Red / Blue / Yellow	REEL 100M	<b>SRVL04RBY</b>



## Polylock



- ◆ Cover: 8-plait HT Polyester
- ◆ Core: HT Polyester
- ◆ Construction: braid on braid
- ◆ Limited water absorption
- ◆ Abrasion Resistant
- ◆ Applications: Halyards, sheets, control lines, outhaul, downhauls and kickers/Vangs

Available Colour - xx	Colour
<b>BL</b>	Blue
<b>R</b>	Red
<b>W</b>	White
<b>Y</b>	Yellow
<b>BKR</b>	Black/Red
<b>BL/BK/W</b>	Blue/Black/White
<b>GR/BK/W</b>	Green/Black/White
<b>R/BK/W</b>	Red/Black/White
<b>W/BL</b>	White Blue
<b>W/O</b>	White/Orange
<b>W/R</b>	White/Red
<b>W/Y</b>	White/Yellow

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
3	-	Blue, Red, White, Yellow	REEL 100M	<b>SRPL03xx</b>
4	360	Black/Red, Blue, Blue/Black/White, Green/Black/White, Red, Red/Black/White, White, Yellow	REEL 100M	<b>SRPL04xx</b>
5	590	Blue, Blue/Black/White, Green/Black/White, Red, Red/Black/White, White, White/Blue, White/Orange, White/Red, White/Yellow	REEL 100M	<b>SRPL05xx</b>
6	780	Blue, Black/Red, Blue/Black/White	REEL 100M	<b>SRPL06xx</b>

## 3 Strand Nylon



- ◆ Material: Nylon
- ◆ Construction: 3 strand
- ◆ Sinking rope
- ◆ Excellent stretch and recovery
- ◆ Applications: Anchor warps, mooring lines, towing lines, fishing lines, kinetic ropes

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
4	-	White	REEL 100M	<b>SRPA304</b>
5	-	White	REEL 100M	<b>SRPA305</b>
6	750	White	REEL 100M	<b>SRPA306</b>
8	1,350	White	REEL 100M	<b>SRPA308</b>
10	2,080	White	REEL 100M	<b>SRPA310</b>
12	3,000	White	REEL 100M	<b>SRPA312</b>
16	5,300	White	REEL 100M	<b>SRPA316</b>
18	6,700	White	REEL 100M	<b>SRPA318</b>
20	8,300	White	REEL 100M	<b>SRPA320</b>
22	10,000	White	REEL 100M	<b>SRPA322</b>
24	12,000	White	REEL 100M	<b>SRPA324</b>



## 3 Strand HT Polyester

- ◆ Material: HT Polyester
- ◆ Construction: 3 strand
- ◆ Strength not affected by water
- ◆ Does not shrink
- ◆ UV resistant
- ◆ Abrasion resistant
- ◆ Sinking rope
- ◆ Applications: Anchor lines, mooring lines, lanyards, fender lines, towing lines, net frame ropes and general purpose industrial ropes



Available Colour - xx	Colour
<b>BE</b>	Beige
<b>BK</b>	Black
<b>BUR</b>	Burgundy
<b>DG</b>	Dark Green
<b>N</b>	Navy
<b>R</b>	Red
<b>W</b>	White

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
4	-	Black, Navy, Red, White	REEL 100M	<b>SRPS304xx</b>
5	-	Black, Navy, White	REEL 100M	<b>SRPS305xx</b>
6	850	Beige, Black, Navy, Red, White	REEL 100M	<b>SRPS306xx</b>
8	1,450	Beige, Black, Burgundy, Dark Green, Navy, Red, White	REEL 100M	<b>SRPS308xx</b>
10	2,290	Beige, Black, Burgundy, Dark Green, Navy, Red, White	REEL 100M	<b>SRPS310xx</b>
12	3,450	Beige, Black, Bugundy, Dark Green, Navy, Red, White, Beige	REEL 100M	<b>SRPS312xx</b>
14	4,400	Beige, Black, Bugundy, Dark Green, Navy, Red, White, Beige	REEL 100M	<b>SRPS314xx</b>
16	6000	Black, Burgundy, Dark Green, Navy, White	REEL 100M	<b>SRPS316xx</b>
18	7,000	Beige, Black, Navy, White	REEL 100M	<b>SRPS318xx</b>
20	8,400	Beige, Black, Navy, White	REEL 100M	<b>SRPS320xx</b>
22	10,800	Beige, Black, Navy, White	REEL 100M	<b>SRPS322xx</b>
24	12,500	Black, Navy, White	REEL 100M	<b>SRPS324xx</b>
26	14,250	Black, Navy, White	REEL 100M	<b>SRPS326xx</b>
28	16,500	Black, Navy, White	REEL 100M	<b>SRPS328xx</b>
30	-	Black, Navy, White	REEL 100M	<b>SRPS330xx</b>
32	-	Black, Navy, White	REEL 100M	<b>SRPS332xx</b>
36	-	Black, Navy, White	REEL 100M	<b>SRPS336xx</b>
38	-	Black, Navy, White	REEL 100M	<b>SRPS338xx</b>
40	-	Black, Navy, White	REEL 100M	<b>SRPS340xx</b>

## Multifilament Polypropylene

- ◆ Multifilament polypropylene
- ◆ Lightweight
- ◆ Soft hand
- ◆ Floats
- ◆ Applications: General purpose, draw cords, decorative cords, retaining cords, tie-downs and light duty control lines



Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
6	500	White	REEL 100M	<b>SRMFPP06W</b>
7	-	White	REEL 100M	<b>SRMFPP07W</b>
8	1,020	White	REEL 100M	<b>SRMFPP08W</b>
10	1,590	Navy	REEL 100M	<b>SRMFPP10N</b>
10	1,590	White	REEL 100M	<b>SRMFPP10W</b>
12	2,250	Black	REEL 100M	<b>SRMFPP12BK</b>
16	4,060	White	REEL 100M	<b>SRMFPP16W</b>



## Octoplaît



- ◆ Material: HT Polyester
- ◆ Construction: 8 single braid
- ◆ Low stretch
- ◆ High tenacity
- ◆ Abrasion resistance
- ◆ High resistivity to UV and most chemicals
- ◆ Applications: Anchor lines, mooring lines, towing lines, drogue lines and children's toys

Available Colour - xx	Colour
<b>BK</b>	Black
<b>N</b>	Navy
<b>W</b>	White

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
8	-	Black, White	REEL 100M	<b>SRPS808xx</b>
10	-	Black, Navy, White	REEL 100M	<b>SRPS810xx</b>
12	3,795	Black, Navy, White	REEL 100M	<b>SRPS812xx</b>
14	4,840	Black, Navy, White	REEL 100M	<b>SRPS814xx</b>
16	6,600	Black, Navy, White	REEL 100M	<b>SRPS816xx</b>
18	7,700	Black, Navy, White	REEL 100M	<b>SRPS818xx</b>
20	8,140	Black, Navy, White	REEL 100M	<b>SRPS820xx</b>
22	11,880	Black, Navy, White	REEL 100M	<b>SRPS822xx</b>
24	13,750	Black, White	REEL 100M	<b>SRPS824xx</b>
28	18,150	Black, White	REEL 100M	<b>SRPS828xx</b>
32	22,880	Black	REEL 100M	<b>SRPS832xx</b>
42	-	Black	REEL 100M	<b>SRPS842xx</b>

## Cruising Dock Line



- ◆ Cover: HT Polyester
- ◆ Core: Nylon
- ◆ Construction: braid on braid
- ◆ Durable
- ◆ Excellent stretch recovery
- ◆ Easy to handle
- ◆ Easy stowing
- ◆ Applications: Mooring lines, fender lines and painter lines

Available Colour - xx	Colour
<b>BK</b>	Black
<b>N</b>	Navy
<b>W</b>	White

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
12	3,500	Black, Navy, White	REEL 100M	<b>SRMDL12xx</b>
14	5,000	Black, Navy, White	REEL 100M	<b>SRMDL14xx</b>
16	6,575	Black, Navy, White	REEL 100M	<b>SRMDL16xx</b>
18	8,100	Black, Navy, White	REEL 100M	<b>SRMDL18xx</b>

The combination of nylon core and HT Polyester cover gives this rope excellent stretch recovery and abrasion resistant properties – perfect for mooring.

- ◆ Cover: HT Polyester
- ◆ Core: Nylon
- ◆ Construction: braid on braid
- ◆ Durable
- ◆ Excellent stretch recovery
- ◆ Easy to handle
- ◆ Easy stowing
- ◆ Applications: Mooring lines, fender lines and painter lines

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
12	3,500	Black, Navy, White	REEL 100M	<b>SRSYMDL12xx</b>
14	5,000	Black, Navy, White	REEL 100M	<b>SRSYMDL14xx</b>
16	6,575	Black, Navy, White	REEL 100M	<b>SRSYMDL16xx</b>
18	8,100	Black, Navy, White	REEL 100M	<b>SRSYMDL18xx</b>
20	10,000	Black, Navy, White	REEL 100M	<b>SRSYMDL20xx</b>
24	14,400	Black, Navy, White	REEL 100M	<b>SRSYMDL24xx</b>

## Superyacht Dock Line



Available Colour - xx	Colour
<b>BK</b>	Black
<b>N</b>	Navy
<b>W</b>	White

## Burgee Cord

- ◆ Cover: Braided HT Polyester
- ◆ Core: Parallel strands of HT Polyester
- ◆ Rigid construction
- ◆ Low creep
- ◆ Abrasion resistance
- ◆ UV resistance
- ◆ Applications: Flag halyards, mouse lines, boat cover tie downs, tie downs and nets



Available Colour - xx	Colour
<b>BE</b>	Beige
<b>BK</b>	Black
<b>BL</b>	Blue
<b>G</b>	Green
<b>GR</b>	Grey
<b>R</b>	Red
<b>W</b>	White
<b>Y</b>	Yellow

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
2	150	Black, White	REEL 300M	<b>SRBC02xx</b>
3	300	White, Yellow	REEL 300M	<b>SRBC03xx</b>
4	480	Beige, Black, Green, Red, White, Yellow	REEL 100M	<b>SRBC04xx</b>
5	540	Beige, Black, Blue, Green, Red, White, Yellow	REEL 100M	<b>SRBC05xx</b>
6	700	Black, Green, Grey, Red, White, Yellow	REEL 100M	<b>SRBC06xx</b>
7	950	Black, Green, White, Yellow	REEL 100M	<b>SRBC07xx</b>
8	1,255	Black, Green, White, Yellow	REEL 100M	<b>SRBC08xx</b>
10	1,935	White	REEL 100M	<b>SRBC10xx</b>

## Shock Cord



- ◆ Cover: HT Polyester
- ◆ Core: Rubber
- ◆ Construction: Braid over parallel core
- ◆ Minimum 100% stretch
- ◆ Excellent recovery from stretch
- ◆ Applications: Securing objects, tie downs and nets

Available Colour - xx	Colour
<b>B</b>	Blue
<b>BK</b>	Black
<b>G</b>	Green
<b>R</b>	Red
<b>WBK</b>	White/Black
<b>WG</b>	White/Green

Diameter (mm)	Breaking Load (kg)	Available Colours	Unit	No
2	-	Black, Green, Red, White/Black, White/Green	REEL 100M	<b>SRSC02BK</b>
3	-	Blue, Black, Green, Red, White/Black, White/Green	REEL 100M	<b>SRSC03B</b>
4	-	Blue, Black, Green, Red, White/Black, White/Green	REEL 100M	<b>SRSC04B</b>
5	-	Blue, Black, Green, Red, White/Black, White/Green	REEL 100M	<b>SRSC05B</b>
6	-	Blue, Black, Green, Red, White/Black, White/Green	REEL 100M	<b>SRSC06B</b>
7	-	Blue, Black, Green, Red, White/Black, White/Green	REEL 100M	<b>SRSC07B</b>
8	-	Blue, Black, Green, Red, White/Black, White/Green	REEL 100M	<b>SRSC08B</b>
9	-	Blue, Black, Green, Red, White/Black, White/Green	REEL 100M	<b>SRSC09</b>
10	-	Blue, Black, Green, Red, White/Black, White/Green	REEL 100M	<b>SRSC10B</b>





ORIGINAL SAILCLOTH



**BAINBRIDGE**  
SINCE 1917

**New 2016 Season**

Original Sailcloth  
Jacket

MANUFACTURE AND SUPPLY

Completely  
**New Design**



New Colourways

– White with  
Navy detailing,  
Navy with White  
detailing

Improved Comfort

Better Fit &  
Flexibility

Original  
Bainbridge  
Sailcloth

Water Repellent &  
Stain Resistant

Improved Hood

Genuine Red  
Sail Insignia &  
Detailing

Supplied in  
matching Sailcloth  
Deluxe Holdall



**Unisex Fit – better comfort fit**

Sailcloth Jackets



Clothing & Sailing Gear





## Jacket Features



- 1 Tuck Away shaped hood in collar
- 2 Fitted, Shaped Sleeves
- 3 Soft Lycra Inner cuff – with thumbhole
- 4 Warm Microfleece inner lining
- 5 Heavy Duty YKK Two Way Zip
- 6 Storm Flap Closure on main zip with Velcro fastening
- 7 Breathable, Water Resistant Fabric
- 8 Anti-Pill Super Soft touch inner collar
- 9 Storm Flap 'Z' design outer pockets
- 10 Internal Laminate Sailcloth phone / device pocket
- 11 Inner Nelson Zipped pocket for valuables
- 12 Concealed Zip in inner liner allows for embroidery of boat or business name on





## Bainbridge Sailcloth Jacket - Blue

- ◆ NEW Bainbridge Sailcloth Jacket
- ◆ New colourway - Navy and white detailing
- ◆ Improved comfort
- ◆ Better fit and flexibility
- ◆ Original Bainbridge sailcloth
- ◆ Water repellent & stain resistant
- ◆ Improved hood
- ◆ Genuine red sail insignia and detailing
- ◆ Supplied in matching sailcloth deluxe holdall



Size	Colour	Unit	Pack Quantity	No
XS	Blue	EACH	1	<b>JKTP00BU</b>
S	Blue	EACH	1	<b>JKTP01BU</b>
M	Blue	EACH	1	<b>JKTP03BU</b>
L	Blue	EACH	1	<b>JKTP05BU</b>
XL	Blue	EACH	1	<b>JKTP06BU</b>
XXL	Blue	EACH	1	<b>JKTP07BU</b>
XXXL	Blue	EACH	1	<b>JKTP08BU</b>

## Bainbridge Sailcloth Jacket - White

- ◆ NEW Bainbridge Sailcloth Jacket
- ◆ New colourway - White with navy detailing
- ◆ Improved comfort
- ◆ Better fit and flexibility
- ◆ Original Bainbridge sailcloth
- ◆ Water repellent & stain resistant
- ◆ Improved hood
- ◆ Genuine red sail insignia and detailing
- ◆ Supplied in matching sailcloth deluxe holdall



Size	Colour	Unit	Pack Quantity	No
XS	White	EACH	1	<b>JKTP00WT</b>
S	White	EACH	1	<b>JKTP01WT</b>
M	White	EACH	1	<b>JKTP03WT</b>
L	White	EACH	1	<b>JKTP05WT</b>
XL	White	EACH	1	<b>JKTP06WT</b>
XXL	White	EACH	1	<b>JKTP07WT</b>
XXXL	White	EACH	1	<b>JKTP08WT</b>







## Sail Number Bags



Grey



White



Classic Tan

- ◆ Made from genuine Bainbridge woven sailcloth
- ◆ Each bag is unique / individual
- ◆ Durable
- ◆ Reinforced handles
- ◆ Grab handle on the end
- ◆ Splashproof
- ◆ Available in sizes small, medium and large
- ◆ Red, blue or black original insignia sail numbers
- ◆ The strap is not included for the small and medium bags.

Size	Dimensions (cm)	Capacity (litres)	Colour	Unit	Pack Quantity	No
Small	50 x 25	24	Grey	EACH	1	<b>BMZ1001</b>
Medium	60 x 30	43	Grey	EACH	1	<b>BMZ1002</b>
Large	70 x 37	75	Grey	EACH	1	<b>BMZ1003</b>
Small	50 x 25	24	White	EACH	1	<b>BMZ1101</b>
Medium	60 x 30	43	White	EACH	1	<b>BMZ1102</b>
Large	70 x 37	75	White	EACH	1	<b>BMZ1103</b>
Small	50 x 25	24	Tan	EACH	1	<b>BMZ1301</b>
Medium	60 x 30	43	Tan	EACH	1	<b>BMZ1302</b>
Large	70 x 37	75	Tan	EACH	1	<b>BMZ1303</b>

## Sailcloth Deluxe Holdalls



- ◆ Made from genuine Bainbridge woven sailcloth
- ◆ Large top opening for convenience
- ◆ Reinforced handles
- ◆ Splashproof
- ◆ Stylish nautical design
- ◆ Each bag is unique / individual
- ◆ Reinforced handles

Size	Dimensions (cm)	Capacity (litres)	Colour	Unit	Pack Quantity	No
Small	-	24	White	EACH	1	<b>BMZ1201</b>
Medium	-	43	White	EACH	1	<b>BMZ1202</b>
Large	70 x 28	75	White	EACH	1	<b>BMZ1203</b>



## Wash bags

- ◆ Made from genuine Bainbridge woven sailcloth
- ◆ Red, blue or black original insignia sail numbers
- ◆ Splashproof
- ◆ Exterior zipped pocket



Large



Small

Size	Dimensions (cm)	Capacity (litres)	Colour	Unit	Pack Quantity	No
Small	21 x 14	1.8	White	EACH	1	<b>BMZ2001</b>
Large	26 x 18	7.5	White	EACH	1	<b>BMZ2002</b>

## Duffel Bag & Cube Bag

### Duffel Bag

- ◆ Soft natural colour rope carry handles - carries on shoulder in comfort
- ◆ Tan colour with contrast zig zag stitch in cream
- ◆ Top opening rope eyelets compliment nautical look
- ◆ Specially finished cloth to repel dirt and be splashproof
- ◆ Made from Genuine Bainbridge woven sailcloth



### Cube Bag

- ◆ Handle eyelets compliment nautical look
- ◆ Specially finished cloth to repel dirt and be splashproof
- ◆ Toggle and rope closure secures bag when on the move

Size	Dimensions (cm)	Colour	Unit	Pack Quantity	No
One Size	25L x 55H	Tan	EACH	1	<b>BMZ2101</b>
One Size	26L x 20W x 28.5H	Tan	EACH	1	<b>BMZ2201</b>
One Size	26L x 20W x 28.5H	White	EACH	1	<b>BMZ2202</b>

## Tote Bag

- ◆ Made from genuine Bainbridge Ocean woven sailcloth
- ◆ Red, blue or black original insignia sail numbers
- ◆ Durable design
- ◆ Splashproof
- ◆ Soft rope handles for comfort
- ◆ Convenient size
- ◆ interior zipped pockets
- ◆ Magnetic clasp closing



Size	Dimensions (cm)	Capacity (litres)	Colour	Unit	Pack Quantity	No
Small	40 x 30	12	White	EACH	1	<b>BMZ2003</b>



## Dry Tube Bags

5Ltr Blue



12Ltr Red



20Ltr Pink



30Ltr Yellow



40Ltr Yellow

- ◆ 100% Waterproof dry bag - Class 3 - IP66
- ◆ Floats safely if dropped in water
- ◆ Suitable for quick submersion
- ◆ Protects contents from dust, sand, dirt and water
- ◆ High frequency welded seams
- ◆ Made of 600D nylon-coated PVC tarpaulin
- ◆ Durable, wipe clean and easy to store away
- ◆ Multi-purpose storage application
- ◆ Heavy duty and durable materials for rough usage

Diameter (cm)	Height (cm)	Capacity (litres)	Weight (kg)	Colour	Unit	Pack Quantity	No
19	24	5	0.34	Blue	EACH	1	<b>OB1001B</b>
19	24	5	0.34	Black	EACH	1	<b>OB1001BLK</b>
19	24	5	0.34	Pink	EACH	1	<b>OB1001P</b>
19	24	5	0.34	Yellow	EACH	1	<b>OB1001Y</b>
19	24	5	0.34	Red	EACH	1	<b>OB1001R</b>
19	40	12	0.42	Blue	EACH	1	<b>OB1003B</b>
19	40	12	0.42	Black	EACH	1	<b>OB1003BLK</b>
19	40	12	0.42	Red	EACH	1	<b>OB1003R</b>
19	40	12	0.42	Yellow	EACH	1	<b>OB1003Y</b>
24	40	20	0.64	Blue	EACH	1	<b>OB1005B</b>
24	40	20	0.64	Black	EACH	1	<b>OB1005BLK</b>
24	40	20	0.64	Pink	EACH	1	<b>OB1005P</b>
24	40	20	0.64	Red	EACH	1	<b>OB1005R</b>
24	40	20	0.64	Yellow	EACH	1	<b>OB1005Y</b>
29	42	30	0.64	Blue	EACH	1	<b>OB1006B</b>
29	42	30	0.64	Black	EACH	1	<b>OB1006BLK</b>
29	42	30	0.66	Red	EACH	1	<b>OB1006R</b>
29	42	30	0.66	Yellow	EACH	1	<b>OB1006Y</b>
29	56	40	0.80	Blue	EACH	1	<b>OB1007B</b>
29	56	40	0.80	Black	EACH	1	<b>OB1007BLK</b>
29	56	40	0.80	Red	EACH	1	<b>OB1007R</b>
29	56	40	0.80	Yellow	EACH	1	<b>OB1007Y</b>

## Pro-Vis Dry Tube Bags

- ◆ 100% Waterproof dry bag - Class 3 - IP66
- ◆ High Visibility PVC tarpaulin so can be seen day or night
- ◆ 4 x large light reflective strips
- ◆ Floats safely if dropped in water
- ◆ Protects contents from dust, sand, dirt and water
- ◆ Heavy duty and durable materials for rough usage
- ◆ LED light attachment loop

20Ltr - Orange



20Ltr - Yellow



Diameter (cm)	Height (cm)	Capacity (litres)	Weight (kg)	Colour	Unit	Pack Quantity	No
24	40	20	0.37	Orange	EACH	1	OB1148HVO
24	40	20	0.37	Yellow	EACH	1	OB1148HVV

- ◆ Waterproof TPU lining with stitched and taped seams - Class 2 - IP65
- ◆ Durable, wipe clean and easy to store away
- ◆ Protects contents from dirt, sand, dust and water
- ◆ Not suitable for full submersion

## Dry Pouches

Blue



Red



Yellow



Black



Height (cm)	Capacity (litres)	Weight (kg)	Colour	Unit	Pack Quantity	No
11	1	0.06	Blue	EACH	1	OB1031B
11	1	0.06	Black	EACH	1	OB1031BLK
11	1	0.06	Red	EACH	1	OB1031R
11	1	0.06	Yellow	EACH	1	OB1031Y

- ◆ Internal wet / dry pocket
- ◆ Internal side mesh zip pocket
- ◆ Manufactured from strong & hard wearing PVC tarpaulin cloth
- ◆ D-zip with weatherproof zipper flap (Class 1)
- ◆ 4 compression straps
- ◆ Double stitched

## Adventure Duffel

90L



60L



35L



Depth (cm)	Height (cm)	Capacity (litres)	Weight (kg)	Colour	Unit	Pack Quantity	No
39	29	90	1.9	Blue	EACH	1	OB1059B
39	29	90	1.9	Black	EACH	1	OB1059BLK
39	29	90	1.9	White	EACH	1	OB1059WHT
39	29	90	1.9	Yellow	EACH	1	OB1059Y
28	28	35	1.27	Black	EACH	1	OB1091BLK
28	28	35	1.27	White	EACH	1	OB1091WHT
36	31	60	1.33	Black	EACH	1	OB1143BLK
36	31	60	1.33	White	EACH	1	OB1143WHT

## Pro Sports Duffel

Red - 20L



Black - 90L



Black - 20L

- ◆ 2x front and 2x back light reflective strips
- ◆ Made from tough and hardwearing PVC tarpaulin cloth
- ◆ Waterproof front zip pocket - Class 2 - IP65
- ◆ 100% waterproof holdall with Fold Seal System™ Class 3 - IP66

Depth (cm)	Height (cm)	Capacity (litres)	Weight (kg)	Colour	Unit	Pack Quantity	No
32	27	60	1.55	Black	EACH	1	<b>OB1154BLK</b>
32	27	60	1.55	Red	EACH	1	<b>OB1154R</b>
39	29	90	2.06	Black	EACH	1	<b>OB1155BLK</b>

## Pro Sports Backpacks

Blue - 20L



Yellow - 20L



Black - 30L



Brown - 30L



Red - 30L

- ◆ Roll-top 100% waterproof backpack - Class 3 - IP66
- ◆ Floats safely if dropped in water
- ◆ super tough material on side and base
- ◆ 2 way sealing system (traditional top or side compression)
- ◆ Protects contents from dust, sand, dirt and water
- ◆ Front zip mesh pocket
- ◆ High Frequency welded construction
- ◆ Padded shoulder straps and lumbar support
- ◆ Ventilated back panel with air-flow design
- ◆ Comfortable and buoyant light-weight straps with ventilation system

Depth (cm)	Height (cm)	Capacity (litres)	Weight (kg)	Colour	Unit	Pack Quantity	No
16.5	43	20	1.06	Blue	EACH	1	<b>OB1145B</b>
16.5	43	20	1.06	Yellow	EACH	1	<b>OB1145Y</b>
16.5	49.5	30	1.32	Black	EACH	1	<b>OB1146BLK</b>
16.5	49.5	30	1.32	Brown	EACH	1	<b>OB1146BRW</b>
16.5	49.5	30	1.32	Red	EACH	1	<b>OB1146R</b>

## Belt & Arm Packs



Belt Pack - OB1050BLK



Arm Pack - OB1051BLK

- ◆ 100% waterproof arm pack- Class 5 - IP68
- ◆ Floats safely if dropped in water
- ◆ Guaranteed submersible to 19ft / 6m
- ◆ Keeps out dust, sand, dirt and water
- ◆ Made of environmentally-friendly biodegradable thermoplastic polyurethane (TPU)
- ◆ Perfect for storing your phone, keys, cash and credit cards

Length (cm)	Width (cm)	Colour	Unit	Pack Quantity	No
13.5	13	Black	EACH	1	<b>OB1050BLK</b>
20	17	Black	EACH	1	<b>OB1051BLK</b>

## Kayak Deck Bag

- ◆ 100% waterproof main compartment - Class 3 - IP66
- ◆ Front weatherproof zip pocket - Class 2 - IP65
- ◆ Front storage webbing
- ◆ Made of 600D PVC tarpaulin
- ◆ Floats safely if dropped in water
- ◆ Suitable for quick submersion
- ◆ High frequency welded seams
- ◆ Durable, wipe clean and easy to store away
- ◆ Multi-purpose storage application
- ◆ Heavy duty & durable materials for rough usage
- ◆ 6 Side buckle connectors for easy & secure fastening
- ◆ Keeps out dirt, sand, dust and water



Height (cm)	Capacity (L)	Weight (kg)	Colour	Unit	Pack Quantity	No
43	20	0.77	Yellow	EACH	1	<b>OB1094Y</b>

## Dry Ice Cooler Bag

- ◆ 100% waterproof cooler bag - Class 3 - IP66
- ◆ Keeps drinks cold for up to 24 hours
- ◆ Floats safely if dropped in water
- ◆ Suitable for quick submersion
- ◆ Protects contents from dust, sand, dirt and water
- ◆ High frequency welded seams
- ◆ Made of 600D nylon-coated tough PVC tarpaulin
- ◆ Purge valve for flat pack storage
- ◆ Thermal insulating core keeping contents ice cold for 24 hours
- ◆ Top carry handle
- ◆ Removable padded backpack straps



Height (cm)	Capacity (L)	Weight (kg)	Colour	Unit	Pack Quantity	No
42	30	0.9	Yellow	EACH	1	<b>OB1161Y</b>

## Waterproof Tablet Case

- ◆ 100% waterproof iPad mini case - Class 5 - IP68
- ◆ Floats safely if dropped in water
- ◆ Padded back for extra protection
- ◆ Large back window for crystal clear photo & videos
- ◆ Guaranteed submersible to 19ft / 6m
- ◆ Keeps out dust, sand, dirt and water
- ◆ Transparent front allowing full use of touchscreen functions
- ◆ Includes fully adjustable shoulder strap for easy transportation



OB1086BL



OB1083BL

Compatible With	Height (cm)	Width (cm)	Colour	Unit	Pack Quantity	No
iPad Mini, Samsung Galaxy Note 8, Kindle Fire 7" & Google Nexus 7	21	15	Black	EACH	1	<b>OB1083BLK</b>
All iPad models (including Air), Samsung Galaxy Tab 2, Kindle Fire HD	25	20	Black	EACH	1	<b>OB1086BLK</b>



## Waterproof Small Phone Case



Black



Aqua

- ◆ 100% waterproof phone case - Class 5 - IP68
- ◆ Will float "most" phone models safely\*
- ◆ Compatible with all iPhones, Blackberry phones and HTC Desires
- ◆ Guaranteed submersible to 19ft / 6m
- ◆ LENZFLEX back window for ultra clear photos
- ◆ Transparent front window allowing full use of phone features
- ◆ Make & take phone calls when phone is sealed in waterproof phone pouch
- ◆ Keeps out dust, sand, dirt and water

Compatible With	Height (cm)	Width (cm)	Colour	Unit	Pack Quantity	No
iPhone 6, Samsung Galaxy S6, HTC One M9 & Motorola Moto X	15.2	7.5	Aqua	EACH	1	<b>OB1008A</b>
iPhone 6, Samsung Galaxy S6, HTC One M9 & Motorola Moto X	15.2	7.5	Black	EACH	1	<b>OB1008BLK</b>

## Waterproof Large Case



- ◆ 100% waterproof phone case- Class 5 - IP68
- ◆ Will float if dropped in water
- ◆ Guaranteed submersible to 19ft / 6m
- ◆ LENZFLEX back window for ultra clear photos
- ◆ Transparent front window allowing full use of phone features
- ◆ Make & take phone calls when phone is sealed inside the pouch
- ◆ Keeps out dust, sand, dirt and water
- ◆ Made of environmentally-friendly biodegradable thermoplastic polyurethane (TPU)
- ◆ Perfect for the largest of SMART Phones

Compatible With	Height (cm)	Width (cm)	Colour	Unit	Pack Quantity	No
iPhone 6 Plus, Samsung Galaxy Note 5, LG G4, Sony Xperia Z3	17	9	Black	EACH	1	<b>OB1106BLK</b>

## Waterproof GPS Case



- ◆ 100% waterproof GPS case - Class 5 - IP68
- ◆ Suitable for a large phone or GPS device
- ◆ Floats if dropped in water
- ◆ Guaranteed submersible to 19ft / 6m
- ◆ Transparent front window allowing full use of device features
- ◆ Keeps out dust, sand, dirt and water
- ◆ Made of environmentally-friendly biodegradable thermoplastic polyurethane (TPU)

Compatible With	Height (cm)	Width (cm)	Colour	Unit	Pack Quantity	No
Garmin GPS 72H, All Generation PSP Consoles & Garmin GPS Map 62	20	20	Black	EACH	1	<b>OB1009BLK</b>

\*Warning: Always test your device for buoyancy before use and be aware that external environmental factors may affect floatation.



## Waterproof Kindle/eBook Case

- ◆ 100% waterproof eBook / Kindle case - Class 5 - IP68
- ◆ Floats safely if dropped in water
- ◆ Guaranteed submersible to 19ft / 6m
- ◆ Keeps out dust, sand, dirt and water
- ◆ Transparent front allowing full use of device features
- ◆ Made of environmentally-friendly biodegradable thermoplastic polyurethane (TPU)
- ◆ Fits all Amazon Kindles and all other eBook readers, including smaller tablets.



Compatible With	Height (cm)	Width (cm)	Colour	Unit	Pack Quantity	No
All Kindles & Samsung Galaxy Tab 2	20	15	Black	EACH	1	<b>OB1082BLK</b>

## Waterproof VHS Case

- ◆ 100% waterproof VHF case - Class 5 - IP68
- ◆ Floats safely if dropped in water
- ◆ Guaranteed submersible to 19ft / 6m
- ◆ Keeps out dust, sand, dirt and water
- ◆ Made of environmentally-friendly biodegradable thermoplastic polyurethane (TPU)
- ◆ Suitable for right and left handed antenna radios
- ◆ Fits most small handheld VHF radios

Large

Small



Compatible With	Height (cm)	Width (cm)	Colour	Unit	Pack Quantity	No
Polmar NAVY-010 & Standard Horizon HX290E	30.5	20	Black	EACH	1	<b>OB1035BLK</b>
Icom M91D & Standard Horizon HX290E	38	20	Black	EACH	1	<b>OB1036BLK</b>

## Waterproof Map Pouch

- ◆ Freeze-proof, UV sun damage-proof and waterproof pouch - Class 2 - IP65
- ◆ Durable, wipe-clean and easy to store away
- ◆ Protects contents from dust, sand and dirt and water
- ◆ 4 x D-rings for multiple attachment options
- ◆ Fully adjustable shoulder Strap



Height (cm)	Width (cm)	Colour	Unit	Pack Quantity	No
29.7	21.6	Black	EACH	1	<b>OB1081BLK</b>
43.2	29.7	Black	EACH	1	<b>OB1105BLK</b>

\*Warning: Always test your device for buoyancy before use and be aware that external environmental factors may affect floatation.





## Gerber Daily Carry

Zip Hex - GE001740



Zip Driver - GE001738



Zip Light+ - GE001745



Zip Blade - GE001742

### Zip Driver

- ◆ This palm-sized rotating wheel holds the four most commonly used screwdriver heads—two flat and two Phillips.
- ◆ Snap one into place, and a ball detent mechanism locks it tight enough to take on the oldest, rustiest screw.

### Zip Hex

- ◆ The palm-sized hex's rotating wheel holds the five most commonly used metric Allen wrenches. Stem bolts, binding attachments, furniture, exercise equipment—no matter what you're working on, the Zip Hex can help.

### Zip Blade

- ◆ Compact .68-inch fine edge utility blade
- ◆ Frame lock for improved security
- ◆ Quick-release clip for swift removal

### Zip Light+

- ◆ Stainless steel construction for durability
- ◆ Bright white LED light for visibility
- ◆ Zipper loop attachment Clip for quick removal
- ◆ Bottle opener
- ◆ Two replaceable lithium batteries

Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
55	55	EACH	1	GE001738
53	53	EACH	1	GE001740
43	57	EACH	1	GE001742
46	46	EACH	1	GE001745

## Suspension Multi Tool



- ◆ Needlenose Pliers
- ◆ Fine Edge Blade
- ◆ Serrated Edge Blade
- ◆ Saw
- ◆ Phillips Driver
- ◆ Small Flat Driver
- ◆ Medium Driver
- ◆ Lanyard Ring
- ◆ Bottle Opener
- ◆ Can Opener
- ◆ Scissors
- ◆ Vcut Wire Cutters
- ◆ Ballisti Nylon Sheath.

Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
102	165	EACH	1	GE01471





## Bear Grylls Ultimate Multi Tool

### Components:

- ◆ Needlenose pliers
- ◆ Wire cutters
- ◆ Fine edge knife
- ◆ Serrated edge knife
- ◆ Phillips screwdriver
- ◆ Small flat driver
- ◆ Medium flat driver
- ◆ Lanyard ring
- ◆ Bottle opener
- ◆ Can opener
- ◆ Scissors.



Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
101	160	EACH	1	GE31000749

## Bear Grylls Compact Multi Tool

### Components:

- ◆ Needlenose pliers
- ◆ Wire cutters
- ◆ Fine edge knife
- ◆ Serrated edge knife
- ◆ Phillips screwdriver
- ◆ Small flat driver
- ◆ Medium flat driver
- ◆ Lanyard ring
- ◆ Bottle opener
- ◆ Tweezers.



Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
63	109	EACH	1	GE31000750

## Crucial Compact Multi Tool

### Components:

- ◆ Convenient carabiner clip
- ◆ Bottle opener
- ◆ V-cut wire cutters
- ◆ Flathead screw driver
- ◆ Phillips driver
- ◆ Thumbstud
- ◆ Semi-serrated blade
- ◆ Needle nose pliers



Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
9.1	14	EACH	1	GE31001337





## Diesel Multi Tool



Components:

- ◆ Needlenose pliers
- ◆ Wire cutter
- ◆ Partially serrated knife blade
- ◆ Cross point screwdriver
- ◆ Small medium and large flat blade screwdrivers
- ◆ Can opener
- ◆ Bottle opener
- ◆ File saw
- ◆ Scissors

Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
125	168	EACH	1	GE41470

## Suspension Multi Tool



Components:

- ◆ Needlenose pliers
- ◆ Wire cutter
- ◆ Fine edge knife
- ◆ Serrated edge knife
- ◆ Saw
- ◆ Scissors
- ◆ Crosspoint screwdriver
- ◆ Small and medium flat blade screwdrivers
- ◆ Can opener
- ◆ Bottle opener
- ◆ Lanyard hole.

Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
102	165	EACH	1	GE41471

## Evo Multi Tool



Components:

- ◆ Needlenose pliers
- ◆ Pincher style wire cutter
- ◆ Saw blade
- ◆ Cross driver
- ◆ Fine edge blade
- ◆ Scissors
- ◆ Small and medium flat drivers
- ◆ Bottle opener
- ◆ Can opener
- ◆ Serrated knife
- ◆ Lanyard

Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
100	152	EACH	1	GE41771





## Dime Pocket Micro Tool

### Components:

- ◆ Pliers
- ◆ Wire Cutters
- ◆ Spring-Loaded Scissors
- ◆ Fine Edge Knife
- ◆ Retail Package Opener
- ◆ Phillips Driver
- ◆ Medium Flathead Driver
- ◆ Bottle Opener
- ◆ Tweezers
- ◆ File



Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
70	101	EACH	1	GE31001040

## Dime Keychain Multi Tool

### Components:

- ◆ Pliers,
- ◆ Wire Cutters
- ◆ Spring Loaded Scissors
- ◆ Fine Edge Knife
- ◆ Retail Package Opener
- ◆ Phillips Driver
- ◆ Medium Flathead Driver
- ◆ Bottle Opener
- ◆ Tweezers
- ◆ File



Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
70	101	EACH	1	GE31001132

## Bear Grylls Pocket Tool

### Components:

- ◆ Fine edge knife
- ◆ Phillips screwdriver
- ◆ Small flat driver
- ◆ Medium flat driver
- ◆ Bottle opener



Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
81	142	EACH	1	GE31001050





## Splice Pocket Tool



- ◆ Can be used in various military, hunting, survival, tactical, industrial and outdoor situations
- ◆ All products are field tested
- ◆ Ten functions scissors and pliers, fine edge blade, serrated blade, bottle opener, medium flat driver, small flat driver, cross driver, file and retractable lanyard
- ◆ Comfortable to carry in your pocket or attach to a keychain
- ◆ Intuitive opening in lightweight, compact style
- ◆ Two blades for multiple applications
- ◆ New bottle opener design for better leverage

Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
61	101	EACH	1	GE1019241

## River Shorty Knife



- ◆ Ideal for water sports
- ◆ Corrosion resistant blade
- ◆ Hard plastic sheath

Weight (g)	Length (mm)	Unit	Pack Quantity	No
113	171	EACH	1	GE31002645

## E-Z Out Rescue Knife



- ◆ One hand opening - simple to use even in an emergency
- ◆ TacHide SoftGrip inserts - enables a firm grip even when wet
- ◆ Sturdy pocket clip - for convenient pocket carry
- ◆ Lanyard hole

Weight (g)	Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
68	113	202	EACH	1	GE06971

## Bear Grylls Scout Knife



- ◆ ½ Serrated High Carbon Stainless Steel Drop Point Blade - Ideal for edge retention and cutting rope
- ◆ Ergonomic Textured Rubber Grip - Maximizes comfort and reduces slippage
- ◆ Lock Back - Locks blade securely in place and maximizes safety during closing

Weight (g)	Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
68	100	190	EACH	1	GE31000754





## Paraframe Folding Knife

- ◆ Frame lock handle design
- ◆ Lightweight open stainless steel handles
- ◆ Sturdy pocket clip



Weight (g)	Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
73	104	178	EACH	1	GE48443

## Bear Grylls Grandfather Knife

- ◆ The knife's 7 components include a fine edge blade, flat driver, Phillips driver, corkscrew, bottle opener, file and lanyard ring
- ◆ The stainless steel Bear Grylls badge plays on the knife's vintage origins and lends it a classic look
- ◆ The rubber-over-mold grip gives the knife a comfortable feel and adds security to your grip



Weight (g)	Length Closed (mm)	Length Open (mm)	Unit	Pack Quantity	No
99	95	165	EACH	1	GE31001685

## Gator Machete

- ◆ Long-bladed knife with a dual function design. It features a 15" fine edge blade on one side and an 18" saw blade on the other
- ◆ This Gerber machete can be used to effectively chop and saw wooden branches, dense bush growth etc
- ◆ Easy to control during heavy use



Weight (g)	Overall Length (mm)	Blade Length (mm)	Unit	Pack Quantity	No
510	650	460	EACH	1	GE31000758







## Bear Grylls Micro Light



- ◆ Compact design
- ◆ Long Lasting L.E.D. Bulb
- ◆ 4 Settings - High, Low, Beacon/Blinking & Off
- ◆ Easy to Use Soft Rubber Switch

Weight (g)	Overall Length (mm)	Unit	Pack Quantity	No
41	50	EACH	1	<b>GE31001034</b>

## Bear Grylls Canteen Water Bottle



- ◆ Food Grade Aluminum Cup
- ◆ BPA-Free Water Bottle
- ◆ Snug Nylon Sheath
- ◆ Textured Exterior
- ◆ Leak-Proof Lock Top
- ◆ 1 Litre Capacity

Weight (g)	Dimensions (mm)	Unit	Pack Quantity	No
354	250 x 150 x 80	EACH	1	<b>GE31001062</b>



Part No	Page	Part No	Page	Part No	Page	Part No	Page
06R	37	A000	46	A059	74	A117	55
06R30	37	A001	46	A060	72	A118	42
06REC	39	A002	46	A061	73	A118	55
08R	37	A004	46	A061A	73	A122BK	129
08R30	37	A005	46	A062	74	A125BK	129
08REC	39	A006	46	A063A	74	A142BK	128
10DECI	39	A006M	51	A063BP	74	A142BK	129
10DECO	39	A007	51	A066	73	A150	39
10DXSTECI	39	A008	51	A066A	73	A159BK	128
10R	37	A008M	51	A067	73	A160WT	130
10R30	37	A009	51	A067A	73	A161WT	130
10REC	39	A0091	51	A067ABK	73	A170	127
12R	37	A011	53	A068	72	A172	127
12REC	39	A012	53	A068BK	127	A188A	71
14R	37	A013	53	A068WT	127	A300BK	47
14REC	39	A014	53	A069BK	127	A300WT	47
15CT	38	A015	53	A069WT	127	A302	46
15CTECI	39	A016	55	A071	127	A303BK	47
15CTECO	39	A016S	55	A072BK	129	A303WT	47
15CTM	38	A017	55	A073	128	A305BK	47
15CTST	38	A017S	55	A074	128	A305SS	47
15DNECI	39	A018	55	A075	128	A305WT	47
15DNECO	39	A018S	55	A076	128	A306BK	47
15DWECE	39	A019	55	A076HD	128	A306SS	47
15DXSTECI	39	A019S	55	A077HD	128	A310	55
15DXSTECIWT	39	A021	49	A078WT	129	A313	55
15EC002	39	A022	49	A079BK	129	A315	55
15EC006	39	A023	49	A079WT	129	A4081	48
16HCP	38	A024	49	A082	46	A4082	48
16R	37	A026	49	A084	128	A4121	48
16REC	39	A027	49	A085	128	A4121S	48
20CV062	37	A028	49	A086	128	A4122	48
20CV080	37	A031	55	A087	128	A4161	48
20CV107	37	A031	57	A088	128	A4161S	48
20CV125	37	A031C	55	A089	128	A4162	48
20EC002	39	A031C	57	A089WT	128	A4201	48
20EC006	39	A032	55	A090	71	A4201S	48
20EC010	39	A032	57	A090	128	A4202	48
20R	37	A033	55	A095BK	130	A453	48
20REC	39	A033	57	A095WT	130	A511	71
24CTEC	39	A035BK	49	A096BK	129	A512	71
25CTJM	39	A038	71	A096WT	129	A513	71
25NTM	38	A039	71	A097BK	129	A514	71
30CEC	39	A043	61	A097WT	129	A550BK	80
30CT024	38	A045	61	A107	42	B006	53
30CT031	38	A048	61	A107	51	B008	51
30CT031R	38	A052	61	A108	42	B008A	53
30CT044	38	A054	74	A108	51	B009	51
30CT044R	38	A055	74	A109	42	B010	51
30CT052	38	A056	74	A109	51	B011	57
30CT052R	38	A057	73	A114	42	B012	57
30CTEC	39	A057A	73	A114	53	B013	57
40CEC	39	A057ABK	73	A116	42	B014SS	57
40CT	38	A057BP	74	A116	55	B015SS	57
40CTST	38	A058	74	A117	42	B016SS	57

Part No	Page	Part No	Page	Part No	Page	Part No	Page
B035	55	B204	65	B511	70	C037	142
B036	55	B2075	66	B512	70	C038L	151
B037	55	B2075C	66	B513	70	C039	151
B044	53	B2076	66	B514	70	C040	86
B057	72	B2076C	66	B515	70	C041	86
B057A	72	B2095	66	B516	70	C061	152
B057AN	72	B2095C	66	B518	69	C063	152
B067	72	B2096	66	B519	69	C101	145
B067A	72	B2106	66	B520	69	C102	145
B067AN	72	B2108	66	B528	69	C103	145
B087	129	B2116	66	B529	69	C104	145
B089	64	B214	65	B531	69	C105	145
B0901	64	B218B	68	B532	69	C106	145
B0902	64	B218BB	68	B536	80	C107	145
B0903	64	B219	65	B540	75	C108	145
B091	64	B220	65	B541	75	C109	145
B092	64	B221	65	B542	75	C110	145
B093	64	B223	65	B542N	75	C111	145
B097	64	B225	65	B543	75	C112	145
B101	57	B225B	68	B543N	75	C113	145
B102	57	B225BB	68	B544	75	C114	145
B103	57	B226BB	68	B544N	75	C116	145
B110	49	B226BB	68	B545N	75	C117	145
B117	65	B227	65	B546	75	C119	145
B118	65	B228	65	B546N	75	C120	145
B119	65	B229	65	B547	75	C122	145
B120	65	B229B	68	B549	75	C125	145
B121	65	B229BB	68	B605	80	C140	146
B123	68	B248	65	B610	119	C233	145
B124	68	B250	65	B610S	119	C234	145
B125	68	B301	72	B611	119	C301	148
B126	68	B301A	72	B611N	119	C302	148
B127	130	B301AN	72	B611SW	119	C303	148
B127B	130	B303	47	B612	119	C303C	148
B129	49	B307	53	B612S	119	C303S	148
B130	49	B308	53	B615	119	C304	148
B131	49	B309	53	B617S	119	C304C	148
B133	75	B401S	127	B632	119	C304S	148
B134	75	B411	71	B637	119	C305	148
B135	75	B414	71	B651	137	C305C	148
B136	75	B449	23	B701	70	C305S	148
B137	75	B450	23	B702	70	C306	148
B138	75	B451	23	B703	70	C306C	148
B140	75	B452	23	B710	69	C306S	148
B153	75	B453	23	B845	64	C307	148
B154	75	B461	23	B847	64	C307C	148
B155	75	B462	23	B907N	61	C307S	148
B156	75	B463	23	B908	62	C308	148
B158	75	B464	23	B908N	63	C308S	148
B169	137	B504	70	B909	62	C309	148
B170	137	B505	70	B909N	63	C309S	148
B171	137	B506	70	B909SR	62	C321	149
B172	137	B507	70	B910	62	C322	149
B173	137	B508	70	B910N	63	C323	149
B174	137	B510	70	B910SR	62	C324	147

Part No	Page	Part No	Page	Part No	Page	Part No	Page
C325	147	C860	140	C996ROLLER	150	D039S	63
C326	147	C861	140	C997	150	D050N	81
C350	145	C862	140	C997/12	150	D101B	118
C352	150	C865	140	C997/6	150	D102B	118
C360	147	C880	140	C997/8	150	D112SS	118
C361	147	C882	140	C997CLAMP	150	D207x	66
C361BKW	147	C900	141	C997ROLLER	150	D208x	66
C361CAP	147	C901	141	C998	150	D209x	66
C361GYW	147	C903	141	CBA813GY	60	D210x	66
C361SOCKET	147	C903BK	141	CBA833GY	60	D211x	66
C370	147	C903FP	141	CBA834GY	60	D212x	66
C371	147	C905	139	CBA853GY	60	D213x	66
C407	149	C906	139	CBA854GY	60	D214x	66
C408	149	C907	139	D001(x)	77	D331	81
C409	149	C908	139	D001BH	117	D332	81
C410	149	C909	139	D001NH	117	D333	81
C411	149	C910	139	D002(x)	77	D334	81
C412	149	C9105	143	D002B	77	D335	81
C413	149	C9106	143	D002NH	117	D336	81
C414	149	C9108	143	D003(x)	77	D337	81
C449	150	C910US	143	D003B	77	D339	81
C501	141	C912	139	D003BS	76	D602B	117
C515	141	C914	144	D003NH	117	D603B	117
C516	141	C915	144	D003NS	76	D604N	117
C517	141	C916	143	D004(x)	77	D605B	117
C523	141	C917C8	143	D004B	77	D605N	117
C530	145	C917ST8	143	D004BS	76	D606N	117
C531	145	C920	144	D004NH	117	D732	147
C550-10	139	C922	144	D004NS	76	D733	147
C550-12	139	C924	144	D005(x)	77	E062	18
C551-7	139	C933	144	D005B	77	E075WT	109
C551-8	139	C933S	144	D005BS	76	E078	18
C551-9	139	C950	146	D005NS	76	E080	18
C552-10	139	C951	146	D006(x)	77	E085BK	109
C552-12	139	C952	146	D006B	77	E085CR	109
C552L-10	139	C953	146	D006BS	76	E085II	109
C553	139	C953BK	146	D006NS	76	E085NV	109
C554	139	C954	147	D007(x)	77	E085RB	109
C555-10	139	C955	147	D007B	77	E085SD	109
C555-12	139	C956	147	D007BS	76	E085SW	109
C561	139	C959	146	D007NS	76	E085WT	109
C705	144	C960N	149	D008(x)	77	E086BK	109
C706	144	C962N	149	D008B	77	E086WT	109
C710	144	C970	150	D008BS	76	E088	18
C713	144	C980	151	D008NS	76	E088/60	18
C758	147	C981	151	D009(x)	77	E090BK	108
C759	147	C994	150	D009BS	76	E090BU	108
C834	140	C995	150	D009NS	76	E090WT	108
C840	140	C996	150	D011B	77	E095BG	108
C850	140	C996/10	150	D011NS	76	E095BI	108
C852	140	C996/12	150	D011NS	76	E095BK	108
C853	140	C996/6	150	D037N	63	E095BU	108
C857	140	C996/8	150	D038N	63	E095FGR	108
C857B	140	C996B	150	D039N	63	E095GY	108
C857D	140	C996CLAMP	150	D039S	61	E095NV	108

Part No	Page	Part No	Page	Part No	Page	Part No	Page
E520H	113	E569WT	115	EA092WT	84	ET207WT	83
E520L	113	E570xx	115	EA092WT	110	ET346WT	83
E521	113	E571xx	115	EA138BK	84	ET353	86
E521H	113	E572xx	115	EA138BK	110	EVMR02143	141
E521L	113	E574xx	115	EA138WT	84	EVMR05200	141
E523	113	E576xx	115	EA138WT	110	EW346	86
E523H	113	E577xx	115	EB046FWT	84	EW351	86
E523L	113	E578WT	115	EB046GWT	84	EW352	86
E530	113	E579WT	115	EB046LWT	84	EW352BK	86
E530H	113	E580	115	EB069DWT	84	EW462	86
E530L	113	E581	116	EB069FWT	84	EW499	86
E531	113	E583	116	EB069GWT	84	EW500	86
E531H	113	E584	115	EB069LTN	84	EY092xxx8	85
E531L	113	E584BE	115	EB069LWT	84	EY092xxx8	111
E533	113	E584BK	115	EB092DWT	84	EY138xxx8	85
E533H	113	E584BS	116	EB092FWT	84	EY138xxx8	111
E533L	113	E584NB	115	EB092GBK	84	F0200A10Y	95
E534	113	E584SSTS	116	EB092GWT	84	F0200A18Y	95
E534H	113	E584TS	116	EB092LWT	84	F0200A22Y	95
E534L	113	E585	116	EB13839WT	84	F0200A23Y	95
E540	114	E585BE	116	EB138GWT	84	F0200A46Y	95
E540H	114	E585BK	116	EF1500CH1T	85	F0200A60Y	95
E540L	114	E585NB	116	EF1500CH1T	110	F0200A65Y	95
E541	114	E585TSBK	116	EF1500DH1T	85	F0200A67Y	95
E541H	114	E585TSWT	116	EF1500DH1T	110	F0200A75Y	95
E541L	114	E586	116	EF1500WH1T	85	F0200A97Y	95
E542	114	E586BE	116	EF1500WH1T	110	F0200A98Y	95
E542H	114	E586BK	116	EF2640CH1T	85	F0300A00Y	94
E542L	114	E586NB	116	EF2640CH1T	110	F0300A10Y	94
E543	114	E587	116	EF2640DH1T	85	F0300A14Y	94
E543H	114	E588	114	EF2640DH1T	110	F0300A18Y	94
E543L	114	E589	116	EF2640WH1T	85	F0300A22Y	94
E544	114	E591	114	EF2640WH1T	110	F0300A44Y	94
E544H	114	E591BK	114	ET030WT	83	F0300A46Y	94
E544L	114	E592	116	ET046BK	83	F0300A60Y	94
E545	114	E593	116	ET046BU	83	F0300A65Y	94
E545H	114	E594	116	ET046WT	83	F0300A66Y	94
E545L	114	E600WT	115	ET069BK	83	F0300A67Y	94
E546	114	E605xx	115	ET069BU	83	F0300A68Y	94
E546H	114	E608xx	115	ET069GY	83	F0300A74Y	94
E546L	114	E609WT	115	ET069RD	83	F0300A75Y	94
E547	114	EA069BK	84	ET069TN	83	F0300A79Y	94
E547H	114	EA069BK	110	ET069WT	83	F0300A85Y	94
E547L	114	EA069PB	84	ET092BK	83	F0300A89Y	94
E551	46	EA069PB	110	ET092BU	83	F0300A90Y	94
E552	46	EA069WT	84	ET092GY8	83	F0300A97Y	94
E553	46	EA069WT	110	ET092TN8	83	F0300A98Y	94
E560xx	115	EA092BK	84	ET092WT	83	F0350A00Y	96
E561xx	115	EA092BK	110	ET138BK	83	F0350A13Y	96
E562xx	115	EA092BU	84	ET138BU	83	F0350A47Y	96
E562xx	115	EA092BU	110	ET138GY	83	F0350A60Y	96
E564xx	115	EA092GY	84	ET138RD	83	F0350A75Y	96
E565xx	115	EA092GY	110	ET138TN	83	F0350A79Y	96
E566xx	115	EA092PB	84	ET138WT	83	F0350A97Y	96
E568xx	115	EA092PB	110	ET207BK	83	F0400A09Y	89

Part No	Page	Part No	Page	Part No	Page	Part No	Page
F0400A10Y	89	F0805A90Y	92	F7503A00M	14	F86500210	98
F0400A17Y	89	F0808Z00Y	30	F7503B00M	14	F87500101	98
F0400A22Y	89	F0808Z00Y	93	F7565B00M	14	F9309B00M	17
F0400A37Y	89	F0808Z18Y	30	F7682B00M	14	F9313B00M	17
F0400A42Y	89	F0808Z18Y	93	F7705B00M	15	F9318B00M	17
F0400A82Y	89	F0808Z79Y	30	F7707B00M	15	F9324C00M	17
F0400A96Y	89	F0808Z79Y	93	F7710B00M	15	FH062BK	104
F0400A97Y	89	F0808Z88Y	30	F7713B00M	15	FH062WT	104
F0400A98Y	89	F0808Z88Y	93	F7718B00M	15	FH063WT	104
F0550A97Y	94	F0808Z90Y	30	F7723B00M	15	FH070BK	101
F0700A18Y	95	F0808Z90Y	93	F7783B00M	14	FH070GRN	101
F0700A23Y	95	F0808Z97Y	30	F8055B00M	13	FH070GY	101
F0700A46Y	95	F0808Z97Y	93	F8065B00M	13	FH070OR	101
F0700A60Y	95	F0840A00Y	93	F83500100	91	FH070RB	101
F0700A66Y	95	F1715Z00M	13	F83500206	91	FH070RB	101
F0700A77Y	95	F5300D00W	32	F83500207	91	FH070RD	101
F0700A97Y	95	F5300D00W	101	F83500208	91	FH070RD	101
F0700A98Y	95	F5300D08W	32	F83500210	91	FH070WT	101
F0800A00Y	30	F5300D08W	101	F83500220	91	FH070WT	101
F0800A00Y	92	F5300D35W	32	F83500230	91	FH070YE	101
F0800A10Y	30	F5300D35W	101	F83500300	91	FH070YE	101
F0800A10Y	92	F5300D46W	32	F83500400	91	FH160BK	104
F0800A14Y	30	F5300D46W	101	F83500402	91	FH160BU	104
F0800A14Y	92	F5300D60W	32	F83500404	91	FH160FO	104
F0800A18Y	30	F5300D60W	101	F83500450	91	FH160RD	104
F0800A18Y	92	F5300D79W	32	F83500500	91	FH160WT	104
F0800A20Y	30	F5300D79W	101	F83500520	91	FH162WTFR	104
F0800A20Y	92	F5600D00W	32	F83500600	91	FH172GY	104
F0800A44Y	30	F5600D35W	32	F83500700	91	FH210BGR	102
F0800A44Y	92	F5600D40W	32	F83500800	91	FH210BK	102
F0800A46Y	30	F5600D79W	32	F83500910	91	FH210CNW	102
F0800A46Y	92	F6002W00M	13	F8365A00M	13	FH210GR	102
F0800A60Y	30	F6002X00M	18	F8365B00M	13	FH210LBU	102
F0800A60Y	92	F6003W00M	13	F8366A00M	13	FH210NV	102
F0800A62Y	30	F6006Z00M	13	F84500100	90	FH210OR	102
F0800A62Y	92	F6200A00M	16	F84500206	90	FH210RB	102
F0800A65Y	30	F6390B00M	16	F84500207	90	FH210RD	102
F0800A65Y	92	F6390B15M	16	F84500208	90	FH210WT	102
F0800A66Y	30	F6395B06M	16	F84500210	90	FH210YE	102
F0800A66Y	92	F6400C00M	16	F84500220	90	FH350GY	97
F0800A75Y	30	F6400C15M	16	F84500230	90	FH350RB	97
F0800A75Y	92	F6405B06M	16	F84500300	90	FH350WT	97
F0800A79Y	30	F6450C00M	16	F84500401	90	FH354AL	102
F0800A79Y	92	F6450C15M	16	F84500402	90	FH354BK	102
F0800A85Y	30	F6455B06M	16	F84500404	90	FH354GR	102
F0800A85Y	92	F6481B00M	17	F84500420	90	FH354GY	102
F0800A88Y	30	F6486B00M	17	F84500450	90	FH354NV	102
F0800A88Y	92	F6491B00M	17	F84500500	90	FH354RB	102
F0800A90Y	30	F6496B00M	17	F84500520	90	FH354RD	102
F0800A90Y	92	F7010Z00M	24	F84500600	90	FH354WT	102
F0800A97Y	30	F7015Z00M	25	F84500700	90	FH354YE	102
F0800A97Y	92	F7300B01M	15	F84500800	90	FH359BK	102
F0805A00Y	92	F7301B01M	15	F84500910	90	FH359GR	102
F0805A18Y	92	F7304B01M	15	F86500100	98	FH359GY	102
F0805A60Y	92	F7310B01M	15	F86500102	98	FH359NV	102

Part No	Page	Part No	Page	Part No	Page	Part No	Page
FH359PN	102	FWP062200	8	G100	126	G155	121
FH359RB	102	FWP062500	4	G101	126	G156	121
FH359SCST	102	FWP062503F	6	G101FW	126	G157	121
FH359WT	102	FWP062521F	6	G102A	126	G158	121
FH359YE	102	FWP071500	9	G102B	126	G160AWT	125
FH374BK	103	FWP072200	8	G103	126	G160BK	125
FH374BK4	103	FWP072500	4	G104	126	G160BK	125
FH550NV	97	FWP072503F	6	G104A	126	G160WT	125
FH590BK	103	FWP072521F	6	G104BP	126	G161BK	125
FH590WT	103	FWP075500	5	G105	126	G161WT	125
FH592WT	103	FWP075600	9	G105A	126	G170	121
FH600BG	101	FWP081500	9	G105FW	126	G171	121
FH600CG	101	FWP082200	8	G105MW	126	G171FW	121
FH600GR	101	FWP082500	4	G106	126	G174	121
FH600NV	101	FWP082503F	6	G108	126	G175	121
FH600RB	101	FWP082520M	6	G108BP	126	G176	121
FH600RD	101	FWP082521F	6	G110	124	G182	121
FH600SR	101	FWP085500	5	G113	124	G190BK	124
FH600TL	101	FWP085600	9	G115S	124	G190WT	124
FHKP60WT	25	FWP091500	9	G116S	124	G191BK	124
FP072CL	93	FWP092200	8	G118	124	G191WT	124
FP072NB	93	FWP092500	4	G119	124	G192BK	124
FP072SB	93	FWP092503F	6	G119FW	124	G192WT	124
FS82000	96	FWP092521F	6	G120	124	G194BK	124
FS82002	96	FWP095500	5	G130	124	G194WT	124
FS82003	96	FWP095600	9	G140	120	G195CL	124
FS82005	96	FWP102200	8	G140BK	120	G196CL	124
FS82006	96	FWP102500	4	G140BKM	120	G200S	127
FS82008	96	FWP102520M	6	G140BU	120	G203S	127
FS82010	96	FWP105500	5	G140NV	120	G204N	127
FS82012	96	FWP105600	9	G140SS	120	G205S	130
FS82013	96	FWP112200	8	G140TST	120	G209S	130
FS82015	96	FWP115500	5	G140WT	120	G210S	129
FS82016	96	FWP115600	9	G141	120	G211S	129
FS82017	96	FWP122200	8	G141SS	120	G221	129
FWP042200	8	FWP132200	8	G142	120	G221S	129
FWP042500	4	G045BK	127	G142BKM	120	G222	129
FWP042501MU	6	G045WT	127	G142SS	120	G222S	129
FWP042501MU	29	G048BK	138	G143	120	G223	129
FWP042510M	6	G049BK	138	G143BKM	120	G308	138
FWP042513M	6	G049BK	138	G143SS	120	G309	138
FWP042530M	6	G050BK	138	G144	120	G371	138
FWP042550M	6	G050BU	138	G145	120	G590	136
FWP042561M	6	G050GY	138	G145BKM	120	G590C	136
FWP042562MU	6	G050IV	138	G145SS	120	G603	134
FWP042562MU	29	G050WT	138	G146	120	G604S	134
FWP042563M	6	G051BK	138	G147	120	G605S	134
FWP042591MU	6	G055BK	127	G148	120	G607S	134
FWP042591MU	29	G055WT	127	G149SS	121	G610S	133
FWP042599M	6	G061	125	G151	121	G611S	132
FWP052200	8	G061LP	125	G151SS	121	G615S	134
FWP052500	4	G062BK	125	G152	121	G615SQP	134
FWP052521F	6	G062WT	125	G1520S	121	G620BK	133
FWP052599F	6	G063BK	125	G153	121	G620S	133
FWP061500	9	G063WT	125	G154	121	G620SS	132



Part No	Page	Part No	Page	Part No	Page	Part No	Page
G621BK	132	GE001742	192	INS019BU	78	J414	26
G621S	132	GE001745	192	INS023BK	78	J415	26
G622BK	134	GE01471	151	INS023BU	78	J416	26
G622S	134	GE01471	192	INS027B/R	78	J417	26
G623S	134	GE06971	196	INS028BU	78	J418	26
G623SS	134	GE1019241	196	INS029BU	78	J419	26
G624S	134	GE31000749	193	INS031BK	78	J451	27
G625LAN	134	GE31000750	193	INS031BU	78	J452	27
G625PIN	134	GE31000754	196	INS033BK	78	J453	27
G625S	134	GE31000758	197	INS037RD	78	J455	27
G625SQP	134	GE31001034	198	INS039BK	78	J472	28
G626S	134	GE31001040	195	INS041BK	78	J514BK	29
G627PIN	134	GE31001050	195	INS041BU	78	J514BU	29
G628SQP	134	GE31001062	198	INS045BK	78	J514CR	29
G629S	134	GE31001132	195	INS045BU	78	J514FP	29
G630SHD	133	GE31001337	193	INS045GY	78	J514FY	29
G631SHD	132	GE31001685	197	INS045RD	78	J514GR	29
G635S	133	GE31002645	196	INS047BK	78	J514GY	29
G638	136	GE41470	194	INS047BU	78	J514KE	29
G639	136	GE41471	194	INS047GR	78	J514NB	29
G640SHD	133	GE41771	194	INS047RD	78	J514OR	29
G641SHD	132	GE48443	197	INS049BK	78	J514PB	29
G646S	134	GRFAB01	154	INS049RD	78	J514RD	29
G650WT	133	GRFAB03	155	INS051RD	78	J514SL	29
G651WT	133	GRFAB04	155	INS055BK	78	J514TN	29
G652WT	133	GRFAB05	154	INS055BU	78	J514WT	29
G653WT	133	GRFAB06	154	INS055RD	78	J514YE	29
G655	133	GRFAB07	154	INS059BU	78	J530WT	24
G670	136	GRFAB13	154	INS059RD	78	J530WTUV	24
G671S	132	GRFAB16	154	INS061BK	78	J614WT	29
G672S	133	GRFAB23	155	INS061BU	78	J742	24
G674	132	GRFAB24	155	INS061GR	78	J743	24
G674S	134	GRFAB25	155	INS067BK	78	J744	24
G675	132	GRFAB26	154	INS067BU	78	J822	25
G675S	134	GRFAB35	155	INS071RD	78	J832	25
G676	132	HBA912GY	59	INS073BK	78	J872	25
G677S	134	HBA913GY	59	INS073BU	78	J874	25
G678S	132	HBA922GY	59	INS075BU	78	J959	153
G679	132	HBA923GY	59	J080	26	J959A	153
G681S	132	HBA932GY	59	J082	26	J969	153
G682S	133	HBA933GY	59	J132	28	J970	153
G692S	134	HBA943GY	59	J133	28	J971	153
G697S	133	HBA944GY	59	J134	28	JKTP00BU	183
G738	136	HBA953GY	59	J180	28	JKTP00WT	183
G744S	133	HBA954GY	59	J181	28	JKTP01BU	183
G747S	133	HBA963GY	59	J182	28	JKTP01WT	183
G758	136	HBA964GY	59	J310	27	JKTP03BU	183
G820S	133	INS001BU	78	J311	27	JKTP03WT	183
G830S	133	INS003RD	78	J312	27	JKTP05BU	183
G840S	133	INS007BR	78	J313	27	JKTP05WT	183
G840SSP	133	INS009BU	78	J314	27	JKTP06BU	183
G852	126	INS009RD	78	J315	27	JKTP06WT	183
G854	126	INS017BU	78	J411	26	JKTP07BU	183
GE001738	192	INS017RD	78	J412	26	JKTP07WT	183
GE001740	192	INS019BK	78	J413	26	JKTP08BU	183

Part No	Page	Part No	Page	Part No	Page	Part No	Page
JKTP08WT	183	L141	20	L40700125xxxxG20	36	L00220405098	123
K221	100	L142	20	L40700125xxxxG20	36	L00220411000	123
K232	99	L144	20	L40700125xxxxG20	36	L00220802098	123
K305/2	100	L150	20	L40700125xxxxGyy	35	L00222005098	123
K305/5	100	L152	20	L40800125xxxxG15	36	L00222205098	123
K310/2	100	L401	20	L40800125xxxxG15	36	L00222402098	123
K310/2SM	100	L402	20	L40800125xxxxG15	36	L00222502098	123
K310/5	100	L40200075xxxxG10	36	L40800125xxxxG20	36	L00222602098	123
K310/5DSM	100	L40200075xxxxG10	36	L40800125xxxxG20	36	L00222802098	123
K310/5SM	100	L40200075xxxxG10	36	L40800125xxxxG20	36	L00223000000	123
K315/2	100	L40200075xxxxG10	36	L40800125xxxxGyy	35	L00223100000	123
K315/2LSM	100	L40200075xxxxG10	36	L40900125xxxxG20	36	L00223300000	123
K432	99	L40200075xxxxG10	36	L40900125xxxxG20	36	L00223405098	123
K434	99	L40200075xxxxG10	36	L40900125xxxxG20	36	L00438605098	123
K631	99	L40200075xxxxG10	36	L40900125xxxxG20	36	L00438611000	123
K903	18	L40200075xxxxG10	36	L40900125xxxxG25	36	L00438679098	123
L00200200xxxxG10	36	L40200075xxxxGyy	35	L40900125xxxxGyy	35	L00511505000	122
L00200200xxxxG10	36	L40250075xxxxG10	36	L41000175xxxxG20	36	L00511511000	122
L00200200xxxxG10	36	L40250075xxxxG10	36	L41000175xxxxG20	36	L00511525000	122
L00200200xxxxG10	36	L40250075xxxxG10	36	L41000175xxxxG30	36	L00511569000	122
L00200200xxxxGyy	35	L40250075xxxxGyy	35	L41000175xxxxGyy	35	L00511579098	122
L00250250xxxxG10	36	L403	20	L41050175xxxxG20	36	L00513405000	122
L00250250xxxxGyy	35	L40300075xxxxG10	36	L41050175xxxxG25	36	L00513411000	122
L00300300xxxxG10	36	L40300075xxxxG10	36	L41050175xxxxGyy	35	L00513425000	122
L00300300xxxxG10	36	L40300075xxxxG10	36	L41100175xxxxG20	36	L00513469000	122
L00300300xxxxG10	36	L40300075xxxxG10	36	L41100175xxxxG25	36	L00513479098	122
L00300300xxxxG15	36	L40300075xxxxGyy	35	L41100175xxxxG30	36	L00514005000	122
L00300300xxxxGyy	35	L40350075xxxxG10	36	L41100175xxxxG30	36	L00514011000	122
L00350350xxxxG15	36	L40350075xxxxG10	36	L41100175xxxxGyy	35	L00514025000	122
L00350350xxxxG15	36	L40350075xxxxGyy	35	L41150200xxxxG30	36	L00514069000	122
L00350350xxxxGyy	35	L40400100xxxxG10	36	L41150200xxxxGyy	35	L00514079098	122
L00400400xxxxG15	36	L40400100xxxxG10	36	L41200200xxxxGyy	35	L00514105000	122
L00400400xxxxG15	36	L40400100xxxxG10	36	L41300200xxxxG30	36	L00514111000	122
L00400400xxxxG20	36	L40400100xxxxG10	36	L41300200xxxxGyy	35	L00514125000	122
L00400400xxxxGyy	35	L40400100xxxxG15	36	L41400200xxxxG30	36	L00514169000	122
L00500500xxxxG20	36	L40400100xxxxG15	36	L41400200xxxxGyy	35	L00514179098	122
L00500500xxxxGyy	35	L40400100xxxxGyy	35	L440	20	L00514205000	122
L00600600xxxxG15	36	L40500100xxxxG10	36	L441	20	L00514211000	122
L00600600xxxxG20	36	L40500100xxxxG10	36	L442	20	L00514279098	122
L00600600xxxxG20	36	L40500100xxxxG15	36	L443	20	L00518011000	122
L00600600xxxxGyy	35	L40500100xxxxG15	36	L575	131	L00565805000	122
L00700700xxxxG20	36	L40500100xxxxG15	36	L575BK	131	L00565879098	122
L00700700xxxxGyy	35	L40500100xxxxG15	36	L575T	131	L00593105098	123
L00800800xxxxG25	36	L40500100xxxxGyy	35	L585	131	L00719005098	123
L00800800xxxxG30	36	L40600100xxxxG15	36	L585BK	131	L00719011000	123
L00800800xxxxGyy	35	L40600100xxxxG15	36	L705BKA	131	L00719079098	123
L00900900xxxxG30	36	L40600100xxxxG15	36	L710BK	131	L00800305098	123
L00900900xxxxGyy	35	L40600100xxxxG15	36	L710WT	131	L00800311000	123
L01001000xxxxGyy	35	L40600100xxxxG15	36	L00159005098	123	L00800379098	123
L01051050xxxxGyy	35	L40600100xxxxG20	36	L00159011000	123	L00885900000	123
L01101100xxxxGyy	35	L40600100xxxxGyy	35	L00220205098	123	L00886502098	122
L01151150xxxxGyy	35	L40700125xxxxG15	36	L00220211000	123	L00889102098	122
L01201200xxxxGyy	35	L40700125xxxxG15	36	L00220279098	123	L09512105000	123
L01301300xxxxGyy	35	L40700125xxxxG15	36	L00220305098	123	LR001025	20
L01401400xxxxGyy	35	L40700125xxxxG15	36	L00220311000	123	LS001	131

Part No	Page	Part No	Page	Part No	Page	Part No	Page
LS002	131	OB1007Y	186	P25677	166	P63580	150
LS401BG	137	OB1008A	190	P25720	166	Q003035	156
LS401BK	137	OB1008BLK	190	P25722	164	Q054744	82
LS401BU	137	OB1009BLK	190	P25723	164	Q054744P	82
LS401GY	137	OB1031B	187	P25752	166	Q054745	82
LS401TN	137	OB1031BLK	187	P25752	166	Q054745P	82
M005	152	OB1031R	187	P25752	166	Q110	57
M010	152	OB1031Y	187	P25884	166	Q143	118
M012	152	OB1035BLK	191	P26140	166	Q144	118
M013	152	OB1036BLK	191	P26179	166	Q145	118
M016	152	OB1050BLK	188	P26179	166	Q146	118
M020	152	OB1051BLK	188	P26179	166	Q147	118
M030	116	OB1059B	187	P26325	166	Q148	118
M030	157	OB1059BLK	187	P26325	166	Q149	118
M031	116	OB1059WHT	187	P26901	166	RSE5097SPL	82
M031	157	OB1059Y	187	P26901	166	S40025	19
M032	116	OB1081BLK	191	P26901	166	S40040	19
M032	157	OB1082BLK	191	P26901	166	S40045	19
M150	152	OB1083BLK	189	P26902	166	S40050	19
M151	152	OB1086BLK	189	P26902	166	S40060	19
M171	156	OB1091BLK	187	P26902	166	S40063	19
M172	156	OB1091WHT	187	P26902	166	S40070	19
M173	156	OB1094Y	189	P55975	166	S40075	19
M181	156	OB1105BLK	191	P55975	166	S40080	19
M212	156	OB1106BLK	190	P55975	166	S40100	19
M216	152	OB1143BLK	187	P55976	166	S500125	19
M2214	156	OB1143WHT	187	P55976	166	S50040	19
M2224	156	OB1145B	188	P55976	166	S50045	19
M301	152	OB1145Y	188	P55977	166	S50050	19
M305	152	OB1146BLK	188	P55977	166	S50060	19
M321	152	OB1146BRW	188	P55977	166	S50063	19
M322	152	OB1146R	188	P55978	166	S50070	19
M401	152	OB1148HVO	187	P55978	166	S50075	19
M402	152	OB1148HVV	187	P55978	166	S50080	19
OB1001B	186	OB1154BLK	188	P55979	166	S50100	19
OB1001BLK	186	OB1154R	188	P55979	166	S50120	19
OB1001P	186	OB1155BLK	188	P55979	166	S60040	19
OB1001R	186	OB1161Y	189	P55980	166	S60045	19
OB1001Y	186	P10001	166	P55980	166	S60050	19
OB1003B	186	P10001	166	P55980	166	S60060	19
OB1003BLK	186	P17067	166	P58202	164	S60063	19
OB1003R	186	P17067	166	P58203	164	S60070	19
OB1003Y	186	P17069	166	P58204	165	S60075	19
OB1005B	186	P17071	166	P58207	164	S60080	19
OB1005BLK	186	P21291	166	P58208	164	S60100	19
OB1005P	186	P21291	166	P58209	165	S60120	19
OB1005R	186	P21295	166	P58245	166	S60125	19
OB1005Y	186	P21295	166	P58245	166	S60150	19
OB1006B	186	P22850	166	P58248	166	S60175	19
OB1006BLK	186	P22850	166	P58248	166	S70050	19
OB1006R	186	P25184	166	P58248	166	S70060	19
OB1006Y	186	P25184	166	P58248	166	S70063	19
OB1007B	186	P25184	166	P58249	166	S70070	19
OB1007BLK	186	P25200	164	P58249	166	S70075	19
OB1007R	186	P25286	164	P63579	150	S70080	19

Part No	Page	Part No	Page	Part No	Page	Part No	Page
S70100	19	SL002BK	78	SN230xx8	79	SRDL03WPY	172
S70120	19	SL002BU	78	SN250xx0	79	SRDL03YB	172
S70125	19	SL002GR	78	SN250xx1	79	SRDL04BY	172
S70150	19	SL002RD	78	SN250xx2	79	SRDL04BYG	172
S70175	19	SL002WT	78	SN250xx3	79	SRDL04OPG	172
S80050	19	SL003BK	78	SN250xx4	79	SRDL04PGO	172
S80060	19	SL003BU	78	SN250xx5	79	SRDL04WPY	172
S80063	19	SL003WT	78	SN250xx6/9	79	SRDL04YB	172
S80070	19	SL004BK	78	SN250xx7	79	SRDL05BY	172
S80075	19	SL004BU	78	SN250xx8	79	SRDL05BYG	172
S80080	19	SL004WT	78	SN300xx0	79	SRDL05OPG	172
S80080T	19	SL006BK	78	SN300xx1	79	SRDL05PGO	172
S80100	19	SL006WT	78	SN300xx2	79	SRDL05WPY	172
S80100T	19	SL009WT	78	SN300xx3	79	SRDL05YB	172
S80120	19	SL225xxx	79	SN300xx4	79	SRDL06BY	172
S80125	19	SL230xxx	79	SN300xx5	79	SRDL06BYG	172
S80125T	19	SL250xxx	79	SN300xx6/9	79	SRDL06OPG	172
S80150	19	SL300xxx	79	SN300xx7	79	SRDL06PGO	172
S80175	19	SL380xxx	79	SN300xx8	79	SRDL06WPY	172
S80200	19	SL450xxx	79	SN380xx0	79	SRDL06YB	172
SB71600	159	SN100xx0	79	SN380xx1	79	SRLL02B	173
SB71622	159	SN100xx1	79	SN380xx2	79	SRLL03B	173
SB71664	159	SN100xx2	79	SN380xx3	79	SRLL04B	173
SB80216	162	SN100xx3	79	SN380xx4	79	SRLL05B	173
SB80308	162	SN100xx4	79	SN380xx5	79	SRLL06B	173
SB80316	162	SN100xx5	79	SN380xx6/9	79	SRMAR08P05xx	173
SB81900	158	SN100xx6/9	79	SN380xx7	79	SRMAR08P06xx	173
SB81922	158	SN100xx7	79	SN380xx8	79	SRMAR08P07xx	173
SB82016	153	SN100xx8	79	SN457xx0	79	SRMAR08P08xx	173
SB82016	160	SN150xx0	79	SN457xx1	79	SRMAR08P09xx	173
SB83200	158	SN150xx1	79	SN457xx2	79	SRMAR08P10xx	173
SB83222	158	SN150xx2	79	SN457xx3	79	SRMDL12xx	178
SB84904	142	SN150xx3	79	SN457xx4	79	SRMDL14xx	178
SB84905	142	SN150xx4	79	SN457xx5	79	SRMDL16xx	178
SB84906	142	SN150xx5	79	SN457xx6/9	79	SRMDL18xx	178
SB84907	142	SN150xx6/9	79	SN457xx7	79	SRMFPP06W	177
SB84908	142	SN150xx7	79	SN457xx8	79	SRMFPP07W	177
SB85600	160	SN150xx8	79	SRBC02xx	179	SRMFPP08W	177
SB85616	160	SN225xx0	79	SRBC03xx	179	SRMFPP10N	177
SB87308	160	SN225xx1	79	SRBC04xx	179	SRMFPP10W	177
SB88708	161	SN225xx2	79	SRBC05xx	179	SRMFPP12BK	177
SB89102	161	SN225xx3	79	SRBC06xx	179	SRMFPP16W	177
SB89755	161	SN225xx4	79	SRBC07xx	179	SRPA304	176
SB92122	158	SN225xx5	79	SRBC08xx	179	SRPA305	176
SB92722	159	SN225xx6/9	79	SRBC10xx	179	SRPA306	176
SB94816	161	SN225xx7	79	SRDL02BY	172	SRPA308	176
SB95022	162	SN225xx8	79	SRDL02BYG	172	SRPA310	176
SB95122	159	SN230xx0	79	SRDL02OPG	172	SRPA312	176
SB95222	162	SN230xx1	79	SRDL02PGO	172	SRPA316	176
SD002BK	78	SN230xx2	79	SRDL02WPO	172	SRPA318	176
SD002BU	78	SN230xx3	79	SRDL02YB	172	SRPA320	176
SD002GR	78	SN230xx4	79	SRDL03BY	172	SRPA322	176
SD002RD	78	SN230xx5	79	SRDL03BYG	172	SRPA324	176
SD002WT	78	SN230xx6/9	79	SRDL03OPG	172	SRPL03xx	176
SL001xxx	79	SN230xx7	79	SRDL03PGO	172	SRPL04xx	176

Part No	Page	Part No	Page	Part No	Page	Part No	Page
SRPL05xx	176	SRSC04B	180	SRSUPB03xx	169	SUNB5020	88
SRPL06xx	176	SRSC05B	180	SRSUPB04xx	169	SUNB5026	88
SRPS304xx	177	SRSC05WBK	23	SRSUPB05xx	169	SUNB5030	88
SRPS305xx	177	SRSC06B	180	SRSUPB06xx	169	SUNB5031	88
SRPS306xx	177	SRSC07B	180	SRSUPB07xx	169	SUNB5032	88
SRPS308xx	177	SRSC08B	180	SRSUPB08xx	169	SUNB5034	88
SRPS310xx	177	SRSC09	180	SRSUPB09xx	169	SUNB5035	88
SRPS312xx	177	SRSC10B	180	SRSUPB10xx	169	SUNB5048	88
SRPS314xx	177	SRSPB02W	22	SRSUPB12xx	169	SUNB5049	88
SRPS316xx	177	SRSPB02xx	170	SRSUPB14xx	169	SUNB5057	88
SRPS318xx	177	SRSPB03xx	170	SRSUPB16xx	169	SUNB5058	88
SRPS320xx	177	SRSPB04W	22	SRSUPB18xx	169	SUNB5082	88
SRPS322xx	177	SRSPB04xx	170	SRSUPB20xx	169	SUNB5528	88
SRPS324xx	177	SRSPB06W	22	SRSUPB22xx	169	SUNB5530	88
SRPS326xx	177	SRSPB06xx	170	SRSUPB24xx	169	SUNB5548	88
SRPS328xx	177	SRSPB08xx	170	SRSUPSB04xx	169	SUNB5572	88
SRPS330xx	177	SRSPB10xx	170	SRSUPSB05xx	169	SUNBP013	88
SRPS332xx	177	SRSPB12xx	170	SRSUPSB06xx	169	SUNBP015	88
SRPS336xx	177	SRSTPB06xxxx	168	SRSUPSB07xx	169	SUNBP016	88
SRPS338xx	177	SRSTPB08xxxx	168	SRSUPSB08xx	169	SUNBP017	88
SRPS340xx	177	SRSTPB10xxxx	168	SRSUPSB09xx	169	SUNBP019	88
SRPS808xx	178	SRSTPB12xxxx	168	SRSUPSB10xx	169	SUNBP023	88
SRPS810xx	178	SRSTPB14xxxx	168	SRSUPSB12xx	169	SUNFU5020	31
SRPS812xx	178	SRSTPB16xxxx	168	SRSUPSB14xx	169	SUNFU5026	31
SRPS814xx	178	SRSTPB18xxxx	168	SRSUPSB16xx	169	SUNFU5031	31
SRPS816xx	178	SRSTW02xx	168	SRSUPSB18xx	169	SUNFU5035	31
SRPS818xx	178	SRSTW03xx	168	SRSUPSB20xx	169	SUNFU5057	31
SRPS820xx	178	SRSTW04xx	168	SRSUPSB22xx	169	SUNFUA5020	31
SRPS822xx	178	SRSTW05xx	168	SRSUPSB24xx	169	SUNFUA5026	31
SRPS824xx	178	SRSTW06xx	168	SRSYMDL12xx	179	SUNFUA5031	31
SRPS828xx	178	SRSTW08xx	168	SRSYMDL14xx	179	SUNFUA5035	31
SRPS832xx	178	SRSTW10xx	168	SRSYMDL16xx	179	SUNFUA5057	31
SRPS842xx	178	SRSTW12xx	168	SRSYMDL18xx	179	SUNSEAGF5010	97
SRRB06xx	171	SRSTW14xx	168	SRSYMDL20xx	179	SUNSEAGF5010W	97
SRRB08xx	171	SRSTW16xx	168	SRSYMDL24xx	179	SUNSEAGF5020	97
SRRB10xx	171	SRSTW18xx	168	SRTB02W	22	SUNSEAGF5020W	97
SRRB12xx	171	SRSUP1202x	167	SRTB04W	22	SUNSEAGF5026	97
SRRB14xx	171	SRSUP12035xx	167	SRTB06W	22	SUNSEAGF5026W	97
SRRB16xx	171	SRSUP1203xx	167	SRVB02W	170	SUNSEAGF5030	97
SRRB18xx	171	SRSUP1204x	167	SRVB03W	170	SUNSEAGF5030W	97
SRRB20xx	171	SRSUP1205x	167	SRVB04xx	170	SUNSEAGF5035	97
SRRB24xx	171	SRSUP1206x	167	SRVB05xx	170	SUNSEAGF5035W	97
SRRBS06xx	171	SRSUP1207x	167	SRVB06xx	170	SUNSEAGF5057	97
SRRBS08xx	171	SRSUP1208x	167	SRVB08xx	170	SUNSEAGF5057W	97
SRRBS10xx	171	SRSUP1209x	167	SRVB10xx	170	SUNSUP4081	89
SRRBS12xx	171	SRSUP1210x	167	SRVB12xx	170	SUNSUP4330	89
SRRBS14xx	171	SRSUP1211G	167	SRVB14xx	170	SUNSUP4441	89
SRRBS16xx	171	SRSUP1212xx	167	SRVB16xx	170	SUNSUP4461	89
SRRBS18xx	171	SRSUP1214G	167	SRVL04BBY	175	SUNSUR3853	89
SRRBS20xx	171	SRSUP1216G	167	SRVL04RBY	175	SUNSUR3854	89
SRRBS22xx	171	SRSUP1218G	167	SRXDL65BY	175	SUNSUR3862	89
SRRBS24xx	171	SRSUP1220G	167	SRZS7506BK	174	SUNSUR3866	89
SRSC02BK	180	SRSUP1222G	167	SRZS7506BL	174	SUNSWCM005	105
SRSC03B	180	SRSUP1224G	167	SRZS7506R	174	SUNSWCM392	105
SRSC03WBK	23	SRSUPB02xx	169	SRZS75L55Y	174	SUNSWCM652	105

Part No	Page	Part No	Page	Part No	Page
SUNSWCM654	105	SUNTTP020	87	U00462	44
SUNSWCM710	105	SUNTTP021	87	U00462	51
SUNSWCM711	105	SUNTTP022	87	U00463	44
SUNSWCM712	105	SUNTTP023	87	U00463	51
SUNSWKM005	105	SUNTTP024	87	U00464	44
SUNSWKM005W	105	SUNTTP025	87	U00464	51
SUNSWKM228	105	T025xx	19	U00466	44
SUNSWKM228W	105	T040xx	19	U00466	51
SUNSWKM391	105	T050xx	19	U00468	44
SUNSWKM391W	105	T060xx	19	U00472	44
SUNSWKM392	105	T075xx	19	U00474	44
SUNSWKM392W	105	T080xx	19	U00474	53
SUNSWKM393	105	T39025xx	19	U00642	42
SUNSWKM393W	105	T39040xx	19	U01530	42
SUNSWKM652	105	T39050xx	19	U01530	43
SUNSWKM652W	105	T39060xx	19	U01531	42
SUNSWKM654	105	T39075xx	19	U01531	43
SUNSWKM654W	105	T39080xx	19	U01532	42
SUNSWKM710	105	TUB001	132	U01532	43
SUNSWKM710W	105	TUB002	132	U01535	42
SUNSWKM711	105	TUB003	132	U01535	43
SUNSWKM711W	105	TYT12L	69	U01536	42
SUNSWKM712	105	TYT20L	69	U01536	43
SUNSWKM712W	105	TYT5L	69	U01540	42
SUNTEX001	157	TYT8L	69	U01540	43
SUNTEX002	157	U00322	44	U30063	38
SUNTEX003	157	U00341S	43	U30076	38
SUNTEX004	157	U00341S	51	U30102	38
SUNTT5020	87	U00343S	43	U30114	38
SUNTT5026	87	U00343S	51	U30127	38
SUNTT5030	87	U00345S	43	U99980	42
SUNTT5031	87	U00345S	51	V006BK	32
SUNTT5032	87	U00345S	51	V006BR	32
SUNTT5034	87	U00357S	43	V006BU	32
SUNTT5035	87	U00357S	55	V006DG	32
SUNTT5040	87	U00361	43	V006GR	32
SUNTT5048	87	U00361	51	V006GY	32
SUNTT5049	87	U00363	43	V006NB	32
SUNTT5057	87	U00363	51	V006RD	32
SUNTT5058	87	U00365	43	V006WT	32
SUNTT5082	87	U00365	51	V006YE	32
SUNTT5085	87	U00377	43	ZMARKERWT	144
SUNTT5087	87	U00377	55	ZPENCILBU	144
SUNTT5088	87	U00442S	44	ZPENCILW2	144
SUNTT5089	87	U00442S	51		
SUNTT5528	87	U00443S	44		
SUNTT5530	87	U00443S	51		
SUNTT5548	87	U00444S	44		
SUNTT5572	87	U00444S	51		
SUNTTP013	87	U00446S	44		
SUNTTP015	87	U00446S	51		
SUNTTP016	87	U00448S	44		
SUNTTP017	87	U00452S	44		
SUNTTP018	87	U00454S	44		
SUNTTP019	87	U00454S	53		



# TERMS & CONDITIONS

## 1. CONTRACTS

- a. Contracts are made and orders accepted only upon and subject to these Terms and Conditions of Sale. All other conditions are hereby excluded unless expressly accepted in writing by Bainbridge International Ltd or Aqua-Marine International Ltd (hereinafter called the "Seller").
- b. In entering into a contract with the Seller, the contracting party (hereinafter called the "Buyer") acknowledges that the contract has not been induced by any representations orally or in writing made by the Seller, is servants or agents.
- c. Any quotation, estimate or tender previously given or made by the Seller was not an offer but an intimation of the terms upon which the Seller was prepared to negotiate. The offer to contract with the Buyer made by these conditions may be accepted by the Buyer in a formal manner or may be inferred from the Buyer's acceptance of performance, in whole or in part, by the Seller. Any conditions contained in any purported acceptance by the Buyer shall be disregarded and the acceptance shall be construed as an unqualified acceptance of these conditions.
- d. Any typographical, clerical or other error or omission in any sales literature, quotation, price list, acceptance of offer, invoice or other document or information issued by the Seller shall be subject to correction without any liability on the part of the Seller.

## 2. PRICES

- a. Unless expressly stated otherwise by the Sellers, all prices quoted are ex works and exclude the cost of packing. Any applicable value added tax or any other sales tax or excise duties paid or payable by the Seller shall be added to the price and shall be payable by the Buyer.
- b. The Seller may, at their sole absolute discretion, accept or reject any order placed by the Buyer. The Seller may change the price of goods for future invoiced goods to the Buyer without notice.
- c. In the event of the Buyer cancelling a part of the order in accordance with the provisions of Clause 12, the Seller reserves the right to revise the price or prices quoted for goods already delivered.
- d. The contract price is, unless specifically agreed upon in writing by the Seller, payable in Pound Sterling. The Seller reserves the right to review the contract price(s) in the event of devaluation of the Pound Sterling or substantial change in the value of Pound Sterling in the foreign exchange markets.

## 3. CONDITIONS AND WARRANTIES

- a. Seller shall not be liable for the normal manufacturing defects nor any customary variations from quantities or specifications. A variance of not more than 15% either way from the total specified weight, quantity or length shall be deemed compliance with this contract.
- b. Where samples of goods or a colour chart are provided, these are submitted only as indicative of the class, size or colour of goods quoted for and sales of goods shall not be by reference to any such samples or colour charts.
- c. Whilst all description and illustrations of the goods in (interalia) catalogues, brochures, web sites and price lists provided by the Seller have been carefully prepared, they are intended nevertheless for general guidance only and do not form part of any contract for sale of goods and no responsibility is accepted for any errors or omissions therein or for any loss or damage resulting from reliance on such descriptions and illustrations.
- d. When the Seller agrees to provide a specially designed plan, the Buyer agrees that he is obliged to check the accuracy and suitability of the plan and that the Seller shall not be liable for any omissions or inaccuracies in the measurements given. The copyright in the plan drawn up by the Seller is, and remains, their property and may not be reproduced in whole or in part without written consent.
- e. If the Buyer claims or detects a defect in the goods, the Buyer will seek prior approval and return those goods to the Seller or, if the goods are retained by the Buyer, indemnify and keep the Seller indemnified against all liability and claims which may arise out of or incidental to the defect.
- f. The Seller has undertaken no responsibility for learning about the end purpose or use for which the goods are to be used, and the Buyer shall undertake to conduct whatever tests or examinations are necessary to confirm that goods are suitable for such end use.
- g. Any textile products that may be sold hereunder are sold subject to any imperfections that are typically regarded as acceptable in the textile trade resulting from the weaving and finishing thereof, and Seller shall have no liability in connection with any such imperfections. Buyer warrants that all merchandise covered by this contract is purchased for resale as tangible personal property, or to be incorporated as a component or part of other tangible property to be produced for sale by manufacturing, assembling or processing.
- h. The Buyer shall not be entitled to accept part only of the goods.

## 4. DELIVERY BY THE SELLER

- a. Unless and except as otherwise expressly provided in writing by the Seller, delivery shall be ex works place of business.
- b. Any dates quoted for delivery of the goods are approximate only and the Seller shall not be liable for any delay in delivery of the goods howsoever caused. Time for delivery shall not be of the essence unless previously agreed by the Seller in writing.
- c. Where goods are offered for delivery to a site, the Seller's obligation is to deliver as near to the site as safe hard roads permit. The Buyer is to provide at its own expense the labour required for unloading and stacking.
- d. The Seller reserves the right to deliver goods by instalments and in such event each instalment shall be treated as a separate contract save that the delivery of further instalments may be withheld until goods contained in earlier instalments have been paid for in full.
- e. Where goods are held by the Seller awaiting delivery instructions, they may be subject to a storage charge. For account holding customers, payment for these goods must be made on or before the last day of the month following the month of the invoice; for non-account holding customers, payment must be made at the time of ordering.
- f. In the absence of shipping instructions, the issuing of an invoice shall constitute delivery to the Buyer.

## 5. COLLECTION BY THE BUYER

- a. Where goods are sold "ex-factory" the Buyer shall collect the goods at the Seller's premises within seven days of the Seller's notifying the buyers that

the goods are ready for collection.

- b. If the Buyer fails to collect the goods within seven days of notification that they are ready for collection, then, without prejudice to any other right or remedy available to the Seller, the Seller may:
  - i. Store the goods until actual delivery and charge the Buyer for reasonable costs (including insurance) of storage; or
  - ii. Sell the goods at the best price readily obtainable (after deducting all reasonable storage and selling expenses) account to the Buyer for the excess over the price under the contract or charge the Buyer for any shortfall below the price.

## 6. DAMAGE, LOSS, SHORT DELIVERY

- a. On delivery, the Buyer shall examine the goods for defects and completeness. Thereafter no claim for damage in transit, for shortage in delivery, or for loss of goods will be entertained except, in the case of damage, a separate notice in writing is given to the Carriers or to the Seller within three days of the receipt of the goods, followed within 14 days of the date of advice of despatch by a complete claim in writing; or, in the case of loss of goods, a separate notice in writing and a claim is given to the Seller and Carriers within 14 days of the date of the Seller's advice of despatch to the Buyer. In all cases a signature "unexamined" shall be deemed to be an unconditional acceptance of the goods.
- b. The Seller shall not in any circumstances be liable, whether in contract or tort, to the Buyer for any indirect or consequential loss or damage (including without limitation, loss of profits, loss of contracts or damage to property) or for any claim against the Buyer by any third party.
- c. The Seller's liability for damage or non-delivery of goods duly notified in accordance with the above shall in any event be limited to replacement of the goods within a reasonable time (or, at the Seller's option, refunding the price thereof) whether the damage or non-delivery is due to the Seller's negligence or otherwise.

## 7. ROLL LENGTHS

- a. Where goods are sold as a measured length there may be a variation in length of plus or minus 2%. In the event of a claim the seller reserves the right to insist that the roll be returned for measuring before a settlement is agreed.

## 8. CREDIT AGREEMENTS

- a. Where the Sellers has granted the Buyer a credit facility, the price of goods and/or service shall be paid by the Buyer as per the payment terms specified on the invoice or, if the Seller shall so require under Clause (b) of this Clause 7, to be paid on demand without any period of notice.
- b. The Seller reserves the right to withdraw or vary credit facilities at any time to the Buyer without either giving any reason for doing so, or thereby incurring any liability to the Buyer.
- c. If the Buyer takes goods from the Seller in excess of the Buyer's credit limit, the Seller may require payment on delivery for such excess of goods.

## 9. TERMS OF PAYMENT

- a. Unless credit facilities have been granted to the Buyer or unless otherwise specifically provided in writing, the price for the goods shall be paid by the Buyer in cash on delivery and in default the Seller shall be entitled to withhold delivery until payment. In the case of non-cash sales, the Seller shall be entitled to charge and recover interest from the Buyer on the price of the goods calculated at whichever shall be the greater: the statutory interest payable under the Late Payment of Commercial Debts (Interest) Act 1998 or the rate of 4% per annum
- b. Unless otherwise expressly agreed upon in writing, no other discounts or commissions are to become due or allowable to the Buyer (any previous course of dealing between the parties notwithstanding).
- c. Where there is a term of contract that payment of any of the Seller's invoices is dependant upon the issues of the certificate of a third party, the due date for payment of the invoice is not later than 14 days after the issue of the relevant certificate.

## 10. LATE PAYMENT

- a. When payment of any of the Seller's invoices is overdue, the Seller may suspend their performance of the contracts to which the invoice relates and/or of any other contract then subsisting between the Seller and the Buyer.
- b. In the event of legal action being taken by the Seller against the Buyer for breach of payment obligations hereunder, the Buyer shall be responsible for all costs and disbursements incurred by the Seller on a full indemnity basis.

## 11. RISK AND LIABILITY

- a. b. c. Risk of damage to or loss of the goods shall pass to the Buyer at the time of delivery or, if the Buyer at the time of delivery of the goods, the time when the Seller has tendered delivery of the goods. For the purpose of this Clause 10, "delivery" shall mean the arrival of the goods at the place of delivery of the Buyer where delivery is by the Seller, or the safe loading of the goods into the Buyer's vehicles at the Seller's premises where delivery is through collection by the Buyer. In no event shall the Seller be liable for damages with respect to the sale or use of any product sold hereunder in any amount greater than the amount of the purchase price received by the Seller for that particular product. In addition, the Seller shall not be liable for any consequential, incidental, or special damages or costs or expenses in the event of any breach of warranty or in the event of any loss, damage injury or cost resulting fm, or arising out of, or in respect of the goods being sold hereunder. When any goods are sold hereunder bear a particular label, trademark, or trade name, affixed at the request of the Buyer, it is the understanding of the parties that the Buyer warrants that he has the right to use said label trademark or trade name, and that he hereby agrees to indemnify and hold harmless the Seller against any loss, damage or claim by any person with respect thereto.
- d. The Buyer agrees to reimburse the Seller, and hold Seller harmless against liability for all expenses, including legal fees, incurred by the Seller that may arise in connection with Seller's enforcement of its rights under this contract.
- e. The Seller has undertaken no responsibility for learning about the end purpose for which the goods are to be used, and Buyer shall undertake to conduct whatever tests or examinations are necessary to confirm that goods are suitable for such end use.

## 12. RETENTION OF TITLE

- a. Notwithstanding delivery and the passing of risk in the goods or any other provision of these conditions, the property in the goods shall not pass to

the Buyer until the Seller has received in cash (or cleared funds) payment in full of the price of the goods and all other goods agreed to be sold by the Seller to the Buyer for which payment is then due.

- b. Until such time as the property in the goods passes to the Buyer, the Buyer shall hold the goods as the Seller's fiduciary agent and bailee, and shall keep the goods separate from those of the Buyer and third parties and properly stored, protected and insured and identified as the Seller's property. Until that time the Buyer shall be entitled to resell or use the goods in the ordinary course of its business, but shall account to the Seller for the proceeds of the sale or otherwise of the goods, whether tangible or intangible, including insurance proceeds, and shall keep all such proceeds separate from any monies or property of the Buyer and third parties and, in the case of tangible proceeds, properly stored, protected and insured.
- c. Until such time as the property in the goods passes to the Buyer (and provided the goods are still in existence and have not been resold), the Seller shall be entitled at any time to require the Buyer to deliver up the goods to the Seller and, if the Buyer fails to do so forthwith, to enter upon any premises of the Buyer or any third party where the goods are stored and repossess the goods.
- d. The Buyer shall not be entitled to pledge or in any way charge by way of security for any indebtedness any of the goods which remain the property of the Seller, but if the Buyer does so, all monies owing by the Buyer to the Seller shall (without prejudice to any other right or remedy of the Seller) forthwith become due and payable.

## 13. CUSTOMER CANCELLATION OF ORDERS

Contracts and orders and parts thereof may be cancelled only by the Seller's written acceptance of such cancellation. Where the Seller accepts such cancellation, the Seller reserves the right to charge the Buyer with the amount of any losses or expenses directly or indirectly resulting from such cancellation. Where the Seller does not accept such cancellation, the Seller, reserves the right to recover the invoice price from the Buyer and to charge the Buyer with additional losses both direct and indirect resulting from such cancellation. In any case where the Seller were required to place a deposit with a manufacturer or supplier in respect of an order, the Seller may require the Buyer to reimburse such sum in the event of cancellation.

## 14. CUSTOMERS RETURNING GOODS

- a. The Seller will only accept goods being returned by customers if prior consent has been given by the seller. In the event of wishing to return goods customers must contact the seller to obtain a 'goods return note number' that must then be attached in an appropriate manner to the goods. The seller reserves the right to refuse to accept goods being returned by a buyer. In cases where the seller does agree to accept a return the seller reserves the right to charge a handling fee not exceeding 50% based on the invoice price of the goods.
- b. Excluding circumstances where goods are being returned for the reason of damage or are subject to warrantee claim, goods being returned to the seller must arrive in a condition that allows them to be re-sold. In the event that returned goods are not in good condition the seller reserves the right to withdraw any agreement for credit with the buyer or to charge a handling fee.

## 15. CONSENTS

The obtaining of any necessary consents for the installation of the goods, whether from local or other authorities or for ensuring that the installation of the goods is in accordance with the provisions of any by-laws, regulations or statutes shall not be the responsibility of the Seller.

## 16. FORCE MAJEURE

The Seller shall not be liable to the Buyer or be deemed to be in breach of contract by reason of any delay in performing, or any failure to perform, any of the Seller's obligations in relation to the goods, if the delay or failure was due to any cause beyond the Seller's reasonable control. Without prejudice to the generality of the foregoing, the following shall be regarded as causes beyond the Seller's control:

- a. Act of God, explosion, flood, tempest, fire or accident;
- b. War or threat of war, sabotage, insurrection, civil disturbance or requisition;
- c. Acts, restrictions, regulations, by-laws, prohibitions or measures of any kind on the part of any governmental, parliamentary or local authority;
- d. Import or export regulations or embargoes;
- e. Strikes, lock-outs or other industrial actions or trade disputes (whether involving employees of the Seller's or of a third party);
- f. Difficulties in obtaining raw materials, labour, fuel, parts or machinery;
- g. Power failure or breakdown in machinery.

## 17. INSOLVENCY

The Seller shall have the right to terminate the contract forthwith where the buyer becomes insolvent or bankrupt or makes arrangements with its creditors or suffers a receiver to be appointed or being a body corporate enters into liquidation (other than in connection with a reconstruction or amalgamation) in any of which cases the Seller shall have no further obligation hereunder and the price for all goods delivered and work done shall become immediately due and payable.

## 18. LAW APPLICABLE

These conditions shall be governed and construed in accordance with English law and all disputes arising in connection therewith shall be submitted to the jurisdiction of the English courts.

## 19. GENERAL

- a. No provision hereof shall be deemed waived and no breach or default excused unless such waiver or excuse is in writing signed by an authorised officer of the party making the writing.
- b. If any provision or part of a provision of this Agreement shall be, or found by any authority or court of competent jurisdiction to be, invalid or unenforceable, such invalidity or unenforceability shall not affect the other provisions or parts of such provisions of this Agreement, all of which shall remain in full force and effect.
- c. The headings in this document are inserted for convenience only and shall not constitute a part of or are referred to in its interpretation.

©Bainbridge International Limited 2014, Bainbridge® is a registered trademark of Bainbridge International Limited. Bainbridge Marine is a trademark of Bainbridge International Limited. Aqua-Marine is a trademark of Aqua-Marine International Limited  
Bainbridge International Ltd. 8 Flanders Park, Hedge End, Southampton, Hampshire, SO30 2ZF England  
Tel: +44 (0)1489 776030, Fax: +44 (0)1489 776035  
email: info@bainbridgeint.co.uk, www.bainbridgeint.com



**United Kingdom, Europe, Asia & Africa**
**Bainbridge International Ltd.**

8 Flanders Park, Hedge End Southampton, Hampshire SO30 2FZ

Tel: +44 (0) 1489 776010

Fax: +44 (0) 1489 776015

 Email: [info@bainbridgeint.co.uk](mailto:info@bainbridgeint.co.uk)

 Web: [www.bainbridgeint.com](http://www.bainbridgeint.com)
**Australia**
**Bainbridge International Pty. Ltd**

 273 Harbour Road, Brookvale  
 NSW 2100

Tel: +61 (0) 2 9938 1788

Fax: +61 (0) 2 9938 2459

 Email: [info@bainbridgeint.com.au](mailto:info@bainbridgeint.com.au)

 Web: [www.bainbridgeaus.com.au](http://www.bainbridgeaus.com.au)
**Greece / Bulgaria / Romania / Croatia**
**Takis Kokkotas Co. Ltd.**

80 Mezonos Str, 104 38, Athens

Tel: +30 210 52 28 540

Fax: +30 210 52 47 225

 Email: [info@kokkotas.gr](mailto:info@kokkotas.gr)

 Web: [www.kokkotas.gr](http://www.kokkotas.gr)
**New Zealand**
**Q C D Limited**

 8 Taylors Road, Sandringham  
 1025, Auckland

Tel: +64 (0) 9 815 7500

Fax: +64 (0) 9 849 6648

 Email: [sales@qcd.co.nz](mailto:sales@qcd.co.nz)

 Web: [www.qcd.co.nz](http://www.qcd.co.nz)
**Denmark**
**Columbus Marine**

Svejssegangen 3, DK-2690, Karlslunde

Tel: +45 4619 1166

Fax: +45 4619 1353

 Email: [info@columbus-marine.dk](mailto:info@columbus-marine.dk)

 Web: [www.columbus-marine.dk](http://www.columbus-marine.dk)
**Hong Kong / China**
**Sky International**

Room 703, 7/F, Henan Building

90 Jaffe Road, Wanchai

Tel: +852 2827 5876

Fax: +852 2827 7120

 Email: [web@sky-international.com](mailto:web@sky-international.com)

 Web: [www.sky-international.com](http://www.sky-international.com)
**Russia**
**Fordewind-Regatta Ltd**

Petrovskaya Kosa 7, 197110

St. Petersburg

Tel: +7 812 327 4580

Fax: +7 812 323 9563

 Email: [office@fordewind-regatta.ru](mailto:office@fordewind-regatta.ru)

 Web: [www.fordewind-regatta.ru](http://www.fordewind-regatta.ru)
**France / Spain / North Africa**
**UniSails SARL**

 5 Rue Marius Berliet,  
 PA de la Biliais Deniaud,  
 44360 Vigneux de Bretagne

Tel: +33 (0) 251 13 0540

Fax: +33 (0) 251 13 0456

 Email: [info@bainbridgeint.fr](mailto:info@bainbridgeint.fr)

 Web: [www.bainbridgeint.fr](http://www.bainbridgeint.fr)
**Italy / Slovenia**
**Boat Rigging S.R.L**

 Via San Gallo 23, 50028,  
 Tavarnelle Val di Pesa Loc.,  
 Sambuca(FI)

Tel: +39 055 8071964

Fax: +39 055 8091541

 Email: [luca@boatrigging.it](mailto:luca@boatrigging.it)

 Web: [www.boatrigging.it](http://www.boatrigging.it)
**Sweden / Norway**
**Aspero Handels AB**

PO Box 5009, Traneredsvagen 112

SE-426 05 V. Frolunda

Tel: +46 31 299 190

Fax: +46 31 691 965

 Email: [info@aspero.se](mailto:info@aspero.se)

 Web: [www.aspero.se](http://www.aspero.se)
**Germany**
**Herman Gotthardt GmbH**

Leunastrasse 50, D-22761 Hamburg

Tel: +44 40 85150550

Fax: +44 40 8509133

 Email: [info@gotthardt-yacht.de](mailto:info@gotthardt-yacht.de)

 Web: [www.gotthardt-yacht.de](http://www.gotthardt-yacht.de)
**Italy**
**Sacloma S.A.S**

 Via Cisa Sud 125, 19037,  
 S. Stefano di Magra (SP)

Tel: +39 0187 630603

Fax: +39 0187 633264

 Email: [sacloma@sacloma.com](mailto:sacloma@sacloma.com)

 Web: [www.sacloma.com](http://www.sacloma.com)
**Turkey**
**SORG Yelken Promosyon ve**

 Sarayardi Cad., Omer Cemal Bey Sok  
 Terzioglu Apt., 13/1 Acibadem,  
 Istanbul

Tel: +90 (216) 3177575

Fax: +90 (216) 3172725

 Email: [info@sailmaker.org](mailto:info@sailmaker.org)

 Web: [www.sailmaker.org](http://www.sailmaker.org)
**Netherlands**
**On Deck BV**

 Leimuiderdijk 478A, 2156 MX  
 Weteringburg

Tel: +31 71 331 33 66

Fax: +31 71 331 33 87

 Email: [allhands@on-deck.nl](mailto:allhands@on-deck.nl)

 Web: [www.on-deck.nl](http://www.on-deck.nl)
**USA / Canada / South America / Caribbean**
**Bainbridge International Inc.**

 255 Revere Street, Canton 02021  
 Massachusetts

Tel: +1 781 821 2600

Fax: +1 781 821 2609

 Email: [info@bainbridgeintusa.com](mailto:info@bainbridgeintusa.com)

 Web: [www.bainbridgeintusa.com](http://www.bainbridgeintusa.com)
